

Package ‘CoTiMA’

January 20, 2022

Type Package

Title Continuous Time Meta-Analysis ('CoTiMA')

Version 0.5.4

Date 2022-01-20

Description The 'CoTiMA' package performs meta-analyses of correlation matrices of repeatedly measured variables taken from studies that used different time intervals. Different time intervals between measurement occasions impose problems for meta-analyses because the effects (e.g. cross-lagged effects) cannot be simply aggregated, for example, by means of common fixed or random effects analysis. However, continuous time math, which is applied in 'CoTiMA', can be used to extrapolate or intrapolate the results from all studies to any desired time lag. By this, effects obtained in studies that used different time intervals can be meta-analyzed. 'CoTiMA' fits models to empirical data using the structural equation model (SEM) package 'ctsem', the effects specified in a SEM are related to parameters that are not directly included in the model (i.e., continuous time parameters; together, they represent the continuous time structural equation model, CTSEM). Statistical model comparisons and significance tests are then performed on the continuous time parameter estimates. 'CoTiMA' also allows analysis of publication bias (Egger's test, PET-PEESE estimates, zcurve analysis etc.) and analysis of statistical power (post hoc power, required sample sizes). See Dormann, C., Guthier, C., & Cortina, J. M. (2019) <doi:10.1177/1094428119847277>. and Guthier, C., Dormann, C., & Voelkle, M. C. (2020) <doi:10.1037/bul0000304>.

License GPL-3

URL <https://github.com/CoTiMA/CoTiMA>

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0), OpenMx (>= 2.18.1), ctsem (>= 3.3.11), lavaan (>= 0.6), foreach (>= 1.5.1)

Imports MBESS ($\geq 4.6.0$), crayon ($\geq 1.3.4$), psych ($\geq 1.9.12$),
doParallel ($\geq 1.0.15$), rootSolve ($\geq 1.8.2$), abind ($\geq 1.4-5$),
RPushbullet ($\geq 0.3.3$), openxlsx ($\geq 4.2.2$), zcurve ($\geq 1.0.7$),
scholar ($\geq 0.2.0$), stringi ($\geq 1.0.7$), MASS

Suggests R.rsp

VignetteBuilder R.rsp

RoxygenNote 7.1.2

NeedsCompilation no

Author Christian Dormann [aut, cph],
Markus Homberg [aut, com, cre],
Christina Guthier [ctb],
Manuel Voelkle [ctb]

Maintainer Markus Homberg <cotima@uni-mainz.de>

Repository CRAN

Date/Publication 2022-01-20 10:32:42 UTC

R topics documented:

A128	5
A313	6
addedByResearcher2	6
addedByResearcher3	7
addedByResearcher313	7
ageM128	8
ageM18	8
ageM2	9
ageM201	9
ageM3	10
ageM313	10
ageM32	11
ageSD128	11
ageSD18	12
ageSD2	12
ageSD201	13
ageSD3	13
ageSD313	14
ageSD32	14
alphas128	15
alphas313	15
burnout128	16
burnout18	16
burnout2	17
burnout201	17
burnout3	18
burnout313	18

burnout32	19
combineVariables128	19
combineVariablesNames128	20
CoTiMABiG_D_BO	20
CoTiMAFullFit_3	21
CoTiMAFullFit_6	21
CoTiMAFullFit_6_new	22
CoTiMAFullInv23Fit_6	22
CoTiMAFullInvEq23Fit_6	23
CoTiMAInitFit_3	23
CoTiMAInitFit_6	24
CoTiMAInitFit_6_new	24
CoTiMAInitFit_6_NUTS	25
CoTiMAInitFit_D_BO	25
CoTiMAMod1onFullFit_6	26
CoTiMAMod1onFullFit_6_cats12	26
CoTiMAMod2on23Fit_6	27
CoTiMAoptimFit313	27
CoTiMAPart134Inv3Fit_6	28
CoTiMAPower_D_BO	28
CoTiMAStanctArgs	29
CoTiMAstudyList_3	29
CoTiMAstudyList_6	30
CoTiMAstudyList_6_new	30
country128	31
country18	31
country2	32
country201	32
country3	33
country313	33
country32	34
ctmaAllInvFit	34
ctmaBiG	36
ctmaBiGOMX	37
ctmaCombPRaw	38
ctmaCompFit	39
ctmaCorRel	39
ctmaEmpCov	40
ctmaEqual	42
ctmaFit	43
ctmaFitList	46
ctmaFitToPrep	47
ctmaGetPub	47
ctmaInit	48
ctmaLabels	51
ctmaOptimizeInit	52
ctmaPlot	53
ctmaPower	55

ctmaPRaw	57
ctmaPrep	58
ctmaPub	61
ctmaSaveFile	62
ctmaStanResample	63
ctmaSV	64
delta_t128	65
delta_t18	65
delta_t2	66
delta_t201	66
delta_t3	67
delta_t313	67
delta_t32	68
demands128	68
demands18	69
demands2	69
demands201	70
demands3	70
demands313	71
demands32	71
dl_link	72
empcov128	72
empcov18	73
empcov2	73
empcov201	74
empcov3	74
empcov313	75
empcov32	75
malePercent128	76
malePercent18	76
malePercent2	77
malePercent201	77
malePercent3	78
malePercent313	78
malePercent32	79
moderator128	79
moderator18	80
moderator2	80
moderator201	81
moderator3	81
moderator313	82
moderator32	82
moderatorLabels	83
moderatorValues	83
occupation128	84
occupation18	84
occupation2	85
occupation201	85

occupation3	86
occupation313	86
occupation32	87
pairwiseN128	87
plot.CoTiMAFit	88
pubList_8	88
rawData128	89
recodeVariables128	89
results128	90
sampleSize128	90
sampleSize18	91
sampleSize2	91
sampleSize201	92
sampleSize3	92
sampleSize313	93
sampleSize32	93
source128	94
source2	94
source201	95
source3	95
source313	96
summary.CoTiMAFit	96
targetVariables128	97
targetVariables2	97
targetVariables3	98
targetVariables313	98
variableNames128	99

Index**100**

A128

*A128 example matrix***Description**

A128 example matrix

Usage

A128

FormatAn object of class `matrix` (inherits from `array`) with 2 rows and 2 columns.**Author(s)**

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

A313

A313 example matrix

Description

A313 example matrix

Usage

A313

Format

An object of class `matrix` (inherits from `array`) with 2 rows and 2 columns.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

addedByResearcher2

addedByResearcher2 example vector

Description

addedByResearcher2 example vector

Usage

addedByResearcher2

Format

An object of class `character` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

addedByResearcher3 *addedByResearcher3 example vector*

Description

addedByResearcher3 example vector

Usage

addedByResearcher3

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

addedByResearcher313 *addedByResearcher313 example vector*

Description

addedByResearcher313 example vector

Usage

addedByResearcher313

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageM128

ageM128 example vector

Description

ageM128 example vector

Usage

ageM128

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageM18

ageM18 example vector

Description

ageM18 example vector

Usage

ageM18

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageM2

ageM2 example vector

Description

ageM2 example vector

Usage

ageM2

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageM201

ageM201 example vector

Description

ageM201 example vector

Usage

ageM201

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageM3

ageM3 example vector

Description

ageM3 example vector

Usage

ageM3

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageM313

ageM313 example vector

Description

ageM313 example vector

Usage

ageM313

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageM32

ageM32 example vector

Description

ageM32 example vector

Usage

ageM32

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageSD128

ageSD128 example vector

Description

ageSD128 example vector

Usage

ageSD128

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageSD18

ageSD18 example vector

Description

ageSD18 example vector

Usage

ageSD18

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageSD2

ageSD2 example vector

Description

ageSD2 example vector

Usage

ageSD2

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageSD201

ageSD201 example vector

Description

ageSD201 example vector

Usage

ageSD201

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageSD3

ageSD3 example vector

Description

ageSD3 example vector

Usage

ageSD3

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageSD313

ageSD313 example vector

Description

ageSD313 example vector

Usage

ageSD313

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ageSD32

ageSD32 example vector

Description

ageSD32 example vector

Usage

ageSD32

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

alphas128

alphas128 example vector

Description

alphas128 example vector

Usage

alphas128

Format

An object of class `numeric` of length 9.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

alphas313

alphas313 example vector

Description

alphas313 example vector

Usage

alphas313

Format

An object of class `numeric` of length 6.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

burnout128

burnout128 example vector

Description

burnout128 example vector

Usage

burnout128

Format

An object of class character of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

burnout18

burnout18 example vector

Description

burnout18 example vector

Usage

burnout18

Format

An object of class character of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

burnout2 *burnout2 example vector*

Description

burnout2 example vector

Usage

burnout2

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

burnout201 *burnout201 example vector*

Description

burnout201 example vector

Usage

burnout201

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

burnout3

burnout3 example vector

Description

burnout3 example vector

Usage

burnout3

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

burnout313

burnout313 example vector

Description

burnout313 example vector

Usage

burnout313

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

burnout32

burnout32 example vector

Description

burnout32 example vector

Usage

burnout32

Format

An object of class character of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

combineVariables128

combineVariables128 example vector

Description

combineVariables128 example vector

Usage

combineVariables128

Format

An object of class list of length 3.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

combineVariablesNames128

combineVariablesNames128 example vector

Description

combineVariablesNames128 example vector

Usage

combineVariablesNames128

Format

An object of class character of length 3.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMABiG_D_BO

ctmaBiG-object reproducing results of Guthier et al. (2020)

Description

ctmaBiG-object reproducing results of Guthier et al. (2020)

Usage

CoTiMABiG_D_BO

Format

An object of class CoTiMAFit of length 10.

Author(s)

C. Guthier, C. Dormann & J. Cortina <CoTiMA@uni-mainz.org>

CoTiMAFullFit_3 *ctmaFit-object with a 'full' CoTiMA of 3 studies*

Description

ctmaFit-object with a 'full' CoTiMA of 3 studies

Usage

CoTiMAFullFit_3

Format

An object of class CoTiMAFit of length 16.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAFullFit_6 *ctmaFit-object with a 'full' CoTiMA of 6 studies*

Description

ctmaFit-object with a 'full' CoTiMA of 6 studies

Usage

CoTiMAFullFit_6

Format

An object of class CoTiMAFit of length 12.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAFullFit_6_new *ctmaFit-object with a 'full' CoTiMA of 6 studies*

Description

ctmaFit-object with a 'full' CoTiMA of 6 studies

Usage

CoTiMAFullFit_6_new

Format

An object of class CoTiMAFit of length 13.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAFullInv23Fit_6 *1st fitted ctmaFit-object in a series of 2 to test equality of 2 cross effects*

Description

1st fitted ctmaFit-object in a series of 2 to test equality of 2 cross effects

Usage

CoTiMAFullInv23Fit_6

Format

An object of class CoTiMAFit of length 14.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAFullInvEq23Fit_6

2nd fitted ctmaFit-object in a series of 2 to test equality of 2 cross effects

Description

2nd fitted ctmaFit-object in a series of 2 to test equality of 2 cross effects

Usage

CoTiMAFullInvEq23Fit_6

Format

An object of class CoTiMAFit of length 12.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAInitFit_3

ctmaInit-object with of 3 primary studies

Description

ctmaInit-object with of 3 primary studies

Usage

CoTiMAInitFit_3

Format

An object of class CoTiMAFit of length 15.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAInitFit_6 *ctmaInit-object with 6 primary studies*

Description

ctmaInit-object with 6 primary studies

Usage

CoTiMAInitFit_6

Format

An object of class CoTiMAFit of length 17.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAInitFit_6_new *ctmaInit-object with 6 primary studies*

Description

ctmaInit-object with 6 primary studies

Usage

CoTiMAInitFit_6_new

Format

An object of class CoTiMAFit of length 15.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAInitFit_6_NUTS *ctmaInit-object with a 'full' CoTiMA of 6 studies using NUTS sampler*

Description

ctmaInit-object with a 'full' CoTiMA of 6 studies using NUTS sampler

Usage

CoTiMAInitFit_6_NUTS

Format

An object of class CoTiMAFit of length 16.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAInitFit_D_BO *ctmaInit-object created by Guthier et al. (2020) with 48 primary studies*

Description

ctmaInit-object created by Guthier et al. (2020) with 48 primary studies

Usage

CoTiMAInitFit_D_BO

Format

An object of class CoTiMAFit of length 12.

Author(s)

C. Guthier, C. Dormann & J. Cortina <CoTiMA@uni-mainz.org>

CoTiMAMod1onFullFit_6 *ctmaFit-object with a categorical moderator of the full drift matrix*

Description

ctmaFit-object with a categorical moderator of the full drift matrix

Usage

CoTiMAMod1onFullFit_6

Format

An object of class CoTiMAFit of length 15.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAMod1onFullFit_6_cats12
ctmaFit-object with a categorical moderator of the full drift matrix

Description

ctmaFit-object with a categorical moderator of the full drift matrix

Usage

CoTiMAMod1onFullFit_6_cats12

Format

An object of class CoTiMAFit of length 13.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAMod2on23Fit_6 *ctmaFit-object with a continuous moderator of 2 cross effects*

Description

ctmaFit-object with a continuous moderator of 2 cross effects

Usage

CoTiMAMod2on23Fit_6

Format

An object of class CoTiMAFit of length 15.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAoptimFit313 *CoTiMAoptimFit313 example vector*

Description

CoTiMAoptimFit313 example vector

Usage

CoTiMAoptimFit313

Format

An object of class CoTiMAFit of length 4.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAPart134Inv3Fit_6

ctmaFit-object with with only one cross effect and this one set equal across primary studies

Description

ctmaFit-object with with only one cross effect and this one set equal across primary studies

Usage

CoTiMAPart134Inv3Fit_6

Format

An object of class CoTiMAFit of length 16.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAPower_D_BO

ctmaPower-object reproducing results of Guthier et al. (2020)

Description

ctmaPower-object reproducing results of Guthier et al. (2020)

Usage

CoTiMAPower_D_BO

Format

An object of class CoTiMAFit of length 10.

Author(s)

C. Guthier, C. Dormann & J. Cortina <CoTiMA@uni-mainz.org>

CoTiMAStanctArgs *This are preset arguments*

Description

This are preset arguments

Usage

CoTiMAStanctArgs

Format

An object of class list of length 33.

CoTiMAstudyList_3 *ctmaPrep-object created with 3 primary studies*

Description

ctmaPrep-object created with 3 primary studies

Usage

CoTiMAstudyList_3

Format

An object of class CoTiMAFit of length 28.

Author(s)

C. Guthier, C. Dormann & J. Cortina <CoTiMA@uni-mainz.org>

CoTiMAstudyList_6 *ctmaPrep-object created with 6 primary studies*

Description

ctmaPrep-object created with 6 primary studies

Usage

CoTiMAstudyList_6

Format

An object of class CoTiMAFit of length 29.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

CoTiMAstudyList_6_new *ctmaPrep-object created with 6 primary studies*

Description

ctmaPrep-object created with 6 primary studies

Usage

CoTiMAstudyList_6_new

Format

An object of class CoTiMAFit of length 29.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

country128

country128 example vector

Description

country128 example vector

Usage

country128

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

country18

country18 example vector

Description

country18 example vector

Usage

country18

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

country2	<i>country2 example vector</i>
----------	--------------------------------

Description

country2 example vector

Usage

country2

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

country201	<i>country201 example vector</i>
------------	----------------------------------

Description

country201 example vector

Usage

country201

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

country3 *country3 example vector*

Description

country3 example vector

Usage

country3

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

country313 *country313 example vector*

Description

country313 example vector

Usage

country313

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

country32	<i>country32 example vector</i>
-----------	---------------------------------

Description

country32 example vector

Usage

country32

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

ctmaAllInvFit	<i>ctmaAllInvFit</i>
---------------	----------------------

Description

#' @description Fit a CoTiMA model with all params (drift, T0var, diffusion) invariant across primary studies

Usage

```
ctmaAllInvFit(
  ctmaInitFit = NULL,
  activeDirectory = NULL,
  activateRPB = FALSE,
  digits = 4,
  drift = drift,
  coresToUse = c(1),
  n.manifest = 0,
  indVarying = FALSE,
  scaleTime = NULL,
  optimize = TRUE,
  nopriors = TRUE,
  finishsamples = NULL,
  iter = NULL,
  chains = NULL,
  verbose = NULL,
  loadAllInvFit = c(),
```

```

    saveAllInvFit = c(),
    silentOverwrite = FALSE,
    customPar = TRUE
  )

```

Arguments

ctmaInitFit	ctmaInitFit
activeDirectory	activeDirectory
activateRPB	activateRPB
digits	digits
drift	Labels for drift effects. Have to be either of the type V1toV2 or 0 for effects to be excluded, which is usually not recommended)
coresToUse	coresToUse
n.manifest	Number of manifest variables of the model (if left empty it will assumed to be identical with n.latent).
indVarying	Allows ct intercepts to vary at the individual level (random effects model, accounts for unobserved heterogeneity)
scaleTime	scaleTime
optimize	optimize
nopriors	nopriors
finishesamples	finishesamples
iter	iter
chains	chains
verbose	verbose
loadAllInvFit	loadAllInvFit
saveAllInvFit	saveAllInvFit
silentOverwrite	silentOverwrite
customPar	logical. If set TRUE (default) leverages the first pass using priors and ensure that the drift diagonal cannot easily go too negative (helps since ctsem > 3.4)

Value

returns a fitted CoTiMA object, in which all drift parameters, Time 0 variances and covariances, and diffusion parameters were set invariant across primary studies

ctmaBiG	<i>ctmaBiG</i>
---------	----------------

Description

Analysis of publication bias and generalizability. The function takes a CoTiMA fit object (created with `ctmaInit`) and estimates fixed and random effects of single drift coefficients, heterogeneity (Q, I square, H square, tau square), PET-PEESE corrections, Egger's tests, and z-curve analysis yielding expected replication and detection rates (ERR, EDR).

Usage

```
ctmaBiG(
  ctmaInitFit = NULL,
  activeDirectory = NULL,
  PETPEESEalpha = 0.1,
  activateRPB = FALSE,
  digits = 4,
  zcurve = FALSE,
  undoTimeScaling = TRUE
)
```

Arguments

<code>ctmaInitFit</code>	fit object created with <code>ctmaInit</code> containing the fitted ctsem model of each primary study
<code>activeDirectory</code>	the directory where to save results (if not specified, it is taken from <code>ctmaInitFit</code>)
<code>PETPEESEalpha</code>	probability level (condition) below which to switch from PET to PEESE (cf. Stanley, 2017, p. 582, below Eq. 2; default $p = .10$)
<code>activateRPB</code>	if TRUE, messages (warning, finished) could be send to smart phone (default = FALSE)
<code>digits</code>	rounding (default = 4)
<code>zcurve</code>	performs z-curve analysis. Could fail if too few studies (e.g. around 10) are supplied. default=FALSE
<code>undoTimeScaling</code>	if TRUE, the original time scale is used (timeScale argument possibly used in <code>ctmaInit</code> is undone)

Value

`ctmaBiG` returns a list containing some arguments supplied, the results of analyses of publication bias and generalizability, model type, and the type of plot that could be performed with the returned object. The arguments in the returned object are `activeDirectory`, and `coresToUse`. Further arguments, which are just copied from the init-fit object supplied, are, `n.studies`, `n.latent`, `studyList`, `statisticsList`, `modelResults` (all parameter estimates and their standard error), and parameter names.

All new results are returned as the list element "summary", which is printed if the summary function is applied to the returned object. The summary list element comprises a title (model='Analysis of Publication Bias & Generalizability') and "estimates", which is another list comprising "Fixed Effects of Drift Coefficients", "Heterogeneity", "Random Effects of Drift Coefficients", "PET-PEESE corrections", "Egger's tests" (constant of the WLS regression of drift coefficients on their standard errors (SE) with $1/SE^2$ as weights), "Egger's tests Alt. Version" (constant of the OLS regression of the standard normal deviates of the drift coefficients on their precision), and "Z-Curve 2.0 Results". Plot type is `plot.type=c("funnel", "forest")` and `model.type="BiG"`.

Examples

```
## Not run:
# perform analyses of publication bias and generalizability
CoTiMABiG_D_BO$activeDirectory <- "/Users/tmp/" # adapt!
CoTiMABiG_D_BO <- ctmaBiG(ctmaInitFit=CoTiMABiG_D_BO, zcurve=FALSE)

## End(Not run)

# display results
summary(CoTiMABiG_D_BO)

## Not run:
# get funnel & forest plots
CoTiMABiG_D_BO$activeDirectory <- "/Users/tmp/" # adapt!
plot(CoTiMABiG_D_BO)

## End(Not run)
```

ctmaBiGOMX

ctmaBiGOMX

Description

Analysis of publication bias and fixed and random effects analysis of single drift coefficients if OLD OpenMx fit files are supplied

Usage

```
ctmaBiGOMX(
  ctmaInitFit = NULL,
  activeDirectory = NULL,
  PETPEESEalpha = 0.1,
  activateRPB = FALSE,
  digits = 4
)
```

Arguments

<code>ctmaInitFit</code>	fit object created with <code>ctmaInti</code> containing the fitted <code>ctsem</code> model of each primary study
<code>activeDirectory</code>	the directory where to save results (if not specified, it is taken from <code>ctmaInitFit</code>)
<code>PETPEESEalpha</code>	# probability level (condition) below which to switch from PET to PEESE (Stanley, 2017, SPPS, p. 582, below Eq. 2; (default $p = .10$))
<code>activateRPB</code>	if TRUE, messages (warning, finishes) could be send to smart phone (default = FALSE)
<code>digits</code>	rounding (default = 4)

Value

returns a CoTiMA fit object with results of publication bias analysis, fixed and random effect analysis, Egger's tests, PET-PEESE corrections.

<code>ctmaCombPRaw</code>	<i>ctmaCombPRaw</i>
---------------------------	---------------------

Description

Combine Pseudo Raw Data (extract them from 'CoTiMAFit object'\$studyFitList)

Usage

```
ctmaCombPRaw(listOfStudyFits = NULL, moderatorValues = NULL)
```

Arguments

<code>listOfStudyFits</code>	"Listobject of Studyfits"
<code>moderatorValues</code>	"Moderators"

Value

returns a pseudo raw data set that combines pseudo raw data and moderators of primary studies

ctmaCompFit	<i>ctmaCompFit</i>
-------------	--------------------

Description

Performs log-likelihood ratio tests to compare the fit of 2 models (CoTiMAFit objects created with [ctmaFit](#) or [ctmaEqual](#)), i.e., the difference between the two -2 times LLs between the first model and the more constrained second model. The nested structure of the two models is assumed to be given and not checked.

Usage

```
ctmaCompFit(model1 = NULL, model2 = NULL)
```

Arguments

model1	Model 1
model2	Model 2

Value

Returns the the difference between the two -2 times LLs (Diff_Minus2LL), the associated difference in degrees of freedom (Diff_df (= Diff_n.params)), and the probability (prob).

Examples

```
minus2l1DiffTest <- ctmaCompFit(CoTiMAFullInv23Fit_6,
                               CoTiMAFullInvEq23Fit_6)
summary(minus2l1DiffTest)
```

ctmaCorRel	<i>ctmaCorRel</i>
------------	-------------------

Description

Disattenuates the entries in a correlation matrix using a vector of reliabilities.

Usage

```
ctmaCorRel(empcov = NULL, alphas = NULL)
```

Arguments

empcov	Empirical correlation matrix
alphas	Vector reliabilities

Value

A corrected correlation matrix (corEmpcov). Corrections leading to $r > 1.0$ are set to 1.0.

Examples

```
empcov313new <- ctmaCorRel(empcov=empcov313, alphas=alphas313)
```

 ctmaEmpCov

ctmaEmpCov

Description

changes a full covariance matrix by selecting target variables, recoding them, combining them (compute the mean of two or more variables), and by adding rows/columns with NA if focal variables are not available.

Usage

```
ctmaEmpCov(
  targetVariables = NULL,
  recodeVariables = c(),
  combineVariables = c(),
  combineVariablesNames = c(),
  missingVariables = c(),
  nlatents = NULL,
  Tpoints = NULL,
  sampleSize = NULL,
  pairwiseN = NULL,
  empcov = NULL
)
```

Arguments

targetVariables
(col-/row-) number or names of the target variables

recodeVariables
(col-/row-) number or names of the target variables require inverse coding

combineVariables
list of vectors, which put together the targeted variables that should be used for composite variables

combineVariablesNames
new names for combined variables - not really important

missingVariables
missing variables

nlatents
number of (latent) variables - actually it is the number of all variables

Tpoints	number of time points.
sampleSize	sample size
pairwiseN	matrix of same dimensions as empcov containing possible pairwiseN.
empcov	empirical correlation matrix

Value

returns a list with two elements. The first element (results\$r) contains the adapted correlation matrix, and the second element (results\$pairwiseNNew) an adapted version of a matrix of pairwise N if pairwiseN was provided for the original correlation matrix supplied.

Examples

```
source17 <- c()
delta_t17 <- c(12)
sampleSize17 <- 440
empcov17 <- matrix(
  c( 1.00, -0.60, -0.36,  0.20,  0.62, -0.47, -0.18,  0.20,
    -0.60,  1.00,  0.55, -0.38, -0.43,  0.52,  0.27, -0.21,
    -0.36,  0.55,  1.00, -0.47, -0.26,  0.37,  0.51, -0.28,
    0.20, -0.38, -0.47,  1.00,  0.15, -0.28, -0.35,  0.56,
    0.62, -0.43, -0.26,  0.15,  1.00, -0.63, -0.30,  0.27,
    -0.47,  0.52,  0.37, -0.28, -0.63,  1.00,  0.55, -0.37,
    -0.18,  0.27,  0.51, -0.35, -0.30,  0.55,  1.00, -0.51,
    0.20, -0.21, -0.28,  0.56,  0.27, -0.37, -0.51,  1.00),
  nrow=8, ncol=8)
moderator17 <- c(3, 2)
rownames(empcov17) <- colnames(empcov17) <-
  c("Workload_1", "Exhaustion_1", "Cynicism_1", "Values_1",
    "Workload_2", "Exhaustion_2", "Cynicism_2", "Values_2")
targetVariables17 <-
  c("Workload_1", "Exhaustion_1", "Cynicism_1",
    "Workload_2", "Exhaustion_2", "Cynicism_2")
recodeVariables17 <- c("Workload_1", "Workload_2")
combineVariables17 <- list("Workload_1", c("Exhaustion_1", "Cynicism_1"),
  "Workload_2", c("Exhaustion_2", "Cynicism_2"))
combineVariablesNames17 <- c("Demands_1", "Burnout_1",
  "Demands_2", "Burnout_2")
missingVariables17 <- c();
results17 <- ctmaEmpCov(targetVariables = targetVariables17,
  recodeVariables = recodeVariables17,
  combineVariables = combineVariables17,
  combineVariablesNames = combineVariablesNames17,
  missingVariables = missingVariables17,
  nlatents = 2, sampleSize = sampleSize17,
  Tpoints = 2, empcov = empcov17)
empcov17 <- results17$r
```

 ctmaEqual

ctmaEqual

Description

test if the two or more invariant drift parameters in the CoTiMAFit object supplied are equal. The supplied CoTiMA fit-object (ctmaInvariantFit) has to be a model fitted with `ctmaFit` where at least two parameters were set invariant across primary studies (e.g., 2 cross effects). All parameters that are set invariant in the supplied model are then constrained to be equal by `ctmaEqual` (no user action required), the model is fitted, and a log-likelihood ratio test is performed informing about the probability that equality applies.

Usage

```
ctmaEqual(
  ctmaInvariantFit = NULL,
  activeDirectory = NULL,
  activateRPB = FALSE,
  digits = 4,
  coresToUse = 1
)
```

Arguments

<code>ctmaInvariantFit</code>	object to which a CoTiMA fit has been assigned to (i.e., what has been returned by <code>ctmaFit</code>). In most cases probably a model in which (only) two effects were specified with <code>invariantDrift</code> .
<code>activeDirectory</code>	defines another active directory than the one used in <code>ctmaInvariantFit</code>
<code>activateRPB</code>	set to TRUE to receive push messages with CoTiMA notifications on your phone
<code>digits</code>	Number of digits used for rounding (in outputs)
<code>coresToUse</code>	If neg., the value is subtracted from available cores, else value = cores to use

Value

returns a model where two or more parameters were set equal across primary studies and a log-likelihood difference test informing about the probability that the equality assumption is correct.

Examples

```
# Fit a CoTiMA with a set of parameters set equal that were set
# invariant in a previous model (of which the fit object is
# supplied in argument ctmaInvariantFit)
## Not run:
CoTiMAFullInv23Fit_6$activeDirectory <- "/Users/tmp/" # adapt!
CoTiMAFullInvEq23Fit_6 <- ctmaEqual(ctmaInvariantFit=CoTiMAFullInv23Fit_6)
```

```
## End(Not run)
```

ctmaFit

ctmaFit

Description

Fits a ctsem model with invariant drift effects across primary studies, possible multiple moderators (but all of them of the the same type, either "cont" or "cat"), and possible cluster (e.g., countries where primary studies were conducted).

Usage

```
ctmaFit(
  ctmaInitFit = NULL,
  primaryStudyList = NULL,
  cluster = NULL,
  activeDirectory = NULL,
  activateRPB = FALSE,
  digits = 4,
  drift = NULL,
  invariantDrift = NULL,
  moderatedDrift = NULL,
  equalDrift = NULL,
  mod.number = NULL,
  mod.type = "cont",
  mod.names = NULL,
  indVarying = FALSE,
  coresToUse = c(1),
  scaleTI = NULL,
  scaleMod = NULL,
  transfMod = NULL,
  scaleClus = NULL,
  scaleTime = NULL,
  optimize = TRUE,
  nopriors = TRUE,
  finishsamples = NULL,
  iter = NULL,
  chains = NULL,
  verbose = NULL,
  allInvModel = FALSE,
  customPar = FALSE,
  inits = NULL,
  modsToCompare = NULL,
  catsToCompare = NULL,
```

```

    driftsToCompare = NULL,
    useSampleFraction = NULL
)

```

Arguments

ctmaInitFit	object to which all single ctsem fits of primary studies has been assigned to (i.e., what has been returned by ctmaInit)
primaryStudyList	could be a list of primary studies compiled with ctmaPrep that defines the subset of studies in ctmaInitFit that should actually be used
cluster	vector with cluster variables (e.g., countries). Has to be set up carefully. Will be included in ctmaPrep in later 'CoTiMA' versions.
activeDirectory	defines another active directory than the one used in ctmaInitFit
activateRPB	set to TRUE to receive push messages with 'CoTiMA' notifications on your phone
digits	Number of digits used for rounding (in outputs)
drift	labels for drift effects. Have to be either of the type 'V1toV2' or '0' for effects to be excluded.
invariantDrift	drift labels for drift effects that are set invariant across primary studies (default = all drift effects).
moderatedDrift	labels for drift effects that are moderated (default = all drift effects)
equalDrift	Not enabled
mod.number	which in the vector of moderator values shall be used (e.g., 2 for a single moderator or 1:3 for 3 moderators simultaneously)
mod.type	'cont' or 'cat' (mixing them in a single model not yet possible)
mod.names	vector of names for moderators used in output
indVarying	allows continuous time intercepts to vary at the individual level (random effects model, accounts for unobserved heterogeneity)
coresToUse	if negative, the value is subtracted from available cores, else value = cores to use
scaleTI	scale TI predictors - not recommended if TI are dummies representing primary studies, which would be the usual case
scaleMod	scale moderator variables - FALSE (default) highly recommended for categorical moderators, TRUE highly recommended for continuous moderators
transfMod	more general option to change moderator values. A vector as long as number of moderators analyzed (e.g., c("mean(x)", "x - median(x)"))
scaleClus	scale vector of cluster indicators - TRUE (default) yields avg. drift estimates, FALSE yields drift estimates of last cluster
scaleTime	scale time (interval) - sometimes desirable to improve fitting
optimize	if set to FALSE, Stan's Hamiltonian Monte Carlo sampler is used (default = TRUE = maximum a posteriori / importance sampling) .

nopriors	if TRUE, any priors are disabled – sometimes desirable for optimization
finishesamples	number of samples to draw (either from hessian based covariance or posterior distribution) for final results computation (default = 1000).
iter	number of iterations (default = 1000). Sometimes larger values could be required from Bayesian estimation
chains	number of chains to sample, during HMC or post-optimization importance sampling.
verbose	integer from 0 to 2. Higher values print more information during model fit – for debugging
allInvModel	estimates a model with all parameters invariant (DRIFT, DIFFUSION, T0VAR) if set TRUE (default = FALSE)
customPar	logical. If set TRUE leverages the first pass using priors and ensure that the drift diagonal cannot easily go too negative (helps since ctsem > 3.4)
inits	vector of start values
modsToCompare	when performing contrasts for categorical moderators, the moderator numbers (position in mod.number) that is used
catsToCompare	when performing contrasts for categorical moderators, the categories (values, not positions) for which effects are set equal
driftsToCompare	when performing contrasts for categorical moderators, the (subset of) drift effects analyzed
useSampleFraction	to speed up debugging. Provided as fraction (e.g., 1/10).

Value

ctmaFit returns a list containing some arguments supplied, the fitted model, different elements summarizing the main results, model type, and the type of plot that could be performed with the returned object. The arguments in the returned object are activeDirectory, coresToUse, moderator names (mod.names), and moderator type (mod.type). Further arguments, which are just copied from the init-fit object supplied, are, n.latent, studyList, parameterNames, and statisticsList. The fitted model is found in studyFitList, which is a large list with many elements (e.g., the ctsem model specified by CoTiMA, the rstan model created by ctsem, the fitted rstan model etc.). Further results returned are n.studies = 1 (required for proper plotting), data (created pseudo raw data), and a list with modelResults (i.e., DRIFT=model_Drift_Coeff, DIFFUSION=model_Diffusion_Coeff, T0VAR=model_T0var_Coeff, CINT=model_Cint_Coeff, MOD=modTI_Coeff, and CLUS=clusTI_Coeff). Possible invariance constraints are included in invariantDrift. The number of moderators simultaneously analyzed are included in 'n.moderators'. The most important new results are returned as the list element "summary", which is printed if the summary function is applied to the returned object. The summary list element comprises "estimates" (the aggregated effects), possible randomEffects (not yet fully working), the minus2ll value and its n.parameters, the opt.lag sensu Dormann & Griffin (2015) and the max.effects that occur at the opt.lag, clus.effects and mod.effects, and possible warning messages (message). Plot type is plot.type=c("drift") and model.type="stanct" ("omx" was deprecated).

Examples

```
## Not run:
# Example 1. Fit a CoTiMA to all primary studies previously fitted one by one
# with the fits assigned to CoTiMAInitFit_6
CoTiMAFullFit_6 <- ctmaFit(ctmaInitFit=CoTiMAInitFit_6)
summary(CoTiMAFullFit_6)

## End(Not run)

## Not run:
# Example 2. Fit a CoTiMA with only 2 cross effects invariant (not the auto
# effects) to all primary studies previously fitted one by one with the fits
# assigned to CoTiMAInitFit_6
CoTiMAInitFit_6$activeDirectory <- "/Users/tmp/" # adapt!
CoTiMAFullInv23Fit_6 <- ctmaFit(ctmaInitFit=CoTiMAInitFit_6,
                              invariantDrift=c("V1toV2", "V2toV1"))
summary(CoTiMAFullInv23Fit_6)

## End(Not run)

## Not run:
# Example 3. Fit a moderated CoTiMA
CoTiMAInitFit_6$activeDirectory <- "/Users/tmp/" # adapt!
CoTiMAMod1onFullFit_6 <- ctmaFit(ctmaInitFit=CoTiMAInitFit_6,
                                mod.number=1, mod.type="cont",
                                mod.names=c("Control"))
summary(CoTiMAMod1onFullFit_6)

## End(Not run)
```

ctmaFitList

ctmaFitList

Description

Combines CoTiMAFit objects into a list with class CoTiMAFit to inform generic functions what to do

Usage

```
ctmaFitList(...)
```

Arguments

... any number of CoTiMAFit objects

Value

a list that combines all objects supplied and is assigned the class 'CoTiMAFit'

Examples

```
## Not run:
CoTiMAInitFit_3$activeDirectory <- "/Users/tmp/" # adapt!
CoTiMAFullFit_3$activeDirectory <- "/Users/tmp/" # adapt!
plot(ctmaFitList(CoTiMAInitFit_3, CoTiMAFullFit_3),
     timeUnit="Months",
     timeRange=c(1, 144, 1) )

## End(Not run)
```

ctmaFitToPrep

ctmaFitToPrep

Description

Extracts information from fitted CoTiMA objects to (re-)create list of primary studies originally created with [ctmaPrep](#)

Usage

```
ctmaFitToPrep(ctmaFitObject = NULL)
```

Arguments

```
ctmaFitObject  ctmaFitObject
```

Value

list that could be used for fitting new CoTiMA models with [ctmaInit](#) or [ctmaFit](#).

Examples

```
newStudyList <- ctmaFitToPrep(CoTiMAInitFit_3)
```

ctmaGetPub

ctmaGetPub

Description

Retrieves publication and citation information from google scholar based on the supplied author names and their google ID (user)

Usage

```
ctmaGetPub(authorList = NULL, flush = FALSE, yearsToExclude = NULL)
```

Arguments

authorList list of authors and google scholar addresses
 flush if TRUE, the cache will be cleared and the data reloaded from Google.
 yearsToExclude the years to be excluded (default = current year)

Value

list with (cumulative) frequencies and (cumulative) citations in google scholar

Note

Set flush=TRUE only if retrieving is necessary (e.g., first retrieval on a day)

Examples

```
pubList_8 <- ctmaGetPub(authorList = list( c("J; de Jonge",
  "https://scholar.google.de/citations?hl=de&user=0q27IckAAAAJ"),
  c("Arnold B.; Bakker", "user=FT13bwUAAAAJ"),
  c("Evangelia; Demerouti", "user=9mj5LvMAAAAJ"),
  c("Joachim; Stoeber", "user=T9xdVusAAAAJ"),
  c("Claude; Fernet", "user=KwzjP4sAAAAJ"),
  c("Frederic; Guay", "user=99vnhX4AAAAJ"),
  c("Caroline; Senecal", "user=64ArFWQAAAAJ"),
  c("Stéphanie; Austin", "user=PPyTI7EAAAAJ")),
  flush=FALSE)
summary(pubList_8)
```

 ctmaInit

ctmaInit

Description

Fits ctsem models to each primary study in the supplied list of primary studies prepared by [ctmaPrep](#).

Usage

```
ctmaInit(
  primaryStudies = NULL,
  activeDirectory = NULL,
  activateRPB = FALSE,
  checkSingleStudyResults = TRUE,
  digits = 4,
  n.latent = NULL,
  n.manifest = 0,
  lambda = NULL,
```



```

manifestVars = NULL,
drift = NULL,
indVarying = FALSE,
saveRawData = list(),
coresToUse = c(1),
silentOverwrite = FALSE,
saveSingleStudyModelFit = c(),
loadSingleStudyModelFit = c(),
scaleTI = NULL,
scaleTime = NULL,
optimize = TRUE,
nopriors = TRUE,
finishesamples = NULL,
chains = NULL,
iter = NULL,
verbose = NULL,
customPar = FALSE,
doPar = 1,
useSV = TRUE,
experimental = FALSE
)

```

Arguments

primaryStudies list of primary study information created with [ctmaPrep](#)

activeDirectory defines another active directory than the one used in [ctmaPrep](#)

activateRPB set to TRUE to receive push messages with 'CoTiMA' notifications on your phone

checkSingleStudyResults Displays estimates from single study ctsem models and waits for user input to continue. Useful to check estimates before they are saved.

digits number of digits used for rounding (in outputs)

n.latent number of latent variables of the model (has to be specified)!

n.manifest number of manifest variables of the model (if left empty it will assumed to be identical with n.latent).

lambda R-type matrix with pattern of fixed (=1) or free (any string) loadings.

manifestVars define the error variances of the manifests with a single time point using R-type matrix with nrow=n.manifest & ncol=n.manifest.

drift labels for drift effects. Have to be either of the type V1toV2 or 0 for effects to be excluded, which is usually not recommended)

indVarying control for unobserved heterogeneity by having randomly (inter-individually) varying manifest means

saveRawData save (created pseudo) raw data. List: saveRawData\$studyNumbers, \$fileName, \$row.names, col.names, \$sep, \$dec

coresToUse	if neg., the value is subtracted from available cores, else value = cores to use
silentOverwrite	overwrite old files without asking
saveSingleStudyModelFit	save the fit of single study ctsem models (could save a lot of time afterwards if the fit is loaded)
loadSingleStudyModelFit	load the fit of single study ctsem models
scaleTI	scale TI predictors
scaleTime	scale time (interval) - sometimes desirable to improve fitting
optimize	if set to FALSE, Stan's Hamiltonian Monte Carlo sampler is used (default = TRUE = maximum a posteriori / importance sampling) .
nopriors	if TRUE, any priors are disabled - sometimes desirable for optimization
finishesamples	number of samples to draw (either from hessian based covariance or posterior distribution) for final results computation (default = 1000).
chains	number of chains to sample, during HMC or post-optimization importance sampling.
iter	number of interation (default = 1000). Sometimes larger values could be required fom Bayesian estimation
verbose	integer from 0 to 2. Higher values print more information during model fit - for debugging
customPar	logical. If set TRUE leverages the first pass using priors and ensure that the drift diagonal cannot easily go too negative (helps since ctsem > 3.4)
doPar	parallel and multiple fitting if single studies
useSV	if TRUE (default) start values will be used if provided in the list of primary studies
experimental	set TRUE to try new pairwise N function

Value

ctmaFit returns a list containing some arguments supplied, the fitted models, different elements summarizing the main results, model type, and the type of plot that could be performed with the returned object. The arguments in the returned object are activeDirectory, coresToUse, n.latent, n.manifest, and primaryStudyList. The study count is returned as n.studies, the created matrix of loadings of manifest on latent factors is returned as lambda, and a re-organized list of primary studies with some information omitted is returned as studyList. The fitted models for each primary study are found in studyFitList, which is a large list with many elements (e.g., the ctsem model specified by CoTiMA, the rstan model created by ctsem, the fitted rstan model etc.). Further results returned are emprawList (containing the pseudo raw data created), statisticsList (comprising basic stats such as average sample size, no. of measurement points, etc.), a list with modelResults (i.e., DRIFT=model_Drift_Coef, DIFFUSION=model_Diffusion_Coef, T0VAR=model_T0var_Coef, CINT=model_Cint_Coef), and the parameter names internally used. The summary list, which is printed if the summary function is applied to the returned object, comprises "estimates" (the aggregated effects), possible randomEffects (not yet fully working), confidenceIntervals, the minus2ll value and its n.parameters, and possible warning messages (message). Plot type is plot.type=c("drift") and model.type="stanct" ("omx" was deprecated).

Examples

```
# Fit a ctsem model to all three primary studies summarized in
# CoTiMAstudyList_3 and save the three fitted models
## Not run:
CoTiMAInitFit_3 <- ctmaInit(primaryStudies=CoTiMAstudyList_3,
                           n.latent=2,
                           checkSingleStudyResults=FALSE,
                           activeDirectory="/Users/tmp/") # adapt!

summary(CoTiMAInitFit_3)

## End(Not run)
```

ctmaLabels

ctmaLabels

Description

used for consistent labeling of names and parameters

Usage

```
ctmaLabels(
  n.latent = NULL,
  n.manifest = 0,
  lambda = NULL,
  manifestVar = NULL,
  drift = NULL,
  invariantDrift = NULL,
  moderatedDrift = NULL,
  equalDrift = NULL
)
```

Arguments

n.latent	n.latent
n.manifest	n.manifest
lambda	lambda
manifestVar	manifestVar
drift	drift
invariantDrift	invariantDrift
moderatedDrift	moderatedDrift
equalDrift	equalDrift

Value

returns consistently named parameters (e.g., "V1toV2") as well as their symbolic values, which are used to fix or free parameters when fitting a 'CoTiMA' model

ctmaOptimizeInit *ctmaOptimizeInit*

Description

Initial fitting (i.e., applies `ctmaInit`) to a primary study reFit times to capitalize on chance for obtaining a hard-to-find optimal fit. This could be very helpful if a primary yields out-of-range estimates, which could happen if the fitting algorithm unfortunately used random start values that resulted in a locally but not globally optimal fit. Essentially, using `ctmaOptimizeInit` is like gambling, hoping that at least one set of starting values (the number of tries is specified in the `reFits` argument) enables finding the global optimal fit. On unix-like machines (e.g. MacOS), this could be done in parallel mode if `coresToUse > 1`.

Usage

```
ctmaOptimizeInit(
  primaryStudies = NULL,
  activeDirectory = NULL,
  problemStudy = NULL,
  reFits = NULL,
  n.latent = NULL,
  coresToUse = c(1),
  activateRPB = FALSE,
  checkSingleStudyResults = FALSE,
  customPar = TRUE
)
```

Arguments

<code>primaryStudies</code>	list of primary study information created with <code>ctmaPrep</code> or <code>ctmaFitToPrep</code>
<code>activeDirectory</code>	<code>activeDirectory</code>
<code>problemStudy</code>	number (position in list) where the problem study in <code>primaryStudies</code> is found
<code>reFits</code>	how many reFits should be done
<code>n.latent</code>	number of latent variables of the model (has to be specified)!
<code>coresToUse</code>	if neg., the value is subtracted from available cores, else value = cores to use
<code>activateRPB</code>	set to TRUE to receive push messages with 'CoTiMA' notifications on your phone
<code>checkSingleStudyResults</code>	displays estimates from single study 'ctsem' models and waits for user input to continue. Useful to check estimates before they are saved.
<code>customPar</code>	logical. If set TRUE (default) leverages the first pass using priors and ensure that the drift diagonal cannot easily go too negative (helps since <code>ctsem > 3.4</code>)

Value

returns a list with bestFit (= the best fit achieved), all_minus2ll (= all -2ll values for all fitted models), and summary, which is printed if the summary function is applied to the returned object, and which shows the summary information of the ctsem model with the best fit.

Note

All but one of multiple cores are used on unix-type machines for parallel fitting
During fitting, not output is generated. Be patient.

Examples

```
## Not run:
optimFit313 <- ctmaOptimizeInit(primaryStudies=CoTiMAstudyList_3,
                               activeDirectory="/Users/tmp/", # adapt!
                               problemStudy=which(CoTiMAstudyList_3$studyNumbers == 313),
                               reFits=10,
                               n.latent=2)

summary(optimFit313)

## End(Not run)
```

ctmaPlot

ctmaPlot

Description

Forest plot, funnel plots, plots of discrete time cross-lagged and autoregressive effect, and plots of required sample sizes

Usage

```
ctmaPlot(
  ctmaFitObject = NULL,
  activeDirectory = NULL,
  saveFilePrefix = "ctmaPlot",
  activateRPB = FALSE,
  plotCrossEffects = TRUE,
  plotAutoEffects = TRUE,
  timeUnit = "timeUnit (not specified)",
  timeRange = c(),
  yLimitsForEffects = c(),
  mod.number = 1,
  mod.values = -2:2,
  aggregateLabel = "",
  xLabels = NULL,
```

```

    undoTimeScaling = TRUE,
    ...
)

```

Arguments

ctmaFitObject	'CoTiMA' Fit object
activeDirectory	defines another active directory than the one used in ctmaInitFit
saveFilePrefix	Prefix used for saved plots
activateRPB	set to TRUE to receive push messages with 'CoTiMA' notifications on your phone
plotCrossEffects	logical
plotAutoEffects	logical
timeUnit	label for x-axis when plotting discrete time plots
timeRange	vector describing the time range for x-axis as sequence from/to/stepSize (e.g., c(1, 144, 1))
yLimitsForEffects	range for y-axis
mod.number	moderator number that should be used for plots
mod.values	moderator values that should be used for plots
aggregateLabel	label to indicate aggregated discrete time effects
xLabels	labes used for x-axis
undoTimeScaling	if TRUE, the original time scale is used (timeScale argument possibly used in ctmaInit is undone)
...	arguments passed through to plot()

Value

depending on the CoTiMA fit object supplied, generates funnel plots, forest plots, discrete time plots of autoregressive and cross-lagged effects, plots of required samples sizes across a range of discrete time intervals to achieve desired levels of statistical power, and post hoc power of primary studies. Plots are saved to disk.

Examples

```

## Not run:
# cannot run without proper activeDirectory specified. Adapt!
CoTiMAFullFit_3$activeDirectory <- "/Users/tmp/" # adapt!
plot(ctmaFitList(CoTiMAInitFit_3, CoTiMAFullFit_3),
     timeUnit="Months", timeRange=c(1, 144, 1),
     plotAutoEffects=FALSE)

```

```
## End(Not run)

## Not run:
# cannot run without proper activeDirectory specified. Adapt!
CoTiMABiG_D_B0$activeDirectory <- "/Users/tmp/" # adapt!
plot(CoTiMABiG_D_B0)

## End(Not run)
```

ctmaPower

ctmaPower

Description

Fits a full invariant model to a list of primary studies and performs analyses of expected (post hoc) power and required sample sizes.

Usage

```
ctmaPower(
  ctmaInitFit = NULL,
  activeDirectory = NULL,
  statisticalPower = c(),
  failSafeN = NULL,
  failSafeP = NULL,
  timeRange = NULL,
  useMBESS = FALSE,
  coresToUse = 1,
  digits = 4,
  indVarying = FALSE,
  activateRPB = FALSE,
  silentOverwrite = FALSE,
  loadAllInvFit = c(),
  saveAllInvFit = c(),
  loadAllInvWOSingFit = c(),
  saveAllInvWOSingFit = c(),
  skipScaling = TRUE,
  useSampleFraction = NULL,
  optimize = TRUE,
  nopriors = TRUE,
  finishsamples = NULL,
  iter = NULL,
  chains = NULL,
  verbose = NULL,
  customPar = TRUE
)
```

Arguments

ctmaInitFit	object to which all single 'ctsem' fits of primary studies has been assigned to (i.e., what has been returned by <code>ctmaInit</code>)
activeDirectory	defines another active directory than the one used in <code>ctmaInit</code>
statisticalPower	vector of requested statistical power values
failSafeN	sample size used to determine across which time intervals effects become non-significant
failSafeP	p-value used to determine across which time intervals effects become non-significant
timeRange	vector describing the time range for x-axis as sequence from/to/stepSize (e.g., <code>c(1, 144, 1)</code>)
useMBESS	use 'MBESS' package to calculate statistical power (slower)
coresToUse	if negative, the value is subtracted from available cores, else value = cores to use
digits	number of digits used for rounding (in outputs)
indVarying	Allows continuous time intercepts to vary at the individual level (random effects model, accounts for unobserved heterogeneity)
activateRPB	set to TRUE to receive push messages with 'CoTiMA' notifications on your phone
silentOverwrite	overwrite old files without asking
loadAllInvFit	load the fit of fully constrained 'CoTiMA' model
saveAllInvFit	save the fit of fully constrained 'CoTiMA' model
loadAllInvWOSingFit	load series of fits of fully constrained 'CoTiMA' model with single cross effects excluded, respectively
saveAllInvWOSingFit	save series of fits of fully constrained 'CoTiMA' model with single cross effects excluded, respectively
skipScaling	does not (re-)scale raw data (re-scaling of imported pseudo raw data achieves correlations = 1)
useSampleFraction	to speed up debugging. Provided as fraction (e.g., 1/10)
optimize	if set to FALSE, Stan's Hamiltonian Monte Carlo sampler is used (default = TRUE = maximum a posteriori / importance sampling) .
nopriors	if TRUE, any priors are disabled – sometimes desirable for optimization
finishesamples	number of samples to draw (either from hessian based covariance or posterior distribution) for final results computation (default = 1000).
iter	number of iterations (default = 1000). Sometimes larger values could be required from Bayesian estimation
chains	number of chains to sample, during HMC or post-optimization importance sampling.

verbose	integer from 0 to 2. Higher values print more information during model fit – for debugging
customPar	logical. If set TRUE (default) leverages the first pass using priors and ensure that the drift diagonal cannot easily go too negative (helps since ctsem > 3.4)

Value

ctmaPower returns a list containing some arguments supplied, a fitted model with all (!) parameters invariant across primary studies, different elements summarizing the main results, model type, and the type of plot that could be performed with the returned object. The arguments in the returned object are activeDirectory, coresToUse, n.latent, n.manifest, and primaryStudyList. A further result returned is n.studies = 1 (required for proper plotting). Further arguments, which are just copied from the init-fit object supplied, are, n.latent, studyList, and the statisticsList. The fitted model is found in studyFitList, which is a large list with many elements (e.g., the ctsem model specified by CoTiMA, the rstan model created by ctsem, the fitted rstan model etc.). Further results returned are a list with modelResults (i.e., DRIFT=DRIFT, DIFFUSION=DIFFUSION, TOVAR=TOVAR, CINT=NULL) and the paramter names internally used. The summary list, which is printed if the summary function is applied to the returned object, contains "estimates", which is itself a list comprising "Estimates of Model with all Effects Invariant", "Requested Statistical Power" (which just returns the argument statisticalPower), "Power (post hoc) for Drift Effects", "Required Sample Sizes" "Effect Sizes (based on discrete-time calcs; used for power calcs.)", and "Range of significant effects" (across which intervals effects were significant). Plot type is plot.type=c("power") and model.type="stanct" ("omx" was deprecated).

Examples

```
## Not run:
CoTiMAInitFit_D_B0$activeDirectory <- "/Users/tmp/" # adapt!
CoTiMAPower_D_B0 <- ctmaPower(ctmaInitFit=CoTiMAInitFit_D_B0,
                             statisticalPower = c(.50, .80, .95),
                             finishsamples = 10000)

summary(CoTiMAPower_D_B0)

## End(Not run)
```

ctmaPRaw

ctmaPRaw

Description

Converts empirical correlation matrices to pseudo raw data (i.e. random data, that perfectly reproduce the correlations)

Usage

```
ctmaPraw(
  empCovMat = NULL,
  empNMat = matrix(0, 0, 0),
  empN = NULL,
  studyNumber = NULL,
  empMeanVector = NULL,
  empVarVector = NULL,
  activateRPB = FALSE,
  experimental = FALSE
)
```

Arguments

empCovMat	empirical primary study covariance matrix
empNMat	matrix of (possibly pairwise) N
empN	N (in case of listwise N)
studyNumber	internal number
empMeanVector	vector of means for all variables, usually 0
empVarVector	vector of variances for all variables, usually 1
activateRPB	set TRUE to receive push messages with 'CoTiMA' notifications on your phone
experimental	set TRUE to try new pairwise N function

ctmaPrep

ctmaPrep

Description

Combines information of primary studies into a list object and returns this list. This list is then used as input to fit 'ctsem' models. Primary study information is expected to be assigned to 'numbered' objects. Some of these objects are pre-defined (e.g., 'empcov', 'ageM'). Most of the pre-defined objects could be empty, or they could be dropped by entering their names in the excludedElements-object (e.g., excludedElements = c('ageM')), but dropping them is not really necessary. Additional elements could also be added, which could be useful to put together all information about primary studies at the convenience of the researcher.

Usage

```
ctmaPrep(
  selectedStudies = NULL,
  excludedElements = NULL,
  addElements = NULL,
  digits = 4,
  moderatorLabels = NULL,
```

```

    moderatorValues = NULL,
    summary = TRUE,
    activeDirectory = NULL
)

```

Arguments

selectedStudies	Vector of primary study numbers (numeric values with no leading 0; e.g., '2' but not '02')
excludedElements	Vector of predefined objects used to code primary study information. Some predefined objects are strongly defined; they have to be used in a special way because they are actually used in subsequent analyses. Some other objects could be used at the researcher's convenience (information is just collected). Strongly predefined objects are 'delta_t' (vector of time intervals; the only mandatory requirement; should be of the type c(NA, NA) in cases when raw data are provided), 'sampleSize' (single number), 'pairwiseN' (matrix of pairwise N; could be used if correlation matrix is based on pairwise N), 'empcov' (correlation matrix), 'moderator' (vector of numbers; could be continuous or categorical), 'startValues' (vector of start values), 'rawData' (information about file name and structure of raw data), 'empMeans' (means for variables; usually 0), and 'empVars' (variances for variables; usually 1). Weakly predefined objects are 'studyNumber' (intended as a special number used for the outputs of subsequently fitted CoTiMA models), 'source' (intended as vector of authors' names and publication year), 'ageM' (intended as value indicating the mean age of participants in a primary study), 'malePercent' (intended as value indicating the percentage of male participants in a primary study), 'occupation' (intended as vector of character strings representing the occupations of participants in a primary study), 'country' (intended as single character string representing the country in which a primary study was conducted), 'alphas' (intended as vector of Cronbach's alphas of the variables of a primary study; not yet functional), and 'targetVariables' (intended as vector of character strings representing information about the variables used).'
addElement	User-added objects that are handled as the weakly predefined objects. The major purpose is to collect information a researcher regards as important.
digits	Rounding used for summary function
moderatorLabels	character vector of names
moderatorValues	list of character vectors
summary	if TRUE (default) creates summary table and xlsx sheets. Could be set to FALSE in case of errors.
activeDirectory	Mandatory. If subsequent fitting is done using different folders or on different computers, it can be changed so that raw data files can be loaded.

Value

List of primary studies and parameters for the following CoTiMA (plus StudyInformation which could be saved to Excel)

Note

The following example shows information a researcher has about three studies, which have the numbers '2', '4' and '17'. All information about these studies are stored in objects ending with '2', '4', and '17', respectively. In most instances, one relevant piece of information is the empirical correlation (or covariance) matrix reported in this study, which is stored in the objects 'empcov2', 'empcov4', and 'empcov17'. Note that full and symmetric matrices are required for ctmaPrep. Usually, sample sizes ('sampleSize2', 'sampleSize4', & 'sampleSize17') and time lags ('delta_t2', 'delta_t4', & 'delta_t17'), are required, too.

Examples

```
# First Study
empcov2 <- matrix(c(1.00, 0.45, 0.57, 0.18,
                   0.45, 1.00, 0.31, 0.66,
                   0.57, 0.31, 1.00, 0.40,
                   0.18, 0.66, 0.40, 1.00), nrow=4, ncol=4)

delta_t2 <- 12
sampleSize2 <- 148
moderator2 <- c(1, 0.72)
source2 <- c("Houkes, I,", "Janssen, P, P, M,", "de Jonge, J",
            "& Bakker, A, B", "Study1", "2003")
addedByResearcher2 <- "something you want to add"

# Second Study
empcov3 <- matrix(c(1.00, 0.43, 0.71, 0.37,
                   0.43, 1.00, 0.34, 0.69,
                   0.71, 0.34, 1.00, 0.50,
                   0.37, 0.69, 0.50, 1.00), nrow=4, ncol=4)

delta_t3 <- 12
sampleSize3 <- 88
moderator3 <- c(1, 0.72)
source3 <- c("Houkes, I,", "Janssen, P, P, M,", "de Jonge, J",
            "& Bakker, A, B", "Study2", "2003")
addedByResearcher3 <- ""

# Third Study
empcov313 <- matrix(c(1.00, 0.38, 0.54, 0.34, 0.60, 0.28,
                    0.38, 1.00, 0.34, 0.68, 0.28, 0.68,
                    0.54, 0.34, 1.00, 0.47, 0.66, 0.39,
                    0.34, 0.68, 0.47, 1.00, 0.38, 0.72,
                    0.60, 0.28, 0.66, 0.38, 1.00, 0.38,
                    0.28, 0.68, 0.39, 0.72, 0.38, 1.00), nrow=6, ncol=6)

delta_t313 <- c(1.5, 1.5)
sampleSize313 <- 335
moderator313 <- c(0.8, 2.47)
source313 <- c("Demerouti", "Bakker", "& Bulters", "2004")
```

```

addedByResearcher313 <- "check correlation matrix"

# Add Labels and Values for Moderators (just for optional excel tables)
moderatorLabels <- c("Control", "Social Support")
moderatorValues <- list("continuous", c("1 = very low", "2 = low",
    "3 = medium", "4 = high", "5 = very high"))

CoTiMAstudyList_3 <- ctmaPrep(selectedStudies = c(2, 3, 313),
    activeDirectory="/user/",
    excludedElements = "ageM",
    addElements = "addedByResearcher",
    moderatorLabels=moderatorLabels,
    moderatorValues=moderatorValues)

```

ctmaPub

ctmaPub

Description

Compute publication and citation scores for studies based on the (team of) authors' publication scores .

Usage

```

ctmaPub(
  getPubObj = NULL,
  primaryStudyList = NULL,
  yearsToExclude = 0,
  recency = 5,
  targetYear = NULL,
  indFUN = "sum",
  colFUN = "mean",
  addAsMod = FALSE
)

```

Arguments

<code>getPubObj</code>	publication information compiled with ctmaGetPub
<code>primaryStudyList</code>	vector with numbers of studies (e.g., c(1,3); requires source1 and source3 to be available)
<code>yearsToExclude</code>	years to exclude from publications
<code>recency</code>	years before targetYear that are considered for recency analysis
<code>targetYear</code>	year (default = last year) after which publications are ignored
<code>indFUN</code>	function (default = sum) how publications of each author within a collective (team) are summarized

colFUN	function (default = mean) how publications all authors of collective (team) are summarized
addAsMod	currently disabled. Add to existing moderator objects (or create them) in primaryStudyList, which is part of the returned object

Value

returns NEPP (= the `*number*` of studies published by the authors of the primary studies supplied UNTIL the year when the primary study was published), NEPPRecency (like NEPP, but limited to the number of years before the publication as specified with the recency argument), "Meaning of NEPP" and "Meaning of NEPPRecency" which explain what `*number*` exactly means (e.g., could be the mean of the sum of each author's publication, or the sum of the maximum publications per year of the authors), and "primaryStudyList(full)", which just returns the primaryStudyList supplied).

Examples

```
pubResults_6 <- ctmaPub(getPubObj=pubList_8,
                       primaryStudyList=CoTiMAstudyList_6)
summary(pubResults_6)
```

ctmaSaveFile	<i>ctmaSaveFile</i>
--------------	---------------------

Description

Internal function to save files

Usage

```
ctmaSaveFile(
  activateRPB,
  activeDirectory = activeDirectory,
  SaveObject,
  FileName,
  Directory,
  silentOverwrite = FALSE
)
```

Arguments

activateRPB set TRUE to receive push messages with 'CoTiMA' notifications on your phone
 activeDirectory directory name

SaveObject	object to save
FileName	filename
Directory	directory to save file in
silentOverwrite	override old files without asking

Value

No return value. Just saves files

<code>ctmaStanResample</code>	<i>ctmaStanResample</i>
-------------------------------	-------------------------

Description

re-sample from a fitted stanct model to achieve desired number of finishsamples (could be useful to prevent exhausted memory)

Usage

```
ctmaStanResample(ctmaFittedModel = NULL, nsamples = 25, overallSamples = 500)
```

Arguments

<code>ctmaFittedModel</code>	a 'CoTiMA' fit object, usually with few 'finishsamples' to prevent memory exhaustion
<code>nsamples</code>	sample size per run
<code>overallSamples</code>	overall samples size to be achieved

Value

returns a CoTiMA fit object with an increased number of finish samples

 ctmaSV

ctmaSV

Description

derives start values by average discrete time SEM effects, converting them to continuous time, and inversely apply transformations used by 'ctsem'

Usage

```
ctmaSV(
  ctmaInitFit = NULL,
  activeDirectory = NULL,
  primaryStudies = NULL,
  coresToUse = 1,
  replaceSV = TRUE
)
```

Arguments

ctmaInitFit object to which all single 'ctsem' fits of primary studies has been assigned to (i.e., what has been returned by [ctmaInit](#))

activeDirectory defines another active directory than the one used in [ctmaInit](#)

primaryStudies if ctmaInitFit does not contain the primaryStudies object created with [ctmaPrep](#) it could be added

coresToUse if negative, the value is subtracted from available cores, else value = cores to use

replaceSV if TRUE replaces startValues in primaryStudies, else it saves them as list element inits

Value

returns a modified list of primary studies with starting values added or replaced

Examples

```
## Not run:
newPrimaryStudyList <- ctmaSV(ctmaInitFit=CoTiMAInitFit_6)

## End(Not run)
```

`delta_t128`*delta_t128 example vector*

Description

delta_t128 example vector

Usage

`delta_t128`

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

`delta_t18`*delta_t18 example vector*

Description

delta_t18 example vector

Usage

`delta_t18`

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

delta_t2	<i>delta_t2 example vector</i>
----------	--------------------------------

Description

delta_t2 example vector

Usage

delta_t2

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

delta_t201	<i>delta_t201 example vector</i>
------------	----------------------------------

Description

delta_t201 example vector

Usage

delta_t201

Format

An object of class `numeric` of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

delta_t3 *delta_t3 example vector*

Description

delta_t3 example vector

Usage

delta_t3

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

delta_t313 *delta_t313 example vector*

Description

delta_t313 example vector

Usage

delta_t313

Format

An object of class numeric of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

delta_t32

delta_t32 example vector

Description

delta_t32 example vector

Usage

delta_t32

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

demands128

demands128 example vector

Description

demands128 example vector

Usage

demands128

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

demands18

demands18 example vector

Description

demands18 example vector

Usage

demands18

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

demands2

demands2 example vector

Description

demands2 example vector

Usage

demands2

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

demands201

demands201 example vector

Description

demands201 example vector

Usage

demands201

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

demands3

demands3 example vector

Description

demands3 example vector

Usage

demands3

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

demands313

demands313 example vector

Description

demands313 example vector

Usage

demands313

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

demands32

demands32 example vector

Description

demands32 example vector

Usage

demands32

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

dl_link	<i>dl_link example path</i>
---------	-----------------------------

Description

dl_link example path

Usage

dl_link

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

empcov128	<i>empcov128 example matrix</i>
-----------	---------------------------------

Description

empcov128 example matrix

Usage

empcov128

Format

An object of class list of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

empcov18

empcov18 example matrix

Description

empcov18 example matrix

Usage

empcov18

Format

An object of class `matrix` (inherits from `array`) with 4 rows and 4 columns.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

empcov2

empcov2 example matrix

Description

empcov2 example matrix

Usage

empcov2

Format

An object of class `matrix` (inherits from `array`) with 4 rows and 4 columns.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

empcov201

empcov201 example matrix

Description

empcov201 example matrix

Usage

empcov201

Format

An object of class `matrix` (inherits from `array`) with 6 rows and 6 columns.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

empcov3

empcov3 example matrix

Description

empcov3 example matrix

Usage

empcov3

Format

An object of class `matrix` (inherits from `array`) with 4 rows and 4 columns.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

empcov313

empcov313 example matrix

Description

empcov313 example matrix

Usage

empcov313

Format

An object of class `matrix` (inherits from `array`) with 6 rows and 6 columns.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

empcov32

empcov32 example matrix

Description

empcov32 example matrix

Usage

empcov32

Format

An object of class `matrix` (inherits from `array`) with 4 rows and 4 columns.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

malePercent128 *malePercent128 example vector*

Description

malePercent128 example vector

Usage

malePercent128

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

malePercent18 *malePercent18 example vector*

Description

malePercent18 example vector

Usage

malePercent18

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

malePercent2 *malePercent2 example vector*

Description

malePercent2 example vector

Usage

malePercent2

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

malePercent201 *malePercent201 example vector*

Description

malePercent201 example vector

Usage

malePercent201

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

malePercent3 *malePercent3 example vector*

Description

malePercent3 example vector

Usage

malePercent3

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

malePercent313 *malePercent313 example vector*

Description

malePercent313 example vector

Usage

malePercent313

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

malePercent32 *malePercent32 example vector*

Description

malePercent32 example vector

Usage

malePercent32

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

moderator128 *moderator128 example vector*

Description

moderator128 example vector

Usage

moderator128

Format

An object of class numeric of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

moderator18

moderator18 example vector

Description

moderator18 example vector

Usage

moderator18

Format

An object of class `numeric` of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

moderator2

moderator2 example vector

Description

moderator2 example vector

Usage

moderator2

Format

An object of class `numeric` of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

moderator201 *moderator201 example vector*

Description

moderator201 example vector

Usage

moderator201

Format

An object of class `numeric` of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

moderator3 *moderator3 example vector*

Description

moderator3 example vector

Usage

moderator3

Format

An object of class `numeric` of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

moderator313

moderator313 example vector

Description

moderator313 example vector

Usage

moderator313

Format

An object of class `numeric` of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

moderator32

moderator32 example vector

Description

moderator32 example vector

Usage

moderator32

Format

An object of class `numeric` of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

moderatorLabels *moderatorLabels example vector*

Description

moderatorLabels example vector

Usage

moderatorLabels

Format

An object of class character of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

moderatorValues *moderatorValues example vector*

Description

moderatorValues example vector

Usage

moderatorValues

Format

An object of class list of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

occupation128 *occupation128 example vector*

Description

occupation128 example vector

Usage

occupation128

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

occupation18 *occupation18 example vector*

Description

occupation18 example vector

Usage

occupation18

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

occupation2 *occupation2 example vector*

Description

occupation2 example vector

Usage

occupation2

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

occupation201 *occupation201 example vector*

Description

occupation201 example vector

Usage

occupation201

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

occupation3

occupation3 example vector

Description

occupation3 example vector

Usage

occupation3

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

occupation313

occupation313 example vector

Description

occupation313 example vector

Usage

occupation313

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

occupation32	<i>occupation32 example vector</i>
--------------	------------------------------------

Description

occupation32 example vector

Usage

occupation32

Format

An object of class character of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

pairwiseN128	<i>pairwiseN128 example vector</i>
--------------	------------------------------------

Description

pairwiseN128 example vector

Usage

pairwiseN128

Format

An object of class list of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

plot.CoTiMAFit	<i>plot.CoTiMAFit</i>
----------------	-----------------------

Description

call `ctmaPlot` if a `CoTiMAFit` object is supplied to `plot()`

Usage

```
## S3 method for class 'CoTiMAFit'  
plot(x, ...)
```

Arguments

x	list
...	further arguments to be passed through to <code>summary()</code>

Value

returns a call to `'ctmaPlot'`, which is used to plot `CoTiMA` fit objects

pubList_8	<i>pubList_8 example list</i>
-----------	-------------------------------

Description

pubList_8 example list

Usage

```
pubList_8
```

Format

An object of class `CoTiMAFit` of length 9.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

rawData128

rawData128 example list

Description

rawData128 example list

Usage

rawData128

Format

An object of class list of length 7.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

recodeVariables128

recodeVariables128 example vector

Description

recodeVariables128 example vector

Usage

recodeVariables128

Format

An object of class character of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

results128

results128 example list

Description

results128 example list

Usage

results128

Format

An object of class list of length 2.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

sampleSize128

sampleSize128 example vector

Description

sampleSize128 example vector

Usage

sampleSize128

Format

An object of class NULL of length 0.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

sampleSize18 *sampleSize18 example vector*

Description

sampleSize18 example vector

Usage

sampleSize18

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

sampleSize2 *sampleSize2 example vector*

Description

sampleSize2 example vector

Usage

sampleSize2

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

sampleSize201 *sampleSize201 example vector*

Description

sampleSize201 example vector

Usage

sampleSize201

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

sampleSize3 *sampleSize3 example vector*

Description

sampleSize3 example vector

Usage

sampleSize3

Format

An object of class `numeric` of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

sampleSize313 *sampleSize313 example vector*

Description

sampleSize313 example vector

Usage

sampleSize313

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

sampleSize32 *sampleSize32 example vector*

Description

sampleSize32 example vector

Usage

sampleSize32

Format

An object of class numeric of length 1.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

source128

source128 example vector

Description

source128 example vector

Usage

source128

Format

An object of class character of length 4.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

source2

source2 example vector

Description

source2 example vector

Usage

source2

Format

An object of class character of length 6.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

source201

source201 example vector

Description

source201 example vector

Usage

source201

Format

An object of class character of length 6.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

source3

source3 example vector

Description

source3 example vector

Usage

source3

Format

An object of class character of length 6.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

 source313

source313 example vector

Description

source313 example vector

Usage

source313

Format

An object of class character of length 4.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

 summary.CoTiMAFit

summary.CoTiMAFit

Description

defines summary for 'CoTiMA' fit objects

Usage

```
## S3 method for class 'CoTiMAFit'
summary(object, ...)
```

Arguments

object one CoTiMAFit object or more as ctmaFitList(object1, object2, ...)
 ... further arguments to be passed through to summary()

Value

returns a printed summary of a 'CoTiMA' fit object

targetVariables128 *targetVariables128 example vector*

Description

targetVariables128 example vector

Usage

targetVariables128

Format

An object of class character of length 7.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

targetVariables2 *targetVariables2 example vector*

Description

targetVariables2 example vector

Usage

targetVariables2

Format

An object of class character of length 4.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

targetVariables3 *targetVariables3 example vector*

Description

targetVariables3 example vector

Usage

targetVariables3

Format

An object of class character of length 4.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

targetVariables313 *targetVariables313 example vector*

Description

targetVariables313 example vector

Usage

targetVariables313

Format

An object of class character of length 6.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

variableNames128 *variableNames128 example vector*

Description

variableNames128 example vector

Usage

variableNames128

Format

An object of class character of length 9.

Author(s)

C. Dormann & M. Homburg <CoTiMA@uni-mainz.org>

Index

* datasets

CoTiMAStanctArgs, 29

* data

A128, 5

A313, 6

addedByResearcher2, 6

addedByResearcher3, 7

addedByResearcher313, 7

ageM128, 8

ageM18, 8

ageM2, 9

ageM201, 9

ageM3, 10

ageM313, 10

ageM32, 11

ageSD128, 11

ageSD18, 12

ageSD2, 12

ageSD201, 13

ageSD3, 13

ageSD313, 14

ageSD32, 14

alphas128, 15

alphas313, 15

burnout128, 16

burnout18, 16

burnout2, 17

burnout201, 17

burnout3, 18

burnout313, 18

burnout32, 19

combineVariables128, 19

combineVariablesNames128, 20

CoTiMABiG_D_BO, 20

CoTiMAFullFit_3, 21

CoTiMAFullFit_6, 21

CoTiMAFullFit_6_new, 22

CoTiMAFullInv23Fit_6, 22

CoTiMAFullInvEq23Fit_6, 23

CoTiMAInitFit_3, 23

CoTiMAInitFit_6, 24

CoTiMAInitFit_6_new, 24

CoTiMAInitFit_6_NUTS, 25

CoTiMAInitFit_D_BO, 25

CoTiMAMod1onFullFit_6, 26

CoTiMAMod1onFullFit_6_cats12, 26

CoTiMAMod2on23Fit_6, 27

CoTiMAoptimFit313, 27

CoTiMAPart134Inv3Fit_6, 28

CoTiMAPower_D_BO, 28

CoTiMAstudyList_3, 29

CoTiMAstudyList_6, 30

CoTiMAstudyList_6_new, 30

country128, 31

country18, 31

country2, 32

country201, 32

country3, 33

country313, 33

country32, 34

delta_t128, 65

delta_t18, 65

delta_t2, 66

delta_t201, 66

delta_t3, 67

delta_t313, 67

delta_t32, 68

demands128, 68

demands18, 69

demands2, 69

demands201, 70

demands3, 70

demands313, 71

demands32, 71

d1_link, 72

empcov128, 72

empcov18, 73

empcov2, 73

- empcov201, 74
- empcov3, 74
- empcov313, 75
- empcov32, 75
- malePercent128, 76
- malePercent18, 76
- malePercent2, 77
- malePercent201, 77
- malePercent3, 78
- malePercent313, 78
- malePercent32, 79
- moderator128, 79
- moderator18, 80
- moderator2, 80
- moderator201, 81
- moderator3, 81
- moderator313, 82
- moderator32, 82
- moderatorLabels, 83
- moderatorValues, 83
- occupation128, 84
- occupation18, 84
- occupation2, 85
- occupation201, 85
- occupation3, 86
- occupation313, 86
- occupation32, 87
- pairwiseN128, 87
- pubList_8, 88
- rawData128, 89
- recodeVariables128, 89
- results128, 90
- sampleSize128, 90
- sampleSize18, 91
- sampleSize2, 91
- sampleSize201, 92
- sampleSize3, 92
- sampleSize313, 93
- sampleSize32, 93
- source128, 94
- source2, 94
- source201, 95
- source3, 95
- source313, 96
- targetVariables128, 97
- targetVariables2, 97
- targetVariables3, 98
- targetVariables313, 98
- variableNames128, 99
- A128, 5
- A313, 6
- addedByResearcher2, 6
- addedByResearcher3, 7
- addedByResearcher313, 7
- ageM128, 8
- ageM18, 8
- ageM2, 9
- ageM201, 9
- ageM3, 10
- ageM313, 10
- ageM32, 11
- ageSD128, 11
- ageSD18, 12
- ageSD2, 12
- ageSD201, 13
- ageSD3, 13
- ageSD313, 14
- ageSD32, 14
- alphas128, 15
- alphas313, 15
- burnout128, 16
- burnout18, 16
- burnout2, 17
- burnout201, 17
- burnout3, 18
- burnout313, 18
- burnout32, 19
- combineVariables128, 19
- combineVariablesNames128, 20
- CoTiMABiG_D_B0, 20
- CoTiMAFullFit_3, 21
- CoTiMAFullFit_6, 21
- CoTiMAFullFit_6_new, 22
- CoTiMAFullInv23Fit_6, 22
- CoTiMAFullInvEq23Fit_6, 23
- CoTiMAInitFit_3, 23
- CoTiMAInitFit_6, 24
- CoTiMAInitFit_6_new, 24
- CoTiMAInitFit_6_NUTS, 25
- CoTiMAInitFit_D_B0, 25
- CoTiMAMod1onFullFit_6, 26
- CoTiMAMod1onFullFit_6_cats12, 26
- CoTiMAMod2on23Fit_6, 27
- CoTiMAoptimFit313, 27

- CoTiMAPart134Inv3Fit_6, 28
- CoTiMAPower_D_B0, 28
- CoTiMAStanctArgs, 29
- CoTiMAstudyList_3, 29
- CoTiMAstudyList_6, 30
- CoTiMAstudyList_6_new, 30
- country128, 31
- country18, 31
- country2, 32
- country201, 32
- country3, 33
- country313, 33
- country32, 34
- ctmaAllInvFit, 34
- ctmaBiG, 36
- ctmaBiGOMX, 37
- ctmaCombPRaw, 38
- ctmaCompFit, 39
- ctmaCorRel, 39
- ctmaEmpCov, 40
- ctmaEqual, 39, 42
- ctmaFit, 39, 42, 43, 47
- ctmaFitList, 46
- ctmaFitToPrep, 47, 52
- ctmaGetPub, 47, 61
- ctmaInit, 36, 44, 47, 48, 52, 54, 56, 64
- ctmaLabels, 51
- ctmaOptimizeInit, 52
- ctmaPlot, 53, 88
- ctmaPower, 55
- ctmaPRaw, 57
- ctmaPrep, 44, 47–49, 52, 58, 64
- ctmaPub, 61
- ctmaSaveFile, 62
- ctmaStanResample, 63
- ctmaSV, 64

- delta_t128, 65
- delta_t18, 65
- delta_t2, 66
- delta_t201, 66
- delta_t3, 67
- delta_t313, 67
- delta_t32, 68
- demands128, 68
- demands18, 69
- demands2, 69
- demands201, 70
- demands3, 70

- demands313, 71
- demands32, 71
- dl_link, 72

- empcov128, 72
- empcov18, 73
- empcov2, 73
- empcov201, 74
- empcov3, 74
- empcov313, 75
- empcov32, 75

- malePercent128, 76
- malePercent18, 76
- malePercent2, 77
- malePercent201, 77
- malePercent3, 78
- malePercent313, 78
- malePercent32, 79
- moderator128, 79
- moderator18, 80
- moderator2, 80
- moderator201, 81
- moderator3, 81
- moderator313, 82
- moderator32, 82
- moderatorLabels, 83
- moderatorValues, 83

- occupation128, 84
- occupation18, 84
- occupation2, 85
- occupation201, 85
- occupation3, 86
- occupation313, 86
- occupation32, 87

- pairwiseN128, 87
- plot.CoTiMAFit, 88
- pubList_8, 88

- rawData128, 89
- recodeVariables128, 89
- results128, 90

- sampleSize128, 90
- sampleSize18, 91
- sampleSize2, 91
- sampleSize201, 92
- sampleSize3, 92

sampleSize313, [93](#)
sampleSize32, [93](#)
source128, [94](#)
source2, [94](#)
source201, [95](#)
source3, [95](#)
source313, [96](#)
summary.CoTiMAFit, [96](#)

targetVariables128, [97](#)
targetVariables2, [97](#)
targetVariables3, [98](#)
targetVariables313, [98](#)

variableNames128, [99](#)