

Package ‘Rnmr1D’

November 10, 2021

Type Package

Title Perform the Complete Processing of a Set of Proton Nuclear
Magnetic Resonance Spectra

Version 1.3.0

Date 2021-11-08

Copyright Institut national de recherche pour l’agriculture,
l’alimentation et l’environnement (INRAE)

URL <https://github.com/INRA/Rnmr1D>

Encoding UTF-8

Maintainer Daniel Jacob <daniel.jacob@inrae.fr>

Description Perform the complete processing of a set of proton nuclear magnetic resonance spectra from the free induction decay (raw data) and based on a processing sequence (macro-command file). An additional file specifies all the spectra to be considered by associating their sample code as well as the levels of experimental factors to which they belong. More detail can be found in Jacob et al. (2017) <[doi:10.1007/s11306-017-1178-y](https://doi.org/10.1007/s11306-017-1178-y)>.

Depends R (>= 3.1.0)

License GPL (>= 2)

Imports Rcpp (>= 0.12.7), base64enc (>= 0.1), MASS (>= 7.3), Matrix,
methods, doParallel (>= 1.0.11), foreach (>= 1.4.4), igraph (>= 1.2.1), impute (>= 1.54.0), MassSpecWavelet (>= 1.46.0), ptw (>= 1.9), signal (>= 0.7), speaq (>= 2.3.3), XML (>= 3.98), ggplot2 (>= 3.0.0), plotly (>= 4.8.0), plyr (>= 1.8.4), minqa (>= 1.2.4)

LinkingTo Rcpp

RoxygenNote 7.1.1

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation yes

Author Daniel Jacob [cre, aut] (<<https://orcid.org/0000-0002-6687-7169>>),
Catherine Deborde [ctb],
Marie Lefebvre [ctb]

Repository CRAN

Date/Publication 2021-11-10 08:00:11 UTC

R topics documented:

| | |
|-----------------------------|-----------|
| checkMacroCmdFile | 2 |
| detectCores | 3 |
| doProcCmd | 4 |
| doProcessing | 5 |
| generateMetadata | 6 |
| getBucketsDataset | 7 |
| getBucketsTable | 8 |
| getClusters | 9 |
| getMergedDataset | 11 |
| getSnrDataset | 11 |
| getSpectraData | 12 |
| ggplotClusters | 12 |
| ggplotCriterion | 13 |
| ggplotLoadings | 13 |
| ggplotPlotly | 14 |
| ggplotScores | 15 |
| plotClusters | 16 |
| plotCriterion | 16 |
| plotLoadings | 17 |
| plotScores | 18 |
| plotSpecMat | 19 |
| RWrapperCMD1D | 20 |
| setLogFile | 20 |
| setPPMbounds | 21 |
| Spec1rDoProc | 21 |
| Spec1rProcpa | 22 |
| Index | 24 |

| | |
|-------------------|--------------------------|
| checkMacroCmdFile | <i>checkMacroCmdFile</i> |
|-------------------|--------------------------|

Description

checkMacroCmdFile Check if the macro-commands included in the input file (commandfile) are compliant with the allowed commands.

Usage

```
checkMacroCmdFile(commandfile)
```

Arguments

commandfile The macro-commands file - the allowed commands are : 'align', 'warp', 'clupa', 'gbaseline', 'baseline', 'qnmrbline', 'airpls', 'binning', 'calibration', 'normalisation', 'denoising', 'bucket', 'zero'.

Value

return 1 if the macro-commands included in the input file are compliant, 0 if not.

See Also

the NMRProcFlow online documentation <https://nmrprocflow.org/> and especially the Macro-command Reference Guide (<https://nmrprocflow.org/themes/pdf/Macrocommand.pdf>)

Examples

```
data_dir <- system.file("extra", package = "Rnmr1D")
CMDFILE <- file.path(data_dir, "NP_macro_cmd.txt")
ret <- checkMacroCmdFile(CMDFILE)
```

detectCores

detectCores

Description

detectCores is simply a shortcut for parallel::detectCores().

Usage

```
detectCores(...)
```

Arguments

... See parallel::detectCores

`doProcCmd`*doProcCmd*

Description

`doProcCmd` it process the Macro-commands string array specified at input.

Usage

```
doProcCmd(specObj, cmdstr, ncpu = 1, debug = FALSE)
```

Arguments

| | |
|----------------------|---|
| <code>specObj</code> | a complex list return by <code>doProcessing</code> function. See the manual page of the doProcessing function for more details on its structure. |
| <code>cmdstr</code> | the Macro-commands string array; See the Macro-command Reference Guide (https://nmrprocflow.org/themes/pdf/Macrocommand.pdf) to have more details about macro-commands. |
| <code>ncpu</code> | The number of cores [default: 1] |
| <code>debug</code> | a boolean to specify if we want the function to be more verbose. |

Value

`specMat` : a 'specMat' object - See the manual page of the [doProcessing](#) function for more details on its structure

Examples

```
data_dir <- system.file("extra", package = "Rnmr1D")
CMDFILE <- file.path(data_dir, "NP_macro_cmd.txt")
SAMPLEFILE <- file.path(data_dir, "Samples.txt")
out <- Rnmr1D::doProcessing(data_dir, cmdfile=CMDFILE,
                           samplefile=SAMPLEFILE, ncpu=2)
# Apply an intelligent bucketing (AIBIN)
specMat.new <- Rnmr1D::doProcCmd(out,
  c("bucket aibin 10.2 10.5 0.3 3 0",
    "9.5 4.9",
    "4.8 0.5",
    "EOL"
  ), ncpu=2, debug=TRUE)
out$specMat <- specMat.new
```

| | |
|--------------|---------------------|
| doProcessing | <i>doProcessing</i> |
|--------------|---------------------|

Description

doProcessing is the main function of this package. Indeed, this function performs the complete processing of a set of 1D NMR spectra from the FID (raw data) and based on a processing sequence (macro-command file). An additional file specifies all the spectra to be considered by associating their sample code as well as the levels of experimental factors to which they belong. In this way it is possible to select only a subset of spectra instead of the whole set.

Usage

```
doProcessing(path, cmdfile, samplefile = NULL, bucketfile = NULL, ncpu = 1)
```

Arguments

| | |
|------------|--|
| path | The full path of either the raw spectra directory on the disk |
| cmdfile | The full path name of the Macro-commands file for processing (text format) |
| samplefile | The full path name of the Sample file (tabular format) |
| bucketfile | The full path name of the file of bucket's zones (tabular format) |
| ncpu | The number of cores [default: 1] |

Value

doProcessing returns a list containing the following components:

- `samples` : the samples matrix with the correspondence of the raw spectra, as well as the levels of the experimental factors if specified in the input.
- `factors` : the factors matrix with the corresponding factor names. At minimum, the list contains the Samplecode label corresponding to the samples without their group level.
- `rawids` : list of the full directories of the raw spectra (i.e. where the FID files are accessible)
- `infos` : list of the acquisition and processing parameters for each (raw) spectra.
- `specMat` : objects list regarding the spectra data.
 - `int` : the matrix of the spectra data (`nspec` rows X `size` columns)
 - `nspec` : the number of spectra
 - `size` : the size (i.e number of points) of each spectra
 - `ppm_min`, `ppm_max` : the minimum and the maximum ppm values of spectra
 - `ppm` : the vector of the ppm values (`size` values)
 - `dppm` : the ppm increment between each point
 - `buckets_zones` : the matrix of the buckets zones including two columns (min and max)
 - `namesASintMax` : boolean - If TRUE, generate all output matrix with bucket names based on ppm values of the maximum of the average intensity of all spectra within the ppm range of each bucket. If FALSE (default), then bucket names will be based on the ppm range center of each bucket.

See Also

the NMRProcFlow online documentation <https://nmrprocflow.org/> and especially the Macrocommand Reference Guide (<https://nmrprocflow.org/themes/pdf/Macrocommand.pdf>)

Examples

```
data_dir <- system.file("extra", package = "Rnmr1D")
cmdfile <- file.path(data_dir, "NP_macro_cmd.txt")
samplefile <- file.path(data_dir, "Samples.txt")
out <- Rnmr1D::doProcessing(data_dir, cmdfile=cmdfile,
                           samplefile=samplefile, ncpu=2)
```

| | |
|------------------|-------------------------|
| generateMetadata | <i>generateMetadata</i> |
|------------------|-------------------------|

Description

generateMetadata Generate the metadata from the list of raw spectra namely the samples, the experimental factors and the list of selected raw spectra. Depending on whether the sample matrix is supplied as input or not,

Usage

```
generateMetadata(RAWDIR, procParams, samples = NULL)
```

Arguments

| | |
|------------|--|
| RAWDIR | The full path of either the raw spectra directory on the disk |
| procParams | the list of processing parameters. First initialize this list with the <code>Spec1r.Procpar.default</code> list, then modify parameters depending of your spectra set. |
| samples | the samples matrix with the correspondence of the raw spectra |

Value

generateMetadata returns a list containing the following components:

- `samples` : the samples matrix with the correspondence of the raw spectra, as well as the levels of the experimental factors if specified in the input.
- `factors` : the factors matrix with the corresponding factor names. At minimum, the list contains the `Samplecode` label corresponding to the samples without their group level.
- `rawids` : list of the full directories of the raw spectra (i.e. where the FID files are accessible)

Examples

```
data_dir <- system.file("extra", package = "Rnmr1D")
samplefile <- file.path(data_dir, "Samples.txt")
samples <- read.table(samplefile, sep="\t", header=TRUE, stringsAsFactors=FALSE)
metadata <- generateMetadata(data_dir, procParams=Spec1rProcpar, samples)
```

getBucketsDataset *getBucketsDataset*

Description

Generates the matrix including the integrations of the areas defined by the buckets (columns) on each spectrum (rows)

Usage

```
getBucketsDataset(specObj, norm_meth = "none", zoneref = NA)
```

Arguments

| | |
|-----------|---|
| specObj | a complex list return by doProcessing function. See the manual page of the doProcessing function for more details on its structure. |
| norm_meth | Normalization method. The possible values are : 'none', 'CSN' or 'PDN'. See below. |
| zoneref | Specify the ppm zone of the internal reference (i.e. ERETIC) if applicable. default is NA. |

Details

Before bucket data export in order to make all spectra comparable with each other, the variations of the overall concentrations of samples have to be taken into account. We propose two normalization methods. In NMR metabolomics, the total intensity normalization (called the Constant Sum Normalization) is often used so that all spectra correspond to the same overall concentration. It simply consists in normalizing the total intensity of each individual spectrum to a same value. An other method called Probabilistic Quotient Normalization (Dieterle et al. 2006) assumes that biologically interesting concentration changes influence only parts of the NMR spectrum, while dilution effects will affect all metabolites signals. Probabilistic Quotient Normalization (PQN) starts by the calculation of a reference spectrum based on the median spectrum. Next, for each variable of interest the quotient of a given test spectrum and reference spectrum is calculated and the median of all quotients is estimated. Finally, all variables of the test spectrum are divided by the median quotient. An internal reference can be used to normalize the data. For example, an electronic reference (ERETIC, see Akoka et al. 1999, or ERETIC2 generated with TopSpin software) can be used for this purpose. The integral value of each bucket will be divided by the integral value of the ppm range given as reference.

Value

the data matrix

References

Akoka S1, Barantin L, Trierweiler M. (1999) Concentration Measurement by Proton NMR Using the ERETIC Method, *Anal. Chem* 71(13):2554-7. doi: 10.1021/ac981422i.

Dieterle F., Ross A., Schlotterbeck G. and Senn H. (2006). Probabilistic Quotient Normalization as Robust Method to Account for Dilution of Complex Biological Mixtures. Application in 1H NMR Metabonomics. *Analytical Chemistry*, 78:4281-4290. doi: 10.1021/ac051632c

Examples

```
data_dir <- system.file("extra", package = "Rnmr1D")
cmdfile <- file.path(data_dir, "NP_macro_cmd.txt")
samplefile <- file.path(data_dir, "Samples.txt")
out <- Rnmr1D::doProcessing(data_dir, cmdfile=cmdfile,
                           samplefile=samplefile, ncpu=2)
outMat <- getBucketsDataset(out, norm_meth='CSN')
```

| | |
|------------------------------|------------------------|
| <code>getBucketsTable</code> | <i>getBucketsTable</i> |
|------------------------------|------------------------|

Description

Generates the buckets table

Usage

```
getBucketsTable(specObj)
```

Arguments

`specObj` a complex list return by `doProcessing` function. See the manual page of the [doProcessing](#) function for more details on its structure.

Value

the buckets table

`getClusters`*getClusters*

Description

From the data matrix generated from the integration of all bucket zones (columns) for each spectrum (rows), we can take advantage of the concentration variability of each compound in a series of samples by performing a clustering based on significant correlations that link these buckets together into clusters. Bucket Clustering based on either a lower threshold applied on correlations or a cutting value applied on a hierarchical tree of the variables (buckets) generated by an Hierarchical Clustering Analysis (HCA).

Usage

```
getClusters(data, method = "hca", ...)
```

Arguments

| | |
|---------------------|---|
| <code>data</code> | the matrix including the integrations of the areas defined by the buckets (columns) on each spectrum (rows) |
| <code>method</code> | Clustering method of the buckets. Either 'corr' for 'correlation' or 'hca' for 'hierarchical clustering analysis'. |
| <code>...</code> | Depending on the chosen method: <ul style="list-style-type: none">• <code>corr</code> : <code>cval</code>, <code>dC</code>, <code>ncpu</code>• <code>hca</code> : <code>vcutusr</code> |

Details

At the bucketing step (see above), we have chosen the intelligent bucketing, it means that each bucket exact matches with one resonance peak. Thanks to this, the buckets now have a strong chemical meaning, since the resonance peaks are the fingerprints of chemical compounds. However, to assign a chemical compound, several resonance peaks are generally required in 1D 1H-NMR metabolic profiling. To generate relevant clusters (i.e. clusters possibly matching to chemical compounds), two approaches have been implemented:

- Bucket Clustering based on a lower threshold applied on correlations
 - In this approach an appropriate correlation threshold is applied on the correlation matrix before its cluster decomposition. Moreover, an improvement can be done by searching for a trade-off on a tolerance interval of the correlation threshold : from a fixed threshold of the correlation (`cval`), the clustering is calculated for the three values (`cval-dC`, `cval`, `cval+dC`), where `dC` is the tolerance interval of the correlation threshold. From these three sets of clusters, we establish a merger according to the following rules: 1) if a large cluster is broken, we keep the two resulting clusters. 2) If a small cluster disappears, the initial cluster is conserved. Generally, an interval of the correlation threshold included between 0.002 and 0.01 gives good trade-off.

- Bucket Clustering based on a hierarchical tree of the variables (buckets) generated by an Hierarchical Clustering Analysis (HCA)
 - In this approach a Hierarchical Classification Analysis (HCA, `hclust`) is applied on the data after calculating a matrix distance ("euclidian" by default). Then, a cut is applied on the tree (`cutree`) resulting from `hclust`, into several groups by specifying the cut height(s). For finding best cut value, the cut height is chosen i) by testing several values equally spaced in a given range of the cut height, then, 2) by keeping the one that gives the more cluster and by including most bucket variables. Otherwise, a cut value has to be specified by the user (`vcutusr`)

Value

`getClusters` returns a list containing the following components:

- `vstats` Statistics that served to find the best value of the criterion (matrix)
- `clusters` List of the ppm value corresponding to each cluster. the length of the list equal to number of clusters
- `clustertab` the associations matrix that gives for each cluster (column 2) the corresponding buckets (column 1)
- `params` List of parameters related to the chosen method for which the clustering was performed.
- `vcrit` Value of the (best/user) criterion, i.e correlation threshold for 'corr' method or the cut value for the 'hca' method.
- `indxopt` Index value within the `vstats` matrix corresponding to the criterion value (`vcrit`)

References

Jacob D., Deborde C. and Moing A. (2013) An efficient spectra processing method for metabolite identification from 1H-NMR metabolomics data. *Analytical and Bioanalytical Chemistry* 405(15) 5049-5061 doi: 10.1007/s00216-013-6852-y

Examples

```
data_dir <- system.file("extra", package = "Rnmr1D")
cmdfile <- file.path(data_dir, "NP_macro_cmd.txt")
samplefile <- file.path(data_dir, "Samples.txt")
out <- Rnmr1D::doProcessing(data_dir, cmdfile=cmdfile,
                           samplefile=samplefile, ncpu=2)
outMat <- getBucketsDataset(out, norm_meth='CSN')
clustcorr <- getClusters(outMat, method='corr', cval=0, dC=0.003, ncpu=2)
clusthca <- getClusters(outMat, method='hca', vcutusr=0)
```

```
getMergedDataset      getMergedDataset
```

Description

merged variables for each cluster (based on their average)

Usage

```
getMergedDataset(data, clustObj, onlycluster = FALSE)
```

Arguments

| | |
|-------------|---|
| data | the matrix including the integrations of the areas defined by the buckets (columns) on each spectrum (rows) |
| clustObj | a list generated by the getClusters function |
| onlycluster | boolean - specifies if the merged data matrix at output must only contain the merged clusters (TRUE) or if it must also contain the buckets that are not include within a cluster (FALSE) |

```
getSnrDataset      getSnrDataset
```

Description

Generates the Signal-Noise-Ratio dataset

Usage

```
getSnrDataset(specObj, zone_noise = c(10.2, 10.5), ratio = TRUE)
```

Arguments

| | |
|------------|---|
| specObj | a complex list return by doProcessing function. See the manual page of the doProcessing function for more details on its structure. |
| zone_noise | Specify a ppm range of noisy zone default is c(10.2,10.5) |
| ratio | boolean; TRUE for output Signal-Noise Ratio, or FALSE to output maximum value of each bucket and in addition, the estimate noise as a separate column |

Details

whatever the bucketing approach used, the Signal-to-Noise ratio is a good quality indicator. Thus, it is possible to check buckets based on their Signal-to-Noise ratio.

Value

the Signal-Noise-Ratio matrix

getSpectraData *getSnrDataset*

Description

Generates the spectral data matrix. The first column indicates the value of ppm, then the following columns correspond to spectral data, one column per spectrum.

Usage

```
getSpectraData(specObj)
```

Arguments

specObj a complex list return by doProcessing function.

Value

the spectral data matrix

ggplotClusters *ggplotClusters*

Description

Plots the boxplot of all clusters allowing to have an insight on the clusters distribution. Plot based on ggplot2

Usage

```
ggplotClusters(data, clustObj)
```

Arguments

data the matrix including the integrations of the areas defined by the buckets (columns) on each spectrum (rows)

clustObj a list generated by the getClusters function

ggplotCriterion *ggplotCriterion*

Description

Plots the curves that show the number of clusters, the number of clustered buckets and the size of biggest cluster versus the criterion, namely the correlation threshold for the 'corr' method, the cutting value for the 'hca' method.

Usage

```
ggplotCriterion(clustObj, reverse = FALSE)
```

Arguments

| | |
|----------|--|
| clustObj | a list generated by the getClusters function |
| reverse | indicates if the x axis need to be reversed |

ggplotLoadings *plotLoadings*

Description

Plots the two components defined by pc1, pc2 of the matrix of variable loadings coming from a multivariable analysis, typically a Principal Component Analysis (PCA). It can also plot the ellipses corresponding to each cluster defined by the associations matrix if not null. (in fact it is the main interest of this function).

Usage

```
ggplotLoadings(  
  data,  
  pc1 = 1,  
  pc2 = 2,  
  EV = NULL,  
  associations = NULL,  
  main = "Loadings",  
  onlylabels = FALSE,  
  highlabels = FALSE,  
  gcontour = "ellipse"  
)
```

Arguments

| | |
|---------------------------|---|
| <code>data</code> | the matrix of variable loadings coming from a multivariable analysis, typically a Principal Component Analysis (PCA) |
| <code>pc1</code> | the first component of the matrix of variable loadings to be plotted. |
| <code>pc2</code> | the second component of the matrix of variable loadings to be plotted. |
| <code>EV</code> | Eigenvalues vector |
| <code>associations</code> | the associations matrix that gives for each cluster (column 2) the corresponding buckets (column 1). See <code>getClusters</code> |
| <code>main</code> | Change the default plot title on the right corner |
| <code>onlylabels</code> | if TRUE, put only the association names without drawing the cluster contours. Implies that association matrix is provided. |
| <code>highlabels</code> | if TRUE, put the the association names in blue, and others in grey. Implies that association matrix is provided and <code>fONLYLABELS</code> equal to TRUE. |
| <code>gcontour</code> | type of contour; possible values are : 'ellipse', 'polygon', 'ellipse2', 'none' |

ggplotPlotly

ggplotPlotly

Description

Translate 'ggplot2' graphs to an interactive plotly version

Usage

```
ggplotPlotly(g, width = NULL, height = NULL, textposition = "right")
```

Arguments

| | |
|---------------------------|---|
| <code>g</code> | The ggplot2 graph object to be translated into an interactive plotly version |
| <code>width</code> | Width of the plot in pixels (optional, defaults to automatic sizing). |
| <code>height</code> | Height of the plot in pixels (optional, defaults to automatic sizing) |
| <code>textposition</code> | Position of the labels on the graphs relative to the points. Possible values are : 'right', 'left', 'top' or 'bottom' |

`ggplotScores`*ggplotScores*

Description

Plots the two components defined by `pc1`, `pc2` of the matrix of scores coming from a multivariable analysis, typically a Principal Component Analysis (PCA).

Usage

```
ggplotScores(  
  data,  
  pc1 = 1,  
  pc2 = 2,  
  groups = NULL,  
  EV = NULL,  
  main = "Scores",  
  glabels = FALSE,  
  psize = 3,  
  gcontour = "ellipse",  
  params = list(ellipse = 0.95)  
)
```

Arguments

| | |
|-----------------------|---|
| <code>data</code> | the matrix of scores coming from a multivariable analysis, typically a Principal Component Analysis (PCA) |
| <code>pc1</code> | the first component of the matrix of variable loadings to be plotted. |
| <code>pc2</code> | the second component of the matrix of variable loadings to be plotted. |
| <code>groups</code> | the vector defining the factorial groups (same dimension as data rows) |
| <code>EV</code> | Eigenvalues vector |
| <code>main</code> | the plot main title |
| <code>glabels</code> | boolean indicating if labels have to be plotted |
| <code>psize</code> | point size |
| <code>gcontour</code> | type of contour; possible values are : 'ellipse', 'polygon', 'ellipse2', 'none' |
| <code>params</code> | parameters depending on the contour type |

| | |
|--------------|---------------------|
| plotClusters | <i>plotClusters</i> |
|--------------|---------------------|

Description

Plots the boxplot of all clusters allowing to have an insight on the clusters distribution

Usage

```
plotClusters(
  data,
  clustObj,
  horiz = TRUE,
  main = "Boxplot by clusters (log10 transformed)"
)
```

Arguments

| | |
|----------|---|
| data | the matrix including the integrations of the areas defined by the buckets (columns) on each spectrum (rows) |
| clustObj | a list generated by the getClusters function |
| horiz | Boolean - Indicates if the plot is horizontal (TRUE) or vertical (FALSE) |
| main | Main title of the plot |

| | |
|---------------|----------------------|
| plotCriterion | <i>plotCriterion</i> |
|---------------|----------------------|

Description

Plots the curves that show the number of clusters, the number of clustered buckets and the size of biggest cluster versus the criterion, namely the correlation threshold for the 'corr' method, the cutting value for the 'hca' method.

Usage

```
plotCriterion(clustObj, reverse = FALSE)
```

Arguments

| | |
|----------|--|
| clustObj | a list generated by the getClusters function |
| reverse | Boolean - indicates if x-axis must be reversed (TRUE) or nor (FALSE) |

| | |
|--------------|---------------------|
| plotLoadings | <i>plotLoadings</i> |
|--------------|---------------------|

Description

Plots the two components defined by pc1, pc2 of the matrix of variable loadings coming from a multivariable analysis, typically a Principal Component Analysis (PCA). It can also plot the ellipses corresponding to each cluster defined by the associations matrix if not null. (in fact it is the main interest of this function).

Usage

```
plotLoadings(  
  data,  
  pc1,  
  pc2,  
  associations = NULL,  
  main = "Loadings",  
  xlimu = c(min(data[, pc1]), max(data[, pc1])),  
  ylimu = c(min(data[, pc2]), max(data[, pc2])),  
  cexlabel = 1,  
  pch = 20,  
  ellipse = TRUE,  
  level = 0.8  
)
```

Arguments

| | |
|--------------|--|
| data | the matrix of variable loadings coming from a multivariable analysis, typically a Principal Component Analysis (PCA) |
| pc1 | the first component of the matrix of variable loadings to be plotted. |
| pc2 | the second component of the matrix of variable loadings to be plotted. |
| associations | the associations matrix that gives for each cluster (column 2) the corresponding buckets (column 1) |
| main | Change the default plot title on the right corner |
| xlimu | gives the limit to be plotted of the first component |
| ylimu | gives the limit to be plotted of the second component |
| cexlabel | number indicating the amount by which plotting text and symbols should be scaled relative to the default. |
| pch | Plotting Symbols |
| ellipse | boolean - specifies if ellipses are plot or not for each cluster |
| level | confidence level for plotting the ellipses |

 plotScores

plotScores

Description

Plots the two components defined by pc1, pc2 of the matrix of scores coming from a multivariable analysis, typically a Principal Component Analysis (PCA).

Usage

```
plotScores(
  data,
  pc1,
  pc2,
  samples,
  factor = NULL,
  cexlabel = 1.2,
  level = 0.95,
  xlim = NULL,
  ylim = NULL,
  col = NULL
)
```

Arguments

| | |
|----------|--|
| data | the matrix of scores coming from a multivariable analysis, typically a Principal Component Analysis (PCA) |
| pc1 | the first component of the matrix of variable loadings to be plotted. |
| pc2 | the second component of the matrix of variable loadings to be plotted. as well as the levels of the experimental factors if specified in the input. See <code>doProcessing</code> or <code>generateMetadata</code> |
| samples | the samples matrix with the correspondence of the raw spectra, |
| factor | if not null, the name of one of the columns defining the factorial groups in the samples matrix at input |
| cexlabel | number indicating the amount by which plotting text and symbols should be scaled relative to the default. |
| level | confidence level for plotting the corresponding ellipse |
| xlim | gives the limit to be plotted of the first component |
| ylim | gives the limit to be plotted of the second component |
| col | colors vector for ellipses - automatically defined by default |

plotSpecMat *plotSpecMat Overlaid/Stacked Plot*

Description

plotSpecMat Plot spectra set, overlaid or stacked; if stacked, plot with or without a perspective effect.

Usage

```
plotSpecMat(
  specMat,
  ppm_lim = c(min(specMat$ppm), max(specMat$ppm)),
  K = 0.67,
  pY = 1,
  dppm_max = 0.2 * (max(ppm_lim) - min(ppm_lim)),
  asym = 1,
  beta = 0,
  cols = NULL
)
```

Arguments

| | |
|----------|---|
| specMat | a 'specMat' object - Spectra matrix in specMat\$int (rows = samples, columns = buckets) |
| ppm_lim | ppm range of the plot |
| K | Graphical height of the stack (0 .. 1),(default=0.67) |
| pY | Intensity limit factor (default 1) |
| dppm_max | Max ppm shift to have a perspective effect |
| asym | Correction of vertical parallax effect (-1 .. 1) -1 : parallelogram 0 : trapeze with maximum asymmetric 1 : symmetric trapeze |
| beta | Correction of horizontal parallax effect (0 .. 0.2) (default 0) |
| cols | Vector of colors (same size that the number of spectra, i.e dim(specmat)[1]) |

Examples

```
data_dir <- system.file("extra", package = "Rnmr1D")
cmdfile <- file.path(data_dir, "NP_macro_cmd.txt")
samplefile <- file.path(data_dir, "Samples.txt")
out <- Rnmr1D::doProcessing(data_dir, cmdfile=cmdfile,
                           samplefile=samplefile, ncpu=2)

# Overlaid plot
plotSpecMat(out$specMat, ppm_lim=c(0.5,9), K=0, pY=0.1)
# Stacked plot with perspective effect
plotSpecMat(out$specMat, ppm_lim=c(-0.1,9),K=0.33)
```

```
# Stacked plot with perspective effect with maximum asymmetric
plotSpecMat(out$specMat, ppm_lim=c(0.5,5), K=0.33, asym=0)
cols <- c(rep("red",3), rep("blue",3))
# Stacked plot with colors accordings to group levels
plotSpecMat(out$specMat, ppm_lim=c(0.5,5), K=0.67, dppm_max=0, cols=cols)
```

RWwrapperCMD1D

RWrapperCMD1D

Description

RWrapperCMD1D belongs to the low-level functions group - it serves as a wrapper to call interneale functions for processing.

Usage

```
RWrapperCMD1D(cmdName, specMat, ...)
```

Arguments

| | |
|---------|---|
| cmdName | the name of internal function |
| specMat | a 'specMat' object |
| ... | specific parameters of the requested function |

Value

specMat : a 'specMat' object

setLogFile

setLogFile

Description

setLogFile allows to redirect all log messages to a file

Usage

```
setLogFile(con = stdout())
```

Arguments

| | |
|-----|--|
| con | a connection object which inherits from class "connection" |
|-----|--|

Examples

```
# Redirect all log messages to a temporary file
outtmp <- tempfile()
con <- file(outtmp, "wt", encoding = "UTF-8")
setLogFile(con)
data_dir <- system.file("extra", package = "Rnmr1D")
RAWDIR <- file.path(data_dir, "CD_BBI_16P02")
CMDFILE <- file.path(data_dir, "NP_macro_cmd.txt")
SAMPLEFILE <- file.path(data_dir, "Samples.txt")
out <- Rnmr1D::doProcessing(RAWDIR, cmdfile=CMDFILE, samplefile=SAMPLEFILE, ncpu=6)
close(con)
readLines(outtmp)
```

setPPMbounds

setPPMbounds

Description

Set the PPM bounds for proton (1H) and carbon (13C) to consider in the processing step and then to store in the specMat object

Usage

```
setPPMbounds(proton = c(-0.5, 11), carbon = c(0, 200))
```

Arguments

| | |
|--------|---|
| proton | Minimal and Maximal ppm value for 1H NMR |
| carbon | Minimal and Maximal ppm value for 13C NMR |

Spec1rDoProc

Spec1rDoProc

Description

Spec1rDoProc belongs to the low-level functions group - it processes only one raw spectrum at time.

Usage

```
Spec1rDoProc(Input, param = Spec1rProccpar)
```

Arguments

| | |
|-------|---|
| Input | Full directory path of the raw spectrum |
| param | a Spec1rProcpar list |

Value

spec object

| | |
|---------------|----------------------|
| Spec1rProcpar | <i>Spec1rProcpar</i> |
|---------------|----------------------|

Description

Initialize Parameter Lists by the default ones

Usage

Spec1rProcpar

Format

An object of class `list` of length 32.

Value

- `DEBUG` : Debug - default value = `TRUE`
- `LOGFILE` : Messages output file - default value = ""
- `VENDOR` : Instrumental origin of the raw data (bruker, varian, jeol, rs2d) - default value = 'bruker'
- `READ_RAW_ONLY` : Read raw file only; do not carry out processing; raw file is depending on `INPUT_SIGNAL` - default value = `FALSE`
- `INPUT_SIGNAL` : What type of input signal: 'fid' or '1r' - default value = 'fid'
- `PDATA_DIR` : subdirectory containing the 1r file (bruker's format only) - default value = 'pdata/1'
- `LB` : Exponential Line Broadening parameter - default value = 0.3
- `GB` : Gaussian Line Broadening parameter - default value = 0
- `REMLFREQ` : Remove low frequencies by applying a polynomial subtraction method. - default order of the model = 0
- `REVPPM` : Reverse ppm scale - default value = `FALSE`
- `BLPHC` : Number of points for baseline smoothing during phasing - default value = 50
- `KSIG` : Number of times the noise signal to be considered during phasing - default value = 6
- `CPMG` : Indicate if CPMG sequence - default value = `FALSE`
- `ZEROFILLING` : Zero Filling - - default value = `FALSE`

- ZFFAC : Max factor for Zero Filling - default value = 4
- LINEBROADENING : Line Broadening - default value = TRUE
- TSP : PPM referencing - default value = FALSE
- RABOT : Zeroing of Negative Values - default value = FALSE
- OPTPHC0 : Zero order phase optimization - default value = TRUE
- OPTPHC1 : First order phase optimization - default value = FALSE
- OPTCRIT1 : Criterium for phasing optimization (1 for SSpos, 2 for SSneg, 3 for Entropy - default value = 2)
- JGD_INNER : JEOL : internal (or external) estimation for Group Delay - default value = TRUE

Index

* datasets

Spec1rProcpair, [22](#)

checkMacroCmdFile, [2](#)
cutree, [10](#)

detectCores, [3](#)
doProcCmd, [4](#)
doProcessing, [4, 5, 7, 8, 11](#)

generateMetadata, [6](#)
getBucketsDataset, [7](#)
getBucketsTable, [8](#)
getClusters, [9](#)
getMergedDataset, [11](#)
getSnrDataset, [11](#)
getSpectraData, [12](#)
ggplotClusters, [12](#)
ggplotCriterion, [13](#)
ggplotLoadings, [13](#)
ggplotPlotly, [14](#)
ggplotScores, [15](#)

hclust, [10](#)

plotClusters, [16](#)
plotCriterion, [16](#)
plotLoadings, [17](#)
plotScores, [18](#)
plotSpecMat, [19](#)

RWrapperCMD1D, [20](#)

setLogFile, [20](#)
setPPMbounds, [21](#)
Spec1rDoProc, [21](#)
Spec1rProcpair, [22](#)