

Package ‘SEA’

March 30, 2022

Type Package

Title Segregation Analysis

Version 2.0.1

Date 2022-3-28

Maintainer Yuan-Ming Zhang <soy Zhang@mail.hzau.edu.cn>

Contact Yuan-Ming Zhang <soy Zhang@mail.hzau.edu.cn>

Description A few major genes and a series of polygene are responsive for each quantitative trait. Major genes are individually identified while polygene is collectively detected. This is mixed major genes plus polygene inheritance analysis or segregation analysis (SEA). In the SEA, phenotypes from a single or multiple bi-parental segregation populations along with their parents are used to fit all the possible models and the best model of the trait for population phenotypic distributions is viewed as the model of the trait. There are fourteen types of population combinations available. Zhang Yuan-Ming, Gai Jun-Yi, Yang Yong-Hua (2003, <doi:10.1017/S0016672303006141>).

Depends shiny, MASS, doParallel, foreach, methods

Imports KScorrect, utils, stats, grDevices, graphics, data.table

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2022-03-30 07:30:12 UTC

Author Jing-Tian Wang [aut],

Ya-Wen Zhang [aut],

Yuan-Ming Zhang [aut, cre] (<<https://orcid.org/0000-0003-2317-2190>>)

R topics documented:

SEA-package	2
BCexdata	3
BCFexdata	4
BCFFun	4
BCFun	5

BILexdata	5
BILFun	6
DHexdata	6
DHFun	7
F23exdata	7
F23Fun	8
F2exdata	8
F2Fun	9
G3DHexdata	9
G3DHFun	10
G4F2exdata	10
G4F2Fun	11
G4F3exdata	11
G4F3Fun	12
G5BCexdata	12
G5BCFexdata	13
G5BCFFun	13
G5BCFun	14
G5exdata	14
G5Fun	15
G6exdata	15
G6Fexdata	16
G6FFun	16
G6Fun	17
PosPro	17

Index	19
--------------	-----------

SEA-package	<i>Segregation Analysis</i>
-------------	-----------------------------

Description

A few major genes and a series of polygene are responsive for each quantitative trait. Major genes are individually identified while polygene is collectively detected. This is mixed major genes plus polygene inheritance analysis or segregation analysis (SEA). In the SEA, phenotypes from a single or multiple bi-parental segregation populations along with their parents are used to fit all the possible models and the best model for population phenotypic distributions is viewed as the model of the trait. There are fourteen types of population combinations available. Zhang Yuan-Ming, Gai Jun-Yi, Yang Yong-Hua (2003, <doi:10.1017/S0016672303006141>), and Wang Jing-Tian, Zhang Ya-Wen, Du Ying-Wen, Ren Wen-Long, Li Hong-Fu, Sun Wen-Xian, Ge Chao, and Zhang Yuan-Ming(2022, <doi:10.3724/SP.J.1006.2022.14088>)

Details

Package: SEA
Type: Package
Version: 2.0.1
Date: 2022-03-28
Depends: shiny,MASS,doParallel,foreach
Imports: KScorrect,kolmim,utils,stats,grDevices,graphics,data.table
License: GPL(>=2)
LazyLoad: yes

Users can use 'SEA()' start the GUI.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

References

The EIM algorithm in the joint segregation analysis of quantitative traits. Zhang Yuan-Ming*, Gai Junyi, Yang Yonghua(2003).

Examples

```
## Not run: SEA()
```

BCexdata

BC population dataset

Description

The phenotype of BC population .

Usage

```
data(BCexdata)
```

Details

Dataset input of BCFun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

BCFexdata

BCF population dataset

Description

The phenotype of BCF population .

Usage

```
data(BCFexdata)
```

Details

Dataset input of BCFFun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

BCFFun

segregation analysis of BCF population

Description

Phenotypic observations in BCF population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
BCFFun(df, model, BCFtext2)
```

Arguments

df	phenotype matrix.
model	genetic model.
BCFtext2	number of plants measured in each family.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
BCF=data(BCFexdata)  
BCFFun(BCFexdata, "0MG", 1)
```

BCFun *segregation analysis of BC population*

Description

Phenotypic observations in BC population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
BCFun(df, model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
BC=data(BCexdata)  
BCFun(BCexdata, "0MG")
```

BILexdata *BIL population dataset*

Description

The phenotype of BIL population .

Usage

```
data(BILexdata)
```

Details

Dataset input of BILFun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

BILFun *segregation analysis of BIL population*

Description

Phenotypic observations in BIL population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
BILFun(df,model,BILfr)
```

Arguments

df	phenotype matrix.
model	genetic model.
BILfr	BIL type.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
BIL=data(BILexdata)  
BILFun(BILexdata,"0MG","BIL1(F1xP1)")
```

DHexdata *DH population dataset*

Description

The phenotype of DH population .

Usage

```
data(DHexdata)
```

Details

Dataset input of DHFun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

DHFun	<i>segregation analysis of DH population</i>
-------	--

Description

Phenotypic observations in DH population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
DHFun(df, model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
DH=data(DHexdata)  
DHFun(DHexdata, "OMG")
```

F23exdata	<i>F23 population dataset</i>
-----------	-------------------------------

Description

The phenotype of F23 population .

Usage

```
data(F23exdata)
```

Details

Dataset input of F23Fun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

F23Fun *segregation analysis of F23 population*

Description

Phenotypic observations in F23 population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
F23Fun(df, model, m_nf)
```

Arguments

df	phenotype matrix.
model	genetic model.
m_nf	number of plants measured in each family.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
F23=data(F23exdata)  
F23Fun(F23exdata, "0MG", 1)
```

F2exdata *F2 population dataset*

Description

The phenotype of F2 population .

Usage

```
data(F2exdata)
```

Details

Dataset input of F2Fun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

F2Fun

segregation analysis of F2 population

Description

Phenotypic observations in F2 population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
F2Fun(df, model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
F2=data(F2exdata)  
F2Fun(F2exdata, "0MG")
```

G3DHexdata

G3DH population dataset

Description

The phenotype of G3DH population .

Usage

```
data(G3DHexdata)
```

Details

Dataset input of G3DHFun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G3DHFun

segregation analysis of G3DH population

Description

Phenotypic observations in G3DH population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
G3DHFun(df, model, G3DHtext2)
```

Arguments

df	phenotype matrix.
model	genetic model.
G3DHtext2	number of plants measured in each family.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G3DH=data(G3DHexdata)  
G3DHFun(G3DHexdata, "0MG", 1)
```

G4F2exdata

G4F2 population dataset

Description

The phenotype of G4F2 population .

Usage

```
data(G4F2exdata)
```

Details

Dataset input of G4F2Fun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G4F2Fun	<i>segregation analysis of G4F2 population</i>
---------	--

Description

Phenotypic observations in G4F2 population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
G4F2Fun(df, model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G4F2=data(G4F2exdata)  
G4F2Fun(G4F2exdata, "PG-AD")
```

G4F3exdata	<i>G4F3 population dataset</i>
------------	--------------------------------

Description

The phenotype of G4F3 population .

Usage

```
data(G4F3exdata)
```

Details

Dataset input of G4F3Fun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G4F3Fun

segregation analysis of G4F3 population

Description

Phenotypic observations in G4F3 population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
G4F3Fun(df, model, G4F3text2)
```

Arguments

df	phenotype matrix.
model	genetic model.
G4F3text2	number of plants measured in each family.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
 Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G4F3=data(G4F3exdata)
G4F3Fun(G4F3exdata, "PG-AD", 1)
```

G5BCexdata

G5BC population dataset

Description

The phenotype of G5BC population .

Usage

```
data(G5BCexdata)
```

Details

Dataset input of G5BCFun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
 Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G5BCFexdata	<i>G5BCF population dataset</i>
-------------	---------------------------------

Description

The phenotype of G5BCF population .

Usage

```
data(G5BCFexdata)
```

Details

Dataset input of G5BCFFun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
 Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G5BCFFun	<i>segregation analysis of G5BCF population</i>
----------	---

Description

Phenotypic observations in G5BCF population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
G5BCFFun(df, model, G5BCFtext2)
```

Arguments

df	phenotype matrix.
model	genetic model.
G5BCFtext2	number of plants measured in each family.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
 Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G5BCF=data(G5BCFexdata)
G5BCFFun(G5BCFexdata, "1MG-AD", 1)
```

G5BCFun

segregation analysis of G5BC population

Description

Phenotypic observations in G5BC population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
G5BCFun(df,model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G5BC=data(G5BCexdata)  
G5BCFun(G5BCexdata,"1MG-AD")
```

G5exdata

G5 population dataset

Description

The phenotype of G5 population .

Usage

```
data(G5exdata)
```

Details

Dataset input of G5Fun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G5Fun	<i>segregation analysis of G5 population</i>
-------	--

Description

Phenotypic observations in G5 population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
G5Fun(df, model, G5text2)
```

Arguments

df	phenotype matrix.
model	genetic model.
G5text2	number of plants measured in each family.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G5=data(G5exdata)  
G5Fun(G5exdata, "PG-AD", 1)
```

G6exdata	<i>G6 population dataset</i>
----------	------------------------------

Description

The phenotype of G6 population .

Usage

```
data(G6exdata)
```

Details

Dataset input of G6Fun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G6Fexdata	<i>G6F population dataset</i>
-----------	-------------------------------

Description

The phenotype of G6F population .

Usage

```
data(G6Fexdata)
```

Details

Dataset input of G6FFun function.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
 Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

G6FFun	<i>segregation analysis of G6F population</i>
--------	---

Description

Phenotypic observations in G6F population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
G6FFun(df, model, G6Ftext2)
```

Arguments

df	phenotype matrix.
model	genetic model.
G6Ftext2	number of plants measured in each family.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
 Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G6F=data(G6Fexdata)
G6FFun(G6Fexdata,"PG-AD",1)
```

G6Fun

segregation analysis of G6 population

Description

Phenotypic observations in G6 population have often been used to identify mixed major-gene plus polygene inheritance model for quantitative traits in plants.

Usage

```
G6Fun(df, model)
```

Arguments

df	phenotype matrix.
model	genetic model.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
G6=data(G6exdata)  
G6Fun(G6exdata, "PG-AD")
```

PosPro

Posterior Probability

Description

calculate posterior probability of the optimal model

Usage

```
PosPro(Population, result, data)
```

Arguments

Population	which Population to analysis.
result	result of calculation used corresponding population function.
data	phenotype matrix.

Author(s)

Wang Jing-Tian, Zhang Ya-Wen, and Zhang Yuan-Ming
Maintainer: Yuanming Zhang<soy Zhang@mail.hzau.edu.cn>

Examples

```
F23=data(F23exdata)
result<-F23Fun(F23exdata,"1MG-AD",1)
PosPro("F2:3",result,F23exdata)
```

Index

B1 (BCexdata), [3](#)
B2 (BCexdata), [3](#)
BCexdata, [3](#)
BCF-B12 (BCFexdata), [4](#)
BCF-B22 (BCFexdata), [4](#)
BCFexdata, [4](#)
BCFFun, [4](#)
BCFun, [5](#)
BIL (BILexdata), [5](#)
BILexdata, [5](#)
BILFun, [6](#)

DH (DHexdata), [6](#)
DHexdata, [6](#)
DHFun, [7](#)

F2 (F2exdata), [8](#)
F23 (F23exdata), [7](#)
F23exdata, [7](#)
F23Fun, [8](#)
F2exdata, [8](#)
F2Fun, [9](#)

G3DH-DH (G3DHexdata), [9](#)
G3DH-P1 (G3DHexdata), [9](#)
G3DH-P2 (G3DHexdata), [9](#)
G3DHexdata, [9](#)
G3DHFun, [10](#)
G4F2-F1 (G4F2exdata), [10](#)
G4F2-F2 (G4F2exdata), [10](#)
G4F2-P1 (G4F2exdata), [10](#)
G4F2-P2 (G4F2exdata), [10](#)
G4F2exdata, [10](#)
G4F2Fun, [11](#)
G4F3-F1 (G4F3exdata), [11](#)
G4F3-F23 (G4F3exdata), [11](#)
G4F3-P1 (G4F3exdata), [11](#)
G4F3-P2 (G4F3exdata), [11](#)
G4F3exdata, [11](#)
G4F3Fun, [12](#)

G5-F1 (G5exdata), [14](#)
G5-F2 (G5exdata), [14](#)
G5-F23 (G5exdata), [14](#)
G5-P1 (G5exdata), [14](#)
G5-P2 (G5exdata), [14](#)
G5BC-B1 (G5BCexdata), [12](#)
G5BC-B2 (G5BCexdata), [12](#)
G5BC-F1 (G5BCexdata), [12](#)
G5BC-P1 (G5BCexdata), [12](#)
G5BC-P2 (G5BCexdata), [12](#)
G5BCexdata, [12](#)
G5BCF-B12 (G5BCFexdata), [13](#)
G5BCF-B22 (G5BCFexdata), [13](#)
G5BCF-F1 (G5BCFexdata), [13](#)
G5BCF-P1 (G5BCFexdata), [13](#)
G5BCF-P2 (G5BCFexdata), [13](#)
G5BCFexdata, [13](#)
G5BCFFun, [13](#)
G5BCFun, [14](#)
G5exdata, [14](#)
G5Fun, [15](#)
G6-B1 (G6exdata), [15](#)
G6-B2 (G6exdata), [15](#)
G6-F1 (G6exdata), [15](#)
G6-F2 (G6exdata), [15](#)
G6-P1 (G6exdata), [15](#)
G6-P2 (G6exdata), [15](#)
G6exdata, [15](#)
G6F-B12 (G6Fexdata), [16](#)
G6F-B22 (G6Fexdata), [16](#)
G6F-F1 (G6Fexdata), [16](#)
G6F-F23 (G6Fexdata), [16](#)
G6F-P1 (G6Fexdata), [16](#)
G6F-P2 (G6Fexdata), [16](#)
G6Fexdata, [16](#)
G6FFun, [16](#)
G6Fun, [17](#)

PosPro, [17](#)

SEA (SEA-package), [2](#)

SEA-package, [2](#)