

Package ‘ToolsForCoDa’

September 20, 2021

Type Package

Title Multivariate Tools for Compositional Data Analysis

Version 1.0.6

Date 2021-09-18

Author Jan Graffelman <jan.graffelman@upc.edu>

Maintainer Jan Graffelman <jan.graffelman@upc.edu>

Depends R (>= 1.8.0), MASS, calibrate, HardyWeinberg

Description Provides functions for multivariate analysis with compositional data. Includes a function for doing compositional canonical correlation analysis. This analysis requires two data matrices of compositions, which can be adequately transformed and used as entries in a specialized program for canonical correlation analysis, that is able to deal with singular covariance matrices. The methodology is described in Graffelman et al. (2017) <doi:10.1101/144584>. A function for log-ratio principal component analysis with condition number computations has been added to the package.

License GPL (>= 2)

URL www.R-project.org, <http://www-eio.upc.edu/~jan/>

NeedsCompilation no

Repository CRAN

Date/Publication 2021-09-20 14:30:02 UTC

R topics documented:

Artificial	2
bentonites	2
canocov	3
cen	5
clrmat	6
largest.kappas	6
lrpca	7
tr	8

Index	9
--------------	----------

Artificial	<i>Two sets of 3-part compositions</i>
------------	--

Description

The list object `Artificial` contains two data frames of 3-part compositions. The data refer to the example in Section 3.1 of Graffelman et al. (2017)

Usage

```
data(Artificial)
```

Format

A list containing two data frames containing 100 observations.

Source

Laird, N. M. and Lange, C. Table 7.11, p. 124

References

Graffelman, J., Pawlowsky-Glahn, V., Egozcue, J.J. and Buccianti, A. (2017) Compositional Canonical Correlation Analysis.

bentonites	<i>Isotopic and chemical compositions of bentonites</i>
------------	---

Description

The data consists of 14 geological samples from the US with their major oxide composition (SiO₂, Al₂O₃, Fe₂O₃, MnO, MgO, CaO, K₂O, Na₂O and H₂O+) and delta Deuterium and delta-18-Oxygen (dD,d18O).

Usage

```
data("bentonites")
```

Format

A data frame with 14 observations on the following 11 variables.

Si a numeric vector

Al a numeric vector

Fe a numeric vector

Mn a numeric vector

Mg a numeric vector

Ca a numeric vector

K a numeric vector

Na a numeric vector

H2O a numeric vector

dD a numeric vector

d18O a numeric vector

Source

Cadrin, A.A.J (1995), Tables 1 and 2. Reyment, R. A. and Savazzi, E. (1999), pp. 220-222.

References

Cadrin, A.A.J., Kyser, T.K., Caldwell, W.G.E. and Longstaffe, F.J. (1995) Isotopic and chemical compositions of bentonites as paleoenvironmental indicators of the Cretaceous Western Interior Seaway Palaeogeography, Palaeoclimatology, Palaeoecology 119 pp. 301–320.

Reyment, R. A. and Savazzi, E. (1999) Aspects of Multivariate Statistical Analysis in Geology, Elsevier Science B.V., Amsterdam. <https://doi.org/10.1016/B978-044482568-1/50012-4>

Examples

```
data(bentonites)
```

canocov

Canonical correlation analysis.

Description

Function canocov performs a canonical correlation analysis. It operates on raw data matrices, which are only centered in the program. It uses generalized inverses and can deal with structurally singular covariance matrices.

Usage

```
canocov(X, Y)
```

Arguments

X	The n times p X matrix of observations
Y	The n times q Y matrix of observations

Details

canocov computes the solution by a singular value decomposition of the transformed between set covariance matrix.

Value

Returns a list with the following results

ccor	the canonical correlations
A	canonical weights of the X variables
B	canonical weights of the Y variables
U	canonical X variates
V	canonical Y variates
Fs	biplot markers for X variables (standard coordinates)
Gs	biplot markers for Y variables (standard coordinates)
Fp	biplot markers for X variables (principal coordinates)
Gp	biplot markers for Y variables (principal coordinates)
Rxu	canonical loadings, (correlations X variables, canonical X variates)
Rxv	canonical loadings, (correlations X variables, canonical Y variates)
Ryu	canonical loadings, (correlations Y variables, canonical X variates)
Ryv	canonical loadings, (correlations Y variables, canonical Y variates)
Sxu	covariance X variables, canonical X variates
Sxv	covariance X variables, canonical Y variates
Syu	covariance Y variables, canonical X variates
Syv	covariance Y variables, canonical Y variates
fitRxy	goodness of fit of the between-set correlation matrix
fitXs	adequacy coefficients of X variables
fitXp	redundancy coefficients of X variables
fitYs	adequacy coefficients of Y variables
fitYp	redundancy coefficients of Y variables

Author(s)

Jan Graffelman <jan.graffelman@upc.edu>

References

- Hotelling, H. (1935) The most predictable criterion. *Journal of Educational Psychology* (26) pp. 139-142.
- Hotelling, H. (1936) Relations between two sets of variates. *Biometrika* (28) pp. 321-377.
- Johnson, R. A. and Wichern, D. W. (2002) *Applied Multivariate Statistical Analysis*. New Jersey: Prentice Hall.

See Also

[cancor](#)

Examples

```
set.seed(123)
X <- matrix(runif(75),ncol=3)
Y <- matrix(runif(75),ncol=3)
cca.results <- canocov(X,Y)
```

cen	<i>centring of a data matrix</i>
-----	----------------------------------

Description

centres the columns of a matrix to mean zero.

Usage

```
cen(X,w=rep(1,nrow(X))/nrow(X))
```

Arguments

X	a raw data matrix.
w	a vector of case weights.

Value

returns a matrix

Author(s)

Jan Graffelman (jan.graffelman@upc.edu)

Examples

```
X<-matrix(runif(10),ncol=2)
Y<-cen(X)
print(Y)
```

clrmat *Centred log-ratio transformation*

Description

Program clrmat calculates the centred log-ratio transformation for a matrix of compositions.

Usage

```
clrmat(X)
```

Arguments

X A matrix of compositions

Value

A matrix containing the transformed data

Author(s)

Jan Graffelman <jan.graffelman@upc.edu>

Examples

```
data(Artificial)
Xsim.com <- Artificial$Xsim.com
Xclr <- clrmat(Xsim.com)
```

largest.kappas *Calculate condition indices for subcompositions*

Description

Function largest.kappas calculates the condition numbers for all subcompositions of a given size, for a particular compositional data set.

Usage

```
largest.kappas(Xcom, nparts = 3, sizetoplist = 10)
```

Arguments

Xcom A data matrix with compositions in rows
nparts The number of parts for the subcompositions to be analysed.
sizetoplist The length of the list of the "best" subcompositions

Details

Log-ratio PCA is executed for each subcomposition, and the resulting eigenvalues and eigenvectors are stored.

Value

A data frame with an ordered list of subcompositions

Author(s)

Jan Graffelman (jan.graffelman@upc.edu)

Examples

```
X <- matrix(runif(600), ncol=6)
Xcom <- X/rowSums(X)
Results <- largest.kappas(Xcom)
```

lrpca

Logratio principal component analysis with condition indices

Description

Function lrpca performs logratio principal component analysis. It returns the variance decomposition, principal components, biplot coordinates and a table with condition indices.

Usage

```
lrpca(Xcom)
```

Arguments

Xcom A matrix with compositions in its rows

Details

Calculations are based on the singular value decomposition of the clr transformed compositions.

Value

Fp	matrix with principal components
Fs	matrix with standardized principal components
Gp	biplot markers for parts (principal coordinates)
Gs	biplot markers for parts (standard coordinates)
La	eigenvalues
D	singular values
decom	table with variance decomposition
kappalist	table with condition indices and eigenvectors

Author(s)

Jan Graffelman (jan.graffelman@upc.edu)

See Also

[princomp](#),

Examples

```
data(bentonites)
Ben <- bentonites[,1:8]
Ben.com <- Ben/rowSums(Ben)
out.lrpca <- lrpca(Ben.com)
```

tr	<i>Compute the trace of a matrix</i>
----	--------------------------------------

Description

tr computes the trace of a matrix.

Usage

```
tr(X)
```

Arguments

X a (square) matrix

Value

the trace (a scalar)

Author(s)

Jan Graffelman (jan.graffelman@upc.edu)

Examples

```
X <- matrix(runif(25),ncol=5)
print(X)
print(tr(X))
```


Index

* **algebra**

tr, 8

* **array**

tr, 8

* **datasets**

Artificial, 2

bentonites, 2

* **multivariate**

canocov, 3

cen, 5

clrmat, 6

largest.kappas, 6

lrpca, 7

Artificial, 2

bentonites, 2

cancor, 5

canocov, 3

cen, 5

clrmat, 6

largest.kappas, 6

lrpca, 7

princomp, 8

tr, 8