

# Package ‘biogrowth’

August 28, 2022

**Type** Package

**Title** Modelling of Population Growth

**Version** 1.0.0-3

**Description** Modelling of population growth under static and dynamic environmental conditions. Includes functions for model fitting and making prediction under isothermal and dynamic conditions. The methods (algorithms & models) are based on predictive microbiology (See Perez-Rodriguez and Valero (2012, ISBN:978-1-4614-5519-6)).

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.2.1

**Imports** deSolve (>= 1.28), tibble (>= 3.0.3), dplyr (>= 0.8.5), FME (>= 1.3.6), MASS (>= 7.3), rlang (>= 0.4.7), purrr (>= 0.3.4), ggplot2 (>= 3.3.2), cowplot (>= 1.0.0), lamW (>= 1.3.0), tidyr (>= 1.0.2), formula.tools (>= 1.7.1), lifecycle

**Suggests** knitr, rmarkdown, tidyverse (>= 1.3.0)

**VignetteBuilder** knitr

**Depends** R (>= 2.10)

**NeedsCompilation** no

**Author** Alberto Garre [aut, cre] (<<https://orcid.org/0000-0002-4404-3550>>),  
Jeroen Koomen [aut],  
Heidy den Besten [aut],  
Marcel Zwietering [aut]

**Maintainer** Alberto Garre <garre.alberto@gmail.com>

**Repository** CRAN

**Date/Publication** 2022-08-28 20:50:05 UTC

## R topics documented:

approx\_env . . . . . 4

arabian_tractors . . . . .	4
calculate_gammas . . . . .	5
calculate_gammas_secondary . . . . .	5
check_growth_guess . . . . .	6
check_primary_pars . . . . .	8
check_secondary_pars . . . . .	8
check_stochastic_pars . . . . .	9
compare_growth_fits . . . . .	9
compare_secondary_fits . . . . .	13
conditions_pH_temperature . . . . .	15
CPM_model . . . . .	15
dBaranyi . . . . .	16
distribution_to_logcount . . . . .	16
DynamicGrowth . . . . .	17
example_cardinal . . . . .	19
example_dynamic_growth . . . . .	19
example_env_conditions . . . . .	20
extract_primary_pars . . . . .	20
extract_secondary_pars . . . . .	21
FitDynamicGrowth . . . . .	21
FitDynamicGrowthMCMC . . . . .	24
FitIsoGrowth . . . . .	27
FitMultipleDynamicGrowth . . . . .	29
FitMultipleGrowthMCMC . . . . .	32
FitSecondaryGrowth . . . . .	36
fit_dynamic_growth . . . . .	38
fit_growth . . . . .	40
fit_isothermal_growth . . . . .	47
fit_MCMC_growth . . . . .	49
fit_multiple_growth . . . . .	51
fit_multiple_growth_MCMC . . . . .	53
fit_secondary_growth . . . . .	55
full_Ratkowski . . . . .	57
get_all_predictions . . . . .	57
get_dyna_residuals . . . . .	58
get_iso_residuals . . . . .	59
get_multi_dyna_residuals . . . . .	59
get_secondary_residuals . . . . .	60
GlobalGrowthComparison . . . . .	61
GlobalGrowthFit . . . . .	63
GrowthComparison . . . . .	66
GrowthFit . . . . .	68
GrowthPrediction . . . . .	71
GrowthUncertainty . . . . .	73
growth_pH_temperature . . . . .	74
growth_salmonella . . . . .	75
is.DynamicGrowth . . . . .	75
is.FitDynamicGrowth . . . . .	76

is.FitDynamicGrowthMCMC . . . . .	76
is.FitIsoGrowth . . . . .	77
is.FitMultipleDynamicGrowth . . . . .	77
is.FitMultipleDynamicGrowthMCMC . . . . .	78
is.FitSecondaryGrowth . . . . .	78
is.GlobalGrowthFit . . . . .	79
is.GrowthFit . . . . .	79
is.GrowthPrediction . . . . .	80
is.GrowthUncertainty . . . . .	80
is.IsothermalGrowth . . . . .	81
is.MCMCgrowth . . . . .	81
is.StochasticGrowth . . . . .	82
IsothermalGrowth . . . . .	82
iso_Baranyi . . . . .	83
iso_repGompertz . . . . .	84
lambda_to_Q0 . . . . .	85
logistic_model . . . . .	85
make_guess_factor . . . . .	86
make_guess_primary . . . . .	86
make_guess_secondary . . . . .	87
MCMCgrowth . . . . .	88
multiple_conditions . . . . .	90
multiple_counts . . . . .	90
multiple_experiments . . . . .	91
predictMCMC . . . . .	91
predict_dynamic_growth . . . . .	92
predict_growth . . . . .	94
predict_growth_uncertainty . . . . .	98
predict_isothermal_growth . . . . .	100
predict_MCMC_growth . . . . .	101
predict_stochastic_growth . . . . .	103
primary_model_data . . . . .	104
Q0_to_lambda . . . . .	105
richards_model . . . . .	105
SecondaryComparison . . . . .	106
secondary_model_data . . . . .	107
show_guess_dynamic . . . . .	108
show_guess_primary . . . . .	109
StochasticGrowth . . . . .	109
TimeDistribution . . . . .	111
time_to_logcount . . . . .	112
time_to_size . . . . .	113
trilinear_model . . . . .	115
zwietering_gamma . . . . .	116

---

approx_env	<i>Generates functions for linear interpolation of environmental conditions</i>
------------	---

---

### Description

Generates functions for linear interpolation of environmental conditions

### Usage

```
approx_env(env_conditions)
```

### Arguments

`env_conditions` A tibble describing the variation of the environmental conditions through the storage time. Must contain a column named `time` and as many additional columns as environmental factors.

### Value

A list of functions that return the value of each environmental condition for some storage time

---

arabian_tractors	<i>Number of tractors in the Arab World according to the World Bank</i>
------------------	---

---

### Description

A dataset showing the increase in tractors in the Arab World. It was retrieved from <https://data.worldbank.org/indicator/AG.AA>

### Usage

```
arabian_tractors
```

### Format

A tibble with 40 rows (each corresponding to one year) and 7 columns:

**year** Year for the recording

**tractors** Number of tractors

---

calculate_gammas	<i>Calculates every gamma factor</i>
------------------	--------------------------------------

---

**Description**

A helper function for `predict_dynamic_growth()` that calculates the value of every gamma factor corresponding to some storage time.

**Usage**

```
calculate_gammas(this_t, env_func, sec_models)
```

**Arguments**

<code>this_t</code>	Storage time
<code>env_func</code>	A list of functions (generated using <code>approxfun</code> ) that give the value of each environmental function for some storage time.
<code>sec_models</code>	A nested list describing the secondary models.

**Value**

A vector of gamma factors (one per environmental factor).

---

calculate_gammas_secondary	<i>Gamma factors for fitting secondary models</i>
----------------------------	---

---

**Description**

A helper for fitting the secondary gamma models. Calculates the gamma factors corresponding to the models defined and the experimental conditions. In order for it to work, the environmental factors must be named identically in the 3 arguments.

**Usage**

```
calculate_gammas_secondary(sec_model_names, my_data, secondary_models)
```

**Arguments**

<code>sec_model_names</code>	named character vector defining the type of secondary model. Its names correspond to the environmental conditions and its values define the corresponding type of secondary model.
<code>my_data</code>	Tibble of experimental conditions.
<code>secondary_models</code>	A list defining the parameters of the secondary models.

**Value**

a numeric vector of length `nrow(my_data)` with the gamma factor for each experimental condition.

---

check_growth_guess	<i>Visual check of an initial guess of the model parameters</i>
--------------------	---

---

**Description****[Stable]**

Generates a plot comparing a set of data points against the model prediction corresponding to an initial guess of the model parameters

**Usage**

```
check_growth_guess(
  fit_data,
  model_keys,
  guess,
  environment = "constant",
  env_conditions = NULL,
  approach = "single",
  logbase_mu = 10,
  formula = logN ~ time
)
```

**Arguments**

<code>fit_data</code>	Tibble (or <code>data.frame</code> ) of data for the fit. It must have two columns, one with the elapsed time ( <code>time</code> by default) and another one with the decimal logarithm of the populatoin size ( <code>logN</code> by default). Different column names can be defined using the <code>formula</code> argument.
<code>model_keys</code>	Named the equations of the secondary model as in <code>fit_growth()</code>
<code>guess</code>	Named vector with the initial guess of the model parameters as in <code>fit_growth()</code>
<code>environment</code>	type of environment. Either "constant" (default) or "dynamic" (see below for details on the calculations for each condition)
<code>env_conditions</code>	Tibble describing the variation of the environmental conditions for dynamic experiments. See <code>fit_growth()</code> . Ignored when <code>environment = "constant"</code>
<code>approach</code>	whether "single" (default) or "global". Please see <code>fit_growth()</code> for details.“
<code>logbase_mu</code>	Base of the logarithm the growth rate is referred to. By default, 10 (i.e. <code>log10</code> ). See vignette about units for details.
<code>formula</code>	an object of class "formula" describing the x and y variables. <code>logN ~ time</code> as a default.

**Value**

A `ggplot()` comparing the model prediction against the data

**Examples**

```
## Examples under constant environmental conditions -----

## We need some data

my_data <- data.frame(time = 0:9,
                      logN = c(2, 2.1, 1.8, 2.5, 3.1, 3.4, 4, 4.5, 4.8, 4.7)
                      )

## We can directly plot the comparison for some values

check_growth_guess(my_data, list(primary = "modGompertz"),
                  c(logN0 = 1.5, mu = .8, lambda = 4, C = 3)
                  )

## Or it can be combined with the automatic initial guess

check_growth_guess(my_data, list(primary = "modGompertz"),
                  make_guess_primary(my_data, "modGompertz")
                  )

## Examples under dynamic environmental conditions -----

## We will use the datasets included in the package

data("example_dynamic_growth")
data("example_env_conditions")

## Model equations are assigned as in fit_growth

sec_models <- list(temperature = "CPM", aw = "CPM")

## Guesses of model parameters are also defined as in fit_growth

guess <- list(Nmax = 1e4,
             N0 = 1e0, Q0 = 1e-3,
             mu_opt = 4,
             temperature_n = 1,
             aw_xmax = 1, aw_xmin = .9, aw_n = 1,
             temperature_xmin = 25, temperature_xopt = 35,
             temperature_xmax = 40, aw_xopt = .95
             )

## We can now check our initial guess

check_growth_guess(example_dynamic_growth, sec_models, guess,
                  "dynamic",
```

```
example_env_conditions)
```

---

```
check_primary_pars    Basic check of parameters for primary models
```

---

### Description

Checks that: the model name is correct, the right number of model parameters have been defined and that the parameters have the right names

### Usage

```
check_primary_pars(model_name, pars)
```

### Arguments

model_name	Model identifier
pars	A named list of model parameters

### Value

If there is no error, the model function.

---

```
check_secondary_pars    Basic checks of secondary parameters
```

---

### Description

Checks that the model names are correct, that no parameter is defined twice, that every parameter is defined and that no unknown parameter has been defined. Raises an error if any of these conditions is not met.

### Usage

```
check_secondary_pars(
  starting_point,
  known_pars,
  sec_model_names,
  primary_pars = "mu_opt"
)
```



**Arguments**

starting_point	Named vector with initial values for the model parameters to estimate from the data. The growth rate under optimum conditions must be named <code>mu_opt</code> . The rest must be called <code>'env_factor'+ '_' + 'parameter'</code> . For instance, the minimum pH for growth is <code>'pH_xmin'</code> .
known_pars	Named vector of fixed model parameters. Must be named using the same convention as <code>starting_point</code> .
sec_model_names	Named character vector defining the secondary model for each environmental factor.
primary_pars	Character vector with the parameter names of the primary model.

---

check\_stochastic\_pars *Model definition checks for predict\_stochastic\_growth*

---

**Description**

Does several checks of the model parameters. Besides those by `check_primary_pars`, it checks that `corr_matrix` is square, that `pars` and `corr_matrix` have compatible dimensions, and that `pars` has the correct names.

**Usage**

```
check_stochastic_pars(model_name, pars, corr_matrix)
```

**Arguments**

model_name	Character describing the primary growth model.
pars	A tibble describing the parameter uncertainty (see details).
corr_matrix	Correlation matrix of the model parameters. Defined in the same order as in <code>pars</code> . An identity matrix by default (uncorrelated parameters).

---

compare\_growth\_fits *Model comparison and selection for growth models*

---

**Description****[Experimental]**

This function is a constructor for [GrowthComparison](#) or [GlobalGrowthComparison](#), a class that provides several functions for model comparison and model selection for growth models fitted using [fit\\_growth\(\)](#). Please see the help pages for [GrowthComparison](#) or [GlobalGrowthComparison](#) for further details.

Although it is not necessary, we recommend passing the models as a named list, as these names will later be kept in plots and tables.

**Usage**

```
compare_growth_fits(models)
```

**Arguments**

`models` a (we recommend named) list of models fitted using `fit_growth()`. Every model should be of the same class. Otherwise, some functions may give unexpected results.

**Examples**

```
## Example 1 - Fitting under static environmental conditions -----  
  
## We will use the data on growth of Salmonella included in the package  
data("growth_salmonella")  
  
## We will fit 3 different models to the data  
  
fit1 <- fit_growth(growth_salmonella,  
                  list(primary = "Baranyi"),  
                  start = c(lambda = 0, logNmax = 8, mu = .1, logN0 = 2),  
                  known = c(),  
                  environment = "constant",  
                  )  
  
fit2 <- fit_growth(growth_salmonella,  
                  list(primary = "Baranyi"),  
                  start = c(logNmax = 8, mu = .1, logN0 = 2),  
                  known = c(lambda = 0),  
                  environment = "constant",  
                  )  
  
fit3 <- fit_growth(growth_salmonella,  
                  list(primary = "modGompertz"),  
                  start = c(C = 8, mu = .1, logN0 = 2),  
                  known = c(lambda = 0),  
                  environment = "constant",  
                  )  
  
## We can now put them in a (preferably named) list  
  
my_models <- list(`Baranyi` = fit1,  
                 `Baranyi no lag` = fit2,  
                 `Gompertz no lag` = fit3)  
  
## And pass them to compare_growth_fits  
  
model_comparison <- compare_growth_fits(my_models)  
  
## The instance of GrowthComparison has useful S3 methods
```

```
print(model_comparison)
plot(model_comparison)
plot(model_comparison, type = 2)
plot(model_comparison, type = 3)

## The statistical indexes can be accessed through summary and coef

summary(model_comparison)
coef(model_comparison)

## Example 2 - Fitting under dynamic environmental conditions -----

## We will use one of the example datasets

data("example_dynamic_growth")
data("example_env_conditions")

## First model fitted

sec_models <- list(temperature = "CPM", aw = "CPM")

known_pars <- list(Nmax = 1e4,
                  N0 = 1e0, Q0 = 1e-3,
                  mu_opt = 4,
                  temperature_n = 1,
                  aw_xmax = 1, aw_xmin = .9, aw_n = 1
                  )

my_start <- list(temperature_xmin = 25, temperature_xopt = 35,
                temperature_xmax = 40, aw_xopt = .95)

dynamic_fit <- fit_growth(example_dynamic_growth,
                          sec_models,
                          my_start, known_pars,
                          environment = "dynamic",
                          env_conditions = example_env_conditions
                          )

## Second model (different secondary model for temperature)

sec_models <- list(temperature = "Zwietering", aw = "CPM")

known_pars <- list(Nmax = 1e4,
                  N0 = 1e0, Q0 = 1e-3,
                  mu_opt = 4,
                  temperature_n = 1,
                  aw_xmax = 1, aw_xmin = .9, aw_n = 1
                  )

my_start <- list(temperature_xmin = 25, temperature_xopt = 35,
                aw_xopt = .95)
```

```

dynamic_fit2 <- fit_growth(example_dynamic_growth,
                          sec_models,
                          my_start, known_pars,
                          environment = "dynamic",
                          env_conditions = example_env_conditions
                          )

## Once both models have been fitted, we can call the function

dynamic_comparison <- compare_growth_fits(list(m1 = dynamic_fit, m2 = dynamic_fit2))

## Which also returns an instance of GrowthComparison with the same S3 methods

print(dynamic_comparison)
plot(dynamic_comparison)
plot(dynamic_comparison, type = 2)
plot(dynamic_comparison, type = 3)

## The statistical indexes can be accessed through summary and coef

summary(dynamic_comparison)
coef(dynamic_comparison)

## Example 3 - Global fitting -----

## We use the example data

data("multiple_counts")
data("multiple_conditions")

## We need to fit (at least) two models

sec_models <- list(temperature = "CPM", pH = "CPM")

known_pars <- list(Nmax = 1e8, N0 = 1e0, Q0 = 1e-3,
                  temperature_n = 2, temperature_xmin = 20,
                  temperature_xmax = 35,
                  pH_n = 2, pH_xmin = 5.5, pH_xmax = 7.5, pH_xopt = 6.5)

my_start <- list(mu_opt = .8, temperature_xopt = 30)

global_fit <- fit_growth(multiple_counts,
                        sec_models,
                        my_start,
                        known_pars,
                        environment = "dynamic",
                        algorithm = "regression",
                        approach = "global",
                        env_conditions = multiple_conditions
                        )

```

```

sec_models <- list(temperature = "CPM", pH = "CPM")

known_pars <- list(Nmax = 1e8, N0 = 1e0, Q0 = 1e-3,
                  temperature_n = 1, temperature_xmin = 20,
                  temperature_xmax = 35,
                  pH_n = 2, pH_xmin = 5.5, pH_xmax = 7.5, pH_xopt = 6.5)

my_start <- list(mu_opt = .8, temperature_xopt = 30)

global_fit2 <- fit_growth(multiple_counts,
                        sec_models,
                        my_start,
                        known_pars,
                        environment = "dynamic",
                        algorithm = "regression",
                        approach = "global",
                        env_conditions = multiple_conditions
                        )

## We can now pass both models to the function as a (named) list
global_comparison <- compare_growth_fits(list(`n=2` = global_fit,
                                             `n=1` = global_fit2)
                                         )

## The residuals and model fits plots are divided by experiments

plot(global_comparison)
plot(global_comparison, type = 3)

## The remaining S3 methods are the same as before

print(global_comparison)
plot(global_comparison, type = 2)
summary(global_comparison)
coef(global_comparison)

```

---

compare\_secondary\_fits

*Model comparison and selection for secondary growth models*

---

## Description

### [Experimental]

This function is a constructor for [SecondaryComparison](#) a class that provides several functions for model comparison and model selection for growth models fitted using [fit\\_secondary\\_growth\(\)](#). Please see the help pages for [SecondaryComparison](#) for further details.

Although it is not necessary, we recommend passing the models as a named list, as these names will later be kept in plots and tables.

### Usage

```
compare_secondary_fits(models)
```

### Arguments

models            a (we recommend named) list of models fitted using [fit\\_secondary\\_growth\(\)](#).

### Examples

```
## We first need to fit some models

data("example_cardinal")

sec_model_names <- c(temperature = "Zwietering", pH = "CPM")

known_pars <- list(mu_opt = 1.2, temperature_n = 1,
                  pH_n = 2, pH_xmax = 6.8, pH_xmin = 5.2)

my_start <- list(temperature_xmin = 5, temperature_xopt = 35,
                pH_xopt = 6.5)

fit1 <- fit_secondary_growth(example_cardinal, my_start, known_pars, sec_model_names)

known_pars <- list(mu_opt = 1.2, temperature_n = 2,
                  pH_n = 2, pH_xmax = 6.8, pH_xmin = 5.2)

fit2 <- fit_secondary_growth(example_cardinal, my_start, known_pars, sec_model_names)

## We can now pass the models to the constructor

comparison <- compare_secondary_fits(list(`n=1` = fit1,
                                         `n=2` = fit2))

## The function includes several S3 methods for model selection and comparison

print(comparison)

plot(comparison)
plot(comparison, type = 2)

## The numerical indexes can be accessed using coef and summary

coef(comparison)
summary(comparison)
```

---

 conditions\_pH\_temperature

*Conditions during a dynamic growth experiment*


---

### Description

A dataset to demonstrate the use of `fit_dynamic_growth`. The observations environmental conditions are described in `conditions_pH_temperature`.

### Usage

```
conditions_pH_temperature
```

### Format

A tibble with 4 rows and 3 columns:

**time** elapsed time

**temperature** temperature

**pH** pH

---

 CPM\_model

*Secondary Cardinal Parameter (CPM) model*


---

### Description

Secondary cardinal parameter model as defined by Rosso et al. (1995).

### Usage

```
CPM_model(x, xmin, xopt, xmax, n)
```

### Arguments

<code>x</code>	Value of the environmental factor.
<code>xmin</code>	Minimum value for growth.
<code>xopt</code>	Optimum value for growth.
<code>xmax</code>	Maximum value for growth.
<code>n</code>	Order of the CPM model.

### Value

The corresponding gamma factor.

---

dBaranyi

*Baranyi growth model*


---

### Description

Microbial growth model as defined in Baranyi and Roberts (1994). It has been implemented according to the requirements of `ode()`. For consistency in the function for isothermal growth, calculations are done assuming the user input for  $\mu$  is in log10 scale. In other words, the input is multiplied by  $\ln(10)$ .

### Usage

```
dBaranyi(time, state, pars, env_func, sec_models)
```

### Arguments

time	numeric vector (length 1) of storage time
state	named numeric vector with two components: Q and N
pars	named numeric vector of model parameters (Nmax and mu_opt)
env_func	named list of functions returning the values of the environmental conditions for time (t)
sec_models	named list of parameters of the secondary model

### Value

A numeric vector of two components according to the requirements of `ode()`.

---

distribution\_to\_logcount

*Distribution of times to reach a certain microbial count*


---

### Description

#### [Superseded]

The function `distribution_to_logcount()` has been superseded by function `time_to_size()`, which provides more general interface.

Returns the probability distribution of the storage time required for the microbial count to reach `log_count` according to the predictions of a stochastic model. Calculations are done using linear interpolation of the individual model predictions.

### Usage

```
distribution_to_logcount(model, log_count)
```



**Arguments**

model            An instance of StochasticGrowth or MCMCgrowth.  
 log\_count        The target microbial count.

**Value**

An instance of `TimeDistribution()`.

**Examples**

```
## We need an instance of StochasticGrowth

my_model <- "modGompertz"
my_times <- seq(0, 30, length = 100)
n_sims <- 3000

library(tibble)

pars <- tribble(
  ~par, ~mean, ~sd, ~scale,
  "logN0", 0, .2, "original",
  "mu", 2, .3, "sqrt",
  "lambda", 4, .4, "sqrt",
  "C", 6, .5, "original"
)

stoc_growth <- predict_stochastic_growth(my_model, my_times, n_sims, pars)
```

---

 DynamicGrowth

*DynamicGrowth class*


---

**Description****[Superseded]**

The class `DynamicGrowth` has been superseded by the top-level class `GrowthPrediction`, which provides a unified approach for growth modelling.

Still, it is returned if the superseded `predict_dynamic_growth()` is called.

A subclass of list with items:

- simulation: A tibble with the model prediction
- gammas: A tibble with the value of each gamma factor for each value of times.
- env\_conditions: A list of functions interpolating the environmental conditions.
- primary\_pars: A list with the model parameters of the primary model.
- sec\_models: A nested list defining the secondary models.

**Usage**

```
## S3 method for class 'DynamicGrowth'
print(x, ...)

## S3 method for class 'DynamicGrowth'
plot(
  x,
  y = NULL,
  ...,
  add_factor = NULL,
  ylims = NULL,
  label_y1 = "logN",
  label_y2 = add_factor,
  line_col = "black",
  line_size = 1,
  line_type = "solid",
  line_col2 = "black",
  line_size2 = 1,
  line_type2 = "dashed",
  label_x = "time"
)

## S3 method for class 'DynamicGrowth'
coef(object, ...)
```

**Arguments**

x	The object of class DynamicGrowth to plot.
...	ignored
y	ignored
add_factor	whether to plot also one environmental factor. If NULL (default), no environmental factor is plotted. If set to one character string that matches one entry of x\$env_conditions, that condition is plotted in the secondary axis
ylims	A two dimensional vector with the limits of the primary y-axis.
label_y1	Label of the primary y-axis.
label_y2	Label of the secondary y-axis.
line_col	Aesthetic parameter to change the colour of the line geom in the plot, see: <a href="#">geom_line()</a>
line_size	Aesthetic parameter to change the thickness of the line geom in the plot, see: <a href="#">geom_line()</a>
line_type	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <a href="#">geom_line()</a>
line_col2	Same as lin_col, but for the environmental factor.
line_size2	Same as line_size, but for the environmental factor.
line_type2	Same as lin_type, but for the environmental factor.

label\_x      Label of the x-axis.  
 object      an instance of [DynamicGrowth](#)

### Methods (by generic)

- `print(DynamicGrowth)`: print of the model
- `plot(DynamicGrowth)`: predicted growth curve under dynamic conditions.
- `coef(DynamicGrowth)`: coefficients of the model

---

example\_cardinal      *Growth rates obtained for several growth experiments*

---

### Description

An example dataset illustrating the requirements of the [fit\\_secondary\\_growth\(\)](#) function.

### Usage

example\_cardinal

### Format

A data frame with 64 rows and 3 variables:

**temperature** storage temperature (°C)  
**pH** pH of the media  
**mu** specific growth rate (log<sub>10</sub> CFU/h)

---

example\_dynamic\_growth      *Microbial growth under dynamic conditions*

---

### Description

An example dataset illustrating the requirements of the [fit\\_dynamic\\_growth\(\)](#) function.

### Usage

example\_dynamic\_growth

### Format

A data frame with 30 rows and 2 variables:

**time** elapsed time (h)  
**logN** log population size (log<sub>10</sub> CFU)

example\_env\_conditions

*Environmental conditions during a dynamic experiment*

---

### Description

An example dataset illustrating the requirements of the `fit_dynamic_growth()` function.

### Usage

```
example_env_conditions
```

### Format

A data frame with 3 rows and 3 variables:

**time** elapsed time (h)

**temperature** storage temperature (°C)

**aw** water activity

---

extract\_primary\_pars *A helper to build the primary models*

---

### Description

Most of the functions for fitting mix in the vectors parameters for the primary and secondary models, but the functions for making predictions need that they are separated. This one extracts the parameters of the primary model.

### Usage

```
extract_primary_pars(this_p, known_pars)
```

### Arguments

`this_p` A named vector of model parameters (usually, the ones fitted).

`known_pars` Another named vector of model parameters (usually the known ones).

### Value

A list with the parameters of the primary model

---

 extract\_secondary\_pars

*A helper to build the secondary models*


---

### Description

Most of the functions for fitting mix in the vectors parameters for the primary and secondary models, but the functions for making predictions need that they are separated. This one extracts the parameters of the secondary model.

### Usage

```
extract_secondary_pars(this_p, known_pars, sec_model_names)
```

### Arguments

this_p	A named vector of model parameters (usually, the ones fitted).
known_pars	Another named vector of model parameters (usually the known ones).
sec_model_names	A named character vector defining for each environmental factor (vector names) the type of secondary model (vector values).

### Value

A nested list defining the secondary models.

---

FitDynamicGrowth

*FitDynamicGrowth class*

### Description

#### [Superseded]

The class `FitDynamicGrowth` has been superseded by the top-level class `GrowthFit`, which provides a unified approach for growth modelling.

Still, it is still returned if the superseded `fit_dynamic_growth()` is called.

It is a subclass of list with the items:

- `fit_results`: the object returned by `modFit`.
- `best_prediction`: the model prediction for the fitted parameters.
- `env_conditions`: environmental conditions for the fit.
- `data`: data used for the fit.
- `starting`: starting values for model fitting
- `known`: parameter values set as known.
- `sec_models`: a named vector with the secondary model for each environmental factor

**Usage**

```
## S3 method for class 'FitDynamicGrowth'
print(x, ...)

## S3 method for class 'FitDynamicGrowth'
plot(
  x,
  y = NULL,
  ...,
  add_factor = NULL,
  ylims = NULL,
  label_y1 = "logN",
  label_y2 = add_factor,
  line_col = "black",
  line_size = 1,
  line_type = 1,
  point_col = "black",
  point_size = 3,
  point_shape = 16,
  line_col2 = "black",
  line_size2 = 1,
  line_type2 = "dashed"
)

## S3 method for class 'FitDynamicGrowth'
summary(object, ...)

## S3 method for class 'FitDynamicGrowth'
residuals(object, ...)

## S3 method for class 'FitDynamicGrowth'
coef(object, ...)

## S3 method for class 'FitDynamicGrowth'
vcov(object, ...)

## S3 method for class 'FitDynamicGrowth'
deviance(object, ...)

## S3 method for class 'FitDynamicGrowth'
fitted(object, ...)

## S3 method for class 'FitDynamicGrowth'
predict(object, times = NULL, newdata = NULL, ...)

## S3 method for class 'FitDynamicGrowth'
logLik(object, ...)
```

```
## S3 method for class 'FitDynamicGrowth'
AIC(object, ..., k = 2)
```

### Arguments

x	The object of class FitDynamicGrowth to plot.
...	ignored
y	ignored
add_factor	whether to plot also one environmental factor. If NULL (default), no environmental factor is plotted. If set to one character string that matches one entry of x\$env_conditions, that condition is plotted in the secondary axis
ylims	A two dimensional vector with the limits of the primary y-axis.
label_y1	Label of the primary y-axis.
label_y2	Label of the secondary y-axis.
line_col	Aesthetic parameter to change the colour of the line geom in the plot, see: <a href="#">geom_line()</a>
line_size	Aesthetic parameter to change the thickness of the line geom in the plot, see: <a href="#">geom_line()</a>
line_type	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <a href="#">geom_line()</a>
point_col	Aesthetic parameter to change the colour of the point geom, see: <a href="#">geom_point()</a>
point_size	Aesthetic parameter to change the size of the point geom, see: <a href="#">geom_point()</a>
point_shape	Aesthetic parameter to change the shape of the point geom, see: <a href="#">geom_point()</a>
line_col2	Same as lin_col, but for the environmental factor.
line_size2	Same as line_size, but for the environmental factor.
line_type2	Same as lin_type, but for the environmental factor.
object	an instance of FitDynamicGrowth
times	A numeric vector with the time points for the simulations. NULL by default (using the same time points as those for the simulation).
newdata	a tibble describing the environmental conditions (as env_conditions) in <a href="#">predict_dynamic_growth()</a> . If NULL (default), uses the same conditions as those for fitting.
k	penalty for the parameters (k=2 by default)

### Methods (by generic)

- `print(FitDynamicGrowth)`: comparison between the fitted model and the data.
- `plot(FitDynamicGrowth)`: comparison between the fitted model and the data.
- `summary(FitDynamicGrowth)`: statistical summary of the fit.
- `residuals(FitDynamicGrowth)`: residuals of the model.
- `coef(FitDynamicGrowth)`: vector of fitted parameters.
- `vcov(FitDynamicGrowth)`: (unscaled) variance-covariance matrix of the model, calculated as  $1/(0.5 \cdot \text{Hessian})$

- `deviance(FitDynamicGrowth)`: deviance of the model.
- `fitted(FitDynamicGrowth)`: fitted values.
- `predict(FitDynamicGrowth)`: model predictions.
- `logLik(FitDynamicGrowth)`: loglikelihood of the model
- `AIC(FitDynamicGrowth)`: Akaike Information Criterion

---

FitDynamicGrowthMCMC *FitDynamicGrowthMCMC class*

---

## Description

### [Superseded]

The class `FitDynamicGrowthMCMC` has been superseded by the top-level class `GrowthFit`, which provides a unified approach for growth modelling.

Still, it is returned if the superseded `fit_MCMC_growth()` is called.

It is a subclass of list with the items:

- `fit_results`: the object returned by `modMCMC`.
- `best_prediction`: the model prediction for the fitted parameters.
- `env_conditions`: environmental conditions for the fit.
- `data`: data used for the fit.
- `starting`: starting values for model fitting
- `known`: parameter values set as known.
- `sec_models`: a named vector with the secondary model for each environmental factor

## Usage

```
## S3 method for class 'FitDynamicGrowthMCMC'
print(x, ...)
```

```
## S3 method for class 'FitDynamicGrowthMCMC'
plot(
  x,
  y = NULL,
  ...,
  add_factor = NULL,
  ylims = NULL,
  label_y1 = "logN",
  label_y2 = add_factor,
  line_col = "black",
  line_size = 1,
  line_type = 1,
  point_col = "black",
```



```
    point_size = 3,
    point_shape = 16,
    line_col2 = "black",
    line_size2 = 1,
    line_type2 = "dashed"
)

## S3 method for class 'FitDynamicGrowthMCMC'
summary(object, ...)

## S3 method for class 'FitDynamicGrowthMCMC'
residuals(object, ...)

## S3 method for class 'FitDynamicGrowthMCMC'
coef(object, ...)

## S3 method for class 'FitDynamicGrowthMCMC'
vcov(object, ...)

## S3 method for class 'FitDynamicGrowthMCMC'
deviance(object, ...)

## S3 method for class 'FitDynamicGrowthMCMC'
fitted(object, ...)

## S3 method for class 'FitDynamicGrowthMCMC'
predict(object, times = NULL, newdata = NULL, ...)

## S3 method for class 'FitDynamicGrowthMCMC'
logLik(object, ...)

## S3 method for class 'FitDynamicGrowthMCMC'
AIC(object, ..., k = 2)

## S3 method for class 'FitDynamicGrowthMCMC'
predictMCMC(
  model,
  times,
  env_conditions,
  niter,
  newpars = NULL,
  formula = . ~ time
)
```

### Arguments

x	The object of class FitDynamicGrowthMCMC to plot.
...	ignored

<code>y</code>	ignored
<code>add_factor</code>	whether to plot also one environmental factor. If NULL (default), no environmental factor is plotted. If set to one character string that matches one entry of <code>x\$env_conditions</code> , that condition is plotted in the secondary axis
<code>ylims</code>	A two dimensional vector with the limits of the primary y-axis.
<code>label_y1</code>	Label of the primary y-axis.
<code>label_y2</code>	Label of the secondary y-axis.
<code>line_col</code>	Aesthetic parameter to change the colour of the line geom in the plot, see: <a href="#">geom_line()</a>
<code>line_size</code>	Aesthetic parameter to change the thickness of the line geom in the plot, see: <a href="#">geom_line()</a>
<code>line_type</code>	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <a href="#">geom_line()</a>
<code>point_col</code>	Aesthetic parameter to change the colour of the point geom, see: <a href="#">geom_point()</a>
<code>point_size</code>	Aesthetic parameter to change the size of the point geom, see: <a href="#">geom_point()</a>
<code>point_shape</code>	Aesthetic parameter to change the shape of the point geom, see: <a href="#">geom_point()</a>
<code>line_col2</code>	Same as <code>line_col</code> , but for the environmental factor.
<code>line_size2</code>	Same as <code>line_size</code> , but for the environmental factor.
<code>line_type2</code>	Same as <code>line_type</code> , but for the environmental factor.
<code>object</code>	an instance of <code>FitDynamicGrowthMCMC</code>
<code>times</code>	Numeric vector of storage times for the predictions.
<code>newdata</code>	a tibble describing the environmental conditions (as <code>env_conditions</code> ) in <a href="#">predict_dynamic_growth()</a> . If NULL (default), uses the same conditions as those for fitting.
<code>k</code>	penalty for the parameters (k=2 by default)
<code>model</code>	An instance of <a href="#">FitDynamicGrowthMCMC</a>
<code>env_conditions</code>	Tibble with the (dynamic) environmental conditions during the experiment. It must have one column named 'time' with the storage time and as many columns as required with the environmental conditions.
<code>niter</code>	Number of iterations.
<code>newpars</code>	A named list defining new values for the some model parameters. The name must be the identifier of a model already included in the model. These parameters do not include variation, so defining a new value for a fitted parameters "fixes" it. NULL by default (no new parameters).
<code>formula</code>	A formula stating the column named defining the elapsed time in <code>env_conditions</code> . By default, <code>. ~ time</code> .

### Value

An instance of [MCMCgrowth\(\)](#).

**Methods (by generic)**

- `print(FitDynamicGrowthMCMC)`: print of the model
- `plot(FitDynamicGrowthMCMC)`: compares the model fitted against the data.
- `summary(FitDynamicGrowthMCMC)`: statistical summary of the fit.
- `residuals(FitDynamicGrowthMCMC)`: model residuals.
- `coef(FitDynamicGrowthMCMC)`: vector of fitted model parameters.
- `vcov(FitDynamicGrowthMCMC)`: variance-covariance matrix of the model, estimated as the variance of the samples from the Markov chain.
- `deviance(FitDynamicGrowthMCMC)`: deviance of the model, calculated as the sum of squared residuals for the parameter values resulting in the best fit.
- `fitted(FitDynamicGrowthMCMC)`: vector of fitted values.
- `predict(FitDynamicGrowthMCMC)`: vector of model predictions.
- `logLik(FitDynamicGrowthMCMC)`: loglikelihood of the model
- `AIC(FitDynamicGrowthMCMC)`: Akaike Information Criterion
- `predictMCMC(FitDynamicGrowthMCMC)`: prediction including parameter uncertainty

---

FitIsoGrowth

*FitIsoGrowth class*

---

**Description****[Superseded]**

The class [FitIsoGrowth](#) has been superseded by the top-level class [GrowthFit](#), which provides a unified approach for growth modelling.

Still, it is still returned if the superseded [fit\\_isothermal\\_growth\(\)](#) is called.

It is a subclass of list with the items:

- `data`: data used for model fitting
- `model`: name of the primary inactivation model
- `starting_point`: initial value of the model parameters
- `known`: fixed model parameters
- `fit`: object returned by [modFit\(\)](#)
- `best_prediction`: model prediction for the model fitted.

**Usage**

```
## S3 method for class 'FitIsoGrowth'
print(x, ...)

## S3 method for class 'FitIsoGrowth'
plot(
  x,
  y = NULL,
  ...,
  line_col = "black",
  line_size = 1,
  line_type = 1,
  point_col = "black",
  point_size = 3,
  point_shape = 16
)

## S3 method for class 'FitIsoGrowth'
summary(object, ...)

## S3 method for class 'FitIsoGrowth'
residuals(object, ...)

## S3 method for class 'FitIsoGrowth'
coef(object, ...)

## S3 method for class 'FitIsoGrowth'
vcov(object, ...)

## S3 method for class 'FitIsoGrowth'
deviance(object, ...)

## S3 method for class 'FitIsoGrowth'
fitted(object, ...)

## S3 method for class 'FitIsoGrowth'
predict(object, times = NULL, ...)

## S3 method for class 'FitIsoGrowth'
logLik(object, ...)

## S3 method for class 'FitIsoGrowth'
AIC(object, ..., k = 2)
```

**Arguments**

x	The object of class FitIsoGrowth to plot.
...	ignored

y	ignored
line_col	Aesthetic parameter to change the colour of the line geom in the plot, see: <a href="#">geom_line()</a>
line_size	Aesthetic parameter to change the thickness of the line geom in the plot, see: <a href="#">geom_line()</a>
line_type	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <a href="#">geom_line()</a>
point_col	Aesthetic parameter to change the colour of the point geom, see: <a href="#">geom_point()</a>
point_size	Aesthetic parameter to change the size of the point geom, see: <a href="#">geom_point()</a>
point_shape	Aesthetic parameter to change the shape of the point geom, see: <a href="#">geom_point()</a>
object	an instance of FitIsoGrowth
times	numeric vector describing the time points for the prediction. If NULL (default), uses the same points as those used for fitting.
k	penalty for the parameters (k=2 by default)

### Methods (by generic)

- `print(FitIsoGrowth)`: print of the model
- `plot(FitIsoGrowth)`: compares the fitted model against the data.
- `summary(FitIsoGrowth)`: statistical summary of the fit.
- `residuals(FitIsoGrowth)`: vector of model residuals.
- `coef(FitIsoGrowth)`: vector of fitted model parameters.
- `vcov(FitIsoGrowth)`: variance-covariance matrix of the model, estimated as  $1/(0.5 * \text{Hessian})$
- `deviance(FitIsoGrowth)`: deviance of the model.
- `fitted(FitIsoGrowth)`: vector of fitted values.
- `predict(FitIsoGrowth)`: vector of model predictions.
- `logLik(FitIsoGrowth)`: loglikelihood of the model
- `AIC(FitIsoGrowth)`: Akaike Information Criterion

---

FitMultipleDynamicGrowth

*FitMultipleDynamicGrowth class*

---

**Description****[Superseded]**

The class `FitMultipleDynamicGrowth` has been superseded by the top-level class `GlobalGrowthFit`, which provides a unified approach for growth modelling.

Still, it is still returned if the superseded `fit_multiple_growth()` is called.

It is a subclass of list with the items:

- `fit_results`: the object returned by `modFit`.
- `best_prediction`: a list with the models predictions for each condition.
- `data`: a list with the data used for the fit.
- `starting`: starting values for model fitting
- `known`: parameter values set as known.
- `sec_models`: a named vector with the secondary model for each environmental factor.

**Usage**

```
## S3 method for class 'FitMultipleDynamicGrowth'
print(x, ...)
```

```
## S3 method for class 'FitMultipleDynamicGrowth'
plot(
  x,
  y = NULL,
  ...,
  add_factor = NULL,
  ylims = NULL,
  label_x = "time",
  label_y1 = "logN",
  label_y2 = add_factor,
  line_col = "black",
  line_size = 1,
  line_type = "solid",
  line_col2 = "black",
  line_size2 = 1,
  line_type2 = "dashed",
  point_size = 3,
  point_shape = 16,
  subplot_labels = "AUTO"
)
```

```
## S3 method for class 'FitMultipleDynamicGrowth'
summary(object, ...)
```

```
## S3 method for class 'FitMultipleDynamicGrowth'
residuals(object, ...)
```

```

## S3 method for class 'FitMultipleDynamicGrowth'
coef(object, ...)

## S3 method for class 'FitMultipleDynamicGrowth'
vcov(object, ...)

## S3 method for class 'FitMultipleDynamicGrowth'
deviance(object, ...)

## S3 method for class 'FitMultipleDynamicGrowth'
fitted(object, ...)

## S3 method for class 'FitMultipleDynamicGrowth'
predict(object, env_conditions, times = NULL, ...)

## S3 method for class 'FitMultipleDynamicGrowth'
logLik(object, ...)

## S3 method for class 'FitMultipleDynamicGrowth'
AIC(object, ..., k = 2)

```

### Arguments

x	an instance of FitMultipleDynamicGrowth.
...	ignored
y	ignored
add_factor	whether to plot also one environmental factor. If NULL (default), no environmental factor is plotted. If set to one character string that matches one entry of x\$env_conditions, that condition is plotted in the secondary axis
ylims	A two dimensional vector with the limits of the primary y-axis.
label_x	label of the x-axis
label_y1	Label of the primary y-axis.
label_y2	Label of the secondary y-axis.
line_col	Aesthetic parameter to change the colour of the line geom in the plot, see: <a href="#">geom_line()</a>
line_size	Aesthetic parameter to change the thickness of the line geom in the plot, see: <a href="#">geom_line()</a>
line_type	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <a href="#">geom_line()</a>
line_col2	Same as lin_col, but for the environmental factor.
line_size2	Same as line_size, but for the environmental factor.
line_type2	Same as lin_type, but for the environmental factor.
point_size	Size of the data points
point_shape	shape of the data points

subplot_labels	labels of the subplots according to plot_grid.
object	an instance of FitMultipleDynamicGrowth
env_conditions	a tibble describing the environmental conditions (as in <a href="#">fit_multiple_growth()</a> ).
times	A numeric vector with the time points for the simulations. NULL by default (using the same time points as the ones defined in env_conditions).
k	penalty for the parameters (k=2 by default)

### Methods (by generic)

- `print(FitMultipleDynamicGrowth)`: print of the model
- `plot(FitMultipleDynamicGrowth)`: comparison between the fitted model and the experimental data.
- `summary(FitMultipleDynamicGrowth)`: statistical summary of the fit.
- `residuals(FitMultipleDynamicGrowth)`: calculates the model residuals. Returns a tibble with 4 columns: time (storage time), logN (observed count), exp (name of the experiment) and res (residual).
- `coef(FitMultipleDynamicGrowth)`: vector of fitted parameters.
- `vcov(FitMultipleDynamicGrowth)`: (unscaled) variance-covariance matrix, estimated as  $1/(0.5 * \text{Hessian})$ .
- `deviance(FitMultipleDynamicGrowth)`: deviance of the model.
- `fitted(FitMultipleDynamicGrowth)`: fitted values. They are returned as a tibble with 3 columns: time (storage time), exp (experiment identifier) and fitted (fitted value).
- `predict(FitMultipleDynamicGrowth)`: vector of model predictions
- `logLik(FitMultipleDynamicGrowth)`: loglikelihood of the model
- `AIC(FitMultipleDynamicGrowth)`: Akaike Information Criterion

---

FitMultipleGrowthMCMC *FitMultipleGrowthMCMC class*

---

### Description

#### [Superseded]

The class [FitMultipleGrowthMCMC](#) has been superseded by the top-level class [GlobalGrowthFit](#), which provides a unified approach for growth modelling.

Still, it is still returned if the superseded [fit\\_multiple\\_growth\\_MCMC\(\)](#) is called.

It is a subclass of list with the items:

- `fit_results`: the object returned by `modFit`.
- `best_prediction`: a list with the models predictions for each condition.
- `data`: a list with the data used for the fit.
- `starting`: starting values for model fitting
- `known`: parameter values set as known.
- `sec_models`: a named vector with the secondary model for each environmental factor.



**Usage**

```
## S3 method for class 'FitMultipleGrowthMCMC'
print(x, ...)

## S3 method for class 'FitMultipleGrowthMCMC'
plot(
  x,
  y = NULL,
  ...,
  add_factor = NULL,
  ylims = NULL,
  label_x = "time",
  label_y1 = "logN",
  label_y2 = add_factor,
  line_col = "black",
  line_size = 1,
  line_type = "solid",
  line_col2 = "black",
  line_size2 = 1,
  line_type2 = "dashed",
  point_size = 3,
  point_shape = 16,
  subplot_labels = "AUTO"
)

## S3 method for class 'FitMultipleGrowthMCMC'
summary(object, ...)

## S3 method for class 'FitMultipleGrowthMCMC'
residuals(object, ...)

## S3 method for class 'FitMultipleGrowthMCMC'
coef(object, ...)

## S3 method for class 'FitMultipleGrowthMCMC'
vcov(object, ...)

## S3 method for class 'FitMultipleGrowthMCMC'
deviance(object, ...)

## S3 method for class 'FitMultipleGrowthMCMC'
fitted(object, ...)

## S3 method for class 'FitMultipleGrowthMCMC'
predict(object, env_conditions, times = NULL, ...)

## S3 method for class 'FitMultipleGrowthMCMC'
logLik(object, ...)
```

```
## S3 method for class 'FitMultipleGrowthMCMC'
AIC(object, ..., k = 2)

## S3 method for class 'FitMultipleGrowthMCMC'
predictMCMC(
  model,
  times,
  env_conditions,
  niter,
  newpars = NULL,
  formula = . ~ time
)
```

### Arguments

x	an instance of FitMultipleGrowthMCMC.
...	ignored
y	ignored
add_factor	whether to plot also one environmental factor. If NULL (default), no environmental factor is plotted. If set to one character string that matches one entry of x\$env_conditions, that condition is plotted in the secondary axis
ylims	A two dimensional vector with the limits of the primary y-axis.
label_x	label of the x-axis
label_y1	Label of the primary y-axis.
label_y2	Label of the secondary y-axis.
line_col	Aesthetic parameter to change the colour of the line geom in the plot, see: <a href="#">geom_line()</a>
line_size	Aesthetic parameter to change the thickness of the line geom in the plot, see: <a href="#">geom_line()</a>
line_type	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <a href="#">geom_line()</a>
line_col2	Same as lin_col, but for the environmental factor.
line_size2	Same as line_size, but for the environmental factor.
line_type2	Same as lin_type, but for the environmental factor.
point_size	Size of the data points
point_shape	shape of the data points
subplot_labels	labels of the subplots according to plot_grid.
object	an instance of FitMultipleGrowthMCMC
env_conditions	Tibble with the (dynamic) environmental conditions during the experiment. It must have one column named 'time' with the storage time and as many columns as required with the environmental conditions.
times	Numeric vector of storage times for the predictions.

k	penalty for the parameters (k=2 by default)
model	An instance of <a href="#">FitMultipleGrowthMCMC</a>
niter	Number of iterations.
newpars	A named list defining new values for the some model parameters. The name must be the identifier of a model already included in the model. These parameters do not include variation, so defining a new value for a fitted parameters "fixes" it. NULL by default (no new parameters).
formula	A formula stating the column named defining the elapsed time in <code>env_conditions</code> . By default, <code>. ~ time</code> .

### Value

An instance of [MCMCgrowth\(\)](#).

### Methods (by generic)

- `print(FitMultipleGrowthMCMC)`: print of the model
- `plot(FitMultipleGrowthMCMC)`: comparison between the model fitted and the data.
- `summary(FitMultipleGrowthMCMC)`: statistical summary of the fit.
- `residuals(FitMultipleGrowthMCMC)`: model residuals. They are returned as a tibble with 4 columns: time (storage time), logN (observed count), exp (name of the experiment) and res (residual).
- `coef(FitMultipleGrowthMCMC)`: vector of fitted model parameters.
- `vcov(FitMultipleGrowthMCMC)`: variance-covariance matrix of the model, estimated as the variance of the samples from the Markov chain.
- `deviance(FitMultipleGrowthMCMC)`: deviance of the model, calculated as the sum of squared residuals of the prediction with the lowest standard error.
- `fitted(FitMultipleGrowthMCMC)`: fitted values of the model. They are returned as a tibble with 3 columns: time (storage time), exp (experiment identifier) and fitted (fitted value).
- `predict(FitMultipleGrowthMCMC)`: model predictions. They are returned as a tibble with 3 columns: time (storage time), logN (observed count), and exp (name of the experiment).
- `logLik(FitMultipleGrowthMCMC)`: loglikelihood of the model
- `AIC(FitMultipleGrowthMCMC)`: Akaike Information Criterion
- `predictMCMC(FitMultipleGrowthMCMC)`: prediction including parameter uncertainty

---

FitSecondaryGrowth      *FitSecondaryGrowth class*

---

### Description

The FitSecondaryGrowth class contains a model fitted to a set of growth rates gathered under a variety of static conditions. Its constructor is `fit_secondary_growth()`.

It is a subclass of list with the items:

- `fit_results`: object returned by `modFit()`.
- `secondary_model`: secondary model fitted to the data.
- `mu_opt_fit`: estimated growth rate under optimum conditions.
- `data`: data used for the fit.
- `transformation`: type of transformation of  $\mu$  for the fit.

### Usage

```
## S3 method for class 'FitSecondaryGrowth'
print(x, ...)

## S3 method for class 'FitSecondaryGrowth'
plot(x, y = NULL, ..., which = 1, add_trend = FALSE, add_segment = FALSE)

## S3 method for class 'FitSecondaryGrowth'
summary(object, ...)

## S3 method for class 'FitSecondaryGrowth'
residuals(object, ...)

## S3 method for class 'FitSecondaryGrowth'
coef(object, ...)

## S3 method for class 'FitSecondaryGrowth'
vcov(object, ...)

## S3 method for class 'FitSecondaryGrowth'
deviance(object, ...)

## S3 method for class 'FitSecondaryGrowth'
fitted(object, ...)

## S3 method for class 'FitSecondaryGrowth'
predict(object, newdata = NULL, ...)

## S3 method for class 'FitSecondaryGrowth'
logLik(object, ...)
```

```
## S3 method for class 'FitSecondaryGrowth'
AIC(object, ..., k = 2)
```

### Arguments

x	An instance of FitSecondaryGrowth.
...	ignored
y	ignored.
which	A numeric with the type of plot. 1 for obs versus predicted (default), 2 for gamma curve
add_trend	Whether to add a trend line (only for which=2)
add_segment	Whether to join the observed and fitted points (only for which=2)
object	an instance of FitSecondaryGrowth
newdata	A tibble describing the environmental conditions as in <a href="#">fit_secondary_growth()</a> . If NULL, it uses the same conditions as for model fitting (default).
k	penalty for the parameters (k=2 by default)

### Methods (by generic)

- `print(FitSecondaryGrowth)`: print of the model
- `plot(FitSecondaryGrowth)`: plots to evaluate the goodness of the fit.
- `summary(FitSecondaryGrowth)`: statistical summary of the fit.
- `residuals(FitSecondaryGrowth)`: vector of model residuals.
- `coef(FitSecondaryGrowth)`: vector of fitted model parameters.
- `vcov(FitSecondaryGrowth)`: variance-covariance matrix of the model, estimated as  $1/(0.5*\text{Hessian})$
- `deviance(FitSecondaryGrowth)`: deviance of the model.
- `fitted(FitSecondaryGrowth)`: vector of fitted values.  
The fitted values are returned in the same scale as the one used for the fitting (sqrt, log or none).
- `predict(FitSecondaryGrowth)`: vector of model predictions.
- `logLik(FitSecondaryGrowth)`: loglikelihood of the model
- `AIC(FitSecondaryGrowth)`: Akaike Information Criterion

---

fit\_dynamic\_growth      *Fit dynamic growth models*


---

## Description

### [Superseded]

The function `fit_dynamic_growth()` has been superseded by the top-level function `fit_growth()`, which provides a unified approach for growth modelling.

Nonetheless, it can still fit a growth model to data obtained under dynamic conditions using the one-step approach (non-linear regression).

## Usage

```
fit_dynamic_growth(
  fit_data,
  env_conditions,
  starting_point,
  known_pars,
  sec_model_names,
  ...,
  check = TRUE,
  logbase_mu = logbase_logN,
  logbase_logN = 10,
  formula = logN ~ time
)
```

## Arguments

- |                             |  |
|-----------------------------|--|
| <code>fit_data</code>       | Tibble with the data to use for model fit. It must contain a column with the elapsed time (named "time" by default) and another one with the decimal logarithm of the observed population size (named "logN" by default). Different column names can be specified using the "formula" argument.  |
| <code>env_conditions</code> | Tibble with the (dynamic) environmental conditions during the experiment. It must have one column with the elapsed time (named "time" by default) and as many columns as required with the environmental conditions. A different column name can be specified using the "formula" argument, although it must be the same one as in "fit_data". Note that only those defined in "sec_model_names" will be considered for the model fit. |
| <code>starting_point</code> | A named vector of starting values for the model parameters. Parameters for the primary model must be named in the usual way. Parameters for the secondary model are named as <code>env_factor+'_'+parameter</code> . For instance, the maximum growth temperature shall be named <code>'temperature_xmax'</code> .   |
| <code>known_pars</code>     | A named vector of known model parameters (i.e. not fitted). They must be named using the same convention as for <code>starting_point</code> .  |

sec_model_names	A named character vector defining the secondary model for each environmental factor. The names define the factor and the value the type of model. Names must match columns in fit_data and env_conditions.
...	Additional arguments passed to modFit.
check	Whether to check model parameters (TRUE by default).
logbase_mu	Base of the logarithm the growth rate is referred to. By default, the same as logbase_logN. See vignette about units for details.
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. log10). See vignette about units for details.
formula	an object of class "formula" describing the x and y variables. logN ~ time as a default.

### Value

An instance of `FitDynamicGrowth()`.

### Examples

```
## We use the datasets included in the package

data("example_dynamic_growth")
data("example_env_conditions")

## Define the secondary models

sec_model_names <- c(temperature = "CPM", aw= "CPM")

## Any model parameter can be fixed

known_pars <- list(Nmax = 1e4, # Primary model
  N0 = 1e0, Q0 = 1e-3, # Initial values of the primary model
  mu_opt = 4, # mu_opt of the gamma model
  temperature_n = 1, # Secondary model for temperature
  aw_xmax = 1, aw_xmin = .9, aw_n = 1 # Secondary model for water activity
)

## The remaining parameters need initial values

my_start <- list(temperature_xmin = 25, temperature_xopt = 35,
  temperature_xmax = 40, aw_xopt = .95)

## We can now call the fitting function

my_dyna_fit <- fit_dynamic_growth(example_dynamic_growth, example_env_conditions,
  my_start, known_pars, sec_model_names)

summary(my_dyna_fit)
```

```
## We can compare the data and the fitted curve

plot(my_dyna_fit)

## We can plot any environmental condition using add_factor

plot(my_dyna_fit, add_factor = "aw",
      label_y1 = "Log count (log CFU/ml)",
      label_y2 = "Water activity")
```

---

fit\_growth

*Fitting microbial growth*


---

## Description

### [Stable]

This function provides a top-level interface for fitting growth models to data describing the variation of the population size through time, either under constant or dynamic environment conditions. See below for details on the calculations.

## Usage

```
fit_growth(
  fit_data,
  model_keys,
  start,
  known,
  environment = "constant",
  algorithm = "regression",
  approach = "single",
  env_conditions = NULL,
  niter = NULL,
  ...,
  check = TRUE,
  logbase_mu = logbase_logN,
  logbase_logN = 10,
  formula = logN ~ time
)
```

## Arguments

fit_data	observed microbial growth. The format varies depending on the type of model fit. See the relevant sections (and examples) below for details.
model_keys	a named list assigning equations for the primary and secondary models. See the relevant sections (and examples) below for details.



start	a named numeric vector assigning initial guesses to the model parameters to estimate from the data. See relevant section (and examples) below for details.
known	named numeric vector of fixed model parameters, using the same conventions as for "start".
environment	type of environment. Either "constant" (default) or "dynamic" (see below for details on the calculations for each condition)
algorithm	either "regression" (default; Levenberg-Marquard algorithm) or "MCMC" (Adaptive Monte Carlo algorithm).
approach	approach for model fitting. Either "single" (the model is fitted to a unique experiment) or "global" (the model is fitted to several dynamic experiments).
env_conditions	Tibble describing the variation of the environmental conditions for dynamic experiments. See the relevant sections (and examples) below for details. Ignored for environment="constant".
niter	number of iterations of the MCMC algorithm. Ignored when algorithm!="MCMC".
...	Additional arguments for <code>modFit()</code> .
check	Whether to check the validity of the models. TRUE by default.
logbase_mu	Base of the logarithm the growth rate is referred to. By default, the same as <code>logbase_logN</code> . See vignette about units for details.
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. $\log_{10}$ ). See vignette about units for details.
formula	An object of class "formula" defining the names of the x and y variables in the data. $\log N \sim \text{time}$ as a default.

## Value

If approach="single, an instance of [GrowthFit](#). If approach="multiple", an instance of [GlobalGrowthFit](#)

Please check the help pages of each class for additional information.

## Fitting under constant conditions

When environment="constant", the functions fits a primary growth model to the population size observed during an experiment. In this case, the data has to be a tibble (or data.frame) with two columns:

- time: the elapsed time
- logN: the logarithm of the observed population size Nonetheless, the names of the columns can be modified with the formula argument.

The model equation is defined through the `model_keys` argument. It must include an entry named "primary" assigned to a model. Valid model keys can be retrieved calling `primary_model_data()`.

The model is fitted by non-linear regression (using `modFit()`). This algorithm needs initial guesses for every model parameter. These are defined as a named numeric vector. The names must be valid model keys, which can be retrieved using `primary_model_data()` (see example below). Apart from that, any model parameter can be fixed using the "known" argument. This is a named numeric vector, with the same conventions as "start".

### Fitting under dynamic conditions to a single experiment

When `environment="constant"` and `approach="single"`, a dynamic growth model combining the Baranyi primary growth model with the gamma approach for the effect of the environmental conditions on the growth rate is fitted to an experiment gathered under dynamic conditions. In this case, the data is similar to fitting under constant conditions: a tibble (or data.frame) with two columns:

- `time`: the elapsed time
- `logN`: the logarithm of the observed population size Note that these default names can be changed using the `formula` argument.

The values of the experimental conditions during the experiment are defined using the `"env_conditions"` argument. It is a tibble (or data.frame) with one column named (`"time"`) defining the elapsed time. Note that this default name can be modified using the `formula` argument of the function. The tibble needs to have as many additional columns as environmental conditions included in the model, providing the values of the environmental conditions.

The model equations are defined through the `model_keys` argument. It must be a named list where the names match the column names of `"env_conditions"` and the values are model keys. These can be retrieved using `secondary_model_data()`.

The model can be fitted using regression (`modFit()`) or an adaptive Monte Carlo algorithm (`modMCMC()`). Both algorithms require initial guesses for every model parameter to fit. These are defined through the named numeric vector `"start"`. Each parameter must be named as `factor+"_"+parameter`, where `factor` is the name of the environmental factor defined in `"model_keys"`. The `parameter` is a valid key that can be retrieved from `secondary_model_data()`. For instance, parameter `Xmin` for the factor `temperature` would be defined as `"temperature_xmin"`.

Note that the argument `...` allows passing additional arguments to the fitting functions.

### Fitting under dynamic conditions to multiple experiments (global fitting)

When `environment="constant"` and `approach="global"`, `fit_growth` tries to find the vector of model parameters that best describe the observations of several growth experiments.

The input requirements are very similar to the case when `approach="single"`. The models (equations, initial guesses, known parameters, algorithms...) are identical. The only difference is that `"fit_data"` must be a list, where each element describes the results of an experiment (using the same conventions as when `approach="single"`). In a similar fashion, `"env_conditions"` must be a list describing the values of the environmental factors during each experiment. Although it is not mandatory, it is recommended that the elements of both lists are named. Otherwise, the function assigns automatically-generated names, and matches them by order.#

### Examples

```
## Example 1 - Fitting a primary model -----
## A dummy dataset describing the variation of the population size
my_data <- data.frame(time = c(0, 25, 50, 75, 100),
                      logN = c(2, 2.5, 7, 8, 8))
```

```
## A list of model keys can be gathered from
primary_model_data()

## The primary model is defined as a list
models <- list(primary = "Baranyi")

## The keys of the model parameters can also be gathered from primary_model_data
primary_model_data("Baranyi")$pars

## Any model parameter can be fixed
known <- c(mu = .2)

## The remaining parameters need initial guesses
start <- c(logNmax = 8, lambda = 25, logN0 = 2)

primary_fit <- fit_growth(my_data, models, start, known,
                        environment = "constant",
                        )

## The instance of FitIsoGrowth includes several useful methods

print(primary_fit)
plot(primary_fit)
coef(primary_fit)
summary(primary_fit)

## time_to_size can be used to calculate the time for some concentration
time_to_size(primary_fit, 4)

## Example 2 - Fitting under dynamic conditions-----

## We will use the example data included in the package
data("example_dynamic_growth")

## And the example environmental conditions (temperature & aw)
data("example_env_conditions")

## Valid keys for secondary models can be retrieved from
secondary_model_data()

## We need to assign a model equation (secondary model) to each environmental factor
sec_models <- list(temperature = "CPM", aw = "CPM")
```



```

    )

## The instance of FitDynamicGrowthMCMC has several S3 methods

plot(MCMC_fit, add_factor = "aw")
summary(MCMC_fit)

## We can use time_to_size to calculate the time required to reach a given size

time_to_size(MCMC_fit, 3)

## It can also make growth predictions including uncertainty

uncertain_growth <- predictMCMC(MCMC_fit,
                                seq(0, 10, length = 1000),
                                example_env_conditions,
                                niter = 1000)

## The instance of MCMCgrowth includes several nice S3 methods

plot(uncertain_growth)
print(uncertain_growth)

## time_to_size can calculate the time to reach some count

time_to_size(uncertain_growth, 2)
time_to_size(uncertain_growth, 2, type = "distribution")

## Example 4 - Fitting a unique model to several dynamic experiments -----

## We will use the data included in the package

data("multiple_counts")
data("multiple_conditions")

## We need to assign a model equation for each environmental factor

sec_models <- list(temperature = "CPM", pH = "CPM")

## Any model parameter (of the primary or secondary models) can be fixed

known_pars <- list(Nmax = 1e8, N0 = 1e0, Q0 = 1e-3,
                  temperature_n = 2, temperature_xmin = 20,
                  temperature_xmax = 35,
                  pH_n = 2, pH_xmin = 5.5, pH_xmax = 7.5, pH_xopt = 6.5)

## The rest, need initial guesses

my_start <- list(mu_opt = .8, temperature_xopt = 30)

## We can now fit the model

```

```

global_fit <- fit_growth(multiple_counts,
                        sec_models,
                        my_start,
                        known_pars,
                        environment = "dynamic",
                        algorithm = "regression",
                        approach = "global",
                        env_conditions = multiple_conditions
                        )

## The instance of FitMultipleDynamicGrowth has nice S3 methods

plot(global_fit)
summary(global_fit)
print(global_fit)

## We can use time_to_size to calculate the time to reach a given size

time_to_size(global_fit, 4.5)

## Example 5 - MCMC fitting a unique model to several dynamic experiments ---

## Again, we can re-use all the arguments from the previous example
## We just need to define the right algorithm and the number of iterations
## On top of that, we will also pass upper and lower bounds to modMCMC

set.seed(12421)
global_MCMC <- fit_growth(multiple_counts,
                          sec_models,
                          my_start,
                          known_pars,
                          environment = "dynamic",
                          algorithm = "MCMC",
                          approach = "global",
                          env_conditions = multiple_conditions,
                          niter = 1000,
                          lower = c(.2, 29), # lower limits of the model parameters
                          upper = c(.8, 34) # upper limits of the model parameters
                          )

## The instance of FitMultipleDynamicGrowthMCMC has nice S3 methods

plot(global_MCMC)
summary(global_MCMC)
print(global_MCMC)

## We can use time_to_size to calculate the time to reach a given size

```

```
time_to_size(global_MCMC, 3)

## It can also be used to make model predictions with parameter uncertainty

uncertain_prediction <- predictMCMC(global_MCMC,
                                   seq(0, 50, length = 1000),
                                   multiple_conditions[[1]],
                                   niter = 100
                                   )

## The instance of MCMCgrowth includes several nice S3 methods

plot(uncertain_growth)
print(uncertain_growth)

## time_to_size can calculate the time to reach some count

time_to_size(uncertain_growth, 2)
time_to_size(uncertain_growth, 2, type = "distribution")
```

---

fit\_isothermal\_growth *Fit primary growth models*

---

## Description

### [Superseded]

The function `fit_isothermal_growth()` has been superseded by the top-level function `fit_growth()`, which provides a unified approach for growth modelling.

Nonetheless, it can still fit a primary growth model to data obtained under static environmental conditions.

## Usage

```
fit_isothermal_growth(
  fit_data,
  model_name,
  starting_point,
  known_pars,
  ...,
  check = TRUE,
  formula = logN ~ time,
  logbase_mu = logbase_logN,
  logbase_logN = 10
)
```

**Arguments**

fit_data	Tibble of data for the fit. It must have two columns, one with the elapsed time (time by default) and another one with the decimal logarithm of the population size (logN by default). Different column names can be defined using the formula argument.
model_name	Character defining the primary growth model
starting_point	Named vector of initial values for the model parameters.
known_pars	Named vector of known model parameters (not fitted).
...	Additional arguments passed to <code>modFit()</code> .
check	Whether to do some basic checks (TRUE by default).
formula	an object of class "formula" describing the x and y variables. $\log N \sim \text{time}$ as a default.
logbase_mu	Base of the logarithm the growth rate is referred to. By default, the same as <code>logbase_logN</code> . See vignette about units for details.
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. $\log_{10}$ ). See vignette about units for details.

**Value**

An instance of `FitIsoGrowth()`.

**Examples**

```
## Some dummy data

library(tibble)

my_data <- tibble(time = c(0, 25, 50, 75, 100),
                  logN = c(2, 2.5, 7, 8, 8))

## Choose the model

my_model <- "Baranyi"

## Initial values for the model parameters

start = c(logNmax = 8, lambda = 25, logN0 = 2)

## Any model parameter can be fixed

known <- c(mu = .2)

## Now, we can call the function

static_fit <- fit_isothermal_growth(my_data, my_model, start, known)

summary(static_fit)
```



```
## We can plot the fitted model against the observations

plot(static_fit)
```

---

fit_MCMC_growth	<i>Fit growth models using MCMC</i>
-----------------	-------------------------------------

---

## Description

### [Superseded]

The function `fit_MCMC_growth()` has been superseded by the top-level function `fit_growth()`, which provides a unified approach for growth modelling.

But, it can still fit a growth model to a data obtained under dynamic conditions using the one-step approach (MCMC algorithm).

## Usage

```
fit_MCMC_growth(
  fit_data,
  env_conditions,
  starting_point,
  known_pars,
  sec_model_names,
  niter,
  ...,
  check = TRUE,
  formula = logN ~ time,
  logbase_mu = logbase_logN,
  logbase_logN = 10
)
```

## Arguments

- |                             |  |
|-----------------------------|--|
| <code>fit_data</code>       | Tibble with the data to use for model fit. It must contain a column with the elapsed time (named "time" by default) and another one with the decimal logarithm of the observed population size (named "logN" by default). Different column names can be specified using the "formula" argument.  |
| <code>env_conditions</code> | Tibble with the (dynamic) environmental conditions during the experiment. It must have one column with the elapsed time (named "time" by default) and as many columns as required with the environmental conditions. A different column name can be specified using the "formula" argument, although it must be the same one as in "fit_data". Note that only those defined in "sec_model_names" will be considered for the model fit. |

starting_point	A named vector of starting values for the model parameters. Parameters for the primary model must be named in the usual way. Parameters for the secondary model are named as env_factor+'_'+parameter. For instance, the maximum growth temperature shall be named 'temperature_xmax'.
known_pars	A named vector of known model parameters (i.e. not fitted). They must be named using the same convention as for starting_point.
sec_model_names	A named character vector defining the secondary model for each environmental factor. The names define the factor and the value the type of model. Names must match columns in fit_data and env_conditions.
niter	number of iterations of the MCMC algorithm.
...	Additional arguments passed to modFit.
check	Whether to check model parameters (TRUE by default).
formula	an object of class "formula" describing the x and y variables. logN ~ time as a default.
logbase_mu	Base of the logarithm the growth rate is referred to. By default, the same as logbase_logN. See vignette about units for details.
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. log10). See vignette about units for details.

### Value

An instance of `FitDynamicGrowthMCMC()`.

### Examples

```
## We use the example data included in the package

data("example_dynamic_growth")
data("example_env_conditions")

## Definition of the secondary models
sec_model_names <- c(temperature = "CPM", aw= "CPM")

## Any model parameter can be fixed
known_pars <- list(Nmax = 1e4, # Primary model
  N0 = 1e0, Q0 = 1e-3, # Initial values of the primary model
  mu_opt = 4, # mu_opt of the gamma model
  temperature_n = 1, # Secondary model for temperature
  aw_xmax = 1, aw_xmin = .9, aw_n = 1 # Secondary model for water activity
)

## We need starting values for the remaining parameters

my_start <- list(temperature_xmin = 25, temperature_xopt = 35,
  temperature_xmax = 40,
  aw_xopt = .95)
```

```
## We can now call the fitting function

set.seed(12124) # Setting seed for repeatability

my_MCMC_fit <- fit_MCMC_growth(example_dynamic_growth, example_env_conditions,
  my_start, known_pars, sec_model_names, niter = 3000)

## Always check the MCMC chain!!

plot(my_MCMC_fit$fit_results)

## We can compare data against fitted curve

plot(my_MCMC_fit)

## Any environmental factor can be included using add_factor

plot(my_MCMC_fit, add_factor = "temperature",
  label_y1 = "Count (log CFU/ml)", label_y2 = "Temperature (C)")
```

---

fit\_multiple\_growth     *Fitting growth models to multiple dynamic experiments*

---

## Description

### [Superseded]

The function `fit_multiple_growth()` has been superseded by the top-level function `fit_growth()`, which provides a unified approach for growth modelling.

But, if you so wish, this function still enables fitting a growth model using a dataset comprised of several experiments with potentially different dynamic experimental conditions. Note that the definition of secondary models must comply with the `secondary_model_data` function.

## Usage

```
fit_multiple_growth(
  starting_point,
  experiment_data,
  known_pars,
  sec_model_names,
  ...,
  check = TRUE,
  formula = logN ~ time,
  logbase_mu = logbase_logN,
  logbase_logN = 10
)
```

**Arguments**

starting_point	a named vector of starting values for the model parameters.
experiment_data	a nested list with the experimental data. Each entry describes one experiment as a list with two elements: data and conditions. data is a tibble with a column giving the elapsed time (named "time" by default) and another one with the decimal logarithm of the population size (named "logN" by default). conditions is a tibble with one column giving the elapsed time (using the same name as data) and as many additional columns as environmental factors. The default column names can be changed with the formula argument.
known_pars	named vector of known model parameters
sec_model_names	named character vector with names of the environmental conditions and values of the secondary model (see secondary_model_data).
...	additional arguments for <code>modFit()</code> .
check	Whether to check the validity of the models. TRUE by default.
formula	an object of class "formula" describing the x and y variables. $\log N \sim \text{time}$ as a default.
logbase_mu	Base of the logarithm the growth rate is referred to. By default, the same as <code>logbase_logN</code> . See vignette about units for details.
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. $\log_{10}$ ). See vignette about units for details.

**Value**

An instance of `FitMultipleDynamicGrowth()`.

**Examples**

```
## We will use the multiple_experiments data set
data("multiple_experiments")

## For each environmental factor, we need to defined a model
sec_names <- c(temperature = "CPM", pH = "CPM")

## Any model parameter can be fixed
known <- list(Nmax = 1e8, N0 = 1e0, Q0 = 1e-3,
             temperature_n = 2, temperature_xmin = 20, temperature_xmax = 35,
             pH_n = 2, pH_xmin = 5.5, pH_xmax = 7.5, pH_xopt = 6.5)

## The rest require starting values for model fitting
start <- list(mu_opt = .8, temperature_xopt = 30)
```

```
## We can now call the fitting function

global_fit <- fit_multiple_growth(start, multiple_experiments, known, sec_names)

## Parameter estimates can be retrieved with summary

summary(global_fit)

## We can compare fitted model against observations

plot(global_fit)

## Any single environmental factor can be added to the plot using add_factor

plot(global_fit, add_factor = "temperature")
```

---

`fit_multiple_growth_MCMC`*Fitting growth models to multiple dynamic experiments using MCMC*

---

## Description

### [Superseded]

The function `fit_multiple_growth_MCMC()` has been superseded by the top-level function `fit_growth()`, which provides a unified approach for growth modelling.

However, this functions can still be used to fit a growth model using a dataset comprised of several experiments with potentially different dynamic experimental conditions.

## Usage

```
fit_multiple_growth_MCMC(  
  starting_point,  
  experiment_data,  
  known_pars,  
  sec_model_names,  
  niter,  
  ...,  
  check = TRUE,  
  formula = logN ~ time,  
  logbase_mu = logbase_logN,  
  logbase_logN = 10  
)
```

**Arguments**

starting_point	a named vector of starting values for the model parameters.
experiment_data	a nested list with the experimental data. Each entry describes one experiment as a list with two elements: data and conditions. data is a tibble with a column giving the elapsed time (named "time" by default) and another one with the decimal logarithm of the population size (named "logN" by default). conditions is a tibble with one column giving the elapsed time (using the same name as data) and as many additional columns as environmental factors. The default column names can be changed with the formula argument.
known_pars	named vector of known model parameters
sec_model_names	named character vector with names of the environmental conditions and values of the secondary model (see secondary_model_data).
niter	number of samples of the MCMC algorithm.
...	additional arguments for <a href="#">modMCMC</a> (e.g. upper and lower bounds).
check	Whether to check the validity of the models. TRUE by default.
formula	an object of class "formula" describing the x and y variables. $\log N \sim \text{time}$ as a default.
logbase_mu	Base of the logarithm the growth rate is referred to. By default, the same as logbase_logN. See vignette about units for details.
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. log10). See vignette about units for details.

**Value**

An instance of [FitMultipleGrowthMCMC\(\)](#).

**Examples**

```
## We will use the multiple_experiments data set
data("multiple_experiments")

## For each environmental factor, we need to defined a model
sec_names <- c(temperature = "CPM", pH = "CPM")

## Any model parameter can be fixed
known <- list(Nmax = 1e8, N0 = 1e0, Q0 = 1e-3,
             temperature_n = 2, temperature_xmin = 20, temperature_xmax = 35,
             pH_n = 2, pH_xmin = 5.5, pH_xmax = 7.5, pH_xopt = 6.5)

## The rest require starting values for model fitting
```

```

start <- list(mu_opt = .8, temperature_xopt = 30)

## We can now call the fitting function

set.seed(12412)
global_MCMC <- fit_multiple_growth_MCMC(start, multiple_experiments, known, sec_names, niter = 1000,
  lower = c(.2, 29), # lower limits of the model parameters
  upper = c(.8, 34)) # upper limits of the model parameters

## Parameter estimates can be retrieved with summary

summary(global_MCMC)

## We can compare fitted model against observations

plot(global_MCMC)

## Any single environmental factor can be added to the plot using add_factor

plot(global_MCMC, add_factor = "temperature")

```

---

fit\_secondary\_growth *Fit secondary growth models*

---

## Description

### [Stable]

Fits a secondary growth model to a set of growth rates obtained experimentally. Modelling is done according to the gamma concept proposed by Zwietering (1992) and cardinal parameter models.

## Usage

```

fit_secondary_growth(
  fit_data,
  starting_point,
  known_pars,
  sec_model_names,
  transformation = "sq",
  ...,
  check = TRUE,
  formula = mu ~ .
)

```

## Arguments

**fit\_data**      Tibble with the data used for the fit. It must have one column with the observed growth rate (named mu by default; can be changed using the "formula" argument) and as many columns as needed with the environmental factors.

starting_point	Named vector with initial values for the model parameters to estimate from the data. The growth rate under optimum conditions must be named <code>mu_opt</code> . The rest must be called <code>'env_factor'+ '_' + 'parameter'</code> . For instance, the minimum pH for growth is <code>'pH_xmin'</code> .
known_pars	Named vector of fixed model parameters. Must be named using the same convention as <code>starting_point</code> .
sec_model_names	Named character vector defining the secondary model for each environmental factor.
transformation	Character defining the transformation of <code>mu</code> for model fitting. One of <code>sq</code> (square root; default), <code>log</code> (log-transform) or <code>none</code> (no transformation).
...	Additional arguments passed to <code>modFit()</code> .
check	Whether to do some basic checks (TRUE by default).
formula	an object of class "formula" describing the y variable. The right hand side must be <code>"."</code> . By default <code>mu ~ ..</code>

### Value

An instance of `FitSecondaryGrowth()`.

### Examples

```
## We use the data included in the package
data("example_cardinal")

## Define the models to fit
sec_model_names <- c(temperature = "Zwietering", pH = "CPM")

## Any model parameter can be fixed
known_pars <- list(mu_opt = 1.2, temperature_n = 1,
  pH_n = 2, pH_xmax = 6.8, pH_xmin = 5.2)

## Initial values must be given for every other parameter
my_start <- list(temperature_xmin = 5, temperature_xopt = 35,
  pH_xopt = 6.5)

## We can now call the fitting function
fit_cardinal <- fit_secondary_growth(example_cardinal, my_start, known_pars, sec_model_names)

## With summary, we can look at the parameter estimates
summary(fit_cardinal)

## The plot function compares predictions against observations
```



```
plot(fit_cardinal)

## Passing which = 2, generates a different kind of plot

plot(fit_cardinal, which = 2)
plot(fit_cardinal, which = 2, add_trend = TRUE)
plot(fit_cardinal, which = 2, add_segment = TRUE)
```

---

full\_Ratkowski      *Full Ratkowsky model*

---

### Description

Gamma model adapted from the one by Ratkowsky et al. (1983).

### Usage

```
full_Ratkowski(x, xmin, xmax, c)
```

### Arguments

x	Value of the environmental factor.
xmin	Minimum value for growth
xmax	Maximum value for growth
c	Parameter defining the speed of the decline

---

get\_all\_predictions      *A helper for making the plots*

---

### Description

A helper for making the plots

### Usage

```
get_all_predictions(model)
```

### Arguments

model	An instance of FitMultipleDynamicGrowth
-------	---

---

get\_dyna\_residuals      *Residuals of dynamic prediction*

---

### Description

Function for calculating residuals of a dynamic prediction according to the requirements of `modFit()`.

### Usage

```
get_dyna_residuals(  
  this_p,  
  fit_data,  
  env_conditions,  
  known_pars,  
  sec_model_names,  
  cost = NULL,  
  logbase_mu = logbase_logN,  
  logbase_logN = 10  
)
```

### Arguments

<code>this_p</code>	named vector of model parameters
<code>fit_data</code>	tibble with the data for the fit
<code>env_conditions</code>	tibble with the environmental conditions
<code>known_pars</code>	named vector of known model parameters
<code>sec_model_names</code>	named character vector with names the environmental conditions and values the secondary model (e.g. 'CPM').
<code>cost</code>	an instance of <code>modCost</code> to be combined (to fit multiple models).
<code>logbase_mu</code>	Base of the logarithm of the growthrate. By default, the same as <code>logbase_logN</code> . See vignette about units for details.
<code>logbase_logN</code>	Base of the logarithm for the population size. By default, 10 (i.e. <code>log10</code> ). See vignette about units for details.

### Value

An instance of `modCost()`.

---

get\_iso\_residuals      *Residuals of isothermal prediction*

---

**Description**

Residuals of isothermal prediction

**Usage**

```
get_iso_residuals(  
  this_p,  
  fit_data,  
  model_name,  
  known_pars,  
  logbase_mu = logbase_logN,  
  logbase_logN = 10  
)
```

**Arguments**

this_p	named vector of model parameters to fit
fit_data	tibble with the data for the fit
model_name	character defining the primary growth model
known_pars	named vector of fixed model parameters
logbase_mu	Base of the logarithm the growth rate is referred to. By default, the same as logbase_logN. See vignette about units for details.
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. log10). See vignette about units for details.

**Value**

An instance of modCost.

---

get\_multi\_dyna\_residuals  
*Residuals of multiple dynamic predictions*

---

**Description**

Function for calculating residuals of dynamic predictions under different conditions for the same model parameters according to the requirements of `modFit()`.

**Usage**

```
get_multi_dyna_residuals(
  this_p,
  experiment_data,
  known_pars,
  sec_model_names,
  logbase_mu = logbase_logN,
  logbase_logN = 10
)
```

**Arguments**

<code>this_p</code>	named vector of model parameters
<code>experiment_data</code>	a nested list with the experimental data. Each entry describes one experiment as a list with two elements: <code>data</code> and <code>conditions</code> . <code>data</code> is a tibble with two columns: <code>time</code> and <code>logN</code> . <code>conditions</code> is a tibble with one column named <code>time</code> and as many additional columns as environmental factors.
<code>known_pars</code>	named vector of known model parameters
<code>sec_model_names</code>	named character vector with names of the environmental conditions and values of the secondary model (see <code>secondary_model_data</code> ).
<code>logbase_mu</code>	Base of the logarithm the growth rate is referred to. By default, the same as <code>logbase_logN</code> . See vignette about units for details.
<code>logbase_logN</code>	Base of the logarithm for the population size. By default, 10 (i.e. <code>log10</code> ). See vignette about units for details.

**Value**

an instance of `modCost`.

---

`get_secondary_residuals`

*Residuals of secondary models*

---

**Description**

Residual function for `fit_secondary_growth()`.

**Usage**

```
get_secondary_residuals(
  this_p,
  my_data,
  known_pars,
  sec_model_names,
  transformation
)
```

**Arguments**

<code>this_p</code>	Named vector of model parameter values.
<code>my_data</code>	Tibble with the data used for the fit.
<code>known_pars</code>	Named vector of fixed model parameters.
<code>sec_model_names</code>	Named character vector defining the secondary model for each environmental factor.
<code>transformation</code>	Character defining the transformation of mu for model fitting. One of <code>sq</code> (square root), <code>log</code> (log-transform) or <code>none</code> (no transformation).

**Value**

A numeric vector of residuals.

---

GlobalGrowthComparison

*GlobalGrowthComparison class*

---

**Description**

The `GlobalGrowthComparison` class contains several functions for model comparison and model selection of growth models. It should not be instanced directly. Instead, it should be constructed using `compare_growth_fits()`. It is similar to `GrowthComparison`, although with specific tools to deal with several experiments.

It includes two type of tools for model selection and comparison: statistical indexes and visual analyses. Please check the sections below for details.

Note that all these tools use the names defined in `compare_growth_fits()`, so we recommend passing a named list to that function.

**Usage**

```
## S3 method for class 'GlobalGrowthComparison'
coef(object, ...)
```

```
## S3 method for class 'GlobalGrowthComparison'
summary(object, ...)
```

```
## S3 method for class 'GlobalGrowthComparison'
print(x, ...)
```

```
## S3 method for class 'GlobalGrowthComparison'
plot(x, y, ..., type = 1, add_trend = TRUE)
```

**Arguments**

object	an instance of GlobalGrowthComparison
...	ignored
x	an instance of GlobalGrowthComparison
y	ignored
type	if type==1, the plot compares the model predictions. If type ==2, the plot compares the parameter estimates. If type==3, the plot shows the residuals
add_trend	should a trend line of the residuals be added for type==3? TRUE by default

**Methods (by generic)**

- `coef(GlobalGrowthComparison)`: table of parameter estimates
- `summary(GlobalGrowthComparison)`: summary table for the comparison
- `print(GlobalGrowthComparison)`: print of the model comparison
- `plot(GlobalGrowthComparison)`: illustrations comparing the fitted models

**Statistical indexes**

GlobalGrowthComparison implements two S3 methods to obtain numerical values to facilitate model comparison and selection.

- the `coef` method returns a tibble with the values of the parameter estimates and their corresponding standard errors for each model.
- the `summary` returns a tibble with the AIC, number of degrees of freedom, mean error and root mean squared error for each model.

**Visual analyses**

The S3 plot method can generate three types of plots:

- when `type = 1`, the plot compares the fitted growth curves against the experimental data used to fit the model.
- when `type = 2`, the plot compares the parameter estimates using error bars, where the limits of the error bars are the expected value +/- one standard error. In case one model does not have some model parameter (i.e. either because it is not defined or because it was fixed), the parameter is not included in the plot.
- when `type=3`, the plot shows the tendency of the residuals for each model. This plot can be used to detect deviations from independence.

These plots are divided by facets for each experiment.

---

GlobalGrowthFit	<i>GlobalGrowthFit class</i>
-----------------	------------------------------

---

## Description

### [Stable]

The `GlobalGrowthFit` class contains a growth model fitted to data using a global approach. Its constructor is `fit_growth()`.

It is a subclass of list with the items:

- `algorithm`: type of algorithm as in `fit_growth()`
- `data`: data used for model fitting
- `start`: initial guess of the model parameters
- `known`: fixed model parameters
- `primary_model`: a character describing the primary model
- `fit_results`: an instance of `modFit` or `modMCMC` with the results of the fit
- `best_prediction`: Instance of `GrowthPrediction` with the best growth fit
- `sec_models`: a named vector with the secondary models assigned for each environmental factor. `NULL` for `environment="constant"`
- `env_conditions`: a list with the environmental conditions used for model fitting. `NULL` for `environment="constant"`
- `niter`: number of iterations of the Markov chain. `NULL` if `algorithm != "MCMC"`
- `logbase_mu`: base of the logarithm for the definition of parameter `mu` (check the relevant vignette)
- `logbase_logN`: base of the logarithm for the definition of the population size (check the relevant vignette)
- `environment`: "dynamic". Always

## Usage

```
## S3 method for class 'GlobalGrowthFit'
print(x, ...)

## S3 method for class 'GlobalGrowthFit'
coef(object, ...)

## S3 method for class 'GlobalGrowthFit'
summary(object, ...)

## S3 method for class 'GlobalGrowthFit'
predict(object, env_conditions, times = NULL, ...)

## S3 method for class 'GlobalGrowthFit'
```

```
residuals(object, ...)

## S3 method for class 'GlobalGrowthFit'
vcov(object, ...)

## S3 method for class 'GlobalGrowthFit'
deviance(object, ...)

## S3 method for class 'GlobalGrowthFit'
fitted(object, ...)

## S3 method for class 'GlobalGrowthFit'
logLik(object, ...)

## S3 method for class 'GlobalGrowthFit'
AIC(object, ..., k = 2)

## S3 method for class 'GlobalGrowthFit'
plot(
  x,
  y = NULL,
  ...,
  add_factor = NULL,
  ylims = NULL,
  label_x = "time",
  label_y1 = NULL,
  label_y2 = add_factor,
  line_col = "black",
  line_size = 1,
  line_type = "solid",
  line_col2 = "black",
  line_size2 = 1,
  line_type2 = "dashed",
  point_size = 3,
  point_shape = 16,
  subplot_labels = "AUTO"
)

## S3 method for class 'GlobalGrowthFit'
predictMCMC(
  model,
  times,
  env_conditions,
  niter,
  newpars = NULL,
  formula = . ~ time
)
```



**Arguments**

x	an instance of <code>GlobalGrowthFit</code>
...	ignored
object	an instance of <code>GlobalGrowthFit</code>
env_conditions	Tibble with the (dynamic) environmental conditions during the experiment. It must have one column named 'time' with the storage time and as many columns as required with the environmental conditions.
times	Numeric vector of storage times for the predictions.
k	penalty for the parameters (k=2 by default)
y	ignored
add_factor	whether to plot also one environmental factor. If NULL (default), no environmental factor is plotted. If set to one character string that matches one entry of <code>x\$env_conditions</code> , that condition is plotted in the secondary axis
ylims	A two dimensional vector with the limits of the primary y-axis.
label_x	label of the x-axis
label_y1	Label of the primary y-axis.
label_y2	Label of the secondary y-axis.
line_col	Aesthetic parameter to change the colour of the line geom in the plot, see: <code>geom_line()</code>
line_size	Aesthetic parameter to change the thickness of the line geom in the plot, see: <code>geom_line()</code>
line_type	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <code>geom_line()</code>
line_col2	Same as <code>line_col</code> , but for the environmental factor.
line_size2	Same as <code>line_size</code> , but for the environmental factor.
line_type2	Same as <code>line_type</code> , but for the environmental factor.
point_size	Size of the data points
point_shape	shape of the data points
subplot_labels	labels of the subplots according to <code>plot_grid</code> .
model	An instance of <code>GlobalGrowthFit</code>
niter	Number of iterations.
newpars	A named list defining new values for the some model parameters. The name must be the identifier of a model already included in the model. These parameters do not include variation, so defining a new value for a fitted parameters "fixes" it. NULL by default (no new parameters).
formula	A formula stating the column named defining the elapsed time in <code>env_conditions</code> . By default, <code>. ~ time</code> .

**Value**

An instance of `MCMCgrowth`.

**Methods (by generic)**

- `print(GlobalGrowthFit)`: print of the model
- `coef(GlobalGrowthFit)`: vector of fitted model parameters.
- `summary(GlobalGrowthFit)`: statistical summary of the fit.
- `predict(GlobalGrowthFit)`: vector of model predictions
- `residuals(GlobalGrowthFit)`: model residuals. They are returned as a tibble with 4 columns: time (storage time), logN (observed count), exp (name of the experiment) and res (residual).
- `vcov(GlobalGrowthFit)`: variance-covariance matrix of the model, estimated as  $1/(0.5 * \text{Hessian})$  for regression and as the variance-covariance of the draws for MCMC
- `deviance(GlobalGrowthFit)`: deviance of the model.
- `fitted(GlobalGrowthFit)`: fitted values. They are returned as a tibble with 3 columns: time (storage time), exp (experiment identifier) and fitted (fitted value).
- `logLik(GlobalGrowthFit)`: loglikelihood of the model
- `AIC(GlobalGrowthFit)`: Akaike Information Criterion
- `plot(GlobalGrowthFit)`: comparison between the fitted model and the experimental data.
- `predictMCMC(GlobalGrowthFit)`: prediction including parameter uncertainty

---

GrowthComparison

*GrowthComparison class*


---

**Description**

The `GrowthComparison` class contains several functions for model comparison and model selection of growth models. It should not be instanced directly. Instead, it should be constructed using `compare_growth_fits()`.

It includes two type of tools for model selection and comparison: statistical indexes and visual analyses. Please check the sections below for details.

Note that all these tools use the names defined in `compare_growth_fits()`, so we recommend passing a named list to that function.

**Usage**

```
## S3 method for class 'GrowthComparison'
plot(x, y, ..., type = 1, add_trend = TRUE)

## S3 method for class 'GrowthComparison'
coef(object, ...)

## S3 method for class 'GrowthComparison'
print(x, ...)

## S3 method for class 'GrowthComparison'
summary(object, ...)
```

**Arguments**

x	an instance of <a href="#">GrowthComparison</a>
y	ignored
...	ignored
type	if type==1, the plot compares the model predictions. If type==2, the plot compares the parameter estimates. If type==3, the plot shows the residuals
add_trend	should a trend line of the residuals be added for type==3? TRUE by default
object	an instance of <a href="#">GrowthComparison</a>

**Methods (by generic)**

- `plot(GrowthComparison)`: illustrations comparing the fitted models
- `coef(GrowthComparison)`: table of parameter estimates
- `print(GrowthComparison)`: print of the model comparison
- `summary(GrowthComparison)`: summary table for the comparison

**Statistical indexes**

`GrowthComparison` implements two S3 methods to obtain numerical values to facilitate model comparison and selection.

- the `coef` method returns a tibble with the values of the parameter estimates and their corresponding standard errors for each model.
- the `summary` returns a tibble with the AIC, number of degrees of freedom, mean error and root mean squared error for each model.

**Visual analyses**

The S3 plot method can generate three types of plots:

- when `type = 1`, the plot compares the fitted growth curves against the experimental data used to fit the model.
- when `type = 2`, the plot compares the parameter estimates using error bars, where the limits of the error bars are the expected value +/- one standard error. In case one model does not have some model parameter (i.e. either because it is not defined or because it was fixed), the parameter is not included in the plot.
- when `type=3`, the plot shows the tendency of the residuals for each model. This plot can be used to detect deviations from independence.

GrowthFit

*GrowthFit class***Description****[Stable]**

The `GrowthFit` class contains a growth model fitted to data under static or dynamic conditions. Its constructor is `fit_growth()`.

It is a subclass of list with the items:

- `environment`: type of environment as in `fit_growth()`
- `algorithm`: type of algorithm as in `fit_growth()`
- `data`: data used for model fitting
- `start`: initial guess of the model parameters
- `known`: fixed model parameters
- `primary_model`: a character describing the primary model
- `fit_results`: an instance of `modFit` or `modMCMC` with the results of the fit
- `best_prediction`: Instance of `GrowthPrediction` with the best growth fit
- `sec_models`: a named vector with the secondary models assigned for each environmental factor. NULL for `environment="constant"`
- `env_conditions`: a tibble with the environmental conditions used for model fitting. NULL for `environment="constant"`
- `niter`: number of iterations of the Markov chain. NULL if `algorithm != "MCMC"`
- `logbase_mu`: base of the logarithm for the definition of parameter `mu` (check the relevant vignette)
- `logbase_logN`: base of the logarithm for the definition of the population size (check the relevant vignette)

**Usage**

```
## S3 method for class 'GrowthFit'
print(x, ...)

## S3 method for class 'GrowthFit'
coef(object, ...)

## S3 method for class 'GrowthFit'
summary(object, ...)

## S3 method for class 'GrowthFit'
predict(object, times = NULL, env_conditions = NULL, ...)

## S3 method for class 'GrowthFit'
```

```
residuals(object, ...)

## S3 method for class 'GrowthFit'
vcov(object, ...)

## S3 method for class 'GrowthFit'
deviance(object, ...)

## S3 method for class 'GrowthFit'
fitted(object, ...)

## S3 method for class 'GrowthFit'
logLik(object, ...)

## S3 method for class 'GrowthFit'
AIC(object, ..., k = 2)

## S3 method for class 'GrowthFit'
plot(
  x,
  y = NULL,
  ...,
  add_factor = NULL,
  line_col = "black",
  line_size = 1,
  line_type = 1,
  point_col = "black",
  point_size = 3,
  point_shape = 16,
  ylims = NULL,
  label_y1 = NULL,
  label_y2 = add_factor,
  label_x = "time",
  line_col2 = "black",
  line_size2 = 1,
  line_type2 = "dashed"
)

## S3 method for class 'GrowthFit'
predictMCMC(
  model,
  times,
  env_conditions,
  niter,
  newpars = NULL,
  formula = . ~ time
)
```

**Arguments**

x	The object of class <a href="#">GrowthFit</a> to plot.
...	ignored.
object	an instance of <a href="#">GrowthFit</a>
times	Numeric vector of storage times for the predictions.
env_conditions	Tibble with the (dynamic) environmental conditions during the experiment. It must have one column named 'time' with the storage time and as many columns as required with the environmental conditions.
k	penalty for the parameters (k=2 by default)
y	ignored
add_factor	whether to plot also one environmental factor. If NULL (default), no environmental factor is plotted. If set to one character string that matches one entry of x\$env_conditions, that condition is plotted in the secondary axis. Ignored if environment="constant"
line_col	Aesthetic parameter to change the colour of the line geom in the plot, see: <a href="#">geom_line()</a>
line_size	Aesthetic parameter to change the thickness of the line geom in the plot, see: <a href="#">geom_line()</a>
line_type	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <a href="#">geom_line()</a>
point_col	Aesthetic parameter to change the colour of the point geom, see: <a href="#">geom_point()</a>
point_size	Aesthetic parameter to change the size of the point geom, see: <a href="#">geom_point()</a>
point_shape	Aesthetic parameter to change the shape of the point geom, see: <a href="#">geom_point()</a>
ylims	A two dimensional vector with the limits of the primary y-axis. NULL by default
label_y1	Label of the primary y-axis.
label_y2	Label of the secondary y-axis. Ignored if environment="constant"
label_x	Label of the x-axis
line_col2	Same as line_col, but for the environmental factor. Ignored if environment="constant"
line_size2	Same as line_size, but for the environmental factor. Ignored if environment="constant"
line_type2	Same as line_type, but for the environmental factor. Ignored if environment="constant"
model	An instance of <a href="#">GrowthFit</a>
niter	Number of iterations.
newpars	A named list defining new values for the some model parameters. The name must be the identifier of a model already included in the model. These parameters do not include variation, so defining a new value for a fitted parameters "fixes" it. NULL by default (no new parameters).
formula	A formula stating the column named defining the elapsed time in env_conditions. By default, . ~ time.

**Value**

An instance of [MCMCgrowth](#).

**Methods (by generic)**

- `print(GrowthFit)`: print of the model
- `coef(GrowthFit)`: vector of fitted model parameters.
- `summary(GrowthFit)`: statistical summary of the fit.
- `predict(GrowthFit)`: vector of model predictions.
- `residuals(GrowthFit)`: vector of model residuals.
- `vcov(GrowthFit)`: variance-covariance matrix of the model, estimated as  $1/(0.5*\text{Hessian})$  for regression and as the variance-covariance of the draws for MCMC
- `deviance(GrowthFit)`: deviance of the model.
- `fitted(GrowthFit)`: vector of fitted values.
- `logLik(GrowthFit)`: loglikelihood of the model
- `AIC(GrowthFit)`: Akaike Information Criterion
- `plot(GrowthFit)`: compares the fitted model against the data.
- `predictMCMC(GrowthFit)`: prediction including parameter uncertainty

---

GrowthPrediction

*GrowthPrediction class*


---

**Description****[Stable]**

The `GrowthPrediction` class contains the results of a growth prediction. Its constructor is `predict_growth()`.

It is a subclass of list with the items:

- `simulation`: a tibble with the model simulation
- `primary model`: a list describing the primary model as in `predict_growth()`
- `environment`: a character describing the type of environmental conditions as in `predict_growth()`
- `env_conditions`: a named list with the functions used to approximate the (dynamic) environmental conditions. NULL if `environment="constant"`.
- `sec_models`: a named list describing the secondary models as in `predict_growth()`. NULL if `environment="constant"`.
- `gammas`: a tibble describing the variation of the gamma factors through the experiment. NULL if `environment="constant"`.
- `logbase_mu`: the log-base for the definition of parameter mu (see the relevant vignette)
- `logbase_logN`: the log-base for the definition of the logarithm of the population size

**Usage**

```

## S3 method for class 'GrowthPrediction'
print(x, ...)

## S3 method for class 'GrowthPrediction'
summary(object, ...)

## S3 method for class 'GrowthPrediction'
plot(
  x,
  y = NULL,
  ...,
  add_factor = NULL,
  ylims = NULL,
  label_y1 = NULL,
  label_y2 = add_factor,
  line_col = "black",
  line_size = 1,
  line_type = "solid",
  line_col2 = "black",
  line_size2 = 1,
  line_type2 = "dashed",
  label_x = "time"
)

## S3 method for class 'GrowthPrediction'
coef(object, ...)

```

**Arguments**

x	The object of class GrowthPrediction to plot.
...	ignored
object	an instance of <a href="#">GrowthPrediction</a>
y	ignored
add_factor	whether to plot also one environmental factor. If NULL (default), no environmental factor is plotted. If set to one character string that matches one entry of x\$env_conditions, that condition is plotted in the secondary axis. Ignored for environment="constant".
ylims	A two dimensional vector with the limits of the primary y-axis.
label_y1	Label of the primary y-axis.
label_y2	Label of the secondary y-axis.
line_col	Aesthetic parameter to change the colour of the line geom in the plot, see: <a href="#">geom_line()</a>
line_size	Aesthetic parameter to change the thickness of the line geom in the plot, see: <a href="#">geom_line()</a>



line_type	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <a href="#">geom_line()</a>
line_col2	Same as lin_col, but for the environmental factor.
line_size2	Same as line_size, but for the environmental factor.
line_type2	Same as lin_type, but for the environmental factor.
label_x	Label of the x-axis.

### Methods (by generic)

- `print(GrowthPrediction)`: print of the model
- `summary(GrowthPrediction)`: summary of the model
- `plot(GrowthPrediction)`: predicted growth curve.
- `coef(GrowthPrediction)`: coefficients of the model

---

GrowthUncertainty      *GrowthUncertainty class*

---

### Description

#### [Stable]

The GrowthUncertainty class contains the results of a growth prediction under isothermal conditions considering parameter uncertainty. Its constructor is [predict\\_growth\\_uncertainty\(\)](#).

It is a subclass of list with the items:

- sample: parameter sample used for the calculations.
- simulations: growth curves predicted for each parameter.
- quantiles: limits of the credible intervals (5%, 10%, 50%, 90%, 95%) for each time point.
- model: Model used for the calculations.
- mus: Mean parameter values used for the simulations.
- sigma: Variance-covariance matrix used for the simulations.

### Usage

```
## S3 method for class 'GrowthUncertainty'
print(x, ...)

## S3 method for class 'GrowthUncertainty'
plot(
  x,
  y = NULL,
  ...,
  line_col = "black",
  line_size = 0.5,
```

```

    line_type = "solid",
    ribbon80_fill = "grey",
    ribbon90_fill = "grey",
    alpha80 = 0.5,
    alpha90 = 0.4
  )

```

### Arguments

x	The object of class GrowthUncertainty to plot.
...	ignored.
y	ignored
line_col	Aesthetic parameter to change the colour of the line geom in the plot, see: <a href="#">geom_line()</a>
line_size	Aesthetic parameter to change the thickness of the line geom in the plot, see: <a href="#">geom_line()</a>
line_type	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <a href="#">geom_line()</a>
ribbon80_fill	fill colour for the space between the 10th and 90th quantile, see: <a href="#">geom_ribbon()</a>
ribbon90_fill	fill colour for the space between the 5th and 95th quantile, see: <a href="#">geom_ribbon()</a>
alpha80	transparency of the ribbon aesthetic for the space between the 10th and 90th quantile. Takes a value between 0 (fully transparant) and 1 (fully opaque)
alpha90	transparency of the ribbon aesthetic for the space between the 5th and 95th quantile. Takes a value between 0 (fully transparant) and 1 (fully opaque).

### Methods (by generic)

- `print(GrowthUncertainty)`: print of the model
- `plot(GrowthUncertainty)`: Growth prediction (prediction band) considering parameter uncertainty.

---

growth\_pH\_temperature *Example of dynamic growth*

---

### Description

A dataset to demonstrate the use of `fit_dynamic_growth`. The values of the environmental conditions are described in `conditions_pH_temperature`.

### Usage

```
growth_pH_temperature
```

**Format**

A tibble with 20 rows and 2 columns:

**time** elapsed time

**logN** decimal logarithm of the population size

---

growth_salmonella	<i>Growth of Salmonella spp in broth</i>
-------------------	--

---

**Description**

An example dataset to illustrate `fit_isothermal_growth()`. It describes the growth of Salmonella spp. in broth. It was retrieved from ComBase (ID: B092\_10).

**Usage**

```
growth_salmonella
```

**Format**

A tibble with 21 rows and 2 columns:

**time** elapsed time in hours.

**logN** observed population size (log CFU/g).

---

is.DynamicGrowth	<i>Test of DynamicGrowth object</i>
------------------	-------------------------------------

---

**Description**

Tests if an object is of class `DynamicGrowth`.

**Usage**

```
is.DynamicGrowth(x)
```

**Arguments**

**x** object to be checked.

**Value**

A boolean specifying whether `x` is of class `DynamicGrowth`

---

is.FitDynamicGrowth     *Test of FitDynamicGrowth object*

---

**Description**

Tests if an object is of class FitDynamicGrowth.

**Usage**

```
is.FitDynamicGrowth(x)
```

**Arguments**

x                    object to be checked.

**Value**

A boolean specifying whether x is of class FitDynamicGrowth

---

is.FitDynamicGrowthMCMC  
                                  *Test of FitDynamicGrowthMCMC object*

---

**Description**

Tests if an object is of class FitDynamicGrowthMCMC.

**Usage**

```
is.FitDynamicGrowthMCMC(x)
```

**Arguments**

x                    object to be checked.

**Value**

A boolean specifying whether x is of class FitDynamicGrowthMCMC

---

is.FitIsoGrowth      *Test of FitIsoGrowth object*

---

**Description**

Tests if an object is of class FitIsoGrowth.

**Usage**

is.FitIsoGrowth(x)

**Arguments**

x                    object to be checked.

**Value**

A boolean specifying whether x is of class FitIsoGrowth

---

is.FitMultipleDynamicGrowth  
                                 *Test of FitMultipleDynamicGrowth object*

---

**Description**

Tests if an object is of class FitMultipleDynamicGrowth.

**Usage**

is.FitMultipleDynamicGrowth(x)

**Arguments**

x                    object to be checked.

**Value**

A boolean specifying whether x is of class FitMultipleDynamicGrowth

is.FitMultipleDynamicGrowthMCMC

*Test of FitMultipleDynamicGrowthMCMC object*

---

**Description**

Tests if an object is of class FitMultipleDynamicGrowthMCMC.

**Usage**

```
is.FitMultipleDynamicGrowthMCMC(x)
```

**Arguments**

x                    object to be checked.

**Value**

A boolean specifying whether x is of class FitMultipleDynamicGrowthMCMC

---

is.FitSecondaryGrowth    *Test of FitSecondaryGrowth object*

---

**Description**

Tests if an object is of class FitSecondaryGrowth.

**Usage**

```
is.FitSecondaryGrowth(x)
```

**Arguments**

x                    object to be checked.

**Value**

A boolean specifying whether x is of class FitSecondaryGrowth

---

is.GlobalGrowthFit      *Test of GlobalGrowthFit object*

---

**Description**

Tests if an object is of class [GlobalGrowthFit](#)

**Usage**

is.GlobalGrowthFit(x)

**Arguments**

x                      object to be checked.

**Value**

A boolean specifying whether x is of class GlobalGrowthFit

---

is.GrowthFit              *Test of GrowthFit object*

---

**Description**

Tests if an object is of class [GrowthFit](#)

**Usage**

is.GrowthFit(x)

**Arguments**

x                      object to be checked.

**Value**

A boolean specifying whether x is of class GrowthFit

---

`is.GrowthPrediction`    *Test of GrowthPrediction object*

---

**Description**

Tests if an object is of class [GrowthPrediction](#)

**Usage**

`is.GrowthPrediction(x)`

**Arguments**

`x`                    object to be checked.

**Value**

A boolean specifying whether `x` is of class `GrowthPrediction`

---

`is.GrowthUncertainty`    *Test of GrowthUncertainty object*

---

**Description**

Tests if an object is of class [GrowthUncertainty](#)

**Usage**

`is.GrowthUncertainty(x)`

**Arguments**

`x`                    object to be checked.

**Value**

A boolean specifying whether `x` is of class `GrowthUncertainty`



---

*is.IsothermalGrowth*     *Test of IsothermalGrowth object*

---

**Description**

Tests if an object is of class IsothermalGrowth.

**Usage**

`is.IsothermalGrowth(x)`

**Arguments**

`x`                    object to be checked.

**Value**

A boolean specifying whether `x` is of class IsothermalGrowth

---

*is.MCMCgrowth*             *Test of MCMCgrowth object*

---

**Description**

Tests if an object is of class MCMCgrowth.

**Usage**

`is.MCMCgrowth(x)`

**Arguments**

`x`                    object to be checked.

**Value**

A boolean specifying whether `x` is of class MCMCgrowth

---

is.StochasticGrowth     *Test of StochasticGrowth object*

---

### Description

Tests if an object is of class StochasticGrowth.

### Usage

```
is.StochasticGrowth(x)
```

### Arguments

x                    object to be checked.

### Value

A boolean specifying whether x is of class StochasticGrowth

---

IsothermalGrowth     *IsothermalGrowth class*

---

### Description

#### [Superseded]

The class [IsothermalGrowth](#) has been superseded by the top-level class [GrowthPrediction](#), which provides a unified approach for growth modelling.

Still, it is still returned if the superseded [predict\\_isothermal\\_growth\(\)](#) is called.

It is a subclass of list with the items:

- simulation: A tibble with the model simulation.
- model: The name of the model used for the predictions.
- pars: A list with the values of the model parameters.

### Usage

```
## S3 method for class 'IsothermalGrowth'
print(x, ...)
```

```
## S3 method for class 'IsothermalGrowth'
plot(
  x,
  y = NULL,
  ...,
```

```

    line_col = "black",
    line_size = 1,
    line_type = "solid",
    ylims = NULL,
    label_y = NULL,
    label_x = "time"
)

## S3 method for class 'IsothermalGrowth'
coef(object, ...)

```

### Arguments

x	The object of class <code>IsothermalGrowth</code> to plot.
...	ignored
y	ignored
line_col	Aesthetic parameter to change the colour of the line, see: <code>geom_line()</code>
line_size	Aesthetic parameter to change the thickness of the line, see: <code>geom_line()</code>
line_type	Aesthetic parameter to change the type of the line, takes numbers (1-6) or strings ("solid") see: <code>geom_line()</code>
ylims	Two-dimensional numeric vector with the limits of the y-axis (or NULL, which is the default)
label_y	Title of the y-axis
label_x	Title of the x-axis
object	an instance of <code>IsothermalGrowth</code>

### Methods (by generic)

- `print(IsothermalGrowth)`: print of the model
- `plot(IsothermalGrowth)`: plot of the predicted growth curve.
- `coef(IsothermalGrowth)`: coefficients of the model

---

iso\_Baranyi

*Isothermal Baranyi model*

---

### Description

Baranyi growth model as defined by Baranyi and Roberts (1994). We use the solution calculated by Poschet et al. (2005, doi: <https://doi.org/10.1016/j.ijfoodmicro.2004.10.008>) after log-transformation according to MONTE CARLO ANALYSIS FOR MICROBIAL GROWTH CURVES, by Oksuz and Buzrul.

### Usage

```
iso_Baranyi(times, logN0, mu, lambda, logNmax)
```

**Arguments**

times	Numeric vector of storage times
logN0	Initial log microbial count
mu	Maximum specific growth rate (in ln CFU/t)
lambda	Lag phase duration
logNmax	Maximum log microbial count

**Value**

Numeric vector with the predicted microbial count.

---

iso_repGompertz	<i>Reparameterized Gompertz model</i>
-----------------	---------------------------------------

---

**Description**

Reparameterized Gompertz growth model defined by Zwietering et al. (1990).

**Usage**

```
iso_repGompertz(times, logN0, C, mu, lambda)
```

**Arguments**

times	Numeric vector of storage times
logN0	Initial log microbial count
C	Difference between logN0 and the maximum log-count.
mu	Maximum specific growth rate (in ln CFU/t)
lambda	Lag phase duration

**Value**

Numeric vector with the predicted microbial count.

---

lambda_to_Q0	<i>Q0 from lag phase duration</i>
--------------	-----------------------------------

---

**Description****[Stable]**

Convenience function to calculate the value of Q0 for the Baranyi model from the duration of the lag phase

**Usage**

```
lambda_to_Q0(lambda, mu, logbase_mu = 10)
```

**Arguments**

lambda	Duration of the lag phase.
mu	Specific growth rate in the exponential phase.
logbase_mu	Base of the logarithm the growth rate is referred to. By default, 10 (i.e. log10). See vignette about units for details.

---

logistic_model	<i>Logistic growth model</i>
----------------	------------------------------

---

**Description**

Logistic growth model

**Usage**

```
logistic_model(times, logN0, mu, lambda, C)
```

**Arguments**

times	Numeric vector of storage times
logN0	Initial log microbial count
mu	Maximum specific growth rate (in ln CFU/t)
lambda	Lag phase duration
C	Difference between logN0 and the maximum log-count.

**Value**

Numeric vector with the predicted microbial count

---

make\_guess\_factor      *Initial guesses for the secondary model of one factor*

---

### Description

Initial guesses for the secondary model of one factor

### Usage

```
make_guess_factor(fit_data, sec_model, factor)
```

### Arguments

fit_data	Tibble with the data used for the fit. It must have one column with the observed growth rate (named mu by default; can be changed using the "formula" argument) and as many columns as needed with the environmental factors.
sec_model	character defining the secondary model equation according to <a href="#">secondary_model_data()</a>
factor	character defining the environmental factor

---

make\_guess\_primary      *Initial guesses for fitting primary growth models*

---

### Description

#### [Experimental]

The function uses some heuristics to provide initial guesses for the parameters of the growth model selected that can be used with [fit\\_growth\(\)](#).

### Usage

```
make_guess_primary(
  fit_data,
  primary_model,
  logbase_mu = 10,
  formula = logN ~ time
)
```

### Arguments

fit_data	the experimental data. A tibble (or data.frame) with a column named time with the elapsed time and one called logN with the logarithm of the population size
primary_model	a string defining the equation of the primary model, as defined in <a href="#">primary_model_data()</a>
logbase_mu	Base of the logarithm the growth rate is referred to. By default, 10 (i.e. log10). See vignette about units for details.
formula	an object of class "formula" describing the x and y variables. logN ~ time as a default.

**Value**

A named numeric vector of initial guesses for the model parameters

**Examples**

```
## An example of experimental data
my_data <- data.frame(time = 0:9,
                      logN = c(2, 2.1, 1.8, 2.5, 3.1, 3.4, 4, 4.5, 4.8, 4.7))

## We just need to pass the data and the model equation
make_guess_primary(my_data, "Logistic")

## We can use this together with fit_growth()
fit_growth(my_data,
           list(primary = "Logistic"),
           make_guess_primary(my_data, "Logistic"),
           c()
           )

## The parameters returned by the function are adapted to the model
make_guess_primary(my_data, "Baranyi")

## It can express mu in other logbases
make_guess_primary(my_data, "Baranyi", logbase_mu = exp(1)) # natural
make_guess_primary(my_data, "Baranyi", logbase_mu = 2) # base2
```

---

make\_guess\_secondary *Initial guesses for the parameters of a secondary model*

---

**Description****[Experimental]**

Uses some heuristic rules to generate an initial guess of the model parameters of secondary growth models that can be used for model fitting with [fit\\_secondary\\_growth\(\)](#).

**Usage**

```
make_guess_secondary(fit_data, sec_model_names)
```

**Arguments**

<code>fit_data</code>	Tibble with the data used for the fit. It must have one column with the observed growth rate (named <code>mu</code> by default; can be changed using the "formula" argument) and as many columns as needed with the environmental factors.
<code>sec_model_names</code>	Named character vector defining the secondary model for each environmental factor.

**Examples**

```
## We can use the example dataset included in the package
data("example_cardinal")

## We assign model equations to factors as usual
sec_model_names <- c(temperature = "Zwietering", pH = "fullRatkowsky")

## We can then calculate the initial guesses
make_guess_secondary(example_cardinal, sec_model_names)

## We can pass these parameters directly to fit_secondary_growth
fit_secondary_growth(example_cardinal,
                     make_guess_secondary(example_cardinal, sec_model_names),
                     c(),
                     sec_model_names)
```

---

MCMCgrowth

*MCMCgrowth class*


---

**Description****[Stable]**

The MCMCgrowth class contains the results of a growth prediction consider parameter variability based on a model fitted using an MCMC algorithm.

It is a subclass of list with items:

- `sample`: Parameter sample used for the calculations.
- `simulations`: Individual growth curves calculated based on the parameter sample.
- `quantiles`: Tibble with the limits of the credible intervals (5%, 10%, 50%, 90% and 95%) for each time point.
- `model`: Instance of `FitDynamicGrowthMCMC` used for predictions.
- `env_conditions`: A tibble with the environmental conditions of the simulation.



**Usage**

```

## S3 method for class 'MCMCgrowth'
print(x, ...)

## S3 method for class 'MCMCgrowth'
plot(
  x,
  y = NULL,
  ...,
  add_factor = NULL,
  alpha_80 = 0.5,
  fill_80 = "grey",
  alpha_90 = 0.5,
  fill_90 = "grey",
  label_y1 = "logN",
  label_y2 = add_factor,
  line_col = "black",
  line_type = 1,
  line_size = 1,
  line_type2 = 2,
  line_col2 = "black",
  line_size2 = 1,
  ylims = NULL
)

```

**Arguments**

x	The object of class MCMCgrowth to plot.
...	ignored.
y	ignored
add_factor	Includes the variation of one environmental factor in the plot. It must be one of the column names in x\$env_conditions.
alpha_80	transparency of the ribbon for the 80th posterior. .5 by default.
fill_80	fill colour of the ribbon for the 80th posterior. "grey" by default.
alpha_90	transparency of the ribbon for the 90th posterior. .5 by default.
fill_90	fill colour of the ribbon for the 90th posterior. "grey" by default.
label_y1	label of the primary y axis. "logN" by default.
label_y2	label of the secondary y axis. The name of the environmental factor by default.
line_col	colour of the line representing the median. "black" by default.
line_type	linetype for the line representing the median. solid by default.
line_size	size of the line representing the median. 1 by default.
line_type2	linetype for the line representing the environmental condition. Dashed by default.
line_col2	colour of the line representing the environmental condition. "black" by default.

line\_size2      size of the line representing the environmental condition. 1 by default.  
 ylims            limits of the primary y-axis. NULL by default (let ggplot choose).

### Methods (by generic)

- print(MCMCgrowth): print of the model
- plot(MCMCgrowth): plot of predicted growth (prediction band).

---

multiple\_conditions      *Environmental conditions during several dynamic experiments*

---

### Description

This dataset is paired with [multiple\\_counts](#) to illustrate the global fitting of `fit_growth()`.

### Usage

```
multiple_conditions
```

### Format

A nested list with two elements, each one corresponding to one experiment. Each element is a data.frame with three columns:

- time: elapsed time
- temperature: observed temperature
- pH: observed pH

---

multiple\_counts          *Population growth observed in several dynamic experiments*

---

### Description

This dataset is paired with [multiple\\_conditions](#) to illustrate the global fitting of `fit_growth()`.

### Usage

```
multiple_counts
```

### Format

A nested list with two elements, each one corresponding to one experiment. Each element is a data.frame with two columns:

- time: elapsed time
- logN: log10 of the microbial concentration

---

multiple\_experiments *A set of growth experiments under dynamic conditions*

---

### Description

An example dataset illustrating the requirements of `fit_multiple_growth()` and `fit_multiple_growth_MCMC()`.

### Usage

```
multiple_experiments
```

### Format

A nested list with two elements. Each element corresponds to one experiment and is described by a list with two data frames:

**data** a tibble describing the microbial counts. It has 2 columns: time (elapsed time) and logN (logarithm of the microbial count).

**conditions** a tibble describing the environmental conditions. It has 3 columns: time (elapsed time), temperature (storage temperature) and pH (pH of the media).

---

predictMCMC *Generic for calculating predictions with uncertainty from fits*

---

### Description

Generic for calculating predictions with uncertainty from fits

### Usage

```
predictMCMC(  
  model,  
  times,  
  env_conditions,  
  niter,  
  newpars = NULL,  
  formula = . ~ time  
)
```

**Arguments**

model	Fit object
times	see specific methods for each class
env_conditions	see specific methods for each class
niter	see specific methods for each class
newpars	see specific methods for each class
formula	A formula stating the column named defining the elapsed time in env_conditions. By default, . ~ time.

---

predict\_dynamic\_growth

*Growth under dynamic conditions*

---

**Description****[Superseded]**

The function `predict_dynamic_growth()` has been superseded by the top-level function `predict_growth()`, which provides a unified approach for growth modelling.

Regardless on that, it can still predict population growth under dynamic conditions based on the Baranyi model (Baranyi and Roberts, 1994) and secondary models based on the gamma concept (Zwietering et al. 1992).

Model predictions are done by linear interpolation of the environmental conditions defined in env\_conditions.

**Usage**

```
predict_dynamic_growth(
  times,
  env_conditions,
  primary_pars,
  secondary_models,
  ...,
  check = TRUE,
  logbase_logN = 10,
  logbase_mu = logbase_logN,
  formula = . ~ time
)
```

**Arguments**

times	Numeric vector of storage times to make the predictions
env_conditions	Tibble (or data.frame) describing the variation of the environmental conditions during storage. It must have with the elapsed time (named time by default; can be changed with the "formula" argument), and as many additional columns as environmental factors.

primary_pars	A named list defining the parameters of the primary model and the initial values of the model variables. That is, with names mu_opt, Nmax, N0, Q0.
secondary_models	A nested list describing the secondary models.
...	Additional arguments for <code>ode()</code> .
check	Whether to check the validity of the models. TRUE by default.
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. log10). See vignette about units for details.
logbase_mu	Base of the logarithm the growth rate is referred to. By default, the same as logbase_logN. See vignette about units for details.
formula	An object of class "formula" describing the x variable. <code>. ~ time</code> as a default.

### Value

An instance of `DynamicGrowth()`.

### Examples

```
## Definition of the environmental conditions

library(tibble)

my_conditions <- tibble(time = c(0, 5, 40),
  temperature = c(20, 30, 35),
  pH = c(7, 6.5, 5)
)

## Definition of the model parameters

my_primary <- list(mu_opt = 2,
  Nmax = 1e8, N0 = 1e0,
  Q0 = 1e-3)

sec_temperature <- list(model = "Zwietering",
  xmin = 25, xopt = 35, n = 1)

sec_pH = list(model = "CPM",
  xmin = 5.5, xopt = 6.5,
  xmax = 7.5, n = 2)

my_secondary <- list(
  temperature = sec_temperature,
  pH = sec_pH
)

my_times <- seq(0, 50, length = 1000)

## Do the simulation
```

```

dynamic_prediction <- predict_dynamic_growth(my_times,
  my_conditions, my_primary,
  my_secondary)

## Plot the results

plot(dynamic_prediction)

## We can plot some environmental factor with add_factor

plot(dynamic_prediction, add_factor = "temperature", ylims= c(0, 8),
  label_y1 = "Microbial count (log CFU/ml)",
  label_y2 = "Storage temperature (C)")

```

---

predict\_growth

*Prediction of microbial growth*

---

## Description

### [Stable]

This function provides a top-level interface for predicting population growth. Predictions can be made either under constant or dynamic environmental conditions. See below for details on the calculations.

## Usage

```

predict_growth(
  times,
  primary_model,
  environment = "constant",
  secondary_models = NULL,
  env_conditions = NULL,
  ...,
  check = TRUE,
  logbase_mu = logbase_logN,
  logbase_logN = 10,
  formula = . ~ time
)

```

## Arguments

times	numeric vector of time points for making the predictions
primary_model	named list defining the values of the parameters of the primary growth model
environment	type of environment. Either "constant" (default) or "dynamic" (see below for details on the calculations for each condition)

secondary_models	a nested list describing the secondary models. See below for details
env_conditions	Tibble describing the variation of the environmental conditions for dynamic experiments. It must have with the elapsed time (named <code>time</code> by default; can be changed with the "formula" argument), and as many additional columns as environmental factors. Ignored for "constant" environments.
...	Additional arguments for <code>ode()</code> .
check	Whether to check the validity of the models. TRUE by default.
logbase_mu	Base of the logarithm the growth rate is referred to. By default, the same as <code>logbase_logN</code> . See vignette about units for details.
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. <code>log10</code> ). See vignette about units for details.
formula	An object of class "formula" describing the x variable for predictions under dynamic conditions. <code>. ~ time</code> as a default.

### Details

To ease data input, the functions can convert between parameters defined in different scales. Namely, for predictions in constant environments (`environment="constant"`):

- "logN0" can be defined as "N0". The function automatically calculates the log-transformation.
- "logNmax" can be defined as "Nmax". The function automatically calculates the log-transformation.
- "mu" can be defined as "mu\_opt". The function assumes the prediction is under optimal growth conditions.
- "lambda" can be defined by "Q0". The duration of the lag phase is calculated using `Q0_to_lambda()`.

And, for predictions in dynamic environments (`environment="dynamic"`):

- "N0" can be defined as "N0". The function automatically calculates the antilog-transformation.
- "Nmax" can be defined as "logNmax". The function automatically calculates the antilog-transformation.
- "mu" can be defined as "mu\_opt". The function assumes mu was calculated under optimal growth conditions.
- "Q0" can be defined by the value of "lambda" under dynamic conditions. Then, the value of Q0 is calculated using `lambda_to_Q0()`.

### Value

An instance of [GrowthPrediction](#).

### Predictions in constant environments

Predictions under constant environments are calculated using only primary models. Consequently, the arguments "secondary\_models" and "env\_conditions" are ignored. If these were passed, the function would return a warning. In this case, predictions are calculated using the algebraic form of the primary model (see vignette for details).

The growth model is defined through the "primary\_model" argument using a named list. One of the list elements must be named "model" and must take one of the valid keys returned by `primary_model_data()`. The remaining entries of the list define the values of the parameters of the selected model. A list of valid keys can be retrieved using `primary_model_data()` (see example below). Note that the functions can do some operations to facilitate the compatibility between constant and dynamic environments (see Details).

### Predictions in dynamic environments

Predictions under dynamic environments are calculated by solving numerically the differential equation of the Baranyi growth model. The effect of changes in the environmental conditions in the growth rate are calculated according to the gamma approach. Therefore, one must define both primary and secondary models.

The dynamic environmental conditions are defined using a tibble (or data.frame) through the "env\_conditions" argument. It must include one column named "time" stating the elapsed time and as many additional columns as environmental conditions included in the prediction. For values of time not included in the tibble, the values of the environmental conditions are calculated by linear interpolation.

Primary models are defined as a named list through the "primary\_model" argument. It must include the following elements:

- N0: initial population size
- Nmax: maximum population size in the stationary growth phase
- mu\_opt: growth rate under optimal growth conditions
- Q0: value defining the duration of the lag phase Additional details on these parameters can be found in the package vignettes.

Secondary models are defined as a nested list through the "secondary\_models" argument. The list must have one entry per environmental condition, whose name must match those used in the "env\_conditions" argument. Each of these entries must be a named list defining the secondary model for each environmental condition. The model equation is defined in an entry named "model" (valid keys can be retrieved from `secondary_model_data()`). Then, additional entries defined the values of each model parameters (valid keys can be retrieved from `secondary_model_data()`)

For additional details on how to define the secondary models, please see the package vignettes (and examples below).

### Examples

```
## Example 1 - Growth under constant conditions -----
## Valid model keys can be retrieved calling primary_model_data()

primary_model_data()

my_model <- "modGompertz" # we will use the modified-Gompertz

## The keys of the model parameters can also be obtained from primary_model_data()

primary_model_data(my_model)$pars
```



```
## We define the primary model as a list
my_model <- list(model = "modGompertz", logN0 = 0, C = 6, mu = .2, lambda = 20)

## We can now make the predictions
my_time <- seq(0, 100, length = 1000) # Vector of time points for the calculations
my_prediction <- predict_growth(my_time, my_model, environment = "constant")

## The instance of IsothermalGrowth includes several S3 methods

print(my_prediction)
plot(my_prediction)
coef(my_prediction)

## Example 2 - Growth under dynamic conditions -----

## We will consider the effect of two factors: temperature and pH

my_conditions <- data.frame(time = c(0, 5, 40),
                           temperature = c(20, 30, 35),
                           pH = c(7, 6.5, 5)
                           )

## The primary model is defined as a named list
my_primary <- list(mu = 2, Nmax = 1e7, N0 = 1, Q0 = 1e-3)

## The secondary model is defined independently for each factor

sec_temperature <- list(model = "Zwietering",
                       xmin = 25, xopt = 35, n = 1)

sec_pH = list(model = "CPM",
             xmin = 5.5, xopt = 6.5,
             xmax = 7.5, n = 2)

## Then, they are assigned to each factor using a named list

my_secondary <- list(
  temperature = sec_temperature,
  pH = sec_pH
)

## We can call the function now

my_times <- seq(0, 50, length = 1000) # Where the output is calculated

dynamic_prediction <- predict_growth(environment = "dynamic",
                                     my_times, my_primary, my_secondary,
                                     my_conditions)
```

```

)

## The instance of DynamicGrowth includes several useful S3 methods

print(dynamic_prediction)
plot(dynamic_prediction)
plot(dynamic_prediction, add_factor = "pH")
coef(dynamic_prediction)

## The time_to_size function can predict the time to reach a population size

time_to_size(my_prediction, 3)

```

---

predict\_growth\_uncertainty

*Isothermal growth with parameter uncertainty*

---

## Description

### [Stable]

Simulation of microbial growth considering uncertainty in the model parameters. Calculations are based on Monte Carlo simulations, considering the parameters follow a multivariate normal distribution.

## Usage

```

predict_growth_uncertainty(
  model_name,
  times,
  n_sims,
  pars,
  corr_matrix = diag(nrow(pars)),
  check = TRUE
)

```

## Arguments

model_name	Character describing the primary growth model.
times	Numeric vector of storage times for the simulations.
n_sims	Number of simulations.
pars	A tibble describing the parameter uncertainty (see details).
corr_matrix	Correlation matrix of the model parameters. Defined in the same order as in pars. An identity matrix by default (uncorrelated parameters).
check	Whether to do some tests. FALSE by default.

## Details

The distributions of the model parameters are defined in the `pars` argument using a tibble with 4 columns:

- `par`: identifier of the model parameter (according to `primary_model_data()`),
- `mean`: mean value of the model parameter.,
- `sd`: standard deviation of the model parameter.,
- `scale`: scale at which the model parameter is defined. Valid values are 'original' (no transformation), 'sqrt' square root or 'log' log-scale. The parameter sample is generated considering the parameter follows a marginal normal distribution at this scale, and is later converted to the original scale for calculations.

## Value

An instance of `GrowthUncertainty()`.

## Examples

```
## Definition of the simulation settings

my_model <- "Baranyi"
my_times <- seq(0, 30, length = 100)
n_sims <- 3000

library(tibble)

pars <- tribble(
  ~par, ~mean, ~sd, ~scale,
  "logN0", 0, .2, "original",
  "mu", 2, .3, "sqrt",
  "lambda", 4, .4, "sqrt",
  "logNmax", 6, .5, "original"
)

## Calling the function

stoc_growth <- predict_growth_uncertainty(my_model, my_times, n_sims, pars)

## We can plot the results

plot(stoc_growth)

## Adding parameter correlation

my_cor <- matrix(c(1, 0, 0, 0,
  0, 1, 0.7, 0,
  0, 0.7, 1, 0,
  0, 0, 0, 1),
  nrow = 4)
```

```
stoc_growth2 <- predict_growth_uncertainty(my_model, my_times, n_sims, pars, my_cor)
plot(stoc_growth2)

## The time_to_size function can calculate the median growth curve to reach a size
time_to_size(stoc_growth, 4)

## Or the distribution of times
dist <- time_to_size(stoc_growth, 4, type = "distribution")
plot(dist)
```

---

`predict_isothermal_growth`  
*Isothermal microbial growth*

---

## Description

### [Superseded]

The function `predict_isothermal_growth()` has been superseded by the top-level function `predict_growth()`, which provides a unified approach for growth modelling.

Regardless of that, it can still be used to predict population growth under static environmental conditions (i.e. using primary models).

## Usage

```
predict_isothermal_growth(  
  model_name,  
  times,  
  model_pars,  
  check = TRUE,  
  logbase_mu = 10,  
  logbase_logN = 10  
)
```

## Arguments

<code>model_name</code>	Character defining the growth model.
<code>times</code>	Numeric vector of storage times for the predictions.
<code>model_pars</code>	Named vector or list defining the values of the model parameters.
<code>check</code>	Whether to do basic checks (TRUE by default).

logbase_mu	Base of the logarithm the growth rate is referred to. By default, the same as logbase_logN. See vignette about units for details.
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. log10). See vignette about units for details.

### Value

An instance of [IsothermalGrowth\(\)](#).

### Examples

```
## Define the simulations parameters

my_model <- "modGompertz"
my_pars <- list(logN0 = 2, C = 6, mu = .2, lambda = 25)
my_time <- seq(0, 100, length = 1000)

## Do the simulation

static_prediction <- predict_isothermal_growth(my_model, my_time, my_pars)

## Plot the results

plot(static_prediction)
```

---

predict\_MCMC\_growth     *Stochastic growth of MCMC fit*

---

### Description

#### [Superseded]

The function [predict\\_MCMC\\_growth\(\)](#) has been superseded by [predictMCMC\(\)](#) S3 methods of the relevant classes.

Nonetheless, it can still make a prediction of microbial growth including parameter uncertainty based on a growth model fitted using [fit\\_MCMC\\_growth\(\)](#) or [fit\\_multiple\\_growth\\_MCMC\(\)](#). This function predicts growth curves for niter samples (with replacement) of the samples of the MCMC algorithm. Then, credible intervals are calculated based on the quantiles of the model predictions at each time point.

### Usage

```
predict_MCMC_growth(
  MCMCfit,
  times,
  env_conditions,
  niter,
```

```

  newpars = NULL,
  formula = . ~ time
)

```

### Arguments

MCMCfit	An instance of FitDynamicGrowthMCMC or FitMultipleGrowthMCMC.
times	Numeric vector of storage times for the predictions.
env_conditions	Tibble with the (dynamic) environmental conditions during the experiment. It must have one column named 'time' with the storage time and as many columns as required with the environmental conditions.
niter	Number of iterations.
newpars	A named list defining new values for the some model parameters. The name must be the identifier of a model already included in the model. These parameters do not include variation, so defining a new value for a fitted parameters "fixes" it. NULL by default (no new parameters).
formula	A formula stating the column named defining the elapsed time in env_conditions. By default, . ~ time.

### Value

An instance of `MCMCgrowth()`.

### Examples

```

## We need a FitDynamicGrowthMCMC object

data("example_dynamic_growth")
data("example_env_conditions")

sec_model_names <- c(temperature = "CPM", aw= "CPM")

known_pars <- list(Nmax = 1e4, # Primary model
  N0 = 1e0, Q0 = 1e-3, # Initial values of the primary model
  mu_opt = 4, # mu_opt of the gamma model
  temperature_n = 1, # Secondary model for temperature
  aw_xmax = 1, aw_xmin = .9, aw_n = 1 # Secondary model for water activity
)

my_start <- list(temperature_xmin = 25, temperature_xopt = 35,
  temperature_xmax = 40,
  aw_xopt = .95)

set.seed(12124) # Setting seed for repeatability

my_MCMC_fit <- fit_MCMC_growth(example_dynamic_growth, example_env_conditions,
  my_start, known_pars, sec_model_names, niter = 3000)

## Define the conditions for the simulation

```

```
my_times <- seq(0, 15, length = 50)
niter <- 2000

newpars <- list(N0 = 1e-1, # A parameter that was fixed
               temperature_xmax = 120 # A parameter that was fitted
               )

## Make the simulations

my_MCMC_prediction <- predict_MCMC_growth(my_MCMC_fit,
    my_times,
    example_env_conditions, # It could be different from the one used for fitting
    niter,
    newpars)

## We can plot the prediction interval

plot(my_MCMC_prediction)

## We can also get the quantiles at each time point

print(my_MCMC_prediction$quantiles)
```

---

predict\_stochastic\_growth

*Deprecated isothermal growth with parameter uncertainty*

---

## Description

### **[Deprecated]**

[predict\\_stochastic\\_growth\(\)](#) was renamed [predict\\_growth\\_uncertainty\(\)](#) because the original function name may be misleading, as this is not a stochastic differential equation

## Usage

```
predict_stochastic_growth(
  model_name,
  times,
  n_sims,
  pars,
  corr_matrix = diag(nrow(pars)),
  check = TRUE
)
```

**Arguments**

model_name	Character describing the primary growth model.
times	Numeric vector of storage times for the simulations.
n_sims	Number of simulations.
pars	A tibble describing the parameter uncertainty (see details).
corr_matrix	Correlation matrix of the model parameters. Defined in the same order as in pars. An identity matrix by default (uncorrelated parameters).
check	Whether to do some tests. FALSE by default.

---

primary_model_data	<i>Metainformation of primary growth models</i>
--------------------	---

---

**Description****[Stable]**

Provides different types of meta-data about the primary growth models included in biogrowth. This information is the basis of the automatic checks, and can also help in the definition of models for [predict\\_growth\(\)](#) and [fit\\_growth\(\)](#).

**Usage**

```
primary_model_data(model_name = NULL)
```

**Arguments**

model_name	The name of the model or NULL (default).
------------	--

**Value**

If model\_name is NULL, returns a character string with the available models. If is a valid identifier, it returns a list with metainformation about the model. If model\_name name is not a valid identifier, raises an error.



---

Q0_to_lambda	<i>Lag phase duration from Q0</i>
--------------	-----------------------------------

---

**Description****[Stable]**

Convenience function to calculate the lag phase duration (lambda) of the Baranyi model from the maximum specific growth rate and the initial value of the variable Q.

Note that this function uses the unit system of biogrowth (i.e. log10). Care must be taken when using parameters obtained from other sources.

**Usage**

```
Q0_to_lambda(q0, mu, logbase_mu = 10)
```

**Arguments**

q0	Initial value of the variable Q.
mu	Specific growth rate in the exponential phase.
logbase_mu	Base of the logarithm the growth rate is referred to. By default, 10 (i.e. log10). See vignette about units for details.

---

richards_model	<i>Richards growth model</i>
----------------	------------------------------

---

**Description**

Richards growth model

**Usage**

```
richards_model(times, logN0, mu, lambda, C, nu)
```

**Arguments**

times	Numeric vector of storage times
logN0	Initial log microbial count
mu	Maximum specific growth rate (in ln CFU/t)
lambda	Lag phase duration
C	Difference between logN0 and the maximum log-count.
nu	Parameter describing the transition between growth phases

---

SecondaryComparison    *SecondaryComparison class*

---

## Description

The SecondaryComparison class contains several functions for model comparison and model selection of growth models. It should not be instantiated directly. Instead, it should be constructed using `compare_secondary_fits()`.

It includes two type of tools for model selection and comparison: statistical indexes and visual analyses. Please check the sections below for details.

Note that all these tools use the names defined in `compare_secondary_fits()`, so we recommend passing a named list to that function.

## Usage

```
## S3 method for class 'SecondaryComparison'
coef(object, ...)
```

```
## S3 method for class 'SecondaryComparison'
summary(object, ...)
```

```
## S3 method for class 'SecondaryComparison'
print(x, ...)
```

```
## S3 method for class 'SecondaryComparison'
plot(x, y, ..., type = 1, add_trend = TRUE)
```

## Arguments

object	an instance of SecondaryComparison
...	ignored
x	an instance of SecondaryComparison
y	ignored
type	if type==1, the plot compares the model predictions. If type==2, the plot compares the parameter estimates.
add_trend	should a trend line of the residuals be added for type==3? TRUE by default

## Methods (by generic)

- `coef(SecondaryComparison)`: table of parameter estimates
- `summary(SecondaryComparison)`: summary table for the comparison
- `print(SecondaryComparison)`: print of the model comparison
- `plot(SecondaryComparison)`: illustrations comparing the fitted models

### Statistical indexes

SecondaryComparison implements two S3 methods to obtain numerical values to facilitate model comparison and selection.

- the `coef` method returns a tibble with the values of the parameter estimates and their corresponding standard errors for each model.
- the `summary` returns a tibble with the AIC, number of degrees of freedom, mean error and root mean squared error for each model.

### Visual analyses

The S3 plot method can generate three types of plots:

- when `type = 1`, the plot compares the observations against the model predictions for each model. The plot includes a linear model fitted to the residuals. In the case of a perfect fit, the line would have slope=1 and intercept=0 (shown as a black, dashed line).
- when `type = 2`, the plot compares the parameter estimates using error bars, where the limits of the error bars are the expected value +/- one standard error. In case one model does not have some model parameter (i.e. either because it is not defined or because it was fixed), the parameter is not included in the plot.

---

secondary\_model\_data *Metainformation of secondary growth models*

---

### Description

**[Stable]**

Provides different types of meta-data about the secondary growth models included in biogrowth. This information is the basis of the automatic checks, and can also help in the definition of models for `predict_growth()` and `fit_growth()`.

### Usage

```
secondary_model_data(model_name = NULL)
```

### Arguments

`model_name`      The name of the model or NULL (default).

### Value

If `model_name` is NULL, returns a character string with the available models. If is a valid identifier, it returns a list with metainformation about the model. If `model_name` name is not a valid identifier, raises an error.

---

show_guess_dynamic	<i>Plot of the initial guess for growth under dynamic environmental conditions</i>
--------------------	--

---

### Description

Compares the prediction corresponding to a guess of the parameters of the model against experimental data

### Usage

```
show_guess_dynamic(
  fit_data,
  model_keys,
  guess,
  env_conditions,
  logbase_mu = 10,
  formula = logN ~ time
)
```

### Arguments

fit_data	Tibble (or data.frame) of data for the fit. It must have two columns, one with the elapsed time (time by default) and another one with the decimal logarithm of the populatoin size (logN by default). Different column names can be defined using the formula argument.
model_keys	Named the equations of the secondary model as in <a href="#">fit_growth()</a>
guess	Named vector with the initial guess of the model parameters as in <a href="#">fit_growth()</a>
env_conditions	Tibble describing the variation of the environmental conditions for dynamic experiments. See <a href="#">fit_growth()</a> .
logbase_mu	Base of the logarithm the growth rate is referred to. By default, 10 (i.e. log10). See vignette about units for details.
formula	an object of class "formula" describing the x and y variables. logN ~ time as a default.

### Value

A [ggplot\(\)](#) comparing the model prediction against the data

---

show_guess_primary	<i>Plot of the initial guess for growth under constant environmental conditions</i>
--------------------	---

---

### Description

Compares the prediction corresponding to a guess of the parameters of the primary model against experimental data

### Usage

```
show_guess_primary(
  fit_data,
  model_name,
  guess,
  logbase_mu = 10,
  formula = logN ~ time
)
```

### Arguments

fit_data	Tibble (or data.frame) of data for the fit. It must have two columns, one with the elapsed time (time by default) and another one with the decimal logarithm of the populatoin size (logN by default). Different column names can be defined using the formula argument.
model_name	Character defining the primary growth model as per <a href="#">primary_model_data()</a>
guess	Named vector with the initial guess of the model parameters
logbase_mu	Base of the logarithm the growth rate is referred to. By default, 10 (i.e. log10). See vignette about units for details.
formula	an object of class "formula" describing the x and y variables. logN ~ time as a default.

### Value

A [ggplot\(\)](#) comparing the model prediction against the data

---

StochasticGrowth	<i>StochasticGrowth class</i>
------------------	-------------------------------

---

**Description****[Deprecated]**

The class `StochasticGrowth` has been deprecated by class `GrowthUncertainty`, which provides less misleading name.

Still, it is still returned if the deprecated `predict_stochastic_growth()` is called.

The `StochasticGrowth` class contains the results of a growth prediction under isothermal conditions considering parameter uncertainty. Its constructor is `predict_stochastic_growth()`.

It is a subclass of list with the items:

- `sample`: parameter sample used for the calculations.
- `simulations`: growth curves predicted for each parameter.
- `quantiles`: limits of the credible intervals (5%, 10%, 50%, 90%, 95%) for each time point.
- `model`: Model used for the calculations.
- `mus`: Mean parameter values used for the simulations.
- `sigma`: Variance-covariance matrix used for the simulations.

**Usage**

```
## S3 method for class 'StochasticGrowth'
print(x, ...)
```

```
## S3 method for class 'StochasticGrowth'
plot(
  x,
  y = NULL,
  ...,
  line_col = "black",
  line_size = 0.5,
  line_type = "solid",
  ribbon80_fill = "grey",
  ribbon90_fill = "grey",
  alpha80 = 0.5,
  alpha90 = 0.4
)
```

**Arguments**

<code>x</code>	The object of class <code>StochasticGrowth</code> to plot.
<code>...</code>	ignored.
<code>y</code>	ignored
<code>line_col</code>	Aesthetic parameter to change the colour of the line geom in the plot, see: <a href="#">geom_line()</a>
<code>line_size</code>	Aesthetic parameter to change the thickness of the line geom in the plot, see: <a href="#">geom_line()</a>

<code>line_type</code>	Aesthetic parameter to change the type of the line geom in the plot, takes numbers (1-6) or strings ("solid") see: <a href="#">geom_line()</a>
<code>ribbon80_fill</code>	fill colour for the space between the 10th and 90th quantile, see: <a href="#">geom_ribbon()</a>
<code>ribbon90_fill</code>	fill colour for the space between the 5th and 95th quantile, see: <a href="#">geom_ribbon()</a>
<code>alpha80</code>	transparency of the ribbon aesthetic for the space between the 10th and 90th quantile. Takes a value between 0 (fully transparent) and 1 (fully opaque)
<code>alpha90</code>	transparency of the ribbon aesthetic for the space between the 5th and 95th quantile. Takes a value between 0 (fully transparent) and 1 (fully opaque).

## Details

FitIsoGrowth class

## Methods (by generic)

- `print(StochasticGrowth)`: print of the model
- `plot(StochasticGrowth)`: Growth prediction (prediction band) considering parameter uncertainty.

---

TimeDistribution      *TimeDistribution class*

---

## Description

The TimeDistribution class contains an estimate of the probability distribution of the time to reach a given microbial count. Its constructor is [distribution\\_to\\_logcount\(\)](#).

It is a subclass of list with the items:

- `distribution` Sample of the distribution of times to reach `log_count`.
- `summary` Summary statistics of distribution (mean, sd, median, q10 and q90).

## Usage

```
## S3 method for class 'TimeDistribution'
print(x, ...)

## S3 method for class 'TimeDistribution'
summary(object, ...)

## S3 method for class 'TimeDistribution'
plot(x, y = NULL, ..., bin_width = NULL)
```

**Arguments**

x	The object of class TimeDistribution to plot.
...	ignored.
object	An instance of TimeDistribution.
y	ignored.
bin_width	A number that specifies the width of a bin in the histogram, see: <a href="#">geom_histogram()</a> . NULL by default.

**Methods (by generic)**

- `print(TimeDistribution)`: print of the model
- `summary(TimeDistribution)`: summary of the model
- `plot(TimeDistribution)`: plot of the distribution of the time to reach a microbial count.

---

time_to_logcount	<i>Time to reach a given microbial count</i>
------------------	--

---

**Description****[Superseded]**

The function `time_to_logcount()` has been superseded by function `time_to_size()`, which provides a more general interface.

But it still returns the storage time required for the microbial count to reach `log_count` according to the predictions of model. Calculations are done using linear interpolation of the model predictions.

**Usage**

```
time_to_logcount(model, log_count)
```

**Arguments**

model	An instance of IsothermalGrowth or DynamicGrowth.
log_count	The target log microbial count.

**Value**

The predicted time to reach `log_count`.



**Examples**

```
## First of all, we will get an IsothermalGrowth object

my_model <- "modGompertz"
my_pars <- list(logN0 = 2, C = 6, mu = .2, lambda = 25)
my_time <- seq(0, 100, length = 1000)

static_prediction <- predict_isothermal_growth(my_model, my_time, my_pars)
plot(static_prediction)

## And now we calculate the time to reach a microbial count

time_to_logcount(static_prediction, 2.5)

## If log_count is outside the range of the predicted values, NA is returned

time_to_logcount(static_prediction, 20)
```

---

time\_to\_size

*Time for the population to reach a given size*


---

**Description****[Experimental]**

Calculates the elapsed time required for the population to reach a given size (in log scale)

**Usage**

```
time_to_size(model, size, type = "discrete", logbase_logN = NULL)
```

**Arguments**

model	An instance of <a href="#">GrowthPrediction</a> , <a href="#">GrowthFit</a> , <a href="#">GlobalGrowthFit</a> , <a href="#">GrowthUncertainty</a> or <a href="#">MCMCgrowth</a> .
size	Target population size (in log scale)
type	Type of calculation, either "discrete" (default) or "distribution"
logbase_logN	Base of the logarithm for the population size. By default, 10 (i.e. log10). See vignette about units for details.

**Details**

The calculation method differs depending on the value of type. If type="discrete" (default), the function calculates by linear interpolation a discrete time to reach the target population size. If type="distribution", this calculation is repeated several times, generating a distribution of the time. Note that this is only possible for instances of [GrowthUncertainty](#) or [MCMCgrowth](#).

**Value**

If type="discrete", a number. If type="distribution", an instance of [TimeDistribution](#).

**Examples**

```
## Example 1 - Growth predictions -----
## The model is defined as usual with predict_growth
my_model <- list(model = "modGompertz", logN0 = 0, C = 6, mu = .2, lambda = 20)
my_time <- seq(0, 100, length = 1000) # Vector of time points for the calculations
my_prediction <- predict_growth(my_time, my_model, environment = "constant")
plot(my_prediction)

## We just have to pass the model and the size (in log10)
time_to_size(my_prediction, 3)

## If the size is not reached, it returns NA
time_to_size(my_prediction, 8)

## By default, it considers the population size is defined in the same log-base
## as the prediction. But that can be changed using logbase_logN
time_to_size(my_prediction, 3)
time_to_size(my_prediction, 3, logbase_logN = 10)
time_to_size(my_prediction, log(100), logbase_logN = exp(1))

## Example 2 - Model fit -----
my_data <- data.frame(time = c(0, 25, 50, 75, 100),
                     logN = c(2, 2.5, 7, 8, 8))

models <- list(primary = "Baranyi")

known <- c(mu = .2)

start <- c(logNmax = 8, lambda = 25, logN0 = 2)

primary_fit <- fit_growth(my_data, models, start, known,
                        environment = "constant",
                        )

plot(primary_fit)

time_to_size(primary_fit, 4)
```

```

## Example 3 - Global fitting -----
## We need a model first

data("multiple_counts")
data("multiple_conditions")

sec_models <- list(temperature = "CPM", pH = "CPM")

known_pars <- list(Nmax = 1e8, N0 = 1e0, Q0 = 1e-3,
                  temperature_n = 2, temperature_xmin = 20,
                  temperature_xmax = 35,
                  temperature_xopt = 30,
                  pH_n = 2, pH_xmin = 5.5, pH_xmax = 7.5, pH_xopt = 6.5)

my_start <- list(mu_opt = .8)

global_fit <- fit_growth(multiple_counts,
                        sec_models,
                        my_start,
                        known_pars,
                        environment = "dynamic",
                        algorithm = "regression",
                        approach = "global",
                        env_conditions = multiple_conditions
                        )

plot(global_fit)

## The function calculates the time for each experiment

time_to_size(global_fit, 3)

## It returns NA for the particular experiment if the size is not reached

time_to_size(global_fit, 4.5)

```

---

trilinear\_model

*Trilinear growth model*


---

### Description

Trilinear growth model defined by Buchanan et al. (1997).

### Usage

```
trilinear_model(times, logN0, mu, lambda, logNmax)
```

**Arguments**

times	Numeric vector of storage times
logN0	Initial log microbial count
mu	Maximum specific growth rate (in ln CFU/t)
lambda	Lag phase duration
logNmax	Maximum log microbial count

**Value**

Numeric vector with the predicted microbial count.

---

zwietering_gamma	<i>Zwietering gamma model</i>
------------------	-------------------------------

---

**Description**

Gamma model as defined by Zwietering et al. (1992). To avoid unreasonable predictions, it has been modified setting gamma=0 for values of x outside (xmin, xopt)

**Usage**

```
zwietering_gamma(x, xmin, xopt, n)
```

**Arguments**

x	Value of the environmental factor.
xmin	Minimum value of the environmental factor for growth.
xopt	Maximum value for growth
n	Exponent of the secondary model

**Value**

The corresponding gamma factor.

# Index

## \* datasets

- arabian\_tractors, 4
- conditions\_pH\_temperature, 15
- example\_cardinal, 19
- example\_dynamic\_growth, 19
- example\_env\_conditions, 20
- growth\_pH\_temperature, 74
- growth\_salmonella, 75
- multiple\_conditions, 90
- multiple\_counts, 90
- multiple\_experiments, 91

AIC.FitDynamicGrowth  
(FitDynamicGrowth), 21

AIC.FitDynamicGrowthMCMC  
(FitDynamicGrowthMCMC), 24

AIC.FitIsoGrowth (FitIsoGrowth), 27

AIC.FitMultipleDynamicGrowth  
(FitMultipleDynamicGrowth), 29

AIC.FitMultipleGrowthMCMC  
(FitMultipleGrowthMCMC), 32

AIC.FitSecondaryGrowth  
(FitSecondaryGrowth), 36

AIC.GlobalGrowthFit (GlobalGrowthFit),  
63

AIC.GrowthFit (GrowthFit), 68

approx\_env, 4

arabian\_tractors, 4

calculate\_gammas, 5

calculate\_gammas\_secondary, 5

check\_growth\_guess, 6

check\_primary\_pars, 8

check\_secondary\_pars, 8

check\_stochastic\_pars, 9

coef.DynamicGrowth (DynamicGrowth), 17

coef.FitDynamicGrowth  
(FitDynamicGrowth), 21

coef.FitDynamicGrowthMCMC  
(FitDynamicGrowthMCMC), 24

coef.FitIsoGrowth (FitIsoGrowth), 27

coef.FitMultipleDynamicGrowth  
(FitMultipleDynamicGrowth), 29

coef.FitMultipleGrowthMCMC  
(FitMultipleGrowthMCMC), 32

coef.FitSecondaryGrowth  
(FitSecondaryGrowth), 36

coef.GlobalGrowthComparison  
(GlobalGrowthComparison), 61

coef.GlobalGrowthFit (GlobalGrowthFit),  
63

coef.GrowthComparison  
(GrowthComparison), 66

coef.GrowthFit (GrowthFit), 68

coef.GrowthPrediction  
(GrowthPrediction), 71

coef.IsothermalGrowth  
(IsothermalGrowth), 82

coef.SecondaryComparison  
(SecondaryComparison), 106

compare\_growth\_fits, 9

compare\_growth\_fits(), 61, 66

compare\_secondary\_fits, 13

compare\_secondary\_fits(), 106

conditions\_pH\_temperature, 15

CPM\_model, 15

dBaranyi, 16

deviance.FitDynamicGrowth  
(FitDynamicGrowth), 21

deviance.FitDynamicGrowthMCMC  
(FitDynamicGrowthMCMC), 24

deviance.FitIsoGrowth (FitIsoGrowth), 27

deviance.FitMultipleDynamicGrowth  
(FitMultipleDynamicGrowth), 29

deviance.FitMultipleGrowthMCMC  
(FitMultipleGrowthMCMC), 32

deviance.FitSecondaryGrowth  
(FitSecondaryGrowth), 36

- deviance.GlobalGrowthFit  
(GlobalGrowthFit), 63
- deviance.GrowthFit (GrowthFit), 68
- distribution\_to\_logcount, 16
- distribution\_to\_logcount(), 16, 111
- DynamicGrowth, 17, 17, 19
- DynamicGrowth(), 93
  
- example\_cardinal, 19
- example\_dynamic\_growth, 19
- example\_env\_conditions, 20
- extract\_primary\_pars, 20
- extract\_secondary\_pars, 21
  
- fit\_dynamic\_growth, 38
- fit\_dynamic\_growth(), 19–21, 38
- fit\_growth, 40
- fit\_growth(), 6, 9, 10, 38, 47, 49, 51, 53, 63, 68, 86, 90, 104, 107, 108
- fit\_isothermal\_growth, 47
- fit\_isothermal\_growth(), 27, 47, 75
- fit\_MCMC\_growth, 49
- fit\_MCMC\_growth(), 24, 49, 101
- fit\_multiple\_growth, 51
- fit\_multiple\_growth(), 30, 32, 51, 91
- fit\_multiple\_growth\_MCMC, 53
- fit\_multiple\_growth\_MCMC(), 32, 53, 91, 101
- fit\_secondary\_growth, 55
- fit\_secondary\_growth(), 13, 14, 19, 36, 37, 60, 87
- FitDynamicGrowth, 21, 21
- FitDynamicGrowth(), 39
- FitDynamicGrowthMCMC, 24, 24, 26
- FitDynamicGrowthMCMC(), 50
- FitIsoGrowth, 27, 27
- FitIsoGrowth(), 48
- FitMultipleDynamicGrowth, 29, 30
- FitMultipleDynamicGrowth(), 52
- FitMultipleGrowthMCMC, 32, 32, 35
- FitMultipleGrowthMCMC(), 54
- FitSecondaryGrowth, 36
- FitSecondaryGrowth(), 56
- fitted.FitDynamicGrowth  
(FitDynamicGrowth), 21
- fitted.FitDynamicGrowthMCMC  
(FitDynamicGrowthMCMC), 24
- fitted.FitIsoGrowth (FitIsoGrowth), 27
- fitted.FitMultipleDynamicGrowth  
(FitMultipleDynamicGrowth), 29
- fitted.FitMultipleGrowthMCMC  
(FitMultipleGrowthMCMC), 32
- fitted.FitSecondaryGrowth  
(FitSecondaryGrowth), 36
- fitted.GlobalGrowthFit  
(GlobalGrowthFit), 63
- fitted.GrowthFit (GrowthFit), 68
- full\_Ratkowski, 57
  
- geom\_histogram(), 112
- geom\_line(), 18, 23, 26, 29, 31, 34, 65, 70, 72–74, 83, 110, 111
- geom\_point(), 23, 26, 29, 70
- geom\_ribbon(), 74, 111
- get\_all\_predictions, 57
- get\_dyna\_residuals, 58
- get\_iso\_residuals, 59
- get\_multi\_dyna\_residuals, 59
- get\_secondary\_residuals, 60
- ggplot(), 7, 108, 109
- GlobalGrowthComparison, 9, 61
- GlobalGrowthFit, 30, 32, 41, 63, 65, 79, 113
- gompertz (iso\_repGompertz), 84
- growth\_pH\_temperature, 74
- growth\_salmonella, 75
- GrowthComparison, 9, 61, 66, 67
- GrowthFit, 21, 24, 27, 41, 68, 70, 79, 113
- GrowthPrediction, 17, 63, 68, 71, 72, 80, 82, 95, 113
- GrowthUncertainty, 73, 80, 110, 113
- GrowthUncertainty(), 99
  
- is.DynamicGrowth, 75
- is.FitDynamicGrowth, 76
- is.FitDynamicGrowthMCMC, 76
- is.FitIsoGrowth, 77
- is.FitMultipleDynamicGrowth, 77
- is.FitMultipleDynamicGrowthMCMC, 78
- is.FitSecondaryGrowth, 78
- is.GlobalGrowthFit, 79
- is.GrowthFit, 79
- is.GrowthPrediction, 80
- is.GrowthUncertainty, 80
- is.IsothermalGrowth, 81
- is.MCMCgrowth, 81
- is.StochasticGrowth, 82
- iso\_Baranyi, 83

- iso\_repGompertz, 84
- IsothermalGrowth, 82, 82, 83
- IsothermalGrowth(), 101
- lambda\_to\_Q0, 85
- lambda\_to\_Q0(), 95
- logistic\_model, 85
- logLik.FitDynamicGrowth (FitDynamicGrowth), 21
- logLik.FitDynamicGrowthMCMC (FitDynamicGrowthMCMC), 24
- logLik.FitIsoGrowth (FitIsoGrowth), 27
- logLik.FitMultipleDynamicGrowth (FitMultipleDynamicGrowth), 29
- logLik.FitMultipleGrowthMCMC (FitMultipleGrowthMCMC), 32
- logLik.FitSecondaryGrowth (FitSecondaryGrowth), 36
- logLik.GlobalGrowthFit (GlobalGrowthFit), 63
- logLik.GrowthFit (GrowthFit), 68
- make\_guess\_factor, 86
- make\_guess\_primary, 86
- make\_guess\_secondary, 87
- MCMCgrowth, 65, 70, 88, 113
- MCMCgrowth(), 26, 35, 102
- modCost(), 58
- modFit(), 27, 36, 41, 42, 48, 52, 56, 58, 59
- modGompertz (iso\_repGompertz), 84
- modMCMC, 54
- modMCMC(), 42
- multiple\_conditions, 90, 90
- multiple\_counts, 90, 90
- multiple\_experiments, 91
- ode(), 16, 93, 95
- plot.DynamicGrowth (DynamicGrowth), 17
- plot.FitDynamicGrowth (FitDynamicGrowth), 21
- plot.FitDynamicGrowthMCMC (FitDynamicGrowthMCMC), 24
- plot.FitIsoGrowth (FitIsoGrowth), 27
- plot.FitMultipleDynamicGrowth (FitMultipleDynamicGrowth), 29
- plot.FitMultipleGrowthMCMC (FitMultipleGrowthMCMC), 32
- plot.FitSecondaryGrowth (FitSecondaryGrowth), 36
- plot.GlobalGrowthComparison (GlobalGrowthComparison), 61
- plot.GlobalGrowthFit (GlobalGrowthFit), 63
- plot.GrowthComparison (GrowthComparison), 66
- plot.GrowthFit (GrowthFit), 68
- plot.GrowthPrediction (GrowthPrediction), 71
- plot.GrowthUncertainty (GrowthUncertainty), 73
- plot.IsothermalGrowth (IsothermalGrowth), 82
- plot.MCMCgrowth (MCMCgrowth), 88
- plot.SecondaryComparison (SecondaryComparison), 106
- plot.StochasticGrowth (StochasticGrowth), 109
- plot.TimeDistribution (TimeDistribution), 111
- predict.FitDynamicGrowth (FitDynamicGrowth), 21
- predict.FitDynamicGrowthMCMC (FitDynamicGrowthMCMC), 24
- predict.FitIsoGrowth (FitIsoGrowth), 27
- predict.FitMultipleDynamicGrowth (FitMultipleDynamicGrowth), 29
- predict.FitMultipleGrowthMCMC (FitMultipleGrowthMCMC), 32
- predict.FitSecondaryGrowth (FitSecondaryGrowth), 36
- predict.GlobalGrowthFit (GlobalGrowthFit), 63
- predict.GrowthFit (GrowthFit), 68
- predict\_dynamic\_growth, 92
- predict\_dynamic\_growth(), 5, 17, 23, 26, 92
- predict\_growth, 94
- predict\_growth(), 71, 92, 100, 104, 107
- predict\_growth\_uncertainty, 98
- predict\_growth\_uncertainty(), 73, 103
- predict\_isothermal\_growth, 100
- predict\_isothermal\_growth(), 82, 100
- predict\_MCMC\_growth, 101
- predict\_MCMC\_growth(), 101
- predict\_stochastic\_growth, 103
- predict\_stochastic\_growth(), 103, 110
- predictMCMC, 91

predictMCMC(), [101](#)  
 predictMCMC.FitDynamicGrowthMCMC  
     (FitDynamicGrowthMCMC), [24](#)  
 predictMCMC.FitMultipleGrowthMCMC  
     (FitMultipleGrowthMCMC), [32](#)  
 predictMCMC.GlobalGrowthFit  
     (GlobalGrowthFit), [63](#)  
 predictMCMC.GrowthFit (GrowthFit), [68](#)  
 primary\_model\_data, [104](#)  
 primary\_model\_data(), [41](#), [86](#), [96](#), [99](#), [109](#)  
 print.DynamicGrowth (DynamicGrowth), [17](#)  
 print.FitDynamicGrowth  
     (FitDynamicGrowth), [21](#)  
 print.FitDynamicGrowthMCMC  
     (FitDynamicGrowthMCMC), [24](#)  
 print.FitIsoGrowth (FitIsoGrowth), [27](#)  
 print.FitMultipleDynamicGrowth  
     (FitMultipleDynamicGrowth), [29](#)  
 print.FitMultipleGrowthMCMC  
     (FitMultipleGrowthMCMC), [32](#)  
 print.FitSecondaryGrowth  
     (FitSecondaryGrowth), [36](#)  
 print.GlobalGrowthComparison  
     (GlobalGrowthComparison), [61](#)  
 print.GlobalGrowthFit  
     (GlobalGrowthFit), [63](#)  
 print.GrowthComparison  
     (GrowthComparison), [66](#)  
 print.GrowthFit (GrowthFit), [68](#)  
 print.GrowthPrediction  
     (GrowthPrediction), [71](#)  
 print.GrowthUncertainty  
     (GrowthUncertainty), [73](#)  
 print.IsothermalGrowth  
     (IsothermalGrowth), [82](#)  
 print.MCMCgrowth (MCMCgrowth), [88](#)  
 print.SecondaryComparison  
     (SecondaryComparison), [106](#)  
 print.StochasticGrowth  
     (StochasticGrowth), [109](#)  
 print.TimeDistribution  
     (TimeDistribution), [111](#)  
  
 Q0\_to\_lambda, [105](#)  
 Q0\_to\_lambda(), [95](#)  
  
 residuals.FitDynamicGrowth  
     (FitDynamicGrowth), [21](#)  
 residuals.FitDynamicGrowthMCMC  
     (FitDynamicGrowthMCMC), [24](#)  
 residuals.FitIsoGrowth (FitIsoGrowth),  
     [27](#)  
 residuals.FitMultipleDynamicGrowth  
     (FitMultipleDynamicGrowth), [29](#)  
 residuals.FitMultipleGrowthMCMC  
     (FitMultipleGrowthMCMC), [32](#)  
 residuals.FitSecondaryGrowth  
     (FitSecondaryGrowth), [36](#)  
 residuals.GlobalGrowthFit  
     (GlobalGrowthFit), [63](#)  
 residuals.GrowthFit (GrowthFit), [68](#)  
 richards\_model, [105](#)  
  
 secondary\_model\_data, [107](#)  
 secondary\_model\_data(), [42](#), [86](#), [96](#)  
 SecondaryComparison, [13](#), [106](#)  
 show\_guess\_dynamic, [108](#)  
 show\_guess\_primary, [109](#)  
 StochasticGrowth, [109](#), [110](#)  
 summary.FitDynamicGrowth  
     (FitDynamicGrowth), [21](#)  
 summary.FitDynamicGrowthMCMC  
     (FitDynamicGrowthMCMC), [24](#)  
 summary.FitIsoGrowth (FitIsoGrowth), [27](#)  
 summary.FitMultipleDynamicGrowth  
     (FitMultipleDynamicGrowth), [29](#)  
 summary.FitMultipleGrowthMCMC  
     (FitMultipleGrowthMCMC), [32](#)  
 summary.FitSecondaryGrowth  
     (FitSecondaryGrowth), [36](#)  
 summary.GlobalGrowthComparison  
     (GlobalGrowthComparison), [61](#)  
 summary.GlobalGrowthFit  
     (GlobalGrowthFit), [63](#)  
 summary.GrowthComparison  
     (GrowthComparison), [66](#)  
 summary.GrowthFit (GrowthFit), [68](#)  
 summary.GrowthPrediction  
     (GrowthPrediction), [71](#)  
 summary.SecondaryComparison  
     (SecondaryComparison), [106](#)  
 summary.TimeDistribution  
     (TimeDistribution), [111](#)  
  
 t, [84](#), [85](#), [105](#), [116](#)  
 time\_to\_logcount, [112](#)  
 time\_to\_logcount(), [112](#)



time\_to\_size, 113  
time\_to\_size(), 16, 112  
TimeDistribution, 111, 114  
TimeDistribution(), 17  
trilinear\_model, 115

vcov.FitDynamicGrowth  
    (FitDynamicGrowth), 21  
vcov.FitDynamicGrowthMCMC  
    (FitDynamicGrowthMCMC), 24  
vcov.FitIsoGrowth (FitIsoGrowth), 27  
vcov.FitMultipleDynamicGrowth  
    (FitMultipleDynamicGrowth), 29  
vcov.FitMultipleGrowthMCMC  
    (FitMultipleGrowthMCMC), 32  
vcov.FitSecondaryGrowth  
    (FitSecondaryGrowth), 36  
vcov.GlobalGrowthFit (GlobalGrowthFit),  
    63  
vcov.GrowthFit (GrowthFit), 68

zwietering\_gamma, 116