

Package ‘blandr’

May 10, 2018

Title Bland-Altman Method Comparison

Version 0.5.1

Date 2018-05-09

Description Carries out Bland Altman analyses (also known as a Tukey mean-difference plot) as described by JM Bland and DG Altman in 1986 <doi:10.1016/S0140-6736(86)90837-8>. This package was created in 2015 as existing Bland-Altman analysis functions did not calculate confidence intervals. This package was created to rectify this, and create reproducible plots. This package is also available as a module for the 'jamovi' statistical spreadsheet (see <<https://www.jamovi.org>> for more information).

Depends R (>= 3.2.0)

License GPL-3

Encoding UTF-8

LazyData true

URL <https://github.com/deepankardatta/blandr/>

BugReports <https://github.com/deepankardatta/blandr/issues>

Imports ggplot2, knitr, stringr, jmvcore (>= 0.8.5), R6, rmarkdown

Suggests testthat

SystemRequirements pandoc (>=1.12.3)

VignetteBuilder knitr

Collate 'blandr.data.preparation.r' 'blandr.dataset.fibre.r'
'blandr.dataset.sbp.r' 'blandr.dataset.o2sats.r'
'blandr.dataset.pefr.r' 'blandr.dataset.load.r'
'blandr.plot.ggplot.r' 'blandr.plot.rplot.r'
'blandr.plot.limits.r' 'blandr.statistics.r' 'blandr.draw.r'
'blandr.output.text.r' 'blandr.display.and.draw.r'
'blandr.display.and.plot.r' 'blandr.method.comparison.r'
'blandr.output.report.r' 'blandr.plot.normality.r'
'blandr.plot.qq.r' 'blandr.plot.r' 'jamovibaanalysis.b.R'
'jamovibaanalysis.h.R' 'jamovibaplohistogram.b.R'

'jamovibaplohistogram.h.R' 'jamovibaplotqq.b.R'
 'jamovibaplotqq.h.R' 'jamovibastats.b.R' 'jamovibastats.h.R'

RoxygenNote 6.0.1

NeedsCompilation no

Author Deepankar Datta [aut, cre]

Maintainer Deepankar Datta <deepankardatta@nhs.net>

Repository CRAN

Date/Publication 2018-05-10 12:15:56 UTC

R topics documented:

bland.altman.PEFR.1986	3
blandr.data.preparation	3
blandr.dataset.fibre	4
blandr.dataset.load	5
blandr.dataset.o2sats	6
blandr.dataset.pefr	7
blandr.dataset.sbp	8
blandr.display.and.draw	9
blandr.display.and.plot	10
blandr.draw	11
blandr.method.comparison	13
blandr.output.report	14
blandr.output.text	15
blandr.plot	16
blandr.plot.ggplot	17
blandr.plot.limits	19
blandr.plot.normality	20
blandr.plot.qq	21
blandr.plot.rplot	21
blandr.statistics	23
giavarina.2015	25
jamoviBAanalysis	26
jamoviBAplotHistogram	26
jamoviBAplotQQ	27
jamoviBAstats	28
Index	29

`bland.altman.PEFR.1986`*Sample PEFr comparison data from Bland-Altman (1986)*

Description

This is the sample PEFr data set from the 1986 Lancet paper written by Bland and Altman. I do not claim any copyright on the data - this is meant to allow testing of the function. I encourage future package authors to use the .rda file if they so wish.

Usage

```
data("bland.altman.PEFR.1986")
```

Format

A data frame with 17 observations on the following 4 variables.

WrightFirst a numeric vector

WrightSecond a numeric vector

MiniWrightFirst a numeric vector

MiniWrightSecond a numeric vector

References

Bland, J. M., & Altman, D. (1986). Statistical methods for assessing agreement between two methods of clinical measurement. *The Lancet*, 327(8476), 307-310. PMID:2868172. [http://dx.doi.org/10.1016/S0140-6736\(86\)90837-8](http://dx.doi.org/10.1016/S0140-6736(86)90837-8)

Examples

```
data(bland.altman.PEFR.1986)
```

`blandr.data.preparation`*Data preparation for method comparison analysis*

Description

Prepares the data and runs error checks before the calling function runs whatever method analysis mode is wants.

Usage

```
blandr.data.preparation(method1, method2, sig.level)
```

Arguments

method1	A list of numbers.
method2	A list of numbers.
sig.level	Significance level. Is not optional in this function, as the calling package should have a default value to pass if needed

Value

method.comparison A data frame of paired values. These have been data checked, and empty rows omitted, from the originally supplied data.

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

Examples

```
# Generates two random measurements
measurement1 <- rnorm(100)
measurement2 <- rnorm(100)

# Calls the function - do note that this function was really
# meant to be called from other functions and not a stand-alone function
blandr.data.preparation( measurement1 , measurement2, sig.level=0.95 )
```

blandr.dataset.fibre *Function to load D'arbela mean velocity of circumferential fibre shortening dataset from internet*

Description

Loads the D'arbela mean velocity of circumferential fibre shortening dataset from Martin Bland's website.

Usage

```
blandr.dataset.fibre()
```

Value

converted.from.dct A data frame containing the dataset

Note

The function converts the STATA DCT data format into a data frame that R can process.

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

References

<https://www-users.york.ac.uk/~mb55/datasets/pefr.dct> - The D'arbela mean velocity of circumferential fibre shortening dataset from Martin Bland's website

<https://www-users.york.ac.uk/~mb55/datasets/datasets.htm> - Martin Bland's example data-set webpage

Bland JM, Altman DG. (1986) Statistical methods for assessing agreement between two methods of clinical measurement. *Lancet* i, 307-310.

Examples

```
blandr.dataset.fibre()
pefr.data <- blandr.dataset.fibre()
```

`blandr.dataset.load` *Function to load example data sets*

Description

Loads example data sets from the internet.

Usage

```
blandr.dataset.load(dataset.name)
```

Arguments

`dataset.name` Loads the requisite data set. See the description for further details.

Value

example.dataset A data frame containing the requisite dataset

Note

Dataset 1 ("1", "PEFR", "pefr") - Bland Altman PEFR dataset (from `blandr.dataset.pefr`)

Dataset 2 ("2", "o2sats", "sealey") - Selaey oxygen saturations dataset (from `blandr.dataset.o2sats`)

Dataset 3 ("3", "fibre", "darbela") - D'arbela mean velocity of circumferential fibre shortening dataset (from `blandr.dataset.fibre`)

Dataset 4 ("4", "sbp", "close") - Close systolic blood pressure dataset (from `blandr.dataset.sbp`)

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

Examples

```
blandr.dataset.load( "pefr" )  
pefr.data <- blandr.dataset.load( "pefr" )
```

blandr.dataset.o2sats *Function to load Bland-Altman oxygen saturation dataset from internet*

Description

Loads the Bland-Altman oxygen saturation dataset from Martin Bland's website.

Usage

```
blandr.dataset.o2sats()
```

Value

converted.from.dct A data frame containing the dataset

Note

The function converts the STATA DCT data format into a data frame that R can process.

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

References

<https://www-users.york.ac.uk/~mb55/datasets/sealey.dct> - The oxygen saturation dataset from Martin Bland's website

<https://www-users.york.ac.uk/~mb55/datasets/datasets.htm> - Martin Bland's example data-set webpage

Bland JM, Altman DG. (1986) Statistical methods for assessing agreement between two methods of clinical measurement. *Lancet* i, 307-310.

Examples

```
blandr.dataset.o2sats()  
pefr.data <- blandr.dataset.o2sats()
```

`blandr.dataset.pefr` *Function to load Bland-Altman PEFR dataset from internet*

Description

Loads the Bland-Altman PEFR dataset from Martin Bland's website.

Usage

```
blandr.dataset.pefr()
```

Value

converted.from.dct A data frame containing the dataset

Note

The function converts the STATA DCT data format into a data frame that R can process.

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

References

<https://www-users.york.ac.uk/~mb55/datasets/pefr.dct> - The PEFR dataset from Martin Bland's website

<https://www-users.york.ac.uk/~mb55/datasets/datasets.htm> - Martin Bland's example data-set webpage

Bland JM, Altman DG. (1986) Statistical methods for assessing agreement between two methods of clinical measurement. *Lancet* i, 307-310.

Examples

```
blandr.dataset.pefr()  
pefr.data <- blandr.dataset.pefr()
```

`blandr.dataset.sbp` *Function to load Close systolic blood pressure dataset from internet*

Description

Loads the Close systolic blood pressure dataset from Martin Bland's website.

Usage

```
blandr.dataset.sbp()
```

Value

`converted.from.dct` A data frame containing the dataset

Note

The function converts the STATA DCT data format into a data frame that R can process.

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

References

<https://www-users.york.ac.uk/~mb55/datasets/pefr.dct> - The Close systolic blood pressure dataset from Martin Bland's website

<https://www-users.york.ac.uk/~mb55/datasets/datasets.htm> - Martin Bland's example data-set webpage

Bland JM, Altman DG. (1995) Comparing methods of measurement: why plotting difference against standard method is misleading. *Lancet*, 346, 1085-7.

Examples

```
blandr.dataset.sbp()
pefr.data <- blandr.dataset.sbp()
```

 blandr.display.and.draw

Bland-Altman display and draw for R

Description

Stub function: calls both the display and plots functions (in that order). Uses the same parameters as the plot and display functions to allow easy all-in-one use.

This function may be deprecated in future, as you really can use the functions easily separately.

Usage

```
blandr.display.and.draw(method1, method2, plotter = "ggplot",
  method1name = "Method 1", method2name = "Method 2",
  plotTitle = "Bland-Altman plot for comparison of 2 methods",
  sig.level = 0.95, annotate = FALSE, ciDisplay = TRUE,
  ciShading = FALSE, normalLow = FALSE, normalHigh = FALSE,
  lowest_y_axis = FALSE, highest_y_axis = FALSE, point_size = 0.8)
```

Arguments

method1	A list of numbers.
method2	A list of numbers.
plotter	(Optional- default='ggplot') Selects which graphics engine to use to plot the Bland-Altman charts. 2 options are 'ggplot' or 'rplot'. If unknown parameter sent, will default to 'ggplot'
method1name	(Optional) Plotting name for 1st method, default 'Method 1'
method2name	(Optional) Plotting name for 2nd method, default 'Method 2'
plotTitle	(Optional) Title name, default 'Bland-Altman plot for comparison of 2 methods'
sig.level	(Optional) Two-tailed significance level. Expressed from 0 to 1. Defaults to 0.95.
annotate	(Optional) TRUE/FALSE switch to provides annotations to plot, default=FALSE
ciDisplay	(Optional) TRUE/FALSE switch to plot confidence intervals for bias and limits of agreement, default=TRUE
ciShading	(Optional) TRUE/FALSE switch to plot confidence interval shading to plot, default=TRUE
normalLow	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its lower boundary
normalHigh	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its higher boundary
lowest_y_axis	(Optional) Defaults to NULL If given a continuous variable will use this as the lower boundary of the y axis. Useful if need multiple plots with equivalent y-axes.

`highest_y_axis` (Optional) Defaults to NULL. If given a continuous variable will use this as the upper boundary of the y axis. Useful if need multiple plots with equivalent y-axes.

`point_size` (Optional) Size of marker for each dot. Default is `cex=0.8`

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

Examples

```
# Generates two random measurements
measurement1 <- rnorm(100)
measurement2 <- rnorm(100)

# Generates a plot, with no optional arguments
blandr.display.and.draw( measurement1 , measurement2 )

# Generates a plot, with title
blandr.display.and.draw( measurement1 , measurement2 , plotTitle = 'Bland-Altman example plot' )
```

`blandr.display.and.plot`

(DEPRECATED) Bland-Altman display and plot for R

Description

(DEPRECATED) Re-directs to `blandr.display.and.draw`

Usage

```
blandr.display.and.plot(method1, method2, method1name = "Method 1",
  method2name = "Method 2",
  plotTitle = "Bland-Altman plot for comparison of 2 methods",
  sig.level = 0.95, annotate = FALSE, ciDisplay = TRUE,
  ciShading = FALSE, normalLow = FALSE, normalHigh = FALSE,
  lowest_y_axis = FALSE, highest_y_axis = FALSE, point_size = 0.8)
```

Arguments

<code>method1</code>	A list of numbers.
<code>method2</code>	A list of numbers.
<code>method1name</code>	(Optional) Plotting name for 1st method, default 'Method 1'
<code>method2name</code>	(Optional) Plotting name for 2nd method, default 'Method 2'
<code>plotTitle</code>	(Optional) Title name, default 'Bland-Altman plot for comparison of 2 methods'

sig.level	(Optional) Two-tailed significance level. Expressed from 0 to 1. Defaults to 0.95.
annotate	(Optional) TRUE/FALSE switch to provides annotations to plot, default=FALSE
ciDisplay	(Optional) TRUE/FALSE switch to plot confidence intervals for bias and limits of agreement, default=TRUE
ciShading	(Optional) TRUE/FALSE switch to plot confidence interval shading to plot, default=TRUE
normalLow	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its lower boundary
normalHigh	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its higher boundary
lowest_y_axis	(Optional) Defaults to NULL If given a continuous variable will use this as the lower boundary of the y axis. Useful if need multiple plots with equivalent y-axes.
highest_y_axis	(Optional) Defaults to NULL If given a continuous variable will use this as the upper boundary of the y axis. Useful if need multiple plots with equivalent y-axes.
point_size	(Optional) Size of marker for each dot. Default is cex=0.8

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

blandr.draw

Bland-Altman drawing function for R

Description

Bland-Altman drawing function. Depends on the blandr.statistics function in the package. Will generate a plot via the standard R plotting functions.

Usage

```
blandr.draw(method1, method2, method1name = "Method 1",
            method2name = "Method 2",
            plotTitle = "Bland-Altman plot for comparison of 2 methods",
            sig.level = 0.95, LoA.mode = 1, annotate = FALSE, ciDisplay = TRUE,
            ciShading = TRUE, normalLow = FALSE, normalHigh = FALSE,
            lowest_y_axis = FALSE, highest_y_axis = FALSE, point_size = 0.8,
            overlapping = FALSE, plotter = "ggplot", x.plot.mode = "means",
            y.plot.mode = "difference", plotProportionalBias = FALSE,
            plotProportionalBias.se = TRUE, assume.differences.are.normal = TRUE)
```

Arguments

method1	A list of numbers.
method2	A list of numbers.
method1name	(Optional) Plotting name for 1st method, default 'Method 1'
method2name	(Optional) Plotting name for 2nd method, default 'Method 2'
plotTitle	(Optional) Title name, default 'Bland-Altman plot for comparison of 2 methods'
sig.level	(Optional) Two-tailed significance level. Expressed from 0 to 1. Defaults to 0.95.
LoA.mode	(Optional) Switch to change how accurately the limits of agreement (LoA) are calculated from the bias and its standard deviation. The default is LoA.mode=1 which calculates LoA with the more accurate 1.96x multiplier. LoA.mode=2 uses the 2x multiplier which was used in the original papers. This should really be kept at default, except to double check calculations in older papers.
annotate	(Optional) TRUE/FALSE switch to provides annotations to plot, default=FALSE
ciDisplay	(Optional) TRUE/FALSE switch to plot confidence intervals for bias and limits of agreement, default=TRUE
ciShading	(Optional) TRUE/FALSE switch to plot confidence interval shading to plot, default=TRUE
normalLow	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its lower boundary
normalHigh	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its higher boundary
lowest_y_axis	(Optional) Defaults to NULL If given a continuous variable will use this as the lower boundary of the y axis. Useful if need multiple plots with equivalent y-axes.
highest_y_axis	(Optional) Defaults to NULL If given a continuous variable will use this as the upper boundary of the y axis. Useful if need multiple plots with equivalent y-axes.
point_size	(Optional) Size of marker for each dot. Default is cex=0.8
overlapping	(Optional) TRUE/FALSE switch to increase size of plotted point if multiple values using ggplot's geom_count, default=FALSE. Not currently recommend until I can tweak the graphics to make them better
plotter	(Optional- default='ggplot') Selects which graphics engine to use to plot the Bland-Altman charts. 2 options are 'ggplot' or 'rplot'. If unknown parameter sent, will default to 'ggplot'
x.plot.mode	(Optional) Switch to change x-axis from being plotted by means ("means") or by either 1st method ("method1") or 2nd method ("method2"). Default is "means". Anything other than "means" will switch to default mode.
y.plot.mode	(Optional) Switch to change y-axis from being plotted by difference ("difference") or by proportion magnitude of measurements ("proportion"). Default is "difference". Anything other than "proportional" will switch to default mode.

```

plotProportionalBias
    (Optional) TRUE/FALSE switch. Plots a proportional bias line. Default is
    FALSE.
plotProportionalBias.se
    (Optional) TRUE/FALSE switch. If proportional bias line is drawn, switch to
    plot standard errors. See stat_smooth for details. Default is TRUE.
assume.differences.are.normal
    (Optional, not operationally used currently) Assume the difference of means has
    a normal distribution. Will be used to build further analyses

```

Note

Started 2015-11-14
 Last update 2015-11-19
 Originally designed for LAVAS and CVLA

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

Examples

```

# Generates two random measurements
measurement1 <- rnorm(100)
measurement2 <- rnorm(100)

# Generates a plot, with no optional arguments
blandr.draw( measurement1 , measurement2 )

# Generates a plot, using the in-built R graphics
blandr.draw( measurement1 , measurement2 , plotter = 'rplot' )

# Generates a plot, with title changed
blandr.draw( measurement1 , measurement2 , plotTitle = 'Bland-Altman example plot' )

# Generates a plot, with title changed, and confidence intervals off
blandr.draw( measurement1 , measurement2 , plotTitle = 'Bland-Altman example plot' ,
  ciDisplay = FALSE , ciShading = FALSE )

```

blandr.method.comparison

Bland-Altman method comparison

Description

Everyone likes graphs, lines and T-tests. This uses the data provided to generate simple tests whilst trying to explain why they should be treated with caution in method comparison studies. This is hopefully the first step in getting people to use the Bland-Altman functions as I suspect everyone will try to do these tests anyway.

Usage

```
blandr.method.comparison(method1, method2, sig.level = 0.95)
```

Arguments

method1	A list of numbers.
method2	A list of numbers.
sig.level	(Optional) Two-tailed significance level. Expressed from 0 to 1. Defaults to 0.95.

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

References

Based on: (1) Bland, J. M., & Altman, D. (1986). Statistical methods for assessing agreement between two methods of clinical measurement. *The Lancet*, 327(8476), 307-310. [http://dx.doi.org/10.1016/S0140-6736\(86\)90837-8](http://dx.doi.org/10.1016/S0140-6736(86)90837-8)

Linnet K., Limitations of the paired t-test for evaluation of method comparison data. *Clin Chem*. 1999 Feb;45(2):314-5. PMID: 9931067

Zaki R, Bulgiba A, Ismail R, Ismail NA. Statistical Methods Used to Test for Agreement of Medical Instruments Measuring Continuous Variables in Method Comparison Studies: A Systematic Review *PLoS ONE* 2012 7(5): e37908. doi: 10.1371/journal.pone.0037908

Examples

```
# Generates two random measurements
measurement1 <- rnorm(100)
measurement2 <- rnorm(100)

# Call the function
blandr.method.comparison( measurement1 , measurement2 )
```

blandr.output.report *Bland-Altman report generator*

Description

Generates a report for the Bland-Altman statistics using rMarkdown and Shiny.

Usage

```
blandr.output.report(method1, method2)
```

Arguments

method1 A list of numbers for the first method
 method2 A list of numbers for the second method

Note

Use the function to generate a report. You can also take the .Rmd file to customise it and create your own report. Or use rMarkdown to save the contents. I couldn't add this to the function as it's not allowed in CRAN. On the otherhand a full Shiny app would take too long. So this is a stop-gap way of creating this function. Hopefully I can improve it in the future

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

Examples

```
# NOT RUN
# Generates two random measurements
# measurement1 <- rnorm(100)
# measurement2 <- rnorm(100)

# blandr.output.report( measurement1 , measurement2 )
#
# Use this to manually run the rmarkdown template
# However specify where the template is
# Also define your methods as method1 and method2 exactly
# For a reason I can't fathom (or how the list of parameters is constructed)
# not naming them method1 and method2 makes them invisible to the rMarkdown document
#
# rmarkdown::run( file = "blandr_report_template.Rmd" ,
#   render_args = list( runtime = "shiny" ,
#     params = list( method1 = method1 ,
#       method2 = method2 ) ) )
# END OF NOT RUN
```

blandr.output.text *Bland-Altman summary statistics display function*

Description

Displays results of Bland-Altman analysis in a nicer text format. Relies on the blandr.statistics function in the package.

Usage

```
blandr.output.text(method1, method2, sig.level = 0.95)
```

Arguments

method1	A list of numbers.
method2	A list of numbers.
sig.level	(Optional) Two-tailed significance level. Expressed from 0 to 1. Defaults to 0.95.

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

Examples

```
# Generates two random measurements
measurement1 <- rnorm(100)
measurement2 <- rnorm(100)

# Displays basic statistics for the two measurements in a readable form
blandr.output.text( measurement1 , measurement2 )
```

blandr.plot

(DEPRECATED) Bland-Altman drawing function for R

Description

(DEPRECATED) Re-directs to blandr.draw.r

Usage

```
blandr.plot(method1, method2, plotter = "ggplot", method1name = "Method 1",
  method2name = "Method 2",
  plotTitle = "Bland-Altman plot for comparison of 2 methods",
  sig.level = 0.95, annotate = FALSE, ciDisplay = TRUE,
  ciShading = TRUE, normalLow = FALSE, normalHigh = FALSE,
  lowest_y_axis = FALSE, highest_y_axis = FALSE, point_size = 0.8)
```

Arguments

method1	A list of numbers.
method2	A list of numbers.
plotter	(Optional- default='ggplot') Selects which graphics engine to use to plot the Bland-Altman charts. 2 options are 'ggplot' or 'rplot'. If unknown parameter sent, will default to 'ggplot'

method1name	(Optional) Plotting name for 1st method, default 'Method 1'
method2name	(Optional) Plotting name for 2nd method, default 'Method 2'
plotTitle	(Optional) Title name, default 'Bland-Altman plot for comparison of 2 methods'
sig.level	(Optional) Two-tailed significance level. Expressed from 0 to 1. Defaults to 0.95.
annotate	(Optional) TRUE/FALSE switch to provides annotations to plot, default=FALSE
ciDisplay	(Optional) TRUE/FALSE switch to plot confidence intervals for bias and limits of agreement, default=TRUE
ciShading	(Optional) TRUE/FALSE switch to plot confidence interval shading to plot, default=TRUE
normalLow	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its lower boundary
normalHigh	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its higher boundary
lowest_y_axis	(Optional) Defaults to NULL If given a continuous variable will use this as the lower boundary of the y axis. Useful if need multiple plots with equivalent y-axes.
highest_y_axis	(Optional) Defaults to NULL If given a continuous variable will use this as the upper boundary of the y axis. Useful if need multiple plots with equivalent y-axes.
point_size	(Optional) Size of marker for each dot. Default is cex=0.8

`blandr.plot.ggplot` *Bland-Altman plotting function, using ggplot2*

Description

Draws a Bland-Altman plot using data calculated using the other functions, using ggplot2

Usage

```
blandr.plot.ggplot(statistics.results, method1name = "Method 1",
  method2name = "Method 2",
  plotTitle = "Bland-Altman plot for comparison of 2 methods",
  ciDisplay = TRUE, ciShading = TRUE, normalLow = FALSE,
  normalHigh = FALSE, overlapping = FALSE, x.plot.mode = "means",
  y.plot.mode = "difference", plotProportionalBias = FALSE,
  plotProportionalBias.se = TRUE, assume.differences.are.normal = TRUE)
```

Arguments

<code>statistics.results</code>	A list of statistics generated by the <code>blandr.statistics</code> function: see the function's return list to see what variables are passed to this function
<code>method1name</code>	(Optional) Plotting name for 1st method, default "Method 1"
<code>method2name</code>	(Optional) Plotting name for 2nd method, default "Method 2"
<code>plotTitle</code>	(Optional) Title name, default "Bland-Altman plot for comparison of 2 methods"
<code>ciDisplay</code>	(Optional) TRUE/FALSE switch to plot confidence intervals for bias and limits of agreement, default is TRUE
<code>ciShading</code>	(Optional) TRUE/FALSE switch to plot confidence interval shading to plot, default is TRUE
<code>normalLow</code>	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its lower boundary
<code>normalHigh</code>	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its higher boundary
<code>overlapping</code>	(Optional) TRUE/FALSE switch to increase size of plotted point if multiple values using <code>ggplot</code> 's <code>geom_count</code> , default=FALSE. Not currently recommend until I can tweak the graphics to make them better
<code>x.plot.mode</code>	(Optional) Switch to change x-axis from being plotted by means (= "means") or by either 1st method (= "method1") or 2nd method (= "method2"). Default is "means". Anything other than "means" will switch to default mode.
<code>y.plot.mode</code>	(Optional) Switch to change y-axis from being plotted by difference (= "difference") or by proportion magnitude of measurements (= "proportion"). Default is "difference". Anything other than "proportional" will switch to default mode.
<code>plotProportionalBias</code>	(Optional) TRUE/FALSE switch. Plots a proportional bias line. Default is FALSE.
<code>plotProportionalBias.se</code>	(Optional) TRUE/FALSE switch. If proportional bias line is drawn, switch to plot standard errors. See <code>stat_smooth</code> for details. Default is TRUE.
<code>assume.differences.are.normal</code>	(Optional, not operationally used currently) Assume the difference of means has a normal distribution. Will be used to build further analyses

Value

`ba.plot` Returns a `ggplot` data set that can then be plotted

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

Examples

```
# Generates two random measurements
measurement1 <- rnorm(100)
measurement2 <- rnorm(100)

# Generates a ggplot
# Do note the ggplot function wasn't meant to be used on it's own
# and is generally called via the bland.altman.display.and.draw function

# Passes data to the blandr.statistics function to generate Bland-Altman statistics
statistics.results <- blandr.statistics( measurement1 , measurement2 )

# Generates a ggplot, with no optional arguments
blandr.plot.ggplot( statistics.results )

# Generates a ggplot, with title changed
blandr.plot.ggplot( statistics.results , plotTitle = "Bland-Altman example plot" )

# Generates a ggplot, with title changed, and confidence intervals off
blandr.plot.ggplot( statistics.results , plotTitle = "Bland-Altman example plot" ,
ciDisplay = FALSE , ciShading = FALSE )
```

`blandr.plot.limits` *Bland-Altman plot limits for R*

Description

Works out plot limits for the Bland-Altman plots. Depends on the `blandr.statistics` function in the package.

Usage

```
blandr.plot.limits(statistics.results, lowest_y_axis = FALSE,
highest_y_axis = FALSE)
```

Arguments

`statistics.results` A list of statistics generated by the `blandr.statistics` function: see the function's return list to see what variables are passed to this function

`lowest_y_axis` (Optional) Defaults to NULL. If given a continuous variable will use this as the lower boundary of the y axis. Useful if need multiple plots with equivalent y-axes.

`highest_y_axis` (Optional) Defaults to NULL. If given a continuous variable will use this as the upper boundary of the y axis. Useful if need multiple plots with equivalent y-axes.

Value

x_upper The upper limit of the X-axis
x_lower The lower limit of the X-axis
y_upper The upper limit of the Y-axis
y_lower The lower limit of the Y-axis

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

Examples

```
# Generates two random measurements
measurement1 <- rnorm(100)
measurement2 <- rnorm(100)

# Passes data to the blandr.statistics function to generate Bland-Altman statistics
statistics.results <- blandr.statistics( measurement1 , measurement2 )

# Calls the function
blandr.plot.limits( statistics.results )
```

blandr.plot.normality *Bland-Altman histogram and density plot*

Description

Generates a combined histogram and density curve for Bland-Altman differences

Usage

```
blandr.plot.normality(statistics.results)
```

Arguments

statistics.results

A list of statistics generated by the blandr.statistics function: see the function's return list to see what variables are passed to this function

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

blandr.plot.qq	<i>Bland-Altman differences QQ plot</i>
----------------	---

Description

Generates a QQ plot for Bland-Altman differences

Usage

```
blandr.plot.qq(statistics.results)
```

Arguments

statistics.results

A list of statistics generated by the blandr.statistics function: see the function's return list to see what variables are passed to this function

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

blandr.plot.rplot	<i>Bland-Altman plotting function, using basic R drawing functions</i>
-------------------	--

Description

Draws a Bland-Altman plot using data calculated using the other functions, using the in-built R graphics

Usage

```
blandr.plot.rplot(statistics.results, plot.limits, method1name = "Method 1",  
method2name = "Method 2",  
plotTitle = "Bland-Altman plot for comparison of 2 methods",  
annotate = FALSE, ciDisplay = TRUE, ciShading = TRUE,  
normalLow = FALSE, normalHigh = FALSE, point_size = 0.8)
```

Arguments

statistics.results

A list of statistics generated by the blandr.statistics function: see the function's return list to see what variables are passed to this function

plot.limits

A list of statistics generated by the blandr.plot.limits function to define the extent of the x- and y- axes: see the function's return list to see what variables are passed to this function

method1name	(Optional) Plotting name for 1st method, default 'Method 1'
method2name	(Optional) Plotting name for 2nd method, default 'Method 2'
plotTitle	(Optional) Title name, default 'Bland-Altman plot for comparison of 2 methods'
annotate	(Optional) TRUE/FALSE switch to provides annotations to plot, default=FALSE
ciDisplay	(Optional) TRUE/FALSE switch to plot confidence intervals for bias and limits of agreement, default=TRUE
ciShading	(Optional) TRUE/FALSE switch to plot confidence interval shading to plot, default=TRUE
normalLow	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its lower boundary
normalHigh	(Optional) If there is a normal range, entering a continuous variable will plot a vertical line on the plot to indicate its higher boundary
point_size	(Optional) Size of marker for each dot. Default is cex=0.8

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

Examples

```
# Generates two random measurements
measurement1 <- rnorm(100)
measurement2 <- rnorm(100)

# Generates a basic plot
# Do note the blandr.plot.rplot function wasn't meant to be used on it's own
# and is generally called via the bland.altman.display.and.draw function

# Passes data to the blandr.statistics function to generate Bland-Altman statistics
statistics.results <- blandr.statistics( measurement1 , measurement2 )
# Passed data to the blandr.plot.limits function to generate plot limits
plot.limits <- blandr.plot.limits( statistics.results )

# Generates a basic plot, with no optional arguments
blandr.plot.rplot( statistics.results , plot.limits )

# Generates a basic plot, with title changed
blandr.plot.rplot( statistics.results , plot.limits , plotTitle = 'Bland-Altman example plot' )
# Generates a basic plot, with title changed, and confidence intervals off
blandr.plot.rplot( statistics.results , plot.limits , plotTitle = 'Bland-Altman example plot' ,
ciDisplay = FALSE , ciShading = FALSE )
```

blandr.statistics *Bland-Altman statistics for R*

Description

Bland-Altman analysis function for R. Package created as existing functions don't suit my needs, and don't generate 95% confidence intervals for bias and limits of agreement. This base function calculates the basic statistics, and generates return values which can be used in the related `blandr.display` and `bland.altamn.plot` functions. However the return results can be used to generate a custom chart if desired.

Usage

```
blandr.statistics(method1, method2, sig.level = 0.95, LoA.mode = 1)
```

Arguments

<code>method1</code>	A list of numbers.
<code>method2</code>	A list of numbers.
<code>sig.level</code>	(Optional) Two-tailed significance level. Expressed from 0 to 1. Defaults to 0.95.
<code>LoA.mode</code>	(Optional) Switch to change how accurately the limits of agreement (LoA) are calculated from the bias and its standard deviation. The default is <code>LoA.mode=1</code> which calculates LoA with the more accurate 1.96x multiplier. <code>LoA.mode=2</code> uses the 2x multiplier which was used in the original papers. This should really be kept at default, except to double check calculations in older papers.

Value

`means` List of arithmetic mean of the two methods
`differences` List of differences of the two methods
`method1` Returns the 'method1' list in the data frame if further evaluation is needed
`method2` Returns the 'method2' list in the data frame if further evaluation is needed
`sig.level` Significance level supplied to the function
`sig.level.convert.to.z` Significance level convert to Z value
`bias` Bias of the two methods
`biasUpperCI` Upper confidence interval of the bias (based on significance level)
`biasLowerCI` Lower confidence interval of the bias (based on significance level)
`biasStdDev`
`biasSEM` Standard error for the bias
`LOA_SEM` Standard error for the limits of agreement
`upperLOA` Upper limit of agreement

upperLOA_upperCI Upper confidence interval of the upper limit of agreement
 upperLOA_lowerCI Lower confidence interval of the upper limit of agreement
 lowerLOA Lower limit of agreement
 lowerLOA_upperCI Upper confidence interval of the lower limit of agreement
 lowerLOA_lowerCI Lower confidence interval of the lower limit of agreement
 proportion Differences/means*100
 no.of.observations Number of observations
 regression.equation A regression equation to help determine if there is any proportional bias
 regression.fixed.slope The slope value of the regression equation
 regression.fixed.intercept The intercept value of the regression equation

Note

The function will give similar answers when used on the original Bland-Altman PEFR data sets. They won't be exactly the same as (a) for 95% limits of agreement I have used +/-1.96, rather than 2, and (b) the computerised calculation means that the rounding that is present in each step of the original examples does not occur. This will give a more accurate answer, although I can understand why in 1986 rounding would occur at each step for ease of calculation.

The function depends on paired values.

It currently only can currently work out fixed bias.

Improvements for the future: proportional bias charts will need further work

Started 2015-11-14

Last update 2016-02-04

Originally designed for LAVAS and CVLA

Author(s)

Deepankar Datta <deepankardatta@nhs.net>

References

Based on: (1) Bland, J. M., & Altman, D. (1986). Statistical methods for assessing agreement between two methods of clinical measurement. *The Lancet*, 327(8476), 307-310. [http://dx.doi.org/10.1016/S0140-6736\(86\)90837-8](http://dx.doi.org/10.1016/S0140-6736(86)90837-8)

Confidence interval work based on follow-up paper: (2) Altman, D. G., & Bland, J. M. (2002). Commentary on quantifying agreement between two methods of measurement. *Clinical chemistry*, 48(5), 801-802. <http://www.clinchem.org/content/48/5/801.full.pdf>

Examples

```
# Generates two random measurements
measurement1 <- rnorm(100)
measurement2 <- rnorm(100)

# Generates Bland-Altman statistics data of the two measurements
```



```
blandr.statistics( measurement1 , measurement2 )
```

giavarina.2015 *Sample comparison data from Giavarina (2015)*

Description

This is sample comparison data, taken from Giavarina's 2015 paper on Bland-Altman analysis. The data is from table 1 of the paper. I do not claim any copyright on the data - this is meant to allow testing of the function. I encourage future package authors to use the .rda file if they so wish.

Usage

```
data("giavarina.2015")
```

Format

A data frame with 30 observations on the following 5 variables.

Method.A a numeric vector

Method.B a numeric vector

Mean a numeric vector

Difference a numeric vector

Diff.Mean.Proportion a factor with levels

References

Giavarina D. Understanding Bland Altman analysis. *Biochemia Medica*. 2015;25(2):141-151. doi:10.11613/BM.2015.015.

Examples

```
data(giavarina.2015)
```

jamoviBAanalysis *Bland-Altman Analysis*

Description

Bland-Altman Analysis

Usage

```
jamoviBAanalysis(data, method1, method2, ciDisplay = TRUE, ciShading = TRUE,
  plotProportionalBias = FALSE, plotProportionalBias.se = TRUE,
  overlapping = FALSE)
```

Arguments

```
data                    .
method1                .
method2                .
ciDisplay              .
ciShading              .
plotProportionalBias  
                         .
plotProportionalBias.se
                         .
overlapping            .
```

Value

A results object containing:

results\$table	a table
results\$plot	an image

Tables can be converted to data frames with `asDF` or `as.data.frame`. For example:

```
results$table$asDF
as.data.frame(results$table)
```

jamoviBAplotHistogram *Differences Histogram and Density Curve*

Description

Differences Histogram and Density Curve

Usage

```
jamoviBAplotHistogram(data, method1, method2)
```

Arguments

data	.
method1	.
method2	.

Value

A results object containing:

results\$plot	an image
---------------	----------

jamoviBAplotQQ	<i>Differences Q-Q Plot</i>
----------------	-----------------------------

Description

Differences Q-Q Plot

Usage

```
jamoviBAplotQQ(data, method1, method2)
```

Arguments

data	.
method1	.
method2	.

Value

A results object containing:

results\$plot	an image
---------------	----------

`jamoviBAstats`*Bland-Altman Raw Statistics*

Description

Bland-Altman Raw Statistics

Usage`jamoviBAstats(data, method1, method2)`**Arguments**

<code>data</code>	.
<code>method1</code>	.
<code>method2</code>	.

Value

A results object containing:

<code>results\$text</code>	a preformatted
----------------------------	----------------

Index

*Topic **datasets**

bland.altman.PEFR.1986, [3](#)
giavarina.2015, [25](#)

as.data.frame, [26](#)

bland.altman.PEFR.1986, [3](#)
blandr.data.preparation, [3](#)
blandr.dataset.fibre, [4](#)
blandr.dataset.load, [5](#)
blandr.dataset.o2sats, [6](#)
blandr.dataset.pefr, [7](#)
blandr.dataset.sbp, [8](#)
blandr.display.and.draw, [9](#)
blandr.display.and.plot, [10](#)
blandr.draw, [11](#)
blandr.method.comparison, [13](#)
blandr.output.report, [14](#)
blandr.output.text, [15](#)
blandr.plot, [16](#)
blandr.plot.ggplot, [17](#)
blandr.plot.limits, [19](#)
blandr.plot.normality, [20](#)
blandr.plot.qq, [21](#)
blandr.plot.rplot, [21](#)
blandr.statistics, [23](#)

giavarina.2015, [25](#)

jamoviBAanalysis, [26](#)
jamoviBAplotHistogram, [26](#)
jamoviBAplotQQ, [27](#)
jamoviBAstats, [28](#)