

Package ‘calibrator’

March 7, 2019

Type Package

Title Bayesian Calibration of Complex Computer Codes

Version 1.2-8

Depends R (>= 2.0.0), emulator (>= 1.2-11), mvtnorm

Imports cubature

Maintainer Robin K. S. Hankin <hankin.robin@gmail.com>

Description Performs Bayesian calibration of computer models as per Kennedy and O'Hagan 2001. The package includes routines to find the hyperparameters and parameters; see the help page for stage1() for a worked example using the toy dataset. A tutorial is provided in the calex.Rnw vignette; and a suite of especially simple one dimensional examples appears in inst/doc/one.dim/.

License GPL-2

URL <https://github.com/RobinHankin/calibrator.git>

BugReports <https://github.com/RobinHankin/calibrator/issues>

NeedsCompilation no

Author Robin K. S. Hankin [aut, cre] (<<https://orcid.org/0000-0001-5982-0415>>)

Repository CRAN

Date/Publication 2019-03-07 06:52:58 UTC

R topics documented:

| | |
|-----------------------------------|----|
| calibrator-package | 2 |
| beta1hat.fun | 4 |
| beta2hat.fun | 6 |
| betahat.fun.koh | 7 |
| blockdiag | 9 |
| C1 | 10 |
| cov.p5.supp | 11 |
| create.new.toy.datasets | 13 |
| D1.fun | 14 |

| | |
|--------------------------------|-----------|
| D2.fun | 15 |
| dists.2frames | 16 |
| E.theta.toy | 17 |
| EK.eqn10.supp | 20 |
| etahat | 22 |
| extractor.toy | 23 |
| Ez.eqn7.supp | 24 |
| Ez.eqn9.supp | 25 |
| H.fun | 27 |
| H1.toy | 28 |
| h1.toy | 29 |
| hbar.fun.toy | 30 |
| is.positive.definite | 31 |
| MH | 32 |
| p.eqn4.supp | 34 |
| p.eqn8.supp | 35 |
| p.page4 | 36 |
| phi.fun.toy | 38 |
| prob.psi1 | 41 |
| reality | 43 |
| stage1 | 45 |
| symmetrize | 48 |
| tee | 49 |
| toys | 50 |
| tt.fun | 52 |
| V.fun | 55 |
| V1 | 57 |
| V2 | 58 |
| Vd | 59 |
| W | 60 |
| W1 | 61 |
| W2 | 62 |
| Index | 64 |

calibrator-package

Bayesian Calibration of Complex Computer Codes

Description

Performs Bayesian calibration of computer models as per Kennedy and O’Hagan 2001. The package includes routines to find the hyperparameters and parameters; see the help page for stage1() for a worked example using the toy dataset. A tutorial is provided in the calex.Rnw vignette; and a suite of especially simple one dimensional examples appears in inst/doc/one.dim/.

Details

The DESCRIPTION file:

Package: calibrator
 Type: Package
 Title: Bayesian Calibration of Complex Computer Codes
 Version: 1.2-8
 Authors@R: person(given=c("Robin", "K. S."), family="Hankin", role = c("aut","cre"), email="hankin.robin@gmail.com",
 Depends: R (>= 2.0.0), emulator (>= 1.2-11), mvtnorm
 Imports: cubature
 Maintainer: Robin K. S. Hankin <hankin.robin@gmail.com>
 Description: Performs Bayesian calibration of computer models as per Kennedy and O'Hagan 2001. The package includes
 License: GPL-2
 URL: <https://github.com/RobinHankin/calibrator.git>
 BugReports: <https://github.com/RobinHankin/calibrator/issues>
 Author: Robin K. S. Hankin [aut, cre] (<<https://orcid.org/0000-0001-5982-0415>>)

Index of help topics:

| | |
|-------------------------|--|
| C1 | Matrix of distances from D1 to D2 |
| D1.fun | Function to join x.star to t.vec to give matrix D1 |
| D2.fun | Augments observation points with parameters |
| E.theta.toy | Expectation and variance with respect to theta |
| EK.eqn10.supp | Posterior mean of K |
| Ez.eqn7.supp | Expectation of z given y, beta2, phi |
| Ez.eqn9.supp | Expectation as per equation 10 of KOH2001 |
| H.fun | H function |
| H1.toy | Basis functions for D1 and D2 |
| MH | Very basic implementation of the Metropolis-Hastings algorithm |
| V.fun | Variance matrix for observations |
| V1 | Distance matrix |
| V2 | distance between observation points |
| Vd | Variance matrix for d |
| W | covariance matrix for beta |
| W1 | Variance matrix for beta1hat |
| W2 | variance matrix for beta2 |
| beta1hat.fun | beta1 estimator |
| beta2hat.fun | estimator for beta2 |
| betahat.fun.koh | Expectation of beta, given theta, phi and d |
| blockdiag | Assembles matrices blockwise into a block diagonal matrix |
| calibrator-package | Bayesian Calibration of Complex Computer Codes |
| cov.p5.supp | Covariance function for posterior distribution of z |
| create.new.toy.datasets | Create new toy datasets |
| dists.2frames | Distance between two points |
| etahat | Expectation of computer output |

| | |
|----------------------|--|
| extractor.toy | Extracts lat/long matrix and theta matrix from D2. |
| h1.toy | Basis functions |
| hbar.fun.toy | Toy example of hbar (section 4.2) |
| is.positive.definite | Is a matrix positive definite? |
| p.eqn4.supp | Apostiori probability of psi1 |
| p.eqn8.supp | A postiori probability of hyperparameters |
| p.page4 | A postiori probability of hyperparameters |
| phi.fun.toy | Functions to create or change hyperparameters |
| prob.psi1 | A priori probability of psi1, psi2, and theta |
| reality | Reality |
| stage1 | Stage 1,2 and 3 optimization on toy dataset |
| symmetrize | Symmetrize an upper triangular matrix |
| tee | Auxiliary functions for equation 9 of the supplement |
| toys | Toy datasets |
| tt.fun | Integrals needed in KOH2001 |

Further information is available in the following vignettes:

calex Calex: a cookbook for the emulator package (source)

Author(s)

NA

Maintainer: Robin K. S. Hankin <hankin.robin@gmail.com>

References

- M. C. Kennedy and A. O’Hagan 2001. “Bayesian calibration of computer models”. *Journal of the Royal Statistical Society, Series B*, 63(3): 425–464
- R. K. S. Hankin 2005. “Introducing BACCO, an R bundle for Bayesian analysis of computer code output”, *Journal of Statistical Software*, 14(16)

beta1hat.fun

beta1 estimator

Description

Least squares estimator for beta1

Usage

beta1hat.fun(D1, H1, y, phi)

Arguments

| | |
|-----|-----------------------|
| D1 | code run points |
| H1 | regressor basis funks |
| y | code outputs |
| phi | hyperparameters |

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[beta2hat.fun](#)

Examples

```
data(toys)
y.toy <- create.new.toy.datasets(D1=D1.toy , D2=D2.toy)$y.toy
beta1hat.fun(D1=D1.toy, H1=H1.toy, y=y.toy, phi=phi.toy)

# now cheat: force the hyperparameters to have the correct psi1:
phi.fix <- phi.change(old.phi=phi.toy,psi1=c(1, 0.5, 1.0, 1.0, 0.5, 0.4),phi.fun=phi.fun.toy)
# The value for psi1 is obtained by cheating and #examining the source
# code for computer.model(); see ?phi.change

# Create a new toy dataset with 40 observations:
D1.big <- latin.hypercube(40,5)

jj <- create.new.toy.datasets(D1=D1.big , D2=D2.toy)

# We know that the real coefficients are 4:9 because we
# we can cheat and look at the source code for computer.model()

# Now estimate the coefficients without cheating:

beta1hat.fun(D1=D1.big, H1=H1.toy, jj$y, phi=phi.toy)

# Not bad!
```

```

# We can do slightly better by cheating and using the
# correct value for the hyperparameters:

beta1hat.fun(D1=D1.big, H1=H1.toy, jj$y, phi=phi.true.toy(phi=phi.toy))

#marginally worse.

```

| | |
|--------------|----------------------------|
| beta2hat.fun | <i>estimator for beta2</i> |
|--------------|----------------------------|

Description

estimates beta2 as per the equation of page 4 of the supplement. Used by p.page4()

Usage

```
beta2hat.fun(D1, D2, H1, H2, V, z, etahat.d2, extractor, E.theta,
Edash.theta, phi)
```

Arguments

| | |
|-------------|----------------------------------|
| D1 | Matrix of code run points |
| D2 | Matrix of observation points |
| H1 | regression basis functions |
| H2 | regression basis functions |
| V | overall covariance matrix |
| z | vector of observations |
| etahat.d2 | expectation as per etahat.vector |
| extractor | extractor function |
| E.theta | Expectation |
| Edash.theta | Expectation wrt thetadash |
| phi | hyperparameters |

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/cal-sup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[W2](#)

Examples

```
data(toys)

etahat.d2 <- etahat(D1=D1.toy, D2=D2.toy, H1=H1.toy, y=y.toy,
E.theta=E.theta.toy, extractor=extractor.toy, phi=phi.toy)

beta2hat.fun(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy, V=NULL,
z=z.toy, etahat.d2=etahat.d2, extractor=extractor.toy,
E.theta=E.theta.toy, Edash.theta=Edash.theta.toy, phi=phi.toy)

jj <- create.new.toy.datasets(D1.toy , D2.toy)
phi.true <- phi.true.toy(phi=phi.toy)
y.toy <- jj$y.toy
z.toy <- jj$z.toy
d.toy <- jj$d.toy

etahat.d2 <- etahat(D1=D1.toy, D2=D2.toy, H1=H1.toy, y=y.toy,
E.theta=E.theta.toy, extractor=extractor.toy, phi=phi.toy)

beta2hat <- beta2hat.fun(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy, V=NULL,
z=z.toy, etahat.d2=etahat.d2, extractor=extractor.toy,
E.theta=E.theta.toy, Edash.theta=Edash.theta.toy,
phi=phi.toy)

print(beta2hat)

plot(z.toy , H2.toy(D2.toy) %*% beta2hat)
```

Description

Determines the mean of β , given parameters θ , hyperparameters ϕ , and the vector of code outputs and observations d . It is named so as to avoid conflict with function `betahat.fun` of package **emulator**.

Usage

```
betahat.fun.koh(D1, D2, H1, H2, theta, d, phi)
betahat.fun.koh.vector(D1, D2, H1, H2, theta, d, phi)
```

Arguments

| | |
|-------|--|
| D1 | Matrix whose rows are observation points and parameter values at which the code has been run |
| D2 | Matrix whose rows are the observation points |
| H1 | Regression function for D1 |
| H2 | Regression function for D2 |
| theta | Parameters |
| d | Vector of code outputs and observations |
| phi | Hyperparameters |

Details

This function is defined between equations 2 and 3 of the supplement. It is used in functions `Ez.eqn9.supp()` and `p.eqn8.supp()`.

The user should always use `betahat.fun.koh()`, which is a wrapper for `betahat.fun.koh.vector()`. The forms differ in their treatment of θ . In the former, θ must be a vector; in the latter, θ may be a matrix, in which case `betahat.fun.koh.vector()` is applied to the rows.

In `betahat.fun.koh()`, the rownames are assigned by a kludgy call to `H.fun()`, which itself uses a kludge to determine colnames.

The function returns

$$\hat{\beta}(\theta) = \mathbf{W}(\theta)^T \mathbf{H}(\theta)^T \mathbf{V}_d(\theta)^{-1} \mathbf{d}.$$

Author(s)

Robin K. S. Hankin

References

M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464

M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/cal-sup.ps>

R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

Examples

```

data(toys)
betahat.fun.koh(theta=theta.toy, d=d.toy, D1=D1.toy, D2=D2.toy,
  H1=H1.toy, H2=H2.toy, phi=phi.toy)

betahat.fun.koh.vector(theta=theta.toy, d=d.toy, D1=D1.toy,
  D2=D2.toy, H1=H1.toy, H2=H2.toy, phi=phi.toy)
## should be identical

jj.theta <- rbind(theta.toy, theta.toy+1, theta.toy+2, theta.toy*0)
betahat.fun.koh(theta=jj.theta, d=d.toy, D1=D1.toy, D2=D2.toy,
  H1=H1.toy, H2=H2.toy, phi=phi.toy)

## Now try with true hyperparameters:
phi.true <- phi.true.toy(phi=phi.toy)

## And magically create the REAL parameters:
theta.REAL <- create.new.toy.datasets(export=TRUE)$REAL.PARAMS
jj.theta <- rbind(jj.theta, theta.REAL)

## Generate some data:
jj <- create.new.toy.datasets(D1.toy , D2.toy)
d.toy <- jj$d.toy

## And finally, observe that the estimated values for beta are pretty
## close to the real values (which omniscient beings can extract using
## reality() and computer.model()):

betahat.fun.koh(theta=jj.theta, d=d.toy, D1=D1.toy, D2=D2.toy,
  H1=H1.toy, H2=H2.toy, phi=phi.true)

## [
## that is, compare the last column of the above with
## c(computer.model(ex=T)$REAL.COEFFS, reality(ex=T)$REAL.BETA2)
## ]

```

blockdiag

Assembles matrices blockwise into a block diagonal matrix

Description

Assembles matrices blockwise into a block diagonal matrix with optional padding value

Usage

```
blockdiag(m1, m2, p.tr = 0, p.ll = 0)
```

Arguments

| | |
|------|--|
| m1 | Upper left matrix |
| m2 | Lower right matrix |
| p.tr | Padding value for top right quadrant. Defaults to zero. |
| p.ll | Padding value for lower left quadrant. Defaults to zero. |

Note

The function documented here is a subset of `adiag` of package **magic**

Author(s)

Robin K. S. Hankin

Examples

```
data(toys)
blockdiag(D1.toy,D2.toy)
```

C1

Matrix of distances from D1 to D2

Description

Returns a matrix of distances from the code run points to the augmented observation points. A wrapper for `c1.fun()`.

Usage

```
C1(D1, D2, theta, phi)
```

Arguments

| | |
|-------|-----------------|
| D1 | D1 |
| D2 | D2 |
| theta | Parameters |
| phi | Hyperparameters |

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[t.fun](#)

Examples

```
data(toys)
C1(D1=D1.toy, D2=D2.toy, theta=theta.toy, phi=phi.toy)
```

cov.p5.supp

Covariance function for posterior distribution of z

Description

Covariance function for posterior distribution of $z(\cdot)$ conditional on estimated hyperparameters and calibration parameters θ .

Usage

```
Cov.eqn9.supp(x, xdash=NULL, theta, d, D1, D2, H1, H2, phi)
cov.p5.supp(x, xdash=NULL, theta, d, D1, D2, H1, H2, phi)
```

Arguments

| | |
|-------|---|
| x | first point, or (Cov.eqn9.supp()) a matrix whose rows are the points of interest |
| xdash | The second point, or (Cov.eqn9.supp()) a matrix whose rows are the points of interest. The default of NULL means to use xdash=x |
| theta | Parameters. For Cov.eqn9.supp(), supply a vector which will be interpreted as a single point in parameter space. For cov.p5.supp(), supply a matrix whose rows will be interpreted as points in parameter space |
| d | Observed values |
| D1 | Code run design matrix |
| D2 | Observation points of real process |
| H1 | Basis function for D1 |
| H2 | Basis function for D2 |
| phi | Hyperparameters |

Details

Evaluates the covariance function: the last formula on page 5 of the supplement. The two functions documented here are vectorized differently.

Function `Cov.eqn9.supp()` takes matrices for arguments `x` and `xdash` and a single vector for `theta`. Evaluation is thus taken at a single, fixed value of `theta`. The function returns a matrix whose rows correspond to rows of `x` and whose columns correspond to rows of `xdash`.

Function `cov.p5.supp()` takes a vector for arguments `x` and `xdash` and a matrix for argument `theta` whose rows are the points in parameter space. A vector `V`, with elements corresponding to the rows of argument `theta` is returned:

$$V[i] = \text{cov}(z(x), z(x') | \theta_i)$$

Value

Returns a matrix of covariances

Note

May return the transpose of the desired object

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

Examples

```
data(toys)
x <- rbind(x.toy,x.toy+1,x.toy,x.toy,x.toy)
rownames(x) <- letters[1:5]
xdash <- rbind(x*2,x.toy)
rownames(xdash) <- LETTERS[1:6]

Cov.eqn9.supp(x=x,xdash=xdash,theta=theta.toy,d=d.toy,D1=D1.toy,
             D2=D2.toy,H1=H1.toy,H2=H2.toy,phi=phi.toy)

phi.true <- phi.true.toy(phi=phi.toy)

Cov.eqn9.supp(x=x,xdash=xdash,theta=theta.toy,d=d.toy,D1=D1.toy,
             D2=D2.toy,H1=H1.toy,H2=H2.toy,phi=phi.true)
```

```
# Now try a sequence of thetas:  
cov.p5.supp(x=x.toy,theta=t.vec.toy,d=d.toy,D1=D1.toy,D2=D2.toy,  
            H1=H1.toy,H2=H2.toy,phi=phi.toy)
```

```
create.new.toy.datasets
```

Create new toy datasets

Description

Creates new toy datasets, by sampling from an explicitly specified multivariate Gaussian distribution whose covariance matrix is that required for a Gaussian process.

Usage

```
create.new.toy.datasets(D1,D2,export=FALSE)
```

Arguments

| | |
|--------|---|
| export | Boolean, with default FALSE meaning to return toy datasets and TRUE meaning to return, instead, a list of the true values of the parameters |
| D1 | D1; set of code run points |
| D2 | D2; set of field observation points |

Value

Returns a list of three elements:

y.toy

z.toy

d.toy

Note

Because function `create.new.toy.datasets()` calls `computer.model()` and `model.inadequacy()`, the datasets returned are drawn from a multivariate Gaussian distribution which **is** a Gaussian process

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[toys](#), [reality](#), [latin.hypercube](#)

Examples

```
data(toys)
create.new.toy.datasets(D1=D1.toy , D2=D2.toy)
```

D1.fun

Function to join x.star to t.vec to give matrix D1

Description

Function to join x.star to t.vec to give matrix D1 with correct row- and column- names.

Usage

```
D1.fun(x.star, t.vec)
```

Arguments

| | |
|--------|----------------------------------|
| x.star | Matrix of code run points |
| t.vec | Matrix of parameter theta values |

Details

Note that the matrix returned is a D1 matrix: it is a design matrix for code observations as it contains both x and theta

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[toys](#)

Examples

```
data(toys)
jj <- extractor.toy(D1.toy)
x.star.toy <- jj$x.star
t.vec.toy <- jj$t.vec
D1.fun(x.star.toy , t.vec.toy) # both dataframes
D1.fun(x.star.toy , theta.toy) # one dataframe, one vector
D1.fun(x.toy , t.vec.toy)      # one vector, one dataframe
D1.fun(x.toy, theta.toy)      # two vectors
```

D2.fun

Augments observation points with parameters

Description

Augments observation points with parameters; will recycle if necessary

Usage

```
D2.fun(D2, theta)
```

Arguments

| | |
|-------|--------------------|
| D2 | Observation points |
| theta | Parameters |

Author(s)

Robin K. S. Hankin

References

M. C. Kennedy and A. O’Hagan 2001. “Bayesian calibration of computer models”. Journal of the Royal Statistical Society B, 63(3) pp425-464

M. C. Kennedy and A. O’Hagan 2001. “Supplementary details on Bayesian calibration of computer models”, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>

R. K. S. Hankin 2005. “Introducing BACCO, an R bundle for Bayesian analysis of computer code output”, Journal of Statistical Software, 14(16)

See Also

[D1.toy](#), [theta.toy](#)

Examples

```
data(toys)
D2.fun(D2=D2.toy, theta=theta.toy)
D2.fun(D2=t(x.toy), theta=theta.toy)
D2.fun(D2=D2.toy[1,,drop=FALSE], theta=theta.toy)
```

dists.2frames

Distance between two points

Description

Distance between points specified by rows of two matrices, according to a positive definite matrix. If not specified, the second matrix used is the first.

Usage

```
dists.2frames(a, b=NULL, A=NULL, A.lower=NULL, test.for.symmetry=TRUE)
```

Arguments

| | |
|---------|---|
| a | First dataframe whose rows are the points |
| b | Second dataframe whose rows are the points; if NULL, use a |
| A | Positive definite matrix; if NULL, a value for A.lower is needed. If a value for A is supplied, use a clear but possibly slower method |
| A.lower | The lower triangular Cholesky decomposition of A (only needed if A is NULL). If a value for A.lower is specified, this means that a relatively opaque but possibly faster method will be used. The time saving ought to be negligible unless <code>nrow(a)</code> (or <code>nrow(b)</code> if supplied), is huge. Note that this option does not test for symmetry of matrix A |


```
test.for.symmetry
```

Boolean, with default TRUE meaning to calculate all element arrays (elegantly), and FALSE meaning to calculate only the upper triangular elements (using loops), which ought to be faster. The value of this argument should not affect the returned value, up to numerical accuracy

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[dists.2frames](#)

Examples

```
data(toys)

dists.2frames(a=D2.toy,A=diag(2))

A <- diag(2) + matrix(0.2,2,2)
A.lower <- t(chol(A))
jj.1 <- dists.2frames(a=D2.toy, A=A, test=TRUE)
jj.2 <- dists.2frames(a=D2.toy, A=A, test=FALSE)

jj.3 <- dists.2frames(a=D2.toy, A.lower=A.lower, test=FALSE)
jj.4 <- dists.2frames(a=D2.toy, A.lower=A.lower, test=TRUE)
```

E.theta.toy

Expectation and variance with respect to theta

Description

Function E.theta.toy returns expectation of $H_1(D)$ with respect to θ ; Edash.theta.toy returns expectation with respect to E' . Function E.theta.toy also returns information about nonlinear behaviour of $h_1(x, \theta)$.

Usage

```
E.theta.toy(D2=NULL, H1=NULL, x1=NULL, x2=NULL, phi, give.mean=TRUE)
Edash.theta.toy(x, t.vec, k, H1, fast.but.opaque=FALSE, a=NULL, b=NULL,
phi=NULL)
```

Arguments

| | |
|-----------------|--|
| D2 | Observation points |
| H1 | Regression function for D1 |
| phi | hyperparameters. Default value of NULL only to be used in Edash.theta.toy() when fast.but.opaque is TRUE |
| x | lat/long point (for Edash.theta.toy) |
| t.vec | Matrix whose rows are parameter values (for Edash.theta.toy) |
| k | Integer specifying column (for Edash.theta.toy) |
| give.mean | In E.theta.toy(), Boolean, with default TRUE meaning to return the mean (expectation), and FALSE meaning to return the “variance” |
| fast.but.opaque | In Edash.theta.toy(), Boolean, with default FALSE meaning to use a slow but clear method. If TRUE, use faster code but parameters a and b must then be specified |
| a | Constant term, needed if fast.but.opaque is TRUE: $(V_\theta^{-1} + 2\Omega_t)^{-1} V_\theta^{-1} m_\theta$. Specifying a in advance saves execution time |
| b | Linear term, needed if fast.but.opaque is TRUE: $2(V_\theta^{-1} + 2\Omega_t)^{-1} \Omega_t$ (multiplied by t[k,] in Edash.theta.toy()). |
| x1 | In E.theta.toy(g=F, . . .), the value of x in $h_1(x, \theta)$. The default value is NULL because in simple cases such as that implemented here, the output is independent of x1 and x2 |
| x2 | In E.theta.toy(g=F, . . .), the value of x in $h_1(x, \theta)$ |

Note

A terse discussion follows; see the calex.pdf vignette and the 1D case study in directory inst/doc/one/dim/ for more details and examples.

Function E.theta.toy(give.mean=FALSE, . . .) does **not** return the variance! The matrix returned is a **different size** from the variance matrix!

It returns the thing that must be added to crossprod(E_theta(h1(x, theta)), t(E_theta(h1(x, theta)))) to give E_theta(h1(x, theta) . t(h1(x, theta))).

In other words, it returns E_theta(h1(x, theta) . t(h1(x, theta))) - crossprod(E_theta(h1(x, theta)), t(E_theta(h1(x, theta))))

If the terms of h1() are of the form c(o, theta) (where o is a vector that is a function of x alone, and independent of theta), then the function will include the variance matrix, in the lower right corner (zeroes elsewhere).

Function E.theta() must be updated if h1.toy() changes: unlike E.theta() and Edash.theta(), it does not “know” where the elements that vary with theta are, nor their (possibly x-dependent) coefficients.

This form of the function requires x_1 and x_2 arguments, for good form's sake, even though the returned value is independent of x in the toy example. To see why it is necessary to include x , consider a simple case with $h_1(x, \theta) = (1, x\theta)^T$. Now $E_\theta(h(x, \theta))$ is just $(1, x\bar{\theta})^T$ but

$$E_\theta(h_1(x, \theta)h_1(x, \theta)^T)$$

is a 2-by-2 matrix (M , say) with $E_\theta(M) = h_1(x, \bar{\theta})h_1(x, \bar{\theta})^T + \text{variance terms}$.

$$E_\theta \begin{pmatrix} 1 & x\theta \\ x\theta & x^2\theta^2 \end{pmatrix}$$

All three functions here are intimately connected to the form of `h1.toy()` and changing it (or indeed `H1.toy()`) will usually require rewriting all three functions documented here. Look at the definition of `E.theta.toy(give=F)`, and you will see that even changing the meat of `h1.toy()` from `c(1, x)` to `c(x, 1)` would require a redefinition of `E.theta.toy(g=F)`.

The only place that `E.theta.toy(g=F)` is used is internally in `hh.fun()`.

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[toys](#)

Examples

```
data(toys)
E.theta.toy(D2=D2.toy,      H1=H1.toy, phi=phi.toy)
E.theta.toy(D2=D2.toy[1,], H1=H1.toy, phi=phi.toy)
E.theta.toy(D2=x.toy,      H1=H1.toy, phi=phi.toy)
Edash.theta.toy(x=x.toy, t.vec=t.vec.toy, k=1, H1=H1.toy, phi=phi.toy)
```

EK.eqn10.supp

*Posterior mean of K***Description**

Estimates the posterior mean of K as per equation 10 of KOH2001S, section 4.2

Usage

```
EK.eqn10.supp(X.dist, D1, D2, H1, H2, d, hbar.fun,
              lower.theta, upper.theta, extractor, give.info=FALSE,
              include.prior=FALSE, phi, ...)
```

Arguments

| | |
|----------------------------|---|
| <code>X.dist</code> | Probability distribution of X, in the form of a two-element list. The first element is the mean (which should have name “mean”), and the second element is the variance matrix, which should be a positive definite matrix of the correct size, and have name “var” |
| <code>D1</code> | Matrix whose rows are the code run points |
| <code>D2</code> | Matrix whose rows are field observation points |
| <code>H1</code> | Regression function for D1 |
| <code>H2</code> | Regression function for D2 |
| <code>d</code> | Vector of code outputs and field observations |
| <code>include.prior</code> | Boolean; passed to function <code>p.eqn8.supp()</code> (qv) |
| <code>hbar.fun</code> | Function that gives expectation (with respect to X) of $h_1(x, \theta)$ and $h_2(x)$ as per section 4.2 |
| <code>lower.theta</code> | Lower integration limit for theta (NB: a vector) |
| <code>upper.theta</code> | Upper integration limit for theta (NB: a vector) |
| <code>extractor</code> | Extractor function; see <code>extractor.toy()</code> for an example |
| <code>give.info</code> | Boolean, with default FALSE meaning to return just the answer and TRUE to return the answer along with all output from both integrations as performed by <code>adaptIntegrate()</code> |
| <code>phi</code> | Hyperparameters |
| <code>...</code> | Extra arguments passed to the integration function. If multidimensional (ie <code>length(theta)>1</code>), then the arguments are passed to <code>adaptIntegrate()</code> ; if one dimensional, they are passed to <code>integrate()</code> |

Details

This function evaluates a numerical approximation to equation 10 of section 4.2 of the supplement. Equation 10 integrates over the prior distribution of theta. If theta is a vector, multidimensional integration is necessary.

In the case of multidimensional integration, function `adaptIntegrate()` is used.

In the case of one dimensional integration—theta being a scalar—function `integrate()` of the stats package is used.

Note that equation 10 is conditional on the observed data **and** the hyperparameters

Value

Returns a scalar

Note

The function was not reviewed by the Journal of Statistical Software.

The package formerly used `adapt` package, but this is no longer available on CRAN. The package now uses the `cubature` package.

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O’Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O’Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/cal-sup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

Examples

```
1+1
## Not run:
# Not run because it takes R CMD check too long

data(toys)
EK.eqn10.supp(X.dist=X.dist.toy, D1=D1.toy, D2=D2.toy,
             H1=H1.toy, H2=H2.toy, d=d.toy,
             hbar.fun=hbar.fun.toy, lower.theta=c(-3,-3,-3),
             upper.theta=c(3,3,3), extractor=extractor.toy,
             phi=phi.toy)

## End(Not run)
```

 etahat

Expectation of computer output

Description

Returns the aposteriori expectation of the computer program at a particular point with a particular set of parameters, given the code output.

Usage

```
etahat(D1, D2, H1, y, E.theta, extractor, phi)
```

Arguments

| | |
|-----------|--|
| D1 | Matrix of code observation points and parameters |
| D2 | Matrix of field observation points |
| H1 | Basis functions |
| y | Code observations corresponding to rows of D1 |
| E.theta | expectation wrt theta; see details |
| extractor | Extractor function |
| theta | Parameters |
| phi | Hyperparameters |

Details

Argument E.theta is officially a function that, given x,y returns $E_{\theta}(h_1(x, \theta))$.

However, if supplied a non-function (this is tested by `is.function()` in the code), E.theta is interpreted as values of θ to use. Recycling is carried out by function `D1.fun()`

Author(s)

Robin K. S. Hankin

References

M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464

M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>

R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also[p.page4](#)**Examples**

```

data(toys)

etahat(D1=D1.toy, D2=D2.toy, H1=H1.toy, y=y.toy,
       E.theta=E.theta.toy, extractor=extractor.toy, phi=phi.toy)

# Now try giving E.theta=1:3, which will be interpreted as a value for theta:
etahat(D1=D1.toy, D2=D2.toy, H1=H1.toy, y=y.toy, E.theta=1:3,
       extractor=extractor.toy, phi=phi.toy)

```

| | |
|---------------|---|
| extractor.toy | <i>Extracts lat/long matrix and theta matrix from D2.</i> |
|---------------|---|

Description

Extracts `x.star.toy` and `t.vec.toy` from `D2`; toy example needed because the extraction differs from case to case.

Usage

```
extractor.toy(D1)
```

Arguments

`D1` Matrix of code run points

Details

The first two columns give the elements of `x.star` and columns 3 through 5 give the elements of `t.vec`.

Function `extractor.toy` is the inverse of function `D1.fun`, in the sense that `extractor.toy` splits up `D1` into `x.star` and `t.vec`, while `D1.fun` joins them up again

Value

Returns a list with two elements:

| | |
|---------------------|---|
| <code>x.star</code> | A matrix containing the lat/longs of the code run points |
| <code>t.vec</code> | A matrix containing the parameters used for the code runs |

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[toys](#), [D1.fun](#)

Examples

```
data(toys)
extractor.toy(D1.toy)
extractor.toy(D1.toy[1, ,drop=FALSE])
(jj <- extractor.toy(D1.fun(x.star=x.toy , t.vec=theta.toy)))
D1.fun(jj$x.star , jj$t.vec)
```

Ez.eqn7.supp

Expectation of z given y, beta2, phi

Description

Expectation as per equation 7 on the supplement

Usage

```
Ez.eqn7.supp(z, D1, H1, D2, H2, extractor, beta2, y, E.theta, phi)
```

Arguments

| | |
|-----------|--|
| z | Vector of observations |
| D1 | Matrix whose rows are code run points |
| H1 | Regressor basis functions |
| D2 | Matrix whose rows are observation points |
| H2 | Regressor basis functions |
| extractor | Function to split D1 |
| beta2 | coefficients |
| y | Code outputs at points corresponding to rows of D1 |
| E.theta | Expectation function to use |
| phi | hyperparameters |

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[V.fun](#)

Examples

```
data(toys)
etahat.d2 <- etahat(D1=D1.toy, D2=D2.toy, H1=H1.toy, y=y.toy,
  E.theta=E.theta.toy, extractor=extractor.toy, phi=phi.toy)
beta2 <- beta2hat.fun(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy, V=V.toy, z=z.toy,
  etahat.d2=etahat.d2, extractor=extractor.toy, E.theta=E.theta.toy,
  Edash.theta=Edash.theta.toy, phi=phi.toy)
Ez.eqn7.supp(z=z.toy,
  D1=D1.toy, H1=H1.toy, D2=D2.toy, H2=H2.toy,
  extractor=extractor.toy, beta2=beta2, y=y.toy,
  E.theta=E.theta.toy,
  phi=phi.toy)
```

Ez.eqn9.supp

Expectation as per equation 10 of KOH2001

Description

Expectation as per equation 10 of KOH2001 (not the supplement)

Usage

```
Ez.eqn9.supp(x, theta, d, D1, D2, H1, H2, phi)
Ez.eqn9.supp.vector(x, theta, d, D1, D2, H1, H2, phi)
```

Arguments

| | |
|-------|--------------------------------------|
| x | point at which expectation is needed |
| theta | parameters |
| d | observations and code outputs |
| D1 | code run points |
| D2 | observation points |
| H1 | regression function for D1 |
| H2 | regression function for D2 |
| phi | hyperparameters |

Details

The user should always use `Ez.eqn9.supp()`, which is a wrapper for `Ez.eqn9.supp.vector()`. The forms differ in their treatment of θ . In the former, θ must be a vector; in the latter, θ may be a matrix, in which case `Ez.eqn9.supp.vector()` is applied to the rows.

Note that `Ez.eqn9.supp.vector()` is vectorized in `x` but not θ (if given a multi-row object, `apply(theta, 1, ...)` is used to evaluate the function for each row supplied).

Function `Ez.eqn9.supp()` will take multiple-row arguments for `x` and `theta`. The output will be a matrix, with rows corresponding to the rows of `x` and columns corresponding to the rows of `theta`. See the third example below.

Note that function `Ez.eqn9.supp()` determines whether there are multiple values of θ by `is.vector(theta)`. If this returns TRUE, it is assumed that θ is a single point in multidimensional parameter space; if FALSE, it is assumed to be a matrix whose rows correspond to points in parameter space.

So if θ is one dimensional, calling `Ez.eqn9.supp()` with a vector-valued θ will fail because the function will assume that θ is a single, multidimensional, point. To get round this, use `as.matrix(theta)`, which is not a vector; the rows are the (1D) parameter values.

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calSUP.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[tee](#)

Examples

```

data(toys)
Ez.eqn9.supp(x=x.toy, theta=theta.toy, d=d.toy, D1=D1.toy,
             D2=D2.toy, H1=H1.toy,H2=H2.toy, phi=phi.toy)

Ez.eqn9.supp(x=D2.toy, theta=t.vec.toy, d=d.toy, D1=D1.toy,
             D2=D2.toy, H1=H1.toy,H2=H2.toy, phi=phi.toy)

Ez.eqn9.supp(x=x.vec, theta=t.vec.toy, d=d.toy, D1=D1.toy,
             D2=D2.toy, H1=H1.toy,H2=H2.toy, phi=phi.toy)

```

H.fun

*H function***Description**

H. See front page of KOHsupp.

Usage

```
H.fun(theta, D1, D2, H1, H2, phi)
```

Arguments

| | |
|-------|------------------------------|
| theta | parameters |
| D1 | matrix of code run points |
| D2 | matrix of observation points |
| H1 | Regressor function for D1 |
| H2 | Regressor function for D2 |
| phi | hyperparameters |

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/cal-sup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

Examples

```

data(toys)
H.fun(theta=theta.toy, D1=D1.toy, D2=D2.toy, H1=H1.toy,
      H2=H2.toy, phi=phi.toy)

H.fun(theta=theta.toy, D1=D1.toy[1,,drop=FALSE], D2=D2.toy,
      H1=H1.toy, H2=H2.toy, phi=phi.toy)

H.fun(theta=theta.toy, D1=D1.toy[1,,drop=FALSE],
      D2=D2.toy[1,,drop=FALSE],
      H1=H1.toy, H2=H2.toy, phi=phi.toy)

```

H1.toy

Basis functions for D1 and D2

Description

Applies basis functions to rows of D1 and D2

Usage

```

H1.toy(D1)
H2.toy(D2)

```

Arguments

| | |
|----|------------------------------|
| D1 | Matrix of code run points |
| D2 | Matrix of observation points |

Value

Returns a matrix whose rows are the basis functions of the code run points or observation points. Function `H1.toy()` operates on datasets like `D1.toy` (latlong and parameters) and function `H2.toy()` operates on datasets like `D2.toy` (latlong only)

Note

See package **goldstein** for a less trivial example of `h()`.

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[D1.toy](#),

Examples

```
data(toys)
jj <- extractor.toy(D1.toy)
x.star.toy <- jj$x.star
t.vec.toy <- jj$t.vec

H1.toy(D1=D1.toy)
H1.toy(D1.toy[1,,drop=FALSE])
H1.toy(D1.fun(x.star.toy , theta.toy)[1,,drop=FALSE])
H1.toy(D1.fun(x.star=x.toy,t.vec=theta.toy))
H1.toy(D1.fun(x.star=x.star.toy[1,],t.vec=t.vec.toy[1,]))
H1.toy(D1.fun(x.star=x.star.toy[1,],t.vec=t.vec.toy[1:2,]))

H2.toy(D2.toy)
H2.toy(t(x.toy))
```

h1.toy

Basis functions

Description

Basis functions for D1 and D2 respectively.

Usage

```
h1.toy(x)
h2.toy(x)
```

Arguments

x Vector of lat/long or lat/long and theta

Details

Note that `h1()` operates on a vector: for dataframes, use `H1.toy()` which is a wrapper for `apply(D1, 1, h1)`.

NB If the definition of `h1.toy()` or `h2.toy()` is changed, then function `hbar.toy()` must be changed to match. This cannot be done automatically, as the form of `hbar.toy()` depends on the distribution of X . The shibboleth is whether $E_X()$ commutes with `h_1()`; it does in this case but does not in general (for example, consider $h(x, \theta) = c(1, x, x^2)$ and $X \sim N(m, V)$. Then $E_X(h(x, \theta))$ will be $(1, m, m^2 + V, \theta)$; note the V)

Value

Returns basis functions of a vector; in the toy case, just prepend a 1.

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/cal-sup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[H1.toy](#)

Examples

```
data(toys)
h1.toy(D1.toy[1,])
```

`hbar.fun.toy`

Toy example of hbar (section 4.2)

Description

A toy example of the expectation of h as per section 4.2

Usage

```
hbar.fun.toy(theta, X.dist, phi)
```

Arguments

| | |
|--------|--|
| theta | Parameter set |
| X.dist | Distribution of variable inputs X as per section 4.2 |
| phi | Hyperparameters |

Details

Note that if `h1.toy()` or `h2.toy()` change, then `hbar.fun.toy()` will have to change too; see `?h1.toy` for an example in which nonlinearity changes the form of `E.theta.toy()`

Value

Returns a vector as per section 4.2 of KOH2001S

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/cal-sup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[h1.toy](#)

Examples

```
data(toys)
hbar.fun.toy(theta=theta.toy, X.dist=X.dist.toy, phi=phi.toy)
```

is.positive.definite *Is a matrix positive definite?*

Description

Returns TRUE if and only if a matrix is positive definite.

Usage

```
is.positive.definite(a, ...)
```

Arguments

a Matrix to be tested
 ... Extra arguments passed to `eigen()`, such as `symmetric`.

Details

A wrapper for `eigen()` (a matrix is positive definite if all its eigenvalues are positive). This function is included for convenience only.

Author(s)

Robin K. S. Hankin

Examples

```
is.positive.definite(diag(3),sym=TRUE)
is.positive.definite(diag(6)-0.1)
```

 MH

Very basic implementation of the Metropolis-Hastings algorithm

Description

Very basic implementation of the Metropolis-Hastings algorithm using a multivariate Gaussian proposal distribution. Useful for sampling from `p.eqn8.supp()`.

Usage

```
MH(n, start, sigma, pi)
```

Arguments

n Number of samples to take
 start Start value
 sigma Variance matrix for kernel
 pi Functional proportional to the desired sampling pdf

Details

This is a **basic** implementation. The proposal distribution $q(X|Y)$ is $q(\cdot|X) = N(X, \sigma^2)$

Value

Returns a matrix whose rows are samples from $\pi()$. Note that the first few rows will be “burn-in”, so should be ignored

Note

This function is a little slow because it is not vectorized.

Author(s)

Robin K. S. Hankin

References

- W. R. Gilks et al 1996. *Markov Chain Monte Carlo in practice*. Chapman and Hall, 1996. ISBN 0-412-05551-1
- N. Metropolis and others 1953. *Equation of state calculations by fast computing machines*. The Journal of Chemical Physics, volume 21, number 6, pages 1087-1092

See Also

[p.eqn8.supp](#)

Examples

```
# First, a bivariate Gaussian:
A <- diag(3) + 0.7
quad.form <- function(M,x){drop(crossprod(crossprod(M,x),x))}
pi.gaussian <- function(x){exp(-quad.form(A/2,x))}
x.gauss <- MH(n=1000, start=c(0,0,0),sigma=diag(3),pi=pi.gaussian)
cov(x.gauss)/solve(A) # Should be a matrix of 1s.

# Now something a bit weirder:
pi.triangle <- function(x){
  1*as.numeric( (abs(x[1])<1.0) & (abs(x[2])<1.0) ) +
  5*as.numeric( (abs(x[1])<0.5) & (abs(x[2])<0.5) ) *
  as.numeric(x[1]>x[2])
}
x.tri <- MH(n=100,start=c(0,0),sigma=diag(2),pi=pi.triangle)
plot(x.tri,main="Try with a higher n")

# Now a Gaussian mixture model:
pi.2gauss <- function(x){
  exp(-quad.form(A/2,x)) +
  exp(-quad.form(A/2,x+c(2,2,2)))
}
x.2 <- MH(n=100,start=c(0,0,0),sigma=diag(3),pi=pi.2gauss)
## Not run: p3d(x.2, theta=44,d=1e4,d0=1,main="Try with more points")
```

p.eqn4.supp

Apostiori probability of ψ_1

Description

Gives the probability of ψ_1 , given observations. Equation 4 of the supplement

Usage

```
p.eqn4.supp(D1, y, H1, include.prior=TRUE, lognormally.distributed, return.log, phi)
```

Arguments

| | |
|-------------------------|---|
| D1 | Matrix of code run points |
| y | Vector of code outputs |
| H1 | Regression function |
| include.prior | Boolean with default TRUE meaning to return the likelihood multiplied by the aprior probability and FALSE meaning to return the likelihood without the prior. |
| lognormally.distributed | Boolean; see ?prob.theta for details |
| return.log | Boolean, with default FALSE meaning to return the probability and TRUE meaning to return the logarithm of the probability |
| phi | hyperparameters |

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

W1

Examples

```
data(toys)
p.eqn4.supp(D1=D1.toy, y=y.toy, H1=H1.toy, lognormally.distributed=TRUE,
phi=phi.toy)
```

p.eqn8.supp

A posteriori probability of hyperparameters

Description

Function to determine the a-posteriori probability of hyperparameters ρ , λ and ψ_2 , given observations and ψ_1 .

Usage

```
p.eqn8.supp(theta, D1, D2, H1, H2, d, include.prior=FALSE,
lognormally.distributed=FALSE, return.log=FALSE, phi)
p.eqn8.supp.vector(theta, D1, D2, H1, H2, d, include.prior=FALSE,
lognormally.distributed=FALSE, return.log=FALSE, phi)
```

Arguments

| | |
|-------------------------|--|
| theta | Parameters |
| D1 | Matrix of code run points |
| D2 | Matrix of observation points |
| H1 | Regression function for D1 |
| H2 | Regression function for D2 |
| d | Vector of code output values and observations |
| include.prior | Boolean, with TRUE meaning to include the prior PDF for θ and default FALSE meaning return the likelihood, multiplied by an undetermined constant |
| lognormally.distributed | Boolean, with TRUE meaning to assume prior is lognormal (see prob. theta() for more info) |
| return.log | Boolean, with default FALSE meaning to return the probability; TRUE means to return the (natural) logarithm of the answer |
| phi | Hyperparameters |

Details

The user should always use `p.eqn8.supp()`, which is a wrapper for `p.eqn8.supp.vector()`. The forms differ in their treatment of θ . In the former, θ must be a vector; in the latter, θ may be a matrix, in which case `p.eqn8.supp.vector()` is applied to the rows

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O’Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O’Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[W2,stage1](#)

Examples

```
data(toys)
p.eqn8.supp(theta=theta.toy, D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy,
d=d.toy, phi=phi.toy)

## Now try using the true hyperparameters, and data directly drawn from
## the appropriate multivariate distn:

phi.true <- phi.true.toy(phi=phi.toy)
jj <- create.new.toy.datasets(D1.toy , D2.toy)
d.toy <- jj$d.toy
p.eqn8.supp(theta=theta.toy, D1=D1.toy, D2=D2.toy, H1=H1.toy,
H2=H2.toy, d=d.toy, phi=phi.true)

## Now try p.eqn8.supp() with a vector of possible thetas:
p.eqn8.supp(theta=sample.theta(n=11,phi=phi.true), D1=D1.toy,
D2=D2.toy, H1=H1.toy, H2=H2.toy, d=d.toy, phi=phi.true)
```

p.page4

A posteriori probability of hyperparameters

Description

Function to determine a posteriori probability of hyperparameters ρ , λ and ψ_2 , given observations and ψ_1 .

Usage

```
p.page4(D1, D2, H1, H2, V, y, z, E.theta, Edash.theta, extractor, include.prior=FALSE,
lognormally.distributed=FALSE, return.log=FALSE, phi)
```

Arguments

| | |
|-------------------------|--|
| D1 | Matrix of code run points |
| D2 | Matrix of observation points |
| H1 | Basis function (vectorized) |
| H2 | Regression function for D2 |
| V | Covariance matrix; default value of NULL results in the function evaluating it (but this takes a long time, so supply V if known) |
| y | Vector of code outputs |
| z | Vector of observation values |
| E.theta | Expectation over theta |
| Edash.theta | Expectation over theta WRT E' |
| extractor | Function to extract independent variables and parameters from D1 |
| include.prior | Boolean, with TRUE meaning to include the prior PDF for θ and default value of FALSE meaning to return the likelihood multiplied by an undetermined constant |
| lognormally.distributed | Boolean with TRUE meaning to assume lognormality. See prob.psi1 for details |
| return.log | Boolean, with default FALSE meaning to return the probability, and TRUE meaning to return the (natural) logarithm of the probability (which is useful when considering very small probabilities) |
| phi | Hyperparameters |

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/cal-sup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[W2](#)

Examples

```

data(toys)

p.page4(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy, V=NULL, y=y.toy,
z=z.toy, E.theta=E.theta.toy, Edash.theta=Edash.theta.toy, extractor=extractor.toy, phi=phi.toy)

## Now compare the above value with p.page4() calculated with phi
## differing only in psi2:

phi.toy.new <- phi.change(phi.fun=phi.fun.toy, old.phi = phi.toy, psi2=c(8,8,8))

p.page4(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy, V=V.toy, y=y.toy, z=z.toy,
E.theta=E.theta.toy, Edash.theta=Edash.theta.toy,
extractor=extractor.toy, phi=phi.toy.new)
## different!

```

phi.fun.toy

Functions to create or change hyperparameters

Description

Function to create (phi.fun.toy) or modify (phi.change) toy hyperparameters ϕ in a form suitable for passing to the other functions in the library.

The user should never make ϕ by hand; always use one of these functions

Usage

```

phi.fun.toy(rho, lambda, psi1, psi1.apriori, psi2, psi2.apriori,
theta.apriori)
phi.change(phi.fun, old.phi = NULL, rho = NULL, lambda = NULL,
psi1 = NULL, psi1.apriori=NULL, psi1.apriori.mean=NULL,
psi1.apriori.sigma=NULL, psi2 = NULL, psi2.apriori=NULL,
psi2.apriori.mean=NULL, psi2.apriori.sigma=NULL,
theta.apriori=NULL, theta.apriori.mean=NULL,
theta.apriori.sigma=NULL)

```

Arguments

| | |
|---------|---|
| phi.fun | In phi.change(), the name of the function that creates the hyperparameters. Use phi.fun.toy() for the toy dataset |
| old.phi | In function phi.change(), the hyperparameter object ϕ to be modified |
| rho | Correlation hyperparameter appearing in main equation |
| lambda | Noise hyperparameter |

| | |
|---------------------|--|
| psi1 | Roughness lengths hyperparameter for design matrix D1. Internal function <code>pdm.maker.psi1()</code> takes <code>psi1</code> as an argument and returns <code>omega_x</code> , <code>omega_t</code> and <code>sigma1squared</code> . Recall that Ω_x and Ω_t are arbitrary functions of ψ_1 . In this case, the values are <code>omega_x=psi1[1:2]</code> , <code>omega_t=psi1[3:4]</code> and <code>sigma1squared=psi1[6]</code> |
| psi1.apriori | A priori PDF for ψ_1 . In the form of a two element list with first element (mean) the mean and second element (sigma) the covariance matrix; distribution of the logarithms is assumed to be multivariate normal. In the toy example, the mean is a vector of length six (the first five are ψ_1 and the sixth is for σ_1^2), and the variance is the corresponding six-by-six matrix. Use function <code>prob.psi1()</code> to calculate the apriori probability density for a particular value of ψ_1 |
| psi1.apriori.mean | In function <code>phi.change.toy()</code> , use this argument to change just the mean of <code>psi1</code> (and leave the value of <code>sigma</code> unchanged) |
| psi1.apriori.sigma | In function <code>phi.change.toy()</code> , use this argument to change just the variance matrix of <code>psi1</code> |
| psi2 | Roughness lengths hyperparameter for D2. Internal function <code>pdm.maker.psi2()</code> takes <code>psi2</code> as an argument and returns <code>omegastar_x</code> and <code>sigma2squared</code> . In <code>phi.fun.toy()</code> , the values are <code>omegastar_x=psi2[1:2]</code> and <code>sigma2squared=psi2[3]</code> . NB: function <code>stage2()</code> optimizes more than just <code>psi2</code> . It simultaneously optimizes <code>psi2</code> and <code>lambda</code> and <code>rho</code> |
| psi2.apriori | A priori PDF for ψ_2 and hyperparameters ρ and λ (in that order). As for <code>psi1.apriori</code> , this is in the form of a list with the first element (mean) the mean and second element (sigma) the covariance matrix; the logs are multivariate normal. In the toy example, the mean is a vector of length five. The first and second elements of the mean are the apriori mean of ρ and λ respectively; the third and fourth elements are the apriori mean of ψ_2 (that is, x and y respectively); and the fifth is the mean of σ_2^2 . The second element of <code>phi.toy\$psi2.apriori</code> , <code>sigma</code> , is the corresponding four-by-four variance matrix. Use function <code>prob.psi2()</code> to calculate the apriori probability density of a particular value of ψ_2 |
| psi2.apriori.mean | In <code>phi.change.toy()</code> , use to change just the mean of <code>psi2</code> |
| psi2.apriori.sigma | In <code>phi.change.toy()</code> , use to change just the variance matrix of <code>psi2</code> |
| theta.apriori | Apriori PDF for θ . As above, in the form of a list with elements for the mean and covariance. The distribution is multivariate normal (NB: The distribution is multivariate normal and NOT lognormal! To be explicit: $\log(\theta)$ is lognormally distributed). Use function <code>prob.theta()</code> to calculate the apriori probability density of a particular value of θ |
| theta.apriori.mean | In <code>phi.change.toy()</code> , use to change just the mean of <code>theta</code> |
| theta.apriori.sigma | In <code>phi.change.toy()</code> , use to change just the variance matrix of <code>theta</code> |

Details

Note that this toy function contains within itself `pdm.maker.toy()` which extracts `omega_x` and `omega_t` and `sigma1squared` from `psi1`. This will need to be changed for real-world applications.

Earlier versions of the package had `pdm.maker.toy()` defined separately.

Value

Returns a list of several elements:

| | |
|----------------------------|--|
| <code>rho</code> | Correlation hyperparameter |
| <code>lambda</code> | Noise hyperparameter |
| <code>psi1</code> | Roughness lengths hyperparameter for D1 |
| <code>psi1.apriori</code> | Apriori mean and variance matrix for <code>psi1</code> |
| <code>psi2</code> | Roughness lengths hyperparameter for D2 |
| <code>psi2.apriori</code> | Apriori mean and variance matrix for <code>psi2</code> |
| <code>theta.apriori</code> | Apriori mean and variance matrix for the parameters |
| <code>omega_x</code> | Positive definite matrix for the lat/long part of D1, whose diagonal is <code>psi1[1:2]</code> |
| <code>omega_t</code> | Positive definite matrix for the code parameters <code>theta</code> , whose diagonal is <code>psi1[3:5]</code> |
| <code>omegastar_x</code> | Positive definite matrix for use in equation 13 of the supplement; represents distances between rows of D2 |
| <code>sigma1squared</code> | variance |
| <code>sigma2squared</code> | variance |
| <code>omega_x.upper</code> | Upper triangular Cholesky decomposition for <code>omega_x</code> |
| <code>omega_x.lower</code> | Lower triangular Cholesky decomposition for <code>omega_x</code> |
| <code>omega_t.upper</code> | Upper triangular Cholesky decomposition for <code>omega_t</code> |
| <code>omega_t.lower</code> | Lower triangular Cholesky decomposition for <code>omega_t</code> |
| <code>a</code> | Precalculated matrix for use in <code>Edash.theta(..., fast.but.opaque=TRUE)</code> |
| <code>b</code> | Precalculated matrix for use in <code>Edash.theta(..., fast.but.opaque=TRUE)</code> |
| <code>c</code> | Precalculated scalar for use in <code>ht.fun(..., fast.but.opaque=TRUE)</code> |
| <code>A</code> | Precalculated scalar for use in <code>tt.fun()</code> |
| <code>A.upper</code> | Upper triangular Cholesky decomposition for <code>A</code> |
| <code>A.lower</code> | Lower triangular Cholesky decomposition for <code>A</code> |

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[toys](#), [H1.toy](#)

Examples

```
phi.fun.toy(100,101,1:6,list(mean=rep(1,6),sigma=1+diag(6)),50:55,
list(mean=rep(0,4),sigma=0.1+diag(4)),
list(mean=0.1+(1:3),sigma=2.1+diag(3)))

phi.fun.toy(rho=1, lambda=1,
  psi1 = structure(c(1.1, 1.2, 1.3, 1.4, 1.5, 0.7),
    .Names = c("x", "y", "A", "B", "C", "s1sq")),
  psi1.apriori = list(
    mean=rep(0,6), sigma=0.4+diag(6)),
  psi2=structure(c(2.1, 2.2), .Names = c("x", "y")),
  psi2.apriori = list(mean=rep(0,5),sigma=0.2+diag(5)),
  theta.apriori = list(mean=0.1+(1:3),sigma=2.1+diag(3))
)

data(toys)
phi.change(phi.fun=phi.fun.toy, old.phi = phi.toy, rho = 100)
phi.change(phi.fun=phi.fun.toy, old.phi = phi.toy,
  theta.apriori.sigma = 4*diag(3))

identical(phi.toy, phi.change(phi.fun=phi.fun.toy, old.phi=phi.toy))
```

prob.psi1

A priori probability of psi1, psi2, and theta

Description

Function to determine the a-priori probability of ψ_1 and ψ_2 of the hyperparameters, and θ , given the apriori means and standard deviations.

Function `sample.theta()` samples θ from its prior distribution.

Usage

```

prob.psi1(phi, lognormally.distributed=TRUE)
prob.psi2(phi, lognormally.distributed=TRUE)
prob.theta(theta, phi, lognormally.distributed=FALSE)
sample.theta(n=1, phi)

```

Arguments

| | |
|-------------------------|---|
| phi | Hyperparameters |
| theta | Parameters |
| lognormally.distributed | Boolean variable with FALSE meaning to assume a Gaussian distribution and TRUE meaning to use a lognormal distribution. |
| n | In function <code>sample.theta()</code> , the number of observations to take |

Details

These functions use package `mvtnorm` to calculate the probability density under the assumption that the PDF is lognormal. One implication would be that `phi$psi2.apriori$mean` and `phi$psi1.apriori$mean` are the means of the **logarithms** of the elements of `psi1` and `psi2` (which are thus assumed to be positive). The sigma matrix is the covariance matrix of the logarithms as well.

In these functions, interpretation of argument `phi` depends on the value of Boolean argument `lognormally.distributed`. Take `prob.theta()` as an example. If `lognormally.distributed` is TRUE, then `log(theta)` is normally distributed with mean `phi$theta.apriori$mean` and variance `phi$theta.apriori$sigma`. If FALSE, `theta` is normally distributed with mean `phi$theta.apriori$mean` and variance `phi$theta.apriori$sigma`.

Interpretation of `phi$theta.apriori$mean` depends on the value of `lognormally.distributed`: if TRUE it is the expected value of `log(theta)`; if FALSE, it is the expectation of `theta`.

The reason that `prob.theta` has a different default value for `lognormally.distributed` is that some elements of `theta` might be negative, contraindicating a lognormal distribution

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/cal-sup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[p.eqn4.supp](#), [stage1](#), [p.eqn8.supp](#)

Examples

```
data(toys)
prob.psi1(phi=phi.toy)
prob.psi2(phi=phi.toy)

prob.theta(theta=theta.toy,phi=phi.toy)

sample.theta(n=4,phi=phi.toy)
```

reality

Reality

Description

Function to compute reality, gratis *deus ex machina*. Includes a simple computer model that substitutes for a complex climate model, and a simple function that substitutes for the base system, in this case the climate.

Usage

```
model.inadequacy(X, set.seed.to.zero=TRUE, draw.from.prior=FALSE,
  export.true.hyperparameters=FALSE,phi=NULL)
computer.model(X, params=NULL, set.seed.to.zero=TRUE,
  draw.from.prior=FALSE, export.true.hyperparameters=FALSE,phi=NULL)
phi.true.toy(phi)
```

Arguments

| | |
|-----------------------------|--|
| X | Observation point |
| params | Parameters needed by <code>computer.model()</code> |
| set.seed.to.zero | Boolean, with the default value of TRUE meaning to set the RNG seed to zero |
| draw.from.prior | Boolean, with default FALSE meaning to generate observations from the “true” values of the parameters, and TRUE meaning to draw from the relevant apriori distribution. |
| export.true.hyperparameters | Boolean, with default value of FALSE meaning to return the observed scalar. Set to TRUE to exercise omniscience and access the <i>true</i> values of the parameters and hyperparameters. Only the omnipotent should set this variable, and only the omniscient may see its true value. |

`phi` In function `phi.true.toy()` the hyperparameters ϕ . Note that apriori distributions are unchanged (they are irrelevant to omniscient beings).
 In functions `reality()` and `computer.model()`, the prior distributions of the hyperparameters is passed via `phi` (so it only elements `psi1.apriori` and `psi2.apriori` need to be set).

Details

Function `reality()` provides *the* scalar value observed at a point x . Evaluation expense is zero; there is no overhead.

(However, it does not compute “reality”: the function returns a value subject to observational error $N(0, \lambda)$ as per equation 5. It might be better to call this function `observation()`)

Function `computer.model()` returns the output of a simple, nonlinear computer model.

Both functions documented here return a random variable drawn from an appropriate (correlated) multivariate Gaussian distribution, and are thus Gaussian processes.

The approach is more explicit in the help pages of the emulator package. There, Gaussian processes are generated by directly invoking `rmvnorm()` with a suitable correlation matrix

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O’Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O’Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[computer.model](#)

Examples

```
data(toys)
```

```
computer.model(X=D2.toy, params=theta.toy)
computer.model(D1.toy)
computer.model(X=x.toy, params=extractor.toy(D1.toy)$t.vec)
```

```
phi.fix <- phi.change(old.phi=phi.toy,
```

```

    psi1=c(1, 0.5, 1, 1, 0.5, 0.4),phi.fun=phi.fun.toy)
#The values come from c(REAL.SCALES,REAL.SIGMA1SQUARED) as
#seen in the sourcecode for computer.model().

computer.model(D1.toy) # use debug(computer.model) and examine
                      # var.matrix directly. It should match the
                      # output from V1():

    # first fix phi so that it has the correct values for psi1 (see the
    # section on psi1 in ?phi.fun.toy for how to get this):

phi.fix <- phi.change(old.phi=phi.toy,psi1=c(1, 0.5, 1.0, 1.0, 0.5,
0.4), phi.fun=phi.fun.toy)
V1(D1.toy,phi=phi.fix)

# What are the hyperparameters that were used to create reality?
phi.true.toy(phi=phi.toy)

#
computer.model(X=D2.toy,params=theta.toy,draw.from.prior=TRUE,phi=phi.toy)

```

stage1

Stage 1,2 and 3 optimization on toy dataset

Description

Perform O'Hagan's three stage optimization on the toy dataset. Function `stage1()` and `stage2()` find the optimal values for the hyperparameters and `stage3()` finds the optimal values for the three parameters.

Usage

```

stage1(D1, y, H1, maxit, trace=100, method="Nelder-Mead",
       directory = ".", do.filewrite=FALSE, do.print=TRUE,
       phi.fun, lognormally.distributed=FALSE, include.prior=TRUE, phi)
stage2(D1, D2, H1, H2, y, z, maxit, trace=100, method = "Nelder-Mead",
       directory = ".", do.filewrite=FALSE, do.print=TRUE, extractor,
       phi.fun, E.theta, Edash.theta, isotropic=FALSE,
       lognormally.distributed = FALSE, include.prior = TRUE,
       use.stdin = FALSE, rho.eq.1 = TRUE, phi)
stage3(D1, D2, H1, H2, d, maxit, trace=100, method="Nelder-Mead",
       directory = ".", do.filewrite=FALSE, do.print=TRUE,

```

```
include.prior = TRUE, lognormally.distributed=FALSE,
theta.start=NULL, phi)
```

Arguments

| | |
|--------------------------------------|---|
| <code>maxit</code> | Maximum number of iterations as passed to <code>optim()</code> |
| <code>trace</code> | Amount of information displayed, as passed to <code>optim()</code> |
| <code>D1</code> | Matrix whose rows are points at which code output is known |
| <code>D2</code> | Matrix whose rows are points at which observations were made |
| <code>H1,H2</code> | Regressor basis functions for <code>D1</code> and <code>D2</code> |
| <code>y</code> | Code outputs. Toy example is <code>y.toy</code> |
| <code>z</code> | Observations. Toy example is <code>z.toy</code> |
| <code>d</code> | Data vector consisting of the code runs and observations |
| <code>extractor</code> | extractor function for <code>D1</code> |
| <code>E.theta,Edash.theta</code> | Expectation WRT <code>theta</code> , and dashed <code>theta</code> . Toy examples are <code>E.theta.toy()</code> and <code>Edash.theta.toy()</code> |
| <code>phi.fun</code> | Function to create hyperparameters; passed (in <code>stage1()</code> and <code>stage2()</code>) to <code>phi.change()</code> . Toy version is <code>phi.fun.toy()</code> |
| <code>method</code> | Method argument passed to <code>optim()</code> ; <code>qv</code> |
| <code>include.prior</code> | Boolean variable with default <code>TRUE</code> meaning to include the prior distribution in the optimization process and <code>FALSE</code> meaning to use an uninformative prior (effectively uniform support). This variable is passed to <code>p.eqn4.supp()</code> for <code>stage1()</code> , <code>p.page4()</code> for <code>stage2()</code> , and <code>p.eqn8.supp()</code> for <code>stage3()</code> |
| <code>lognormally.distributed</code> | Boolean with <code>TRUE</code> meaning to use a lognormal distn. See <code>prob.theta</code> for details |
| <code>do.filewrite</code> | Boolean, with <code>TRUE</code> meaning to save a loadable file <code>stage[123].<date></code> , containing the interim value of <code>phi</code> and the corresponding optimand to <code>directory</code> at each evaluation of the optimizer. If <code>FALSE</code> , don't write the files |
| <code>directory</code> | The directory to write files to; only matters if <code>do.filewrite</code> is <code>TRUE</code> |
| <code>isotropic</code> | In function <code>stage2()</code> , Boolean with default <code>FALSE</code> meaning to carry out a full optimization, and <code>TRUE</code> meaning to restrict the scope to isotropic roughness matrices. See details section below |
| <code>do.print</code> | Boolean, with default <code>TRUE</code> meaning to print interim values of <code>phi</code> at each evaluation |
| <code>use.standin</code> | In <code>stage2()</code> , a Boolean argument, with default <code>FALSE</code> meaning to use the real value for matrix <code>V.temp</code> , and <code>TRUE</code> meaning to use a standing that is the same size but contains fictitious values. The only time to set <code>use.standin</code> to <code>TRUE</code> is when debugging as it runs several orders of magnitude faster |
| <code>rho.eq.1</code> | Boolean, with default <code>TRUE</code> meaning to hold the value of <code>rho</code> constant at one (1) |
| <code>theta.start</code> | In <code>stage3()</code> , the starting point of the optimization with default <code>NULL</code> meaning to use the maximum likelihood point of the apriori distribution (ie <code>phi\$theta.apriori\$mean</code>) |
| <code>phi</code> | Hyperparameters. Used as initial values for the hyperparameters in the optimization routines |

Details

The three functions documented here carry out the multi-stage optimization detailed in KOH2001 (actually, KOH2001 only defined stage 1 and stage 2, which estimated the hyperparameters. What is here called “stage3()” estimates the true value of θ given the hyperparameters).

stage1() carries out stage 1 of KOH2001 which is used to estimate ψ_1 using optimization.

In function stage2(), setting argument isotropic to TRUE will force phi\$omegastar_x to be a function of a length one scalar. The value of phi\$omegastar_x used will depend on pdm.maker.psi2() (an internal function appearing in hpa.fun.toy()). In stage2(), several kludges are made. The initial conditions are provided by argument phi. The relevant part of this is phi\$psi2.

Function stage2() estimates ψ_2 and ρ and λ , using optimization. Note that ψ_2 includes σ_2^2 in addition to omegastar_X (in the toy case, ψ_2 has three elements: the first two are the diagonal of omegastar_x and the third is σ_2^2 but this information is encoded in phi.fun.toy(), which changes from application to application).

Function stage3() attempts to find the maximum likelihood estimate of θ , given hyperparameters and observations, using optimization

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O’Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O’Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[toys](#), [phi.fun.toy](#)

Examples

```
data(toys)
stage1(D1=D1.toy,y=y.toy,H1=H1.toy, maxit=5, phi.fun=phi.fun.toy, phi=phi.toy)

##now try with a slightly bigger dataset:
##Examples below take a few minutes to run:

set.seed(0)
data(toys)
jj <- create.new.toy.datasets(D1.toy , D2.toy)
y.toy <- jj$y.toy
z.toy <- jj$z.toy
d.toy <- jj$d.toy
```

```

phi.toy.stage1 <- stage1(D1=D1.toy, y=y.toy, H1=H1.toy, maxit=10, phi.fun=phi.fun.toy, phi=phi.toy)

phi.toy.stage2 <- stage2(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy,
  y=y.toy, z=z.toy, extractor=extractor.toy,
  phi.fun=phi.fun.toy, E.theta=E.theta.toy, Edash.theta=Edash.theta.toy,
  maxit=3, phi=phi.toy.stage1)

stage3(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy, d=d.toy, maxit=3, phi=phi.toy.stage2)

# Now try with the true values of the hyperparameters:
phi.true <- phi.true.toy(phi=phi.toy)

stage3(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy, d=d.toy, maxit=3, phi=phi.true)

```

symmetrize

Symmetrize an upper triangular matrix

Description

Symmetrize an upper triangular matrix by copying the upper triangular elements into the lower triangular places

Usage

```
symmetrize(a)
```

Arguments

a Upper triangular matrix to be symmetrized

Details

Also works for lower triangular matrices

Author(s)

Robin K. S. Hankin

Examples

```

jj <- matrix(rnorm(50),10,5)
X <- crossprod(jj,jj)   # X has a Wishart distribution (and in
                         # particular is positive definite)

chol(X)
symmetrize(chol(X))

```

tee *Auxiliary functions for equation 9 of the supplement*

Description

Returns a vector whose elements are the “distances” from a point to the observations and code run points (`tee()`); and basis functions for use in `Ez.eqn9.supp()`

Usage

```
tee(x, theta, D1, D2, phi)
h.fun(x, theta, H1, H2, phi)
```

Arguments

| | |
|-------|---|
| x | Point from which distances are calculated |
| theta | Value of parameters |
| D1,D2 | Design matrices of code run points and field observation points respectively (<code>tee()</code>) |
| H1,H2 | Basis functions for eta and model inadequacy term respectively (<code>h.fun()</code>) |
| phi | Hyperparameters |

Details

Equation 9 of the supplement is identical to equation 10 of KOH2001.

Function `h.fun()` returns the first of the subsidiary equations in equation 9 of the supplement and function `tee()` returns the second (NB: do not confuse this with functions `t1bar()` and `t2bar()` which are internal to `EK.eqn10.supp()`)

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O’Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O’Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/cal-sup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[Ez.eqn9.supp](#)

Examples

```

data(toys)
tee(x=x.toy, theta=theta.toy, D1=D1.toy, D2=D2.toy, phi=phi.toy)

# Now some vectorized examples:
jj <- rbind(x.toy , x.toy , x.toy+0.01,x.toy+1,x.toy*10)

tee(x=jj, theta=theta.toy, D1=D1.toy, D2=D2.toy, phi=phi.toy)
h.fun(x=jj, theta=theta.toy, H1=H1.toy, H2=H2.toy, phi=phi.toy)

```

toys

Toy datasets

Description

Toy datasets that illustrate the package.

Usage

```

data(toys)
D1.toy
D2.toy
d.toy
phi.toy
theta.toy
V.toy
X.dist.toy

```

Format

The `D1.toy` matrix is 8 rows of code run points, with five columns. The first two columns are the lat and long and the next three are parameter values.

The `D2.toy` matrix is five rows of observations on two variables, `x` and `y` which are styled “latitude and longitude”.

`d.toy` is the “data” vector consisting of length 13: elements 1-8 are code runs and elements 9-13 are observations.

`theta.toy` is a vector of length three that is a working example of θ . The parameters are designed to work with `computer.model()`.

`t.vec.toy` is a matrix of eight rows and three columns. Each row specifies a value for θ . The eight rows correspond to eight code runs.

`x.toy` and `x.toy2` are vectors of length two that gives a sample point at which observations may be made (or the code run). The gloss of the two elements is latitude and longitude.

`x.vec` is a matrix whose rows are reasonable `x` values but *not* those in `D2.toy`.

`y.toy` is a vector of length eight. Each element corresponds to the output from a code run at each of the rows of `D1.toy`.

`z.toy` is a vector of length five. Each element corresponds to a measurement at each of the rows of `D2.toy`.

`V.toy` is a five by five variance-covariance matrix for the toy datasets.

`X.dist.toy` is a toy example of a distribution of X for use in calibrated uncertainty analysis, section 4.2.

Brief description of toy functions fully documented under their own manpage

Function `create.new.toy.datasets()` creates new toy datasets with any number of observations and code runs.

Function `E.theta.toy()` returns expectation of $H(D)$ with respect to θ ; `Edash.theta.toy()` returns expectation with respect to E' .

Function `extractor.toy()` extracts `x.star.toy` and `t.vec.toy` from `D2`; toy example needed because the extraction differs from case to case.

Function `H1.toy()` applies basis functions to rows of `D1` and `D2`

Function `phi.fun.toy()` creates a hyperparameter object such as `phi.toy` in a form suitable for passing to the other functions in the library.

Function `phi.change.toy()` modifies the hyperparameter object.

See the helpfiles listed in the “see also” section below

Details

All toy datasets are documented here. There are also several toy functions that are needed for a toy problem; these are documented separately (they are too diverse to document fully in a single manpage). Nevertheless a terse summary for each toy function is provided on this page. All toy functions in the package are listed under “See Also”.

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O’Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O’Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[create.new.toy.datasets](#), [E.theta.toy](#), [extractor.toy](#), [H1.toy](#), [phi.fun.toy](#), [stage1](#)

Examples

```

data(toys)
D1.toy
extractor.toy(D1.toy)

D2.fun(theta=theta.toy , D2=D2.toy)
D2.fun(theta=theta.toy,D2=D2.toy[1, ,drop=FALSE])

library("emulator")
corr.matrix(D1.toy,scales=rep(1,5))
corr.matrix(D1.toy, pos.def.matrix=diag(5))

```

tt.fun

Integrals needed in KOH2001

Description

Calculates the three integrals needed for V , under the restrictions specified in the KOH2001 supplement

Usage

```

tt.fun(D1, extractor, x.i, x.j, test.for.symmetry=FALSE, method=1, phi)
ht.fun(x.i, x.j, D1, extractor, Edash.theta, H1, fast.but.opaque=TRUE,
x.star=NULL, t.vec=NULL, phi)
hh.fun(x.i, x.j, H1, E.theta, phi)
t.fun(x, D1, extractor, phi)

```

Arguments

| | |
|-------------|---|
| D1 | Matrix of code run points |
| H1 | regression basis functions for D1 |
| extractor | Function to extract $x.star$ and $t.vec$ from D1 |
| x | Lat and long of a point in $t.fun()$ (eg $D2[1,]$) |
| x.i | Lat and long of first point (eg $D2[1,]$) |
| x.j | Lat and long of second point (eg $D2[2,]$) |
| theta | parameters |
| Edash.theta | Function to return expectation of H with respect to the alternative distribution of θ ; $Edash.theta.toy$ is the example for the toy dataset |
| E.theta | Function to return expectation of H with respect to θ |

| | |
|-------------------|--|
| test.for.symmetry | In tt.fun(), Boolean with TRUE meaning to calculate each element of C explicitly. If FALSE, then calculate only the elements of C that lie on or over the diagonal and use the fact that C is symmetric to calculate the other matrix elements. For n observations, this means $n(n + 1)/2$ evaluations, compared with n^2 for the full case. Set this argument to TRUE only when debugging, or testing accuracy. |
| fast.but.opaque | In ht.fun(), Boolean with default TRUE meaning to pass some precalculated results as arguments, to save time. Set this argument to FALSE only when debugging. |
| x.star | In ht.fun(), value of x^* (required only if fast.but.opaque is TRUE) |
| t.vec | In ht.fun(), value of t (required only if fast.but.opaque is TRUE) |
| method | In tt.fun(), zero means use the old method and nonzero means use the new method. The new method is faster, but the code is harder to understand. The two methods should give identical results. |
| phi | Hyperparameters |

Details

The four functions return integrals representing means taken over theta. To wit:

- Function tt.fun() evaluates

$$\int t(x_j, \theta) t(x_i, \theta)^T p(\theta) d\theta$$

and is used in V.fun(). Note that this function is symmetric in x_i and x_j .

- Function ht.fun() evaluates

$$\int h_1(x_j, \theta) t(x_i, \theta)^T p(\theta) d\theta$$

and is used in V.fun(). Note that this function is **not** symmetric in x_i and x_j .

- Function hh.fun() evaluates

$$\int h_1(x_j, \theta) h_1(x_i, \theta)^T p(\theta) d\theta$$

and is used in V.fun(). Note that this function is symmetric in x_i and x_j .

- Function t.fun() evaluates

$$\int t(x_i, \theta)^T p(\theta) d\theta = \int c_1((x_i, \theta), (x_j^*, t_j)) p(\theta) d\theta$$

using the formula

$$\sigma_1^2 |I + 2V_\theta \Omega_x|^{-1/2} \exp \left\{ - (x_i - x_j^*)^T \Omega_x (x_i - x_j^*) \right\} \times \exp \left\{ - (m_\theta - t_j)^T (2V_\theta + \Omega_t^{-1})^{-1} (m_\theta - t_j) \right\}.$$

It is used in Ez_eq7.supp(). NB: do not confuse this function with tee(), which is different.

These functions are not generally of much interest to the end user; they are called by V.fun(). They are defined separately as a debugging aid, and to simplify the structure of V.fun().

Value

Each function returns a matrix as described in KOH2001

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O’Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O’Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[V.fun](#)

Examples

```
data(toys)

tt.fun(D1=D1.toy, extractor=extractor.toy, x.i=D2.toy[1,],
       x.j=D2.toy[2,], phi=phi.toy)

ht.fun(x.i=D2.toy[1,], x.j=D2.toy[2,], D1=D1.toy,
       extractor=extractor.toy,
       Edash.theta=Edash.theta.toy, H1=H1.toy, fast.but.opaque=FALSE, phi=phi.toy)

ht.fun(x.i=D2.toy[1,], x.j=D2.toy[2,], D1=D1.toy,
       extractor=extractor.toy,
       Edash.theta=Edash.theta.toy, H1=H1.toy, fast.but.opaque=TRUE,
       x.star=extractor.toy(D1.toy)$x.star, t.vec=extractor.toy(D1.toy)$t.vec,
       phi=phi.toy)

hh.fun(x.i=D2.toy[1,], x.j=D2.toy[2,],
       H1=H1.toy, E.theta=E.theta.toy, phi=phi.toy)

t.fun(x=x.toy, D1=D1.toy, extractor=extractor.toy, phi=phi.toy)
```

V.fun *Variance matrix for observations*

Description

Determines the variance/covariance matrix for the observations and code run points.

Usage

```
V.fun(D1, D2, H1, H2, extractor,
      E.theta, Edash.theta, give.answers=FALSE, test.for.symmetry=FALSE, phi)
```

Arguments

| | |
|-------------------|--|
| D1 | Matrix of code run points |
| D2 | Matrix of observation points |
| H1 | Regression function for D1 |
| H2 | Regression function for D2 |
| extractor | Function to extract <code>x.star</code> and <code>t.vec</code> from D1 |
| Edash.theta | Function to return expectation of H with respect to the alternative distribution of θ ; <code>Edash.theta.toy</code> is the example for the toy dataset |
| E.theta | Expectation of h WRT theta over the apriori distribution. Note that this function must be updated if <code>h1()</code> changes. |
| give.answers | Boolean (defaulting to FALSE) with TRUE meaning to return a list whose elements are V and its constituent parts, viz <code>line1</code> to <code>line6</code> . This argument is used mainly for debugging. |
| test.for.symmetry | Boolean with TRUE meaning to calculate each element of C explicitly, and default FALSE meaning to calculate only the elements of C that lie on or over the diagonal and use the fact that C is symmetric to calculate the other matrix elements. For n observations, this means $n(n+1)/2$ evaluations, compared with n^2 for the full case. The time saving is considerable, even for small matrices. |
| | Set this argument to TRUE only when debugging, or testing accuracy |
| phi | Hyperparameters |

Details

See KOH2001 for full details on page 3 of the supplement

Value

If `give.answers` is the default value of FALSE, returns a matrix of covariances for use in `p.page4()`. If `give.answers` is TRUE, returns a named list of (currently) 17 elements. Elements one to six are lines one to six respectively from page 3 of the supplement; subsequent lines give intermediate steps in the calculation. The final element is the matrix is the covariances as returned when `give.answers` is FALSE.

Note

This function takes a long time to run

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[tt.fun,p.page4](#)

Examples

```
data(toys)
(jj <-V.fun(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy,
  extractor=extractor.toy,
  Edash.theta=Edash.theta.toy,
  E.theta=E.theta.toy, phi=phi.toy))

## Now note that V.fun() changes with the PRIOR used for theta:
phi.different.theta <- phi.change(old.phi=phi.toy,
  theta.apriori.mean=c(100,100,100),phi.fun=phi.fun.toy)
V.fun(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy,
  extractor=extractor.toy,
  Edash.theta=Edash.theta.toy,
  E.theta=E.theta.toy, phi=phi.different.theta)
## different!

## Now compare jj above with V.fun() calculated with
## different phi2:

phi.toy.new <- phi.change(phi.fun=phi.fun.toy, old.phi = phi.toy, psi2=c(8,8,8))

V.fun(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy,
  extractor=extractor.toy,
  Edash.theta=Edash.theta.toy,
  E.theta=E.theta.toy, phi=phi.toy.new)

## different!
```



```

## Not run:
data(toys)
set.seed(0)
jj <- create.new.toy.datasets(D1=D1.toy , D2=D2.toy)
y.toy <- jj$y.toy
z.toy <- jj$z.toy
d.toy <- jj$d.toy

v.fun <- function(...){V.fun(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy,
  extractor=extractor.toy, Edash.theta=Edash.theta.toy,
  E.theta=E.theta.toy, phi=phi.toy, give=TRUE)}

Rprof(file=~ /f.txt");ignore <- v.fun();Rprof(file=NULL)
system("cd ; R CMD Rprof ~/f.txt > ~/ff.txt")

## End(Not run)

```

V1

Distance matrix

Description

Gives the distance matrix between rows of D1 and D1 (or, if supplied, another matrix)

Usage

```
V1(D1, other = NULL, phi)
```

Arguments

| | |
|-------|---|
| D1 | Matrix of code run points |
| other | Second matrix to compute distances to. If NULL, use the first supplied matrix |
| phi | Hyperparameters |

Value

Returns a matrix

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

V2

Examples

```
data(toys)
V1(D1=D1.toy, other=NULL, phi=phi.toy)
V1(D1=D1.toy[1,,drop=FALSE], other=NULL, phi=phi.toy)

V1(D1=D1.toy, other=D1.toy[1:3,], phi=phi.toy)

V1(D1=D1.toy, other=D1.fun(x.star=x.vec, t.vec=theta.toy), phi=phi.toy)
```

V2

distance between observation points

Description

distance between observation points

Usage

```
V2(x, other = NULL, phi)
```

Arguments

| | |
|-------|--|
| x | Matrix whose rows are observation points |
| other | Second matrix; if NULL, use x |
| phi | Hyperparameters |

Details

This function returns the variance matrix of observations of the real process z at points $D_2 = \{x_1, \dots, x_n\}$.

It appears in the lower right corner of the variance matrix on the bottom of page 1 of the supplement, calculated by function `Vd()`.

It is also used in functions `Cov.eqn9.supp()` and `V.fun()`.

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[V1](#)

Examples

```
data(toys)
V2(D2.toy,other=NULL, phi=phi.toy)
V2(D2.toy,x.vec,phi=phi.toy)
```

Vd *Variance matrix for d*

Description

Variance matrix for d, as per the bottom of page 1 of the supplement

Usage

```
Vd(D1, D2, theta, phi)
```

Arguments

| | |
|-------|------------------------------|
| D1 | matrix of code run points |
| D2 | matrix of observation points |
| theta | Parameters |
| phi | hyperparameters |

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[H.fun,V1,V2,C1](#)

Examples

```
data(toys)
Vd(D1=D1.toy, D2=D2.toy, theta=theta.toy, phi=phi.toy)
```

W

covariance matrix for beta

Description

Covariance matrix of beta given theta, phi, d

Usage

```
W(D1, D2, H1, H2, theta, det=FALSE, phi)
```

Arguments

| | |
|-------|--|
| D1 | Matrix whose rows are code run points |
| D2 | Matrix whose rows are observation points |
| H1 | regression function |
| H2 | regression function |
| theta | parameters |
| det | Boolean, with default FALSE meaning to return the covariance matrix, and TRUE meaning to return its determinant. |
| phi | Hyperparameters |

Details

This function is defined between equations 2 and 3 of the supplement. It is used in functions `betahat.fun.koh()`, `p.eqn8.supp()`, and `p.joint()`.

Returns

$$\mathbf{W}(\theta) = (\mathbf{H}(\theta)^T \mathbf{V}_d(\theta)^{-1} \mathbf{H}(\theta))^{-1}$$

If only the determinant is required, setting argument `det` to `TRUE` is faster than using `det(W(..., det=FALSE))`, as the former avoids an unnecessary use of `solve()`.

Author(s)

Robin K. S. Hankin

References

M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464

M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>

R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[betahat.fun.koh](#)

Examples

```
data(toys)
W(D1=D1.toy, D2=D2.toy, H1=H1.toy, H2=H2.toy, theta=theta.toy, phi=phi.toy)
```

W1

Variance matrix for beta1hat

Description

returns the variance-covariance matrix for the estimate of `beta1hat`

Usage

```
W1(D1, H1, det=FALSE, phi)
```

Arguments

| | |
|-----|---|
| D1 | matrix of code points |
| H1 | Basis function generator |
| phi | Hyperparameters |
| det | Boolean, with default FALSE meaning to return the matrix, and TRUE meaning to return its determinant only |

Details

If only the determinant is required, setting argument `det` to TRUE is faster than using `det(W1(..., det=FALSE))`, as the former avoids an unnecessary use of `solve()`.

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/cal-sup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[beta1hat.fun](#)

Examples

```
data(toys)
W1(D1=D1.toy, H1=H1.toy, phi=phi.toy)
```

W2

variance matrix for beta2

Description

Variance matrix for beta2 as per page 4 of the supplement

Usage

```
W2(D2, H2, V, det=FALSE)
```

Arguments

| | |
|-----|---|
| D2 | matrix of observation points |
| H2 | regression function |
| V | Overall covariance matrix |
| det | Boolean, with default FALSE meaning to return the matrix, and TRUE meaning to return its determinant only |

Details

If only the determinant is required, setting argument `det` to TRUE is faster than using `det(W2(..., det=FALSE))`, as the former avoids an unnecessary use of `solve()`

Author(s)

Robin K. S. Hankin

References

- M. C. Kennedy and A. O'Hagan 2001. *Bayesian calibration of computer models*. Journal of the Royal Statistical Society B, 63(3) pp425-464
- M. C. Kennedy and A. O'Hagan 2001. *Supplementary details on Bayesian calibration of computer models*, Internal report, University of Sheffield. Available at <http://www.tonyohagan.co.uk/academic/ps/calsup.ps>
- R. K. S. Hankin 2005. *Introducing BACCO, an R bundle for Bayesian analysis of computer code output*, Journal of Statistical Software, 14(16)

See Also

[V.fun](#)

Examples

```
data(toys)
W2(D2=D2.toy, H2=H2.toy, V=V.toy)
```

Index

*Topic **array**

- beta1hat.fun, 4
- beta2hat.fun, 6
- betahat.fun.koh, 7
- blockdiag, 9
- C1, 10
- cov.p5.supp, 11
- D1.fun, 14
- D2.fun, 15
- dists.2frames, 16
- E.theta.toy, 17
- EK.eqn10.supp, 20
- etahat, 22
- extractor.toy, 23
- Ez.eqn7.supp, 24
- Ez.eqn9.supp, 25
- H.fun, 27
- H1.toy, 28
- h1.toy, 29
- hbar.fun.toy, 30
- is.positive.definite, 31
- MH, 32
- p.eqn4.supp, 34
- p.eqn8.supp, 35
- p.page4, 36
- phi.fun.toy, 38
- prob.psi1, 41
- reality, 43
- stage1, 45
- symmetrize, 48
- tee, 49
- tt.fun, 52
- V.fun, 55
- V1, 57
- V2, 58
- Vd, 59
- w, 60
- w1, 61
- w2, 62

*Topic **datasets**

- create.new.toy.datasets, 13
- toys, 50

*Topic **package**

- calibrator-package, 2

- beta1hat.fun, 4, 62
- beta2hat.fun, 5, 6
- betahat.fun.koh, 7, 61
- blockdiag, 9
- C1, 10, 60
- calibrator (calibrator-package), 2
- calibrator-package, 2
- computer.model, 44
- computer.model (reality), 43
- Cov.eqn9.supp (cov.p5.supp), 11
- cov.p5.supp, 11
- create.new.toy.datasets, 13, 51
- d.toy (toys), 50
- D1.fun, 14, 24
- D1.toy, 16, 29
- D1.toy (toys), 50
- D2.fun, 15
- D2.toy (toys), 50
- dists.2frames, 16, 17
- E.theta.toy, 17, 51
- Edash.theta.toy (E.theta.toy), 17
- EK.eqn10.supp, 20
- etahat, 22
- extractor.toy, 23, 51
- Ez.eqn7.supp, 24
- Ez.eqn9.supp, 25, 49
- H.fun, 27, 60
- h.fun (tee), 49
- H1.toy, 28, 30, 41, 51
- h1.toy, 29, 31
- H2.toy (H1.toy), 28

h2.toy (h1.toy), 29
hbar.fun.toy, 30
hh.fun(tt.fun), 52
ht.fun(tt.fun), 52

is.positive.definite, 31

latin.hypercube, 14

MH, 32
model.inadequacy (reality), 43

p.eqn4.supp, 34, 43
p.eqn8.supp, 33, 35, 43
p.equationn4.supp (p.eqn4.supp), 34
p.page4, 23, 36, 56
phi.change (phi.fun.toy), 38
phi.fun.toy, 38, 47, 51
phi.toy (toys), 50
phi.true (reality), 43
prob.psi1, 41
prob.psi2 (prob.psi1), 41
prob.theta (prob.psi1), 41

reality, 14, 43

sample.theta (prob.psi1), 41
stage1, 36, 43, 45, 51
stage2 (stage1), 45
stage3 (stage1), 45
symmetrize, 48

t.fun, 11
t.fun(tt.fun), 52
t.vec.toy (toys), 50
tee, 26, 49
theta.toy, 16
theta.toy (toys), 50
toys, 14, 15, 19, 24, 41, 47, 50
tt.fun, 52, 56

V.fun, 25, 54, 55, 63
V.toy (toys), 50
V1, 57, 59, 60
V2, 58, 58, 60
Vd, 59

W, 60
W1, 34, 61
W2, 7, 36, 37, 62

X.dist.toy (toys), 50
x.toy (toys), 50
x.toy2 (toys), 50
x.vec (toys), 50

y.toy (toys), 50

z.toy (toys), 50