

Package ‘cholera’

October 11, 2021

Type Package

Title Amend, Augment and Aid Analysis of John Snow's Cholera Map

Version 0.7.9

Date 2021-10-11

Description Amends errors, augments data and aids analysis of John Snow's map of the 1854 London cholera outbreak.

URL <https://github.com/lindbrook/cholera>

BugReports <https://github.com/lindbrook/cholera/issues>

License GPL (>= 2)

LazyData true

Depends R (>= 3.4)

Imports deldir (>= 1.0-2), ggplot2, grDevices, HistData (>= 0.7-8),
igraph, KernSmooth, pracma, raster, RColorBrewer, sp, stats,
tools, threejs, TSP, utils, viridisLite

Suggests knitr, rmarkdown

VignetteBuilder knitr

RoxygenNote 7.1.2

Encoding UTF-8

Language en-US

NeedsCompilation no

Author Peter Li [aut, cre]

Maintainer Peter Li <lindbrook@gmail.com>

Repository CRAN

Date/Publication 2021-10-11 18:40:10 UTC

R topics documented:

cholera-package	4
addCase	5
addDelaunay	6
addEuclideanPath	6
addFrame	7
addIndexCase	8
addKernelDensity	8
addLandmarks	10
addMilePosts	10
addNeighborhoodCases	11
addNeighborhoodEuclidean	12
addNeighborhoodWalking	14
addPlaguePit	15
addPump	16
addRoads	16
addSnow	17
addVoronoi	17
addWalkingPath	18
addWhitehead	19
anchor.case	20
border	21
caseLocator	21
classifierAudit	22
distanceTime	23
euclideanPath	23
fatalities	25
fatalities.address	26
fatalities.unstacked	26
fixFatalities	27
isoLines	28
isoVertices	28
landmark.squares	29
landmarkData	29
landmarks	30
mapRange	30
nearestPump	31
neighborhoodData	32
neighborhoodEuclidean	32
neighborhoodVoronoi	33
neighborhoodWalking	35
ortho.proj	36
ortho.proj.pump	36
ortho.proj.pump.vestry	37
orthogonalProjection	38
oxford.weather	38
oxfordWeather	39

pearsonResiduals	40
plague.pit	40
plot.classifier_audit	41
plot.euclidean	41
plot.euclidean_path	42
plot.iso	43
plot.neighborhood_data	44
plot.oxfordWeather	44
plot.povertyLondon	45
plot.profile_perspective	45
plot.time_series	46
plot.voronoi	47
plot.walking	48
plot.walking_path	49
plot.winterTemperatures	50
povertyLondon	50
print.classifier_audit	51
print.euclidean	51
print.euclidean_path	52
print.iso	53
print.time_series	53
print.voronoi	54
print.walking	54
print.walking_path	55
profile2D	56
profile3D	56
pumpCase	57
pumpData	58
pumpLocator	59
pumps	60
pumps.vestry	60
regular.cases	61
road.segments	62
roads	63
roadSegments	63
segmentHighlight	64
segmentLength	65
segmentLocator	65
sim.ortho.proj	66
sim.pump.case	67
sim.walking.distance	68
simulateFatalities	68
simulateWalkingDistance	69
snow.neighborhood	70
snowColors	70
snowMap	71
snowNeighborhood	72
streetHighlight	72

streetLength	73
streetNameLocator	73
streetNames	74
streetNumberLocator	75
subsetRoadsSamples	76
summary.euclidean	76
summary.voronoi	77
summary.walking	77
timeSeries	78
unitMeter	79
unstackFatalities	79
voronoiPolygons	80
walkingPath	81
winterTemperatures	82
withinRadius	83

Index	84
--------------	-----------

cholera-package	<i>cholera: amend, augment and aid analysis of John Snow's cholera map</i>
-----------------	--

Description

Amend, augment and aid the analysis of John Snow's cholera map.

Details

Features:

- Fixes three apparent coding errors in Dodson and Tobler's 1992 digitization of Snow's map.
- "Unstacks" the data in two ways to make analysis and visualization easier and more meaningful.
- Computes and visualizes "pump neighborhoods" based on Voronoi tessellation, Euclidean distance, and walking distance.
- Ability to overlay graphical elements and features like kernel density, Voronoi diagrams, Snow's Broad Street neighborhood, and notable landmarks (John Snow's residence, the Lion Brewery, etc.) via `add*()` functions.
- Includes a variety of functions to highlight specific cases, roads, pumps and paths.
- Appends actual street names to roads data.
- Includes the revised pump data used in the second version of Snow's map from the Vestry report, which includes the "correct" location of the Broad Street pump.
- Adds two different aggregate time series fatalities data sets, taken from the Vestry report.
- With 'cholera' version $\geq 0.7.0$, support for parallel computation now includes Windows in addition to Linux and macOS.

To learn more, see the vignettes:

```
vignette("duplicate.missing.cases")
```

```
vignette("kernel.density")
```

```
vignette("parallelization")
```

```
vignette("pump.neighborhoods")
```

```
vignette("roads")
```

```
vignette("tiles.polygons")
```

```
vignette("time.series")
```

```
vignette("unstacking.bars")
```

addCase	<i>Add observed case(s) to plot.</i>
---------	--------------------------------------

Description

Add case(s), as "address" or "fatalities" as points or IDs, to a plot.

Usage

```
addCase(case = 1, type = "observed", token = "both", text.size = 0.5,  
        col = "red", pos = 1)
```

Arguments

case	Numeric. Vector of case ID(s). NULL plots all cases.
type	Character. Type of case: "observed" or "expected".
token	Character. Type of token to plot: "point", "id" or "both".
text.size	Numeric. Size of case ID text.
col	Character. Color.
pos	Numeric. Text position.

Examples

```
snowMap(add.cases = FALSE)  
addCase(1)
```

```
snowMap(add.cases = FALSE)  
addCase(100)
```

addDelaunay *Add Delaunay triangles.*

Description

Add Delaunay triangles.

Usage

```
addDelaunay(pump.select = NULL, vestry = FALSE, color = "black",
            line.type = "solid")
```

Arguments

pump.select	Numeric. Default is NULL; all pumps are used. Otherwise, selection by a vector of numeric IDs: 1 to 13 for pumps; 1 to 14 for pumps.vestry. Exclusion (negative selection) is possible (e.g., -6).
vestry	Logical. FALSE for original 13 pumps. TRUE for 14 pumps in Vestry Report.
color	Character. Color of triangle edges.
line.type	Character. Type of line for triangle edges.

Note

This function uses `deldir::deldir()`.

Examples

```
snowMap()
addDelaunay()
```

addEuclideanPath *Add the path for the Euclidean distance between cases and/or pumps.*

Description

Add the path for the Euclidean distance between cases and/or pumps.

Usage

```
addEuclideanPath(origin, destination = NULL, type = "case-pump",
                observed = TRUE, case.location = "address", vestry = FALSE,
                distance.unit = "meter", time.unit = "second", walking.speed = 5,
                unit.posts = "distance", unit.interval = NULL, alpha.level = 1)
```

Arguments

origin	Numeric or Integer. Numeric ID of case or pump.
destination	Numeric or Integer. Numeric ID(s) of case(s) or pump(s). Exclusion is possible via negative selection (e.g., -7). Default is NULL: this returns closest pump or "anchor" case.
type	Character "case-pump", "cases" or "pumps".
observed	Logical. Use observed or simulated expected data.
case.location	Character. For observed = FALSE: "address" or "nominal". "address" is the x-y coordinate of a stack's "anchor" case. "nominal" is the x-y coordinate of a bar.
vestry	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 pumps from the original map.
distance.unit	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. See vignette("roads") for information on unit distances.
time.unit	Character. "hour", "minute", or "second".
walking.speed	Numeric. Walking speed in km/hr.
unit.posts	Character. "distance" for mileposts; "time" for timeposts; NULL for no posts.
unit.interval	Numeric. Sets interval between unit.posts.
alpha.level	Numeric. Alpha level transparency for path: a value in [0, 1].

Value

An R list with 3 data frames: x-y coordinates for the origin and destination, and a summary of results.

Note

Walking time is computed using `distanceTime()`.

addFrame	<i>Add map border to plot.</i>
----------	--------------------------------

Description

Add map border to plot.

Usage

```
addFrame(...)
```

Arguments

... Additional plotting parameters.

addIndexCase *Highlight index case at 40 Broad Street.*

Description

Highlight index case at 40 Broad Street.

Usage

```
addIndexCase(cex = 2, col = "red", pch = 1, add.label = FALSE, text.size = 0.5)
```

Arguments

cex	Numeric. Size of point.
col	Character. Color of point.
pch	Numeric. Type of of point.
add.label	Logical. Add text annotation: "40 Broad Street"
text.size	Numeric. Size of text label.

Value

Add base R point and (optionally) text to a graphics plot.

Examples

```
segmentLocator("216-1")
addIndexCase()
```

addKernelDensity *Add 2D kernel density contours.*

Description

Add 2D kernel density contours based on selected sets of observations.

Usage

```
addKernelDensity(pump.subset = "pooled", pump.select = NULL,
  neighborhood.type = "walking", data = "unstacked", bandwidth = 0.5,
  color = "black", line.type = "solid", multi.core = TRUE)
```


Arguments

<code>pump.subset</code>	Character or Numeric: "pooled", "individual", or numeric vector. "pooled" treats all observations as a single set. "individual" is a shortcut for all individual pump neighborhoods. Use of vector of numeric pump IDs to subset from the neighborhoods defined by <code>pump.select</code> . Negative selection possible. NULL selects all pumps in <code>pump.select</code> .
<code>pump.select</code>	Numeric. Vector of numeric pump IDs to define pump neighborhoods (i.e., the "population"). Negative selection possible. NULL selects all pumps.
<code>neighborhood.type</code>	Character. "voronoi" or "walking"
<code>data</code>	Character. Unit of observation: "unstacked" uses <code>fatalities.unstacked</code> ; "address" uses <code>fatalities.address</code> ; "fatality" uses <code>fatalities</code> .
<code>bandwidth</code>	Numeric. Bandwidth for kernel density estimation.
<code>color</code>	Character. Color of contour lines.
<code>line.type</code>	Character. Line type for contour lines.
<code>multi.core</code>	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. You can also specify the number logical cores. See <code>vignette("Parallelization")</code> for details.

Value

Add contours to a graphics plot.

Note

This function uses `KernSmooth::bkde2D()`.

Examples

```
## Not run:
snowMap()
addKernelDensity()

snowMap()
addKernelDensity("individual")

snowMap()
addKernelDensity(c(6, 8))

snowMap()
addKernelDensity(pump.select = c(6, 8))

## End(Not run)
```

addLandmarks	<i>Add landmarks to plot.</i>
--------------	-------------------------------

Description

Add landmarks to plot.

Usage

```
addLandmarks(text.size = 0.5, highlight.perimeter = TRUE)
```

Arguments

`text.size` Numeric. cex for text labels.
`highlight.perimeter` Logical. Highlight Lion Brewery and Model Housing.

Value

Base R points and text.

Note

The location of 18 Sackville Street and 28 Dean Street are approximate. Falconberg Court & Mews form an isolate: they are not part of the network of roads and are technically unreachable. Adam and Eve Court and its pump also form an isolate.

Examples

```
snowMap(add.landmarks = FALSE)
addLandmarks()
```

addMilePosts	<i>Add distance or time based "mileposts" to an observed walking neighborhood plot.</i>
--------------	---

Description

Add distance or time based "mileposts" to an observed walking neighborhood plot.

Usage

```
addMilePosts(pump.subset = NULL, pump.select = NULL, vestry = FALSE,
  unit = "distance", interval = NULL, walking.speed = 5,
  type = "arrows", multi.core = TRUE, dev.mode = FALSE)
```

Arguments

<code>pump.subset</code>	Numeric. Vector of numeric pump IDs to subset from the neighborhoods defined by <code>pump.select</code> . Negative selection possible. NULL uses all pumps in <code>pump.select</code> .
<code>pump.select</code>	Numeric. Numeric vector of pumps to define possible pump neighborhoods (i.e. the "population"). Negative selection is possible. NULL selects all "observed" pumps (i.e., pumps with at least one case).
<code>vestry</code>	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 from the original map.
<code>unit</code>	Character. Milepost unit of measurement: "distance" or "time".
<code>interval</code>	Numeric. Interval between mileposts: 50 meters for "distance"; 60 seconds for "time".
<code>walking.speed</code>	Numeric. Walking speed in km/hr.
<code>type</code>	Character. "arrows" or "points".
<code>multi.core</code>	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. You can also specify the number logical cores. See <code>vignette("Parallelization")</code> for details.
<code>dev.mode</code>	Logical. Development mode uses <code>parallel::parLapply()</code> .

Value

R base graphics arrows or points.

`addNeighborhoodCases` *Add observed cases by neighborhood.*

Description

Add cases to a plot as "address" or "fatalities" and as points or IDs.

Usage

```
addNeighborhoodCases(pump.subset = NULL, pump.select = NULL,
  metric = "walking", type = "stack.base", token = "point",
  text.size = 0.5, pch = 16, point.size = 0.5, vestry = FALSE,
  weighted = TRUE, color = NULL, case.location = "nominal",
  alpha.level = 0.5, multi.core = TRUE)
```

Arguments

<code>pump.subset</code>	Numeric. Vector of numeric pump IDs to subset from the neighborhoods defined by <code>pump.select</code> . Negative selection possible. NULL uses all pumps in <code>pump.select</code> .
--------------------------	---

pump.select	Numeric. Numeric vector of pump IDs that define which pump neighborhoods to consider (i.e., specify the "population"). Negative selection possible. NULL selects all pumps.
metric	Character. Type of neighborhood: "euclidean" or "walking".
type	Character. Type of case: "stack.base" (base of stack), or "stack" (entire stack). For observed = TRUE.
token	Character. Type of token to plot: "point" or "id".
text.size	Numeric. Size of case ID text.
pch	Numeric.
point.size	Numeric.
vestry	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 in the original map.
weighted	Logical. TRUE computes shortest walking path weighted by road length. FALSE computes shortest walking path in terms of the number of nodes.
color	Character. Use a single color for all paths. NULL uses neighborhood colors defined by snowColors().
case.location	Character. For metric = "euclidean": "address" uses ortho.proj; "nominal" uses fatalities.
alpha.level	Numeric. Alpha level transparency for area plot: a value in [0, 1].
multi.core	Logical or Numeric. TRUE uses parallel::detectCores(). FALSE uses one, single core. You can also specify the number logical cores. See vignette("Parallelization") for details.

Examples

```
## Not run:
snowMap(add.cases = FALSE)
addNeighborhoodCases(pump.subset = c(6, 10))

snowMap(add.cases = FALSE)
addNeighborhoodCases(pump.select = c(6, 10))

## End(Not run)
```

```
addNeighborhoodEuclidean
```

Add expected Euclidean pump neighborhoods.

Description

Add expected Euclidean pump neighborhoods.

Usage

```
addNeighborhoodEuclidean(pump.subset = NULL, pump.select = NULL,
  vestry = FALSE, case.location = "nominal", type = "star",
  alpha.level = 0.5, multi.core = TRUE, dev.mode = FALSE)
```

Arguments

<code>pump.subset</code>	Numeric. Vector of numeric pump IDs to subset from the neighborhoods defined by <code>pump.select</code> . Negative selection possible. NULL selects all pumps in <code>pump.select</code> .
<code>pump.select</code>	Numeric. Vector of numeric pump IDs to define pump neighborhoods (i.e., the "population"). Negative selection possible. NULL selects all pumps.
<code>vestry</code>	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 in the original map.
<code>case.location</code>	Character. "address" or "nominal". "address" is the x-y coordinates of <code>sim.ortho.proj</code> . "nominal" is the x-y coordinates of <code>regular.cases</code> .
<code>type</code>	Character. Type of plot: "star", "area.points" or "area.polygons".
<code>alpha.level</code>	Numeric. Alpha level transparency for area plot: a value in [0, 1].
<code>multi.core</code>	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. You can also specify the number logical cores. See <code>vignette("Parallelization")</code> for details.
<code>dev.mode</code>	Logical. Development mode uses <code>parallel::parLapply()</code> .

Value

R graphic elements.

Examples

```
## Not run:
streetNameLocator("marshall street", zoom = 0.5, highlight = FALSE,
  add.subtitle = FALSE)
addNeighborhoodEuclidean()

streetNameLocator("marshall street", zoom = 0.5, highlight = FALSE,
  add.subtitle = FALSE)
addNeighborhoodEuclidean(type = "area.points")

## End(Not run)
```

 addNeighborhoodWalking

Add expected walking neighborhoods.

Description

Add expected walking neighborhoods.

Usage

```
addNeighborhoodWalking(pump.subset = NULL, pump.select = NULL,
  vestry = FALSE, weighted = TRUE, path = NULL, path.color = NULL,
  path.width = 3, alpha.level = 0.25, polygon.type = "solid",
  polygon.col = NULL, polygon.lwd = 2, multi.core = TRUE,
  dev.mode = FALSE)
```

Arguments

pump.subset	Numeric. Vector of numeric pump IDs to subset from the neighborhoods defined by pump.select. Negative selection possible. NULL uses all pumps in pump.select.
pump.select	Numeric. Numeric vector of pump IDs that define which pump neighborhoods to consider (i.e., specify the "population"). Negative selection possible. NULL selects all pumps.
vestry	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 in the original map.
weighted	Logical. TRUE computes shortest path weighted by road length. FALSE computes shortest path in terms of the number of nodes.
path	Character. "expected" or "observed".
path.color	Character. Use a single color for all paths. NULL uses neighborhood colors defined by snowColors().
path.width	Numeric. Set width of paths.
alpha.level	Numeric. Alpha level transparency for area plot: a value in [0, 1].
polygon.type	Character. "perimeter" or "solid".
polygon.col	Character.
polygon.lwd	Numeric.
multi.core	Logical or Numeric. TRUE uses parallel::detectCores(). FALSE uses one, single core. You can also specify the number logical cores. See vignette("Parallelization") for details.
dev.mode	Logical. Development mode uses parallel::parLapply().

Examples

```
## Not run:  
streetNameLocator("marshall street", zoom = 0.5)  
addNeighborhoodWalking()  
  
## End(Not run)
```

addPlaguePit	<i>Add plague pit (Marshall Street).</i>
--------------	--

Description

Draws a polygon that approximates the plague pit located around Marshall Street. From Vestry Report map.

Usage

```
addPlaguePit(color = "black", line.type = "solid")
```

Arguments

color	Character. Color of polygon.
line.type	Character. Polygon line type.

Value

Adds a polygon to a graphics plot.

Note

In progress.

Examples

```
snowMap(add.landmarks = FALSE)  
addPlaguePit()
```

addPump *Add selected pump(s) to plot.*

Description

Add selected pump(s) to plot.

Usage

```
addPump(pump.select = NULL, vestry = FALSE, col = NULL, pch = 24,
        label = TRUE, pos = 1, cex = 1)
```

Arguments

pump.select	Numeric or Integer. Vector of water pump numerical ID(s). With vestry = TRUE, whole number(s) between 1 and 14. With vestry = FALSE, whole number(s) between 1 and 13. See pumps.vestry and pumps for IDs and details about specific pumps. NULL plots all pumps. Negative selection allowed.
vestry	Logical. TRUE for the 14 pumps from Vestry Report. FALSE for the original 13 pumps.
col	Character. Color of pump points.
pch	Numeric. Shape of point character.
label	Logical. TRUE adds text label.
pos	Numeric. Position of label.
cex	Numeric. point cex.

addRoads *Add all streets and roads to plot.*

Description

Add all streets and roads to plot.

Usage

```
addRoads(col = "gray")
```

Arguments

col	Character. Color
-----	------------------

addSnow	<i>Adds Snow's graphical annotation of the Broad Street pump walking neighborhood.</i>
---------	--

Description

Adds Snow's graphical annotation of the Broad Street pump walking neighborhood.

Usage

```
addSnow(type = "area", color = "dodgerblue", alpha.level = 0.25,
        line.width = 2)
```

Arguments

type	Character. Type of annotation plot: "area", "perimeter" or "street".
color	Character. Neighborhood color.
alpha.level	Numeric. Alpha level transparency: a value in [0, 1].
line.width	Numeric. Line width for type = "street" and type = "perimeter".

Examples

```
## Not run:
plot(neighborhoodVoronoi())
addSnow()

## End(Not run)
```

addVoronoi	<i>Add Voronoi cells.</i>
------------	---------------------------

Description

Add Voronoi cells.

Usage

```
addVoronoi(pump.select = NULL, vestry = FALSE, case.location = "nominal",
          color = "black", line.type = "solid", line.width = 1)
```

Arguments

pump.select	Numeric. Default is NULL; all pumps are used. Otherwise, selection by a vector of numeric IDs: 1 to 13 for pumps; 1 to 14 for pumps.vestry. Exclusion (negative selection) is possible (e.g., -6).
vestry	Logical. FALSE for original 13 pumps. TRUE for 14 pumps in Vestry Report.
case.location	Character. For observed = FALSE: "address" or "nominal". "nominal" is the x-y coordinates of regular.cases.
color	Character. Color of cell edges.
line.type	Character. Type of line for cell edges: lty.
line.width	Numeric. Width of cell edges: lwd.

Note

This function uses `deldir::deldir()`.

Examples

```
snowMap()
addVoronoi()
```

addWalkingPath	<i>Add the shortest walking path between a selected cases or pumps.</i>
----------------	---

Description

Add the shortest walking path between a selected cases or pumps.

Usage

```
addWalkingPath(origin = 1, destination = NULL, type = "case-pump",
  observed = TRUE, weighted = TRUE, vestry = FALSE,
  distance.unit = "meter", time.unit = "second", walking.speed = 5,
  unit.posts = "distance", unit.interval = NULL, alpha.level = 1)
```

Arguments

origin	Numeric or Integer. Numeric ID of case or pump.
destination	Numeric or Integer. Numeric ID(s) of case(s) or pump(s). Exclusion is possible via negative selection (e.g., -7). Default is NULL: this returns closest pump or "anchor" case. Character landmark name (case insensitive).
type	Character "case-pump", "cases" or "pumps".
observed	Logical. Use observed or "simulated" expected data.
weighted	Logical. TRUE computes shortest path in terms of road length. FALSE computes shortest path in terms of nodes.

vestry	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 in the original map.
distance.unit	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. unit is meaningful only when "weighted" is TRUE. See vignette("roads") for information on unit distances.
time.unit	Character. "hour", "minute", or "second".
walking.speed	Numeric. Walking speed in km/hr.
unit.posts	Character. "distance" for mileposts; "time" for timeposts.
unit.interval	Numeric. Sets interval between posts: for "distance", the default is 50 meters; for "time", the default is 60 seconds.
alpha.level	Numeric. Alpha level transparency for path: a value in [0, 1].

Value

An R list with two elements: a character vector of path nodes and a data frame summary.

Note

The function uses a case's "address" (i.e., a stack's "anchor" case) to compute distance. Time is computed using cholera::distanceTime(). Adam and Eve Court, and Falconberg Court and Falconberg Mews, are disconnected from the larger road network; they form two isolated subgraphs. This has two consequences: first, only cases on Adam and Eve Court can reach pump 2 and those cases cannot reach any other pump; second, cases on Falconberg Court and Mews cannot reach any pump. Unreachable pumps will return distances of Inf. Arrow points represent mileposts or timeposts to the destination.

Examples

```
streetNameLocator("broad street", zoom = TRUE, highlight = FALSE,
  add.subtitle = FALSE)
addWalkingPath(447)
```

addWhitehead

Add Rev. Henry Whitehead's Broad Street pump neighborhood.

Description

A circle (polygon), centered around a desired pump with a radius of 210 yards. The Broad Street pump is the default.

Usage

```
addWhitehead(pump = "Broad Street", radius = 210, distance.unit = "yard",
  color = "black", line.type = "solid", vestry = FALSE,
  add.subtitle = FALSE, walking.speed = 5)
```

Arguments

pump	Character or Numeric. Name (road name) or numerical ID of selected pump. See pumps or pumps.vestry.
radius	Numeric. Distance from a pump.
distance.unit	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. See vignette("roads") for information on conversion.
color	Character. Color of circle.
line.type	Character. Circle line type.
vestry	Logical. TRUE uses the 14 pumps and locations from Vestry report. FALSE uses original 13 pumps.
add.subtitle	Logical. Add subtitle with estimated "walking" time in seconds.
walking.speed	Numeric. Walking speed in km/hr.

Value

Adds a circle (polygon) to a graphics plot.

Examples

```
snowMap(add.landmarks = FALSE)
addWhitehead()
```

anchor.case

Anchor or base case of each stack of fatalities.

Description

Data frame that links a fatality to its stack, a stack's base case. For use with [caseLocator](#).

Usage

```
anchor.case
```

Format

```
case numerical case ID
anchor numerical case ID of anchor.case
```

Note

[unstackFatalities](#) documents the code for these data.

border	<i>Numeric IDs of line segments that create the map's border frame.</i>
--------	---

Description

Vector of ordered numbers that identify the line segments that make up the frame of the map. For use with `sp::Polygon()`.

Usage

```
border
```

Format

```
border numerical ID
```

caseLocator	<i>Locate case by numerical ID.</i>
-------------	-------------------------------------

Description

Highlight selected observed or simulated case and its home road segment.

Usage

```
caseLocator(case = 1, zoom = 1, observed = TRUE, add.title = TRUE,
  highlight.segment = TRUE, data = FALSE, add = FALSE, col = "red")
```

Arguments

case	Numeric or Integer. Whole number between 1 and 578.
zoom	Logical or Numeric. A numeric value ≥ 0 controls the degree of zoom. The default is 1.
observed	Logical. TRUE for observed. FALSE for simulated.
add.title	Logical. Include title.
highlight.segment	Logical. Highlight case's segment.
data	Logical. Output data.
add	Logical. Add to existing plot or separate plot.
col	Character. Point color.

Value

A base R graphics plot.

Examples

```
caseLocator(290)
caseLocator(290, zoom = TRUE)
caseLocator(290, observed = FALSE)
```

classifierAudit	<i>Test if case is orthogonal to segment.</i>
-----------------	---

Description

Diagnostic to check classification of case to a road segment.

Usage

```
classifierAudit(case = 483, segment = "326-2", observed = TRUE,
  coordinates = FALSE)
```

Arguments

case	Numeric or Integer. Numeric ID of observed case.
segment	Character. Segment ID. See road.segments.
observed	Logical. FALSE observed case; TRUE simulated case (regular.cases).
coordinates	Logical. Orthogonal projection coordinates.

Value

Logical TRUE or FALSE

Note

This function is a diagnostic. It is not a guarantee of correct classification.

Examples

```
classifierAudit(case = 483, segment = "326-2")
plot(classifierAudit(case = 483, segment = "326-2"))
```

distanceTime	<i>Convert distance to elapsed time.</i>
--------------	--

Description

Convert distance to elapsed time.

Usage

```
distanceTime(x, distance.unit = "meter", time.unit = "second",  
            walking.speed = 5)
```

Arguments

x	Numeric. Nominal map distance.
distance.unit	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. See vignette("roads") for information on conversion.
time.unit	Character. Unit of measurement: "hour", "minute" or "second".
walking.speed	Numeric. Walking speed in km/hr.

Value

An R vector.

euclideanPath	<i>Compute path of the Euclidean distance between cases and/or pumps.</i>
---------------	---

Description

Compute path of the Euclidean distance between cases and/or pumps.

Usage

```
euclideanPath(origin = 1, destination = NULL, type = "case-pump",  
             observed = TRUE, case.location = "nominal", landmark.cases = TRUE,  
             vestry = FALSE, distance.unit = "meter", time.unit = "second",  
             walking.speed = 5)
```

Arguments

origin	Numeric or Character. Numeric ID of case or pump. Character landmark name.
destination	Numeric or Character. Numeric ID(s) of case(s) or pump(s). Exclusion is possible via negative selection (e.g., -7). Default is NULL, which returns the closest pump, "anchor" case or landmark.
type	Character "case-pump", "cases" or "pumps".
observed	Logical. Use observed or "simulated" expected data.
case.location	Character. For observed = FALSE: "address" or "nominal". "nominal" is the x-y coordinates of regular.cases.
landmark.cases	Logical. TRUE includes landmarks as cases.
vestry	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 pumps from the original map.
distance.unit	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. See vignette("roads") for information on unit distances.
time.unit	Character. "hour", "minute", or "second".
walking.speed	Numeric. Default is 5 km/hr.

Value

An R list with 3 data frames: x-y coordinates for the origin and destination, and a summary of results.

Note

The function uses a case's "address" (i.e., "anchor" case of a stack) to compute distance. Time is computed using distanceTime().

Examples

```
# path from case 1 to nearest pump.
euclideanPath(1)

# path from pump 1 to nearest case.
euclideanPath(NULL, 1)

# path from case 1 to pump 6.
euclideanPath(1, 6)

# exclude pump 7 from consideration.
euclideanPath(1, -7)

# path from case 1 to case 6.
euclideanPath(1, 6, type = "cases")

# path from pump 1 to pump 6.
euclideanPath(1, 6, type = "pumps")
```



```
# compute multiple cases.
lapply(1:3, euclideanPath)

# plot path
plot(euclideanPath(1))
```

`fatalities`

Amended Dodson and Tobler's cholera data.

Description

An amended version of Dodson and Tobler's digitization of John Snow's map of the 1854 London cholera outbreak. It removes 3 duplicate observations and imputes the location for 3 "missing" observation. This information is also available in `HistData::Snow.deaths2` (\geq ver. 0.7-8).

Usage

```
fatalities
```

Format

A data frame with 3 variable that records the position and the nearest pump for the 578 bars on Snow's map.

`case` numeric case ID

`x` x-coordinate

`y` y-coordinate

Note

[fixFatalities](#) documents the code for these data. For details, see `vignette("duplicate.missing.cases")`.

See Also

[caseLocator](#)

[streetNameLocator](#)

[streetNumberLocator](#)

[caseLocator](#)

[streetNameLocator](#)

[streetNumberLocator](#)

fatalities.address	<i>"Unstacked" amended cholera data with address as unit of observation.</i>
--------------------	--

Description

An "unstacked" version of the `fatalities` dataset. It changes the unit of observation from the case (bar) to the "address", the x-y coordinates of the case at the base of a stack, and makes the number of fatalities an attribute of the "address".

Usage

```
fatalities.address
```

Format

A data frame with 4 variables for 321 addresses

`anchor` numerical case ID of address

`x` x-coordinate

`y` y-coordinate

`case.count` number of fatalities at address

Note

[unstackFatalities](#) documents the code for these data. For details, see `vignette("unstacking.fatalities")`.

See Also

[caseLocator](#)

[streetNameLocator](#)

[streetNumberLocator](#)

fatalities.unstacked	<i>"Unstacked" amended cholera fatalities data with fatality as unit of observation.</i>
----------------------	--

Description

An "unstacked" version of the `fatalities` dataset. It changes the unit of observation from the case (bar) to the "address", the x-y coordinates of the case at the base of a stack, and assigns the base case's coordinates to all cases in the stack.

Usage

```
fatalities.unstacked
```

Format

A data frame with 3 variable that records the position of the 578 bars on Snow's map.

case numerical case ID

x x-coordinate

y y-coordinate

Note

[unstackFatalities](#) documents the code for these data. For details, see `vignette("unstacking.fatalities")`.

See Also

[caseLocator](#)

[streetNameLocator](#)

[streetNumberLocator](#)

fixFatalities

Fix errors in Dodson and Tobler's digitization of Snow's map.

Description

Fixes two apparent coding errors using three misplaced cases.

Usage

```
fixFatalities()
```

Value

An R data frame.

See Also

`vignette("duplicate.missing.cases")`

isoLines	<i>Plot isochrone and isodistance regions (prototype)</i>
----------	---

Description

Plot isochrone and isodistance regions (prototype)

Usage

```
isoLines(post = 50, post.type = "distance", palette = "plasma",
         alpha.level = 1/2)
```

Arguments

post	Numeric. Distance or time increment.
post.type	Character. "distance" or "time".
palette	Character.
alpha.level	Numeric. Alpha level transparency

isoVertices	<i>Isochrone and isodistance vertices (prototype)</i>
-------------	---

Description

Isochrone and isodistance vertices (prototype)

Usage

```
isoVertices(post = 50, post.type = "distance", multi.core = TRUE,
            dev.mode = FALSE)
```

Arguments

post	Numeric.
post.type	Character. "distance" or "time".
multi.core	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. You can also specify the number logical cores.
dev.mode	Logical. Development mode uses <code>parallel::parLapply()</code> .

landmark.squares	<i>Centers of city squares.</i>
------------------	---------------------------------

Description

Centers of city squares.

Usage

```
landmark.squares
```

Format

A data frame with 6 variables that records the position of the orthogonal projection of landmarks onto the network of roads.

name square name

x x-coordinate

y y-coordinate

case numeric case ID

landmarkData	<i>Landmark data.</i>
--------------	-----------------------

Description

Nominal and orthogonal coordinates

Usage

```
landmarkData(multi.core = TRUE, dev.mode = FALSE)
```

Arguments

`multi.core` Logical or Numeric. TRUE uses `parallel::detectCores()`. FALSE uses one, single core. You can also specify the number logical cores. See `vignette("Parallelization")` for details.

`dev.mode` Logical. Development mode uses `parallel::parLapply()`.

landmarks	<i>Orthogonal projection of landmarks onto road network.</i>
-----------	--

Description

Orthogonal projection of landmarks onto road network.

Usage

landmarks

Format

A data frame with 6 variables that records the position of the orthogonal projection of landmarks onto the network of roads.

road.segment "address" road segment
x.proj orthogonal x-coordinate
y.proj orthogonal y-coordinate
ortho.dist orthogonal distance to home road segment
x nominal x-coordinate
y nominal y-coordinate
name landmark name
case numeric case ID

Note

[landmarkData](#) documents the code for these data.

mapRange	<i>Compute xlim and ylim of Snow's map.</i>
----------	---

Description

Compute xlim and ylim of Snow's map.

Usage

mapRange()

nearestPump	<i>Compute shortest distances or paths to selected pumps.</i>
-------------	---

Description

Compute shortest distances or paths to selected pumps.

Usage

```
nearestPump(pump.select = NULL, metric = "walking", vestry = FALSE,
            weighted = TRUE, case.set = "observed", distance.unit = "meter",
            time.unit = "second", walking.speed = 5, multi.core = TRUE,
            dev.mode = FALSE)
```

Arguments

<code>pump.select</code>	Numeric. Pump candidates to consider. Default is NULL: all pumps are used. Otherwise, selection by a vector of numeric IDs: 1 to 13 for pumps; 1 to 14 for pumps.vestry. Negative selection allowed.
<code>metric</code>	Character. "euclidean" or "walking".
<code>vestry</code>	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 in the original map.
<code>weighted</code>	Logical. TRUE computes shortest path in terms of road length. FALSE computes shortest path in terms of the number of nodes.
<code>case.set</code>	Character. "observed", "expected", or "snow".
<code>distance.unit</code>	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. Meaningful only when "weighted" is TRUE. See vignette("roads") for information on unit distances.
<code>time.unit</code>	Character. "hour", "minute", or "second".
<code>walking.speed</code>	Numeric. Walking speed in km/hr.
<code>multi.core</code>	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. You can also specify the number logical cores. See vignette("Parallelization") for details.
<code>dev.mode</code>	Logical. Development mode uses <code>parallel::parLapply()</code> .

Value

An R data frame or list of 'igraph' path nodes.

Note

Time is computed using `distanceTime()`.

neighborhoodData *Compute network graph of roads, cases and pumps.*

Description

Assembles cases, pumps and road into a network graph.

Usage

```
neighborhoodData(vestry = FALSE, case.set = "observed", embed = TRUE,
  embed.landmarks = TRUE)
```

Arguments

vestry	Logical. Use Vestry Report pump data.
case.set	Character. "observed" or "expected", or "snow". "snow" captures John Snow's annotation of the Broad Street pump neighborhood printed in the Vestry report version of the map.
embed	Logical. Embed cases and pumps into road network.
embed.landmarks	Logical. Embed landmarks into road network.

Value

An R list of nodes, edges and an 'igraph' network graph.

neighborhoodEuclidean *Compute Euclidean path pump neighborhoods.*

Description

Plots star graph from pump to its cases.

Usage

```
neighborhoodEuclidean(pump.select = NULL, vestry = FALSE,
  case.location = "nominal", case.set = "observed", multi.core = TRUE,
  dev.mode = FALSE)
```


Arguments

<code>pump.select</code>	Numeric. Vector of numeric pump IDs to define pump neighborhoods (i.e., the "population"). Negative selection possible. NULL selects all pumps.
<code>vestry</code>	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 in the original map.
<code>case.location</code>	Character. "address" or "nominal". For observed = TRUE: "address" uses <code>ortho.proj</code> and "nominal" uses <code>fatalities</code> . For observed = FALSE: "address" uses <code>sim.ortho.proj</code> and "nominal" uses <code>regular.cases</code> .
<code>case.set</code>	Character. "observed" or "expected".
<code>multi.core</code>	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. You can also specify the number logical cores. See <code>vignette("Parallelization")</code> for details.
<code>dev.mode</code>	Logical. Development mode uses <code>parallel::parLapply()</code> .

Value

An R vector.

Examples

```
## Not run:
neighborhoodEuclidean()
neighborhoodEuclidean(-6)
neighborhoodEuclidean(pump.select = 6:7)

## End(Not run)
```

`neighborhoodVoronoi` *Compute Voronoi pump neighborhoods.*

Description

Group cases into neighborhoods using Voronoi tessellation.

Usage

```
neighborhoodVoronoi(pump.select = NULL, vestry = FALSE,
  case.location = "address", pump.location = "nominal",
  polygon.vertices = FALSE)
```

Arguments

<code>pump.select</code>	Numeric. Vector of numeric pump IDs to define pump neighborhoods (i.e., the "population"). Negative selection possible. NULL selects all pumps.
<code>vestry</code>	Logical. TRUE uses the 14 pumps from the Vestry report. FALSE uses the 13 in the original map.
<code>case.location</code>	Character. "address" or "nominal". "address" uses the x-y coordinates of <code>ortho.proj</code> . "nominal" uses the x-y coordinates of fatalities.
<code>pump.location</code>	Character. "address" or "nominal". "address" uses the x-y coordinates of <code>ortho.proj.pump</code> or <code>ortho.proj.pump.vestry</code> . "nominal" uses the x-y coordinates of pumps or <code>pumps.vestry</code> .
<code>polygon.vertices</code>	Logical. TRUE returns a list of x-y coordinates of the vertices of Voronoi cells. Useful for <code>sp::point.in.polygon()</code> as used in <code>print.voronoi()</code> method.

Value

An R list with 12 objects.

- `pump.id`: vector of selected pumps
- `voronoi`: output from `deldir::deldir()`.
- `snow.colors`: neighborhood color based on `snowColors()`.
- `x.rng`: range of x for plot.
- `y.rng`: range of y for plot.
- `select.string`: description of "pump.select" for plot title.
- `expected.data`: expected neighborhood fatality counts, based on Voronoi cell area.
- `coordinates`: polygon vertices of Voronoi cells.
- `statistic.data`: observed neighborhood fatality counts.
- `pump.select`: "pump.select" from `neighborhoodVoronoi()`.
- `statistic`: "statistic" from `neighborhoodVoronoi()`.
- `vestry`: "vestry" from `neighborhoodVoronoi()`.

Examples

```
neighborhoodVoronoi()
neighborhoodVoronoi(vestry = TRUE)
neighborhoodVoronoi(pump.select = 6:7)
neighborhoodVoronoi(pump.select = -6)
neighborhoodVoronoi(pump.select = -6, polygon.vertices = TRUE)

# coordinates for vertices also available in the returned object.
dat <- neighborhoodVoronoi(pump.select = -6)
dat$coordinates
```

neighborhoodWalking *Compute walking path pump neighborhoods.*

Description

Group cases into neighborhoods based on walking distance.

Usage

```
neighborhoodWalking(pump.select = NULL, vestry = FALSE, weighted = TRUE,
  case.set = "observed", multi.core = TRUE, dev.mode = FALSE)
```

Arguments

pump.select	Numeric. Vector of numeric pump IDs to define pump neighborhoods (i.e., the "population"). Negative selection possible. NULL selects all pumps. Note that you can't just select the pump on Adam and Eve Court (#2) because it's technically an isolate.
vestry	Logical. TRUE uses the 14 pumps from the Vestry report. FALSE uses the 13 in the original map.
weighted	Logical. TRUE computes shortest path weighted by road length. FALSE computes shortest path in terms of the number of nodes.
case.set	Character. "observed", "expected" or "snow". "snow" captures John Snow's annotation of the Broad Street pump neighborhood printed in the Vestry report version of the map.
multi.core	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. You can also specify the number logical cores. See <code>vignette("Parallelization")</code> for details.
dev.mode	Logical. Development mode uses <code>parallel::parLapply()</code> .

Value

An R list with 7 objects:

- paths: list of paths to nearest or selected pump(s).
- cases: list of cases by pump.
- vestry: "vestry" from `neighborhoodWalking()`.
- observed: "observed" from `neighborhoodWalking()`.
- pump.select: "pump.select" from `neighborhoodWalking()`.
- cores: number of cores to use for parallel implementation.
- metric: incremental metric used to find cut point on split road segments.

Examples

```
## Not run:
neighborhoodWalking()
neighborhoodWalking(pump.select = -6)

## End(Not run)
```

ortho.proj

Orthogonal projection of observed cases onto road network.

Description

Orthogonal projection of observed cases onto road network.

Usage

```
ortho.proj
```

Format

A data frame with 5 variables that records the position of the orthogonal projection of the 578 cases onto the network of roads.

road.segment "address" road segment

x.proj x-coordinate

y.proj y-coordinate

ortho.dist orthogonal distance to home road segment

case numeric case ID

Note

[unstackFatalities](#) documents the code for these data.

ortho.proj.pump

Orthogonal projection of 13 original pumps.

Description

Orthogonal projection of 13 original pumps.

Usage

```
ortho.proj.pump
```

Format

A data frame with 6 variables that records the position of the orthogonal projection of the 13 original pumps onto the network of roads.

road.segment "address" road segment
x.proj x-coordinate
y.proj y-coordinate
ortho.dist orthogonal distance to home road segment
node node ID
pump.id numeric ID

Note

[pumpData](#) documents the code for these data.

ortho.proj.pump.vestry

Orthogonal projection of the 14 pumps from the Vestry Report.

Description

Orthogonal projection of the 14 pumps from the Vestry Report.

Usage

ortho.proj.pump.vestry

Format

A data frame with 6 variables that records the position of the orthogonal projection of the 14 pumps onto the network of roads.

road.segment "address" road segment
x.proj x-coordinate
y.proj y-coordinate
ortho.dist orthogonal distance to home road segment
node node ID
pump.id numeric ID

Note

[pumpData](#) documents the code for these data.

orthogonalProjection *Compute coordinates of orthogonal projection from case to road segment.*

Description

Compute coordinates of orthogonal projection from case to road segment.

Usage

```
orthogonalProjection(case = 12, segment.id = "216-1", observed = TRUE,
  use.pump = FALSE, vestry = FALSE, case.data = NULL)
```

Arguments

case	Numeric. case ID from fatalities.
segment.id	Character. Road segment ID.
observed	Logical. FALSE observed case; TRUE simulated case (regular.cases).
use.pump	Logical. Use pump ID as case.
vestry	Logical. Use vestry pump data.
case.data	Object. For use with simulateFatalities.

Value

An R data frame.

oxford.weather *Oxford monthly weather data, January 1853 - December 2019.*

Description

Extract from UK Met Office (<https://www.metoffice.gov.uk/pub/data/weather/uk/climate/stationdata/oxforddata.txt>):
 Lat 51.761 Lon -1.262, 63 metres amsl. Approximate 90 km (55 miles) northwest of Soho.

Usage

```
oxford.weather
```

Format

A data frame with 7 variables and 95 observations.

year yyyy

mo month (mm)

tmax maximum temperature degrees Celsius

tmin minimum temperature degrees Celsius

airfrost days

rain millimeters (mm)

sun sunshine hours

Note

December 1860 excluded due to missing tmin observation.

oxfordWeather

Weather data recorded in Oxford (Met Office UK).

Description

Add and use last day of month as unit of observation to oxford.weather.

Usage

```
oxfordWeather()
```

Value

An R data frame.

Note

December 1860 observation is dropped due to missing "tmin" value.

pearsonResiduals *Compute Pearson Residuals (prototype)*

Description

Compute Pearson Residuals (prototype)

Usage

```
pearsonResiduals(x)
```

Arguments

x An object created by `neighborhoodEuclidean()`, `neighborhoodVoronoi()` or `neighborhoodWalking()`.

Value

An R vector.

Examples

```
## Not run:
pearsonResiduals(neighborhoodEuclidean())
pearsonResiduals(neighborhoodVoronoi())
pearsonResiduals(neighborhoodWalking())

## End(Not run)
```

plague.pit *Plague pit coordinates.*

Description

Coordinates for `polygon()` or `sp::Polygon()`. In progress.

Usage

```
plague.pit
```

Format

A data frame with 13 observations and 2 variables.

x x-coordinate

y y-coordinate

plot.classifier_audit *Plot result of classifierAudit().*

Description

Plot case, segment and orthogonal projector.

Usage

```
## S3 method for class 'classifier_audit'  
plot(x, zoom = 0.5, unit = "meter", ...)
```

Arguments

x	An object of class "classifier_audit" created by classifierAudit().
zoom	Logical or Numeric. A numeric value ≥ 0 controls the degree of zoom. The default is 0.5.
unit	Character. Unit of distance: "meter" (the default), "yard" or "native". "native" returns the map's native scale. "unit" is meaningful only when "weighted" is TRUE. See vignette("roads") for information on unit distances.
...	Additional parameters.

Value

A base R graphic.

Examples

```
plot(classifierAudit(case = 483, segment = "326-2"))
```

plot.euclidean *Plot method for neighborhoodEuclidean().*

Description

Plot method for neighborhoodEuclidean().

Usage

```
## S3 method for class 'euclidean'  
plot(x, type = "star", add.observed.points = TRUE, msg = FALSE, ...)
```

Arguments

x	An object of class "euclidean" created by neighborhoodEuclidean().
type	Character. "star", "area.points" or "area.polygons". "area" flavors only valid when case.set = "expected".
add.observed.points	Logical. Add observed fatality "addresses".
msg	Logical. Toggle in-progress messages.
...	Additional plotting parameters.

Value

A base R plot.

Note

This uses an approximate computation of polygons, using the 'TSP' package, that may produce non-simple and/or overlapping polygons.

Examples

```
## Not run:
plot(neighborhoodEuclidean())
plot(neighborhoodEuclidean(-6))
plot(neighborhoodEuclidean(pump.select = 6:7))
plot(neighborhoodEuclidean(case.set = "expected"), type = "area.points")
plot(neighborhoodEuclidean(case.set = "expected"), type = "area.polygons")

## End(Not run)
```

plot.euclidean_path *Plot the path of the Euclidean distance between cases and/or pumps.*

Description

Plot the path of the Euclidean distance between cases and/or pumps.

Usage

```
## S3 method for class 'euclidean_path'
plot(x, zoom = 0.5, unit.posts = "distance", unit.interval = NULL, ...)
```

Arguments

x	An object of class "euclidean_path" created by euclideanPath().
zoom	Logical or Numeric. A numeric value ≥ 0 controls the degree of zoom. The default is 0.5.
unit.posts	Character. "distance" for mileposts; "time" for timeposts; NULL for no posts.
unit.interval	Numeric. Set interval between posts. When unit.posts is "distance", unit.interval automatically defaults to 50 meters. When unit.posts is "time", unit.interval automatically defaults to 60 seconds.
...	Additional plotting parameters.

Value

A base R plot.

Examples

```
plot(euclideanPath(15))
plot(euclideanPath(15), unit.posts = "time")
```

plot.iso

Plot method for isoVertices().

Description

Plot method for isoVertices().

Usage

```
## S3 method for class 'iso'
plot(x, selected.post = "all", palette = "plasma", alpha.level = 1/2, ...)
```

Arguments

x	An object of class "iso" created by isoVertices().
selected.post	Character or Numeric. Select milepost polygon. "all" or number.
palette	Character.
alpha.level	Numeric. Alpha level transparency
...	Additional arguments.

Value

A vector with observed counts.

```
plot.neighborhood_data
```

Plot method for neighborhoodData().

Description

Visualize underlying road network (with or without cases and pumps).

Usage

```
## S3 method for class 'neighborhood_data'
plot(x, ...)
```

Arguments

`x` An 'igraph' object of class "neighborhood_data" created by neighborhoodData().
`...` Additional plotting parameters.

Value

A base R plot.

Examples

```
plot(neighborhoodData())
plot(neighborhoodData(embed = FALSE))
```

```
plot.oxfordWeather
```

Plot method for oxfordWeather().

Description

Plot method for oxfordWeather().

Usage

```
## S3 method for class 'oxfordWeather'
plot(x, statistic = "temperature", month = "september", ...)
```

Arguments

`x` object.
`statistic` Character.
`month` Character. "august" or "september".
`...` Additional plotting parameters.

Value

A base R plot.

`plot.povertyLondon` *Plot method for povertyLondon().*

Description

Plot method for povertyLondon().

Usage

```
## S3 method for class 'povertyLondon'  
plot(x, district = c("City", "Westminster", "Marylebone", "St. Giles"), ...)
```

Arguments

<code>x</code>	object.
<code>district</code>	Character. Selected district(s).
<code>...</code>	Additional plotting parameters.

`plot.profile_perspective`
Plot method for profilePerspective().

Description

Plot method for profilePerspective().

Usage

```
## S3 method for class 'profile_perspective'  
plot(x, ...)
```

Arguments

<code>x</code>	An object of class "profile" created by profilePerspective().
<code>...</code>	Additional plotting parameters.

plot.time_series *Plot aggregate time series data from Vestry report.*

Description

Plot aggregate fatality data and indicates the date of the removal of the handle of the Broad Street pump.

Usage

```
## S3 method for class 'time_series'
plot(x, statistic = "fatal.attacks",
     pump.handle = TRUE, main = "Removal of the Broad Street Pump Handle",
     type = "o", xlab = "Date", ylab = "Fatalities", ...)
```

Arguments

x	An object of class "time_series" from timeSeries().
statistic	Character. Fatality measure: either "fatal.attacks" or "deaths".
pump.handle	Logical. Indicate date of removal of Broad Street pump handle.
main	Character. Title of graph.
type	Character. R plot type.
xlab	Character. x-axis label.
ylab	Character. y-axis label.
...	Additional plotting parameters.

See Also

[timeSeries](#)

Examples

```
plot(timeSeries())
plot(timeSeries(), statistic = "deaths")
plot(timeSeries(), bty = "n", type = "h", lwd = 4)
```

plot.voronoi	<i>Plot Voronoi neighborhoods.</i>
--------------	------------------------------------

Description

Plot Voronoi neighborhoods.

Usage

```
## S3 method for class 'voronoi'  
plot(x, voronoi.cells = TRUE, delaunay.triangles = FALSE,  
      euclidean.paths = FALSE, ...)
```

Arguments

`x` An object of class "voronoi" created by `neighborhoodVoronoi()`.

`voronoi.cells` Logical. Plot Voronoi tessellation cells.

`delaunay.triangles`
Logical. Plot Delaunay triangles.

`euclidean.paths`
Logical. Plot all Euclidean paths (star graph).

`...` Additional plotting parameters.

Value

A base R graph.

See Also

`neighborhoodVoronoi()`
`addVoronoi()`

Examples

```
plot(neighborhoodVoronoi())
```

plot.walking *Plot method for neighborhoodWalking().*

Description

Plot method for neighborhoodWalking().

Usage

```
## S3 method for class 'walking'  
plot(x, type = "roads", msg = FALSE, ...)
```

Arguments

x	An object of class "walking" created by neighborhoodWalking().
type	Character. "roads", "area.points" or "area.polygons". "area" flavors only valid when case.set = "expected".
msg	Logical. Toggle in-progress messages.
...	Additional plotting parameters.

Value

A base R plot.

Note

When plotting area graphs with simulated data (i.e., case.set = "expected"), there may be discrepancies between observed cases and expected neighborhoods, particularly between neighborhoods.

Examples

```
## Not run:  
plot(neighborhoodWalking())  
plot(neighborhoodWalking(case.set = "expected"))  
plot(neighborhoodWalking(case.set = "expected"), type = "area.points")  
plot(neighborhoodWalking(case.set = "expected"), type = "area.polygons")  
  
## End(Not run)
```

plot.walking_path *Plot the walking path between selected cases and/or pumps.*

Description

Plot the walking path between selected cases and/or pumps.

Usage

```
## S3 method for class 'walking_path'  
plot(x, zoom = 0.5, unit.posts = "distance",  
     unit.interval = NULL, alpha.level = 1, ...)
```

Arguments

x	An object of class "walking_path" created by walkingPath().
zoom	Logical or Numeric. A numeric value ≥ 0 controls the degree of zoom. The default is 0.5.
unit.posts	Character. "distance" for mileposts; "time" for timeposts; NULL for no posts.
unit.interval	Numeric. Set interval between posts. When unit.posts = "distance", unit.interval defaults to 50 meters. When unit.posts = "time", unit.interval defaults to 60 seconds.
alpha.level	Numeric. Alpha level transparency for path: a value in [0, 1].
...	Additional plotting parameters.

Value

A base R plot.

Note

Arrows represent mileposts or timeposts to the destination.

Examples

```
## Not run:  
plot(walkingPath(15))  
plot(walkingPath(15), unit.posts = "time")  
  
## End(Not run)
```

```
plot.winterTemperatures
```

Plot method for winterTemperatures().

Description

Plot method for winterTemperatures().

Usage

```
## S3 method for class 'winterTemperatures'  
plot(x, end.date = "1859-6-1", ...)
```

Arguments

x	object.
end.date	Date. "yyyy-mm-dd" or NULL.
...	Additional plotting parameters.

Value

A base R plot.

Examples

```
plot(winterTemperatures())
```

```
povertyLondon
```

Poverty and Born in London.

Description

Gareth Stedman Jones, p. 132. Census and Charles Booth Data, 1881.

Usage

```
povertyLondon()
```

```
print.classifier_audit
```

Return result of classifierAudit().

Description

Return result of classifierAudit().

Usage

```
## S3 method for class 'classifier_audit'  
print(x, ...)
```

Arguments

x An object of class "classifier_audit" created by classifierAudit().
... Additional parameters.

Value

An R data frame.

Examples

```
classifierAudit(case = 483, segment = "326-2")  
print(classifierAudit(case = 483, segment = "326-2"))
```

```
print.euclidean        Print method for neighborhoodEuclidean().
```

Description

Parameter values for neighborhoodEuclidean().

Usage

```
## S3 method for class 'euclidean'  
print(x, ...)
```

Arguments

x An object of class "euclidean" created by neighborhoodEuclidean().
... Additional parameters.

Value

A list of argument values.

Examples

```
## Not run:  
neighborhoodEuclidean()  
print(neighborhoodEuclidean())  
  
## End(Not run)
```

```
print.euclidean_path Print method for euclideanPath().
```

Description

Summary output.

Usage

```
## S3 method for class 'euclidean_path'  
print(x, ...)
```

Arguments

x	An object of class "euclidean_path" created by euclideanPath().
...	Additional parameters.

Value

An R data frame.

Examples

```
euclideanPath(1)  
print(euclideanPath(1))
```

print.iso	<i>Print method for isoVertices().</i>
-----------	--

Description

Print method for isoVertices().

Usage

```
## S3 method for class 'iso'  
print(x, ...)
```

Arguments

x	An object of class "iso" created by isoVertices().
...	Additional arguments.

Value

A vector with observed counts.

print.time_series	<i>Print summary data for timeSeries().</i>
-------------------	---

Description

Return summary results.

Usage

```
## S3 method for class 'time_series'  
print(x, ...)
```

Arguments

x	An object of class "time_series" created by timeSeries().
...	Additional parameters.

Value

An R data frame.

Examples

```
timeSeries()  
print(timeSeries())
```

print.voronoi	<i>Print method for neighborhoodVoronoi().</i>
---------------	--

Description

Parameter values for neighborhoodVoronoi().

Usage

```
## S3 method for class 'voronoi'  
print(x, ...)
```

Arguments

x	An object of class "voronoi" created by neighborhoodVoronoi().
...	Additional arguments.

Value

A list of argument values.

Examples

```
neighborhoodVoronoi()  
print(neighborhoodVoronoi())
```

print.walking	<i>Print method for neighborhoodWalking().</i>
---------------	--

Description

Parameter values for neighborhoodWalking().

Usage

```
## S3 method for class 'walking'  
print(x, ...)
```

Arguments

x	An object of class "walking" created by neighborhoodWalking().
...	Additional parameters.

Value

A list of argument values.

Examples

```
## Not run:  
neighborhoodWalking()  
print(neighborhoodWalking())  
  
## End(Not run)
```

`print.walking_path` *Print method for walkingPath().*

Description

Summary output.

Usage

```
## S3 method for class 'walking_path'  
print(x, ...)
```

Arguments

`x` An object of class "walking_path" created by walkingPath().
`...` Additional parameters.

Value

An R data frame.

Examples

```
## Not run:  
walkingPath()  
print(walkingPath())  
  
## End(Not run)
```

 profile2D

2D Profile .

Description

2D Profile .

Usage

```
profile2D(angle = 0, pump = 7, vestry = FALSE, type = "base",
  multi.core = TRUE)
```

Arguments

angle	Numeric. Angle of perspective axis in degrees.
pump	Numeric. Select pump as focal point.
vestry	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 in the original map.
type	Character. Type of graphic: "base" or "ggplot2".
multi.core	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. You can also specify the number logical cores. See <code>vignette("Parallelization")</code> for details.

Examples

```
## Not run:
profile2D(angle = 30)
profile2D(angle = 30, type = "ggplot2")

## End(Not run)
```

 profile3D

3D Profile.

Description

3D Profile.

Usage

```
profile3D(pump.select = NULL, pump.subset = NULL, vestry = FALSE,
  drop.neg.subset = FALSE, multi.core = TRUE)
```


Arguments

pump.select	Numeric. Vector of numeric pump IDs to define pump neighborhoods (i.e., the "population"). Negative selection possible. NULL selects all pumps.
pump.subset	Numeric. Vector of numeric pump IDs to subset from the neighborhoods defined by pump.select. Negative selection possible. NULL selects all pumps in pump.select.
vestry	Logical. TRUE uses the 14 pumps from the Vestry Report. FALSE uses the 13 in the original map.
drop.neg.subset	Logical. Drop negative subset selection
multi.core	Logical or Numeric. TRUE uses parallel::detectCores(). FALSE uses one, single core. You can also specify the number logical cores. See vignette("Parallelization") for details.

Examples

```
## Not run:
profile3D(pump.select = 6:7)
profile3D(pump.subset = -7)
profile3D(pump.subset = -7, drop.neg.subset = TRUE)

## End(Not run)
```

pumpCase	<i>Extract numeric case IDs by pump neighborhood.</i>
----------	---

Description

Extract numeric case IDs by pump neighborhood.

Usage

```
pumpCase(x, case)
```

Arguments

x	An object created by neighborhoodEuclidean(), neighborhoodVoronoi() or neighborhoodWalking().
case	Character. "address" or "fatality"

Value

An R list of numeric ID of cases by pump neighborhoods.

Examples

```
## Not run:  
pumpCase(neighborhoodEuclidean())  
pumpCase(neighborhoodVoronoi())  
pumpCase(neighborhoodWalking())  
  
## End(Not run)
```

pumpData

Compute pump coordinates.

Description

Returns either the set of x-y coordinates for the pumps themselves or for their orthogonally projected "addresses" on the network of roads.

Usage

```
pumpData(vestry = FALSE, orthogonal = FALSE, multi.core = TRUE)
```

Arguments

vestry	Logical. TRUE uses the 14 pumps from the Vestry report. FALSE uses the 13 in the original map.
orthogonal	Logical. TRUE returns pump "addresses": the coordinates of the orthogonal projection from a pump's location onto the network of roads. FALSE returns pump location coordinates.
multi.core	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. With Numeric, you specify the number logical cores (rounds with <code>as.integer()</code>). See <code>vignette("Parallelization")</code> for details.

Value

An R data frame.

Note

Note: The location of the fourteenth pump, at Hanover Square, and the "correct" location of the Broad Street pump are approximate. This function documents the code that generates [pumps](#), [pumps.vestry](#), [ortho.proj.pump](#) and [ortho.proj.pump.vestry](#).

See Also

[pumpLocator](#)

pumpLocator	<i>Locate water pump by numerical ID.</i>
-------------	---

Description

Highlight selected water pump.

Usage

```
pumpLocator(id = 7, zoom = 1, vestry = FALSE, add.title = TRUE,  
            highlight.segment = TRUE, data = FALSE)
```

Arguments

id	Numeric or Integer. With vestry = TRUE, a whole number between 1 and 14. With vestry = FALSE, a whole number between 1 and 13. See cholera::pumps.vestry and cholera::pumps for IDs and details about specific pumps.
zoom	Logical or Numeric. A numeric value ≥ 0 controls the degree of zoom. The default is 1.
vestry	Logical. TRUE for the 14 pumps from Vestry Report. FALSE for the original 13 pumps.
add.title	Logical. Include title.
highlight.segment	Logical. Highlight case's segment.
data	Logical. Output data.

Value

A base R graphics plot.

See Also

[pumpData](#)

Examples

```
pumpLocator()  
pumpLocator(zoom = TRUE)  
pumpLocator(14, vestry = TRUE, zoom = TRUE)
```

pumps

Dodson and Tobler's pump data with street name.

Description

Adds and amends road locations for water pumps from John Snow's map to Dodson and Tobler's street data. The latter are available at Michael Friendly's HistData::Snow.streets.

Usage

pumps

Format

A data frame with 13 observations and 4 variables that describe the pumps on Snow's map.

id pump number between 1 and 13

street nearest street

x x-coordinate

y y-coordinate

Note

[pumpData](#) documents the code for these data.

See Also

[pumpLocator](#)

pumps.vestry

Vestry report pump data.

Description

These data include the fourteenth pump, at Hanover Square, and the "corrected" location of the Broad Street pump that Snow includes in the second version of his map in the Vestry report.

Usage

pumps.vestry

Format

A data frame with 14 observations and 4 variables.

id pump number between 1 and 14
street nearest street
x x-coordinate
y y-coordinate

Note

[pumpData](#) documents the code for these data.

See Also

[pumpLocator](#)

regular.cases	<i>"Expected" cases.</i>
---------------	--------------------------

Description

The result of using `sp::spsample()` and `sp::Polygon()` to generate 19,993 regularly spaced simulated cases within the map's borders.

Usage

```
regular.cases
```

Format

A data frame with 2 variable that records the position of 19,993 "expected" cases fitted by `sp::spsample()`.

x x-coordinate
y y-coordinate

Note

[simulateFatalities](#) documents the code for these data.

`road.segments`*Dodson and Tobler's street data transformed into road segments.*

Description

This data set transforms Dodson and Tobler's street data to give each straight line segment of a "road" a unique ID.

Usage`road.segments`**Format**

A data frame with 657 observations and 7 variables. The data describe the straight line segments used to recreate the roads on Snow's map.

`street` numeric street ID, which range between 1 and 528

`id` character segment ID

`name` road name

`x1` x-coordinate of first endpoint

`y1` y-coordinate of first endpoint

`x2` x-coordinate of second endpoint

`y2` y-coordinate of second endpoint

Note

[roadSegments](#) documents the code for these data.

See Also

[roads](#)

`vignette("road.names")`

[streetNameLocator](#)

[streetNumberLocator](#)

[segmentLocator](#)

roads	<i>Dodson and Tobler's street data with appended road names.</i>
-------	--

Description

This data set adds road names from John Snow's map to Dodson and Tobler's street data. The latter are also available from `HistData::Snow.streets`.

Usage

```
roads
```

Format

A data frame with 206 observations and 5 variables. The data describe the roads on Snow's map.

street street segment number, which range between 1 and 528

n number of points in this street line segment

x x-coordinate

y y-coordinate

id unique numeric ID

name road name

See Also

[road.segments](#)

`vignette("road.names")`

[streetNameLocator](#)

[streetNumberLocator](#)

[segmentLocator](#)

roadSegments	<i>Reshape 'roads' data frame into 'road.segments' data frame.</i>
--------------	--

Description

Used to integrate pumps and cases into road network when computing walking neighborhoods.

Usage

```
roadSegments()
```

Value

An R data frame.

Note

This function documents the code that generates `road.segments`.

segmentHighlight	<i>Highlight segment by ID.</i>
------------------	---------------------------------

Description

Highlight segment by ID.

Usage

```
segmentHighlight(id, highlight = TRUE, col = "red", angled = FALSE)
```

Arguments

id	Character. A concatenation of a street's numeric ID, a whole number between 1 and 528, and a second number to identify the segment.
highlight	Logical. Color segment.
col	Character. Highlight color.
angled	Logical. Rotate segment ID label.

Value

A base R graphics segment(s).

Examples

```
streetNameLocator("Soho Square", zoom = TRUE, highlight = FALSE)
ids <- road.segments[road.segments$name == "Soho Square", "id"]
invisible(lapply(ids, function(x) segmentHighlight(x, highlight = FALSE)))
```

segmentLength	<i>Compute length of road segment.</i>
---------------	--

Description

Compute length of road segment.

Usage

```
segmentLength(id = "216-1", distance.unit = "meter")
```

Arguments

id	Character. A concatenation of a street's numeric ID, a whole number between 1 and 528, and a second number used to identify the sub-segments.
distance.unit	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. See vignette("roads") for information on conversion.

Value

An R vector of length one.

Examples

```
segmentLength("242-1")  
segmentLength("242-1", distance.unit = "yard")
```

segmentLocator	<i>Locate road segment by ID.</i>
----------------	-----------------------------------

Description

Highlights the selected road segment and its cases.

Usage

```
segmentLocator(id = "216-1", zoom = 0.5, cases = "address",  
distance.unit = "meter", time.unit = "second", walking.speed = 5,  
add.title = TRUE, add.subtitle = TRUE, highlight = TRUE)
```

Arguments

id	Character. A concatenation of a street's numeric ID, a whole number between 1 and 528, and a second number to identify the segment.
zoom	Logical or Numeric. A numeric value ≥ 0 controls the degree of zoom. The default is 0.5.
cases	Character. Plot cases: NULL, "address" or "fatality".
distance.unit	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. See vignette("roads") for information on conversion.
time.unit	Character. "hour", "minute", or "second".
walking.speed	Numeric. Walking speed in km/hr.
add.title	Logical. Print title.
add.subtitle	Logical. Print subtitle.
highlight	Logical. Highlight selected road and its cases.

Value

A base R graphics plot.

Note

With Dodson and Tobler's data, a street (e.g., Broad Street) is often comprised of multiple straight line segments. To identify each segment individually, an additional number is appended to form a text string ID (e.g., "116-2"). See cholera::road.segments.

Examples

```
segmentLocator("190-1")
segmentLocator("216-1")
segmentLocator("216-1", distance.unit = "yard")
```

sim.ortho.proj

Road "address" of simulated (i.e., "expected") cases.

Description

Road "address" of simulated (i.e., "expected") cases.

Usage

```
sim.ortho.proj
```

Format

A data frame with 6 variables that records the "address" of 19,993 simulate cases along the network of roads.

road.segment "address" road segment

x.proj x-coordinate

y.proj y-coordinate

dist Euclidean or orthogonal distance to home road segment

type type of projection: Euclidean ("eucl") or orthogonal ("ortho")

case numeric case ID

Note

[simulateFatalities](#) documents the code for these data.

sim.pump.case	<i>List of "simulated" fatalities grouped by walking-distance pump neighborhood.</i>
---------------	--

Description

List of "simulated" fatalities grouped by walking-distance pump neighborhood.

Usage

```
sim.pump.case
```

Format

A list 4972 IDs spread over 13 vectors.

```
sim.pump.case numerical ID
```

Note

[neighborhoodWalking](#) documents the code for these data. For details, see `vignette("pump.neighborhoods")`.

Examples

```
## Not run:
pumpCase(neighborhoodWalking(case.set = "expected"))

## End(Not run)
```

sim.walking.distance *Walking distance to Broad Street Pump (#7).*

Description

Walking distance to Broad Street Pump (#7).

Usage

```
sim.walking.distance
```

Format

A data frames with 5 variables.

case case ID

pump pump ID

pump.name pump name

distance walking distance in meters

time walking time in seconds based on 5 km/hr walking speed

simulateFatalities *Generate simulated fatalities.*

Description

Places regularly spaced "simulated" or "expected" cases across the face of the map. The function finds the "addresses" of cases via orthogonal projection or simple proximity. These data are used to generate "expected" pump neighborhoods. The function relies on `sp::spsample()` and `sp::Polygon()`.

Usage

```
simulateFatalities(compute = FALSE, multi.core = TRUE,
  simulated.obs = 20000L, dev.mode = FALSE)
```

Arguments

compute	Logical. TRUE computes data. FALSE uses pre-computed data. For replication of data used in the package,
multi.core	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. With Numeric, you specify the number logical cores (rounds with <code>as.integer()</code>). See <code>vignette("Parallelization")</code> for details.
simulated.obs	Numeric. Number of sample cases.
dev.mode	Logical. Development mode uses <code>parallel::parLapply()</code> .

Value

An R list with two elements: [sim.ortho.proj](#) and [regular.cases](#)

Note

This function is computationally intensive. With "simulated.obs" set to 20,000 simulated cases (actually generating 19,993 cases). This function documents the code that generates [sim.ortho.proj](#) and [regular.cases](#). In real world terms, the distance between of these simulated cases is approximately 6 meters.

simulateWalkingDistance

Compute walking distance for simulated cases.

Description

Compute walking distance for simulated cases.

Usage

```
simulateWalkingDistance(pump.select = 7, multi.core = TRUE,  
  dev.mode = FALSE, compute = FALSE)
```

Arguments

<code>pump.select</code>	Numeric.
<code>multi.core</code>	Logical or Numeric. TRUE uses <code>parallel::detectCores()</code> . FALSE uses one, single core. You can also specify the number logical cores.
<code>dev.mode</code>	Logical. Development mode uses <code>parallel::parLapply()</code> .
<code>compute</code>	Logical.

Note

This function is computationally intensive. See `vignette("Parallelization")` for details. This functions document the code that generates [sim.walking.distance](#).

snow.neighborhood *Snow neighborhood fatalities.*

Description

Numeric IDs of fatalities from Dodson and Tobler that fall within Snow's Broad Street pump neighborhood.

Usage

```
snow.neighborhood
```

Format

A vector with 384 observations.

```
snow.neighborhood numeric case ID
```

snowColors *Create a set of colors for pump neighborhoods.*

Description

Uses RColorBrewer::brewer.pal().

Usage

```
snowColors(vestry = FALSE)
```

Arguments

vestry Logical. TRUE uses the 14 pumps in the Vestry Report. FALSE uses the original 13.

Value

A character vector of colors.

Note

Built with 'RColorBrewer' package.

snowMap	<i>Plot John Snow's cholera map.</i>
---------	--------------------------------------

Description

Plot John Snow's cholera map.

Usage

```
snowMap(vestry = FALSE, stacked = TRUE, add.cases = TRUE,  
        add.landmarks = FALSE, add.pumps = TRUE, add.roads = TRUE,  
        add.frame = TRUE, main = NA, case.col = "gray", case.pch = 15, ...)
```

Arguments

vestry	Logical. TRUE uses the 14 pumps from the map in the Vestry Report. FALSE uses the 13 pumps from the original map.
stacked	Logical. Use stacked fatalities.
add.cases	Logical. Add observed cases.
add.landmarks	Logical. Add landmarks.
add.pumps	Logical. Add pumps.
add.roads	Logical. Add roads.
add.frame	Logical. Add map frame.
main	Character. Title of graph.
case.col	Character. Color of fatalities.
case.pch	Character. Color of fatalities.
...	Additional plotting parameters.

Value

A base R graphics plot.

Note

Uses amended version of Dodson and Tobler's data included in this package.

Examples

```
snowMap()  
snowMap(vestry = TRUE, stacked = FALSE)
```

snowNeighborhood	<i>Plotting data for Snow's graphical annotation of the Broad Street pump neighborhood.</i>
------------------	---

Description

Computes "missing" and split road segments data, and area plot data.

Usage

```
snowNeighborhood()
```

Value

An R list of edge IDs and simulated case IDs.

streetHighlight	<i>Highlight road by name.</i>
-----------------	--------------------------------

Description

Highlight road by name.

Usage

```
streetHighlight(road.name)
```

Arguments

road.name	Character vector. The functions tries to correct for case and to remove extra spaces.
-----------	---

Value

A base R graphics segment(s).

Examples

```
snowMap()  
streetHighlight("Broad Street")
```

streetLength	<i>Compute length of selected street.</i>
--------------	---

Description

Compute length of selected street.

Usage

```
streetLength(road = "Oxford Street", distance.unit = "meter")
```

Arguments

road	Character or Numeric. Road name or number. For names, the function tries to correct for case and to remove extra spaces.
distance.unit	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. See vignette("roads") for information on conversion.

Value

An R vector of length one.

Examples

```
streetLength("Oxford Street")
streetLength("oxford street")
streetLength("oxford street", distance.unit = "yard")
```

streetNameLocator	<i>Locate road by name.</i>
-------------------	-----------------------------

Description

Highlight a road and its cases. See the list of road names in vignette("road.names").

Usage

```
streetNameLocator(road.name = "Broad Street", zoom = FALSE,
  cases = "address", token = "id", add.title = TRUE,
  add.subtitle = TRUE, add.pump = TRUE, vestry = FALSE,
  highlight = TRUE, distance.unit = "meter", time.unit = "minute",
  walking.speed = 5)
```

Arguments

road.name	Character vector. Note that <code>streetNameLocator()</code> tries to correct for case and to remove extra spaces.
zoom	Logical or Numeric. A numeric value ≥ 0 controls the degree of zoom. The default is FALSE, which is equivalent to zero.
cases	Character. Plot cases: NULL, "address" or "fatality".
token	Character. "id" or "point".
add.title	Logical. Include title.
add.subtitle	Logical. Include subtitle with road information.
add.pump	Logical. Include nearby pumps.
vestry	Logical. TRUE uses the 14 pumps from the Vestry report. FALSE uses the 13 in the original map.
highlight	Logical. Highlight selected road and its cases.
distance.unit	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. See <code>vignette("roads")</code> for information on conversion.
time.unit	Character. "hour", "minute", or "second".
walking.speed	Numeric. Walking speed in km/hr.

Value

A base R graphics plot.

Examples

```
streetNameLocator("Oxford Street")
streetNameLocator("oxford street")
streetNameLocator("Cambridge Street", zoom = TRUE)
streetNameLocator("Cambridge Street", zoom = 0.5)
```

streetNames	<i>Street names (alphabetized).</i>
-------------	-------------------------------------

Description

Unique road names from Snow's cholera map.

Usage

```
streetNames()
```

Value

An R character vector.

Note

See `vignette("roads")`, and `roads` and `road.segment` data frames.

streetNumberLocator *Locate road by numerical ID.*

Description

Highlight a road and its cases. See `cholera::roads` for numerical IDs and `vignette("road.names")` for details.

Usage

```
streetNumberLocator(road.number = 216, zoom = FALSE, cases = "address",
  token = "id", add.title = TRUE, add.subtitle = TRUE, add.pump = TRUE,
  vestry = FALSE, highlight = TRUE, distance.unit = "meter",
  time.unit = "second", walking.speed = 5)
```

Arguments

<code>road.number</code>	Numeric or integer. A whole number between 1 and 528.
<code>zoom</code>	Logical or Numeric. A numeric value ≥ 0 controls the degree of zoom. The default is FALSE, which is equivalent to zero.
<code>cases</code>	Character. Plot cases: NULL, "address" or "fatality".
<code>token</code>	Character. "id" or "point".
<code>add.title</code>	Logical. Include title.
<code>add.subtitle</code>	Logical. Include subtitle with road information.
<code>add.pump</code>	Logical. Include nearby pumps.
<code>vestry</code>	Logical. TRUE uses the 14 pumps from the Vestry report. FALSE uses the 13 in the original map.
<code>highlight</code>	Logical. Highlight selected road and its cases.
<code>distance.unit</code>	Character. Unit of measurement: "meter" or "yard". Default is NULL, which returns the map's native scale.
<code>time.unit</code>	Character. "hour", "minute", or "second".
<code>walking.speed</code>	Numeric. Walking speed in km/hr.

Value

A base R graphics plot.

Examples

```
streetNumberLocator(243)
streetNumberLocator(243, zoom = TRUE)
streetNumberLocator(243, zoom = 0.5)
```

subsetRoadsSamples *Sample for road segment endpoints.*

Description

For endpoints with 1 or 3 intersections.

Usage

```
subsetRoadsSamples()
```

summary.euclidean *Summary method for neighborhoodEuclidean().*

Description

Return computed counts for Euclidean neighborhoods.

Usage

```
## S3 method for class 'euclidean'
summary(object, ...)
```

Arguments

object Object. An object of class "euclidean" created by neighborhoodEuclidean().
 ... Additional parameters.

Value

A vector of counts by neighborhood.

Examples

```
## Not run:
summary(neighborhoodEuclidean())

## End(Not run)
```

summary.voronoi	<i>Summary method for neighborhoodVoronoi().</i>
-----------------	--

Description

Return computed counts for Voronoi neighborhoods.

Usage

```
## S3 method for class 'voronoi'  
summary(object, ...)
```

Arguments

object	Object. An object of class "voronoi" created by neighborhoodVoronoi().
...	Additional arguments.

Value

A vector of counts by neighborhood.

See Also

addVoronoi() plot.voronoi()

Examples

```
summary(neighborhoodVoronoi())
```

summary.walking	<i>Summary method for neighborhoodWalking().</i>
-----------------	--

Description

Return computed counts for walking neighborhoods.

Usage

```
## S3 method for class 'walking'  
summary(object, ...)
```

Arguments

object	Object. An object of class "walking" created by neighborhoodWalking().
...	Additional parameters.

Value

An R vector.

Examples

```
## Not run:  
summary(neighborhoodWalking())  
  
## End(Not run)
```

timeSeries	<i>Aggregate time series fatality data from the Vestry report.</i>
------------	--

Description

Aggregate time series fatality data from the Vestry report.

Usage

```
timeSeries(vestry = FALSE)
```

Arguments

vestry Logical. TRUE returns the data from the Vestry committee (Appendix B, p. 175). FALSE returns John Snow's contribution to the report (p.117).

Value

A R list with two objects: "data" and "source" ("snow" or "vestry").

- date: Calendar date.
- day: Day of the week.
- deaths: Measure of fatality.
- fatal.attacks: Measure of fatality.

Note

The "snow" data appears on p. 117 of the report; the "vestry" data appear in Appendix B on p.175.

See Also

[plot.time_series](#), [print.time_series](#), [vignette\("time.series"\)](#)

Examples

```
timeSeries(vestry = TRUE)  
plot(timeSeries())
```

unitMeter	<i>Convert nominal map distance to meters or yards.</i>
-----------	---

Description

A best guess estimate.

Usage

```
unitMeter(x, output.unit = "meter")
```

Arguments

x	Numeric. Nominal map distance.
output.unit	Character. Unit of distance: "meter", "yard" or "nominal". "nominal" returns the map's nominal scale. See vignette("roads") for information on conversion.

unstackFatalities	<i>Unstack "stacks" in Snow's cholera map.</i>
-------------------	--

Description

Unstacks fatalities data by 1) assigning the coordinates of the base case to all cases in a stack and 2) setting the base case as an "address" and making the number of fatalities an attribute.

Usage

```
unstackFatalities(multi.core = TRUE, compute = FALSE,
  fatalities = fixFatalities(), dev.mode = FALSE)
```

Arguments

multi.core	Logical or Numeric. TRUE uses parallel::detectCores(). FALSE uses one, single core. With Numeric, you specify the number logical cores. See vignette("Parallelization") for details.
compute	Logical. TRUE computes data. FALSE uses pre-computed data.
fatalities	Corrected fatalities data from cholera::fixFatalities(). For original data, use HistData::Snow.deaths.
dev.mode	Logical. Development mode uses parallel::parLapply().

Value

An R list that includes anchor.case, fatalities.address, fatalities.unstacked and ortho.proj.

Note

This function is computationally intensive. This function documents the code that generates [anchor.case](#), [fatalities.address](#), [fatalities.unstacked](#) and [ortho.proj](#).

See Also

`vignette("unstacking.fatalities")`

voronoiPolygons	<i>Extract vertices of Delaunay triangles and Dirichelet (Voronoi) tiles.</i>
-----------------	---

Description

For construction and plotting of Delaunay and Voronoi polygons.

Usage

```
voronoiPolygons(sites, rw.data = NULL, rw = NULL, type = "tiles",
  output = "vertices")
```

Arguments

sites	Object. Data frame of sites to compute Delaunay triangulation and Dirichelet (Voronoi) tessellation with variables "x" and "y".
rw.data	Object. Data frame of secondary source of data to set the rectangular window or bounding box: observations, cases, etc. with variables "x" and "y".
rw	Numeric. Alternative to rw.data: vector of corners to define the rectangular window or bounding box: xmin, xmax, ymin, ymax.
type	Character. "tiles" (tessellation) or "triangles" (triangulation) vertices.
output	Character. "vertices" or "polygons". "vertices" re "polygons" will draw base R polygons() to an existing plot.

Value

An R list of data frames or base R graphics polygon()'s'.

Note

This function relies on the 'deldir' package.

Examples

```

snowMap()
voronoiPolygons(pumps, output = "polygons")

snowMap()
voronoiPolygons(pumps, roads, output = "polygons")

snowMap()
voronoiPolygons(pumps, roads, type = "triangles", output = "polygons")

vertices <- voronoiPolygons(pumps, roads)
snow.colors <- grDevices::adjustcolor(snowColors(), alpha.f = 1/3)
snowMap(add.cases = FALSE)
invisible(lapply(seq_along(vertices), function(i) {
  polygon(vertices[[i]], col = snow.colors[[i]])
}))

```

walkingPath

Compute the shortest walking path between cases and/or pumps.

Description

Compute the shortest walking path between cases and/or pumps.

Usage

```

walkingPath(origin = 1, destination = NULL, type = "case-pump",
  observed = TRUE, weighted = TRUE, vestry = FALSE,
  distance.unit = "meter", time.unit = "second", walking.speed = 5)

```

Arguments

origin	Numeric or Character. Numeric ID of case or pump. Character landmark name.
destination	Numeric or Character. Numeric ID(s) of case(s) or pump(s). Exclusion is possible via negative selection (e.g., -7). Default is NULL: this returns closest pump or "anchor" case. Character landmark name (case insensitive).
type	Character "case-pump", "cases" or "pumps".
observed	Logical. Use observed or "simulated" expected data.
weighted	Logical. TRUE computes shortest path in terms of road length. FALSE computes shortest path in terms of nodes.
vestry	Logical. TRUE uses the 14 pumps from the Vestry report. FALSE uses the 13 in the original map.
distance.unit	Character. Unit of distance: "meter", "yard" or "native". "native" returns the map's native scale. "unit" is meaningful only when "weighted" is TRUE. See vignette("roads") for information on unit distances.
time.unit	Character. "hour", "minute", or "second".
walking.speed	Numeric. Walking speed in km/hr.

Value

An R list with two elements: a character vector of path nodes and a data frame summary.

Note

The function uses a case's "address" (i.e., a stack's "anchor" case) to compute distance. Time is computed using `distanceTime()`. Adam and Eve Court, and Falconberg Court and Falconberg Mews, are disconnected from the larger road network; they form two isolated subgraphs. This has two consequences: first, only cases on Adam and Eve Court can reach pump 2 and those cases cannot reach any other pump; second, cases on Falconberg Court and Mews cannot reach any pump. Unreachable pumps will return distances of "Inf".

Examples

```
## Not run:
# path from case 1 to nearest pump.
walkingPath(1)

# path from pump 1 to nearest case.
walkingPath(NULL, 1)

# path from case 1 to pump 6.
walkingPath(1, 6)

# exclude pump 7 from consideration.
walkingPath(1, -7)

# path from case 1 to case 6.
walkingPath(1, 6, type = "cases")

# path from pump 1 to pump 6.
walkingPath(1, 6, type = "pumps")

# for multiple cases.
lapply(1:3, walkingPath)

# path from case 1 to nearest pump.
plot(walkingPath(1))

# path from John Snow's residence to Broad Street pump.
plot(walkingPath("John Snow", 7))

## End(Not run)
```

winterTemperatures *Average Winter Temperatures.*

Description

Gareth Stedman Jones Appendix 2, Table 12, p.384.

Usage

```
winterTemperatures()
```

Examples

```
plot(winterTemperatures(), "1859-6-1")
```

withinRadius	<i>Test whether point "b" is within a given radius of point "a".</i>
--------------	--

Description

Test whether point "b" is within a given radius of point "a".

Usage

```
withinRadius(a, b, radius = 2)
```

Arguments

a	Numeric. Data frame of x-y coordinates.
b	Numeric. Data frame of x-y coordinates.
radius	Numeric.

Index

* datasets

- anchor.case, 20
- border, 21
- fatalities, 25
- fatalities.address, 26
- fatalities.unstacked, 26
- landmark.squares, 29
- landmarks, 30
- ortho.proj, 36
- ortho.proj.pump, 36
- ortho.proj.pump.vestry, 37
- oxford.weather, 38
- plague.pit, 40
- pumps, 60
- pumps.vestry, 60
- regular.cases, 61
- road.segments, 62
- roads, 63
- sim.ortho.proj, 66
- sim.pump.case, 67
- sim.walking.distance, 68
- snow.neighborhood, 70

- addCase, 5
- addDelaunay, 6
- addEuclideanPath, 6
- addFrame, 7
- addIndexCase, 8
- addKernelDensity, 8
- addLandmarks, 10
- addMilePosts, 10
- addNeighborhoodCases, 11
- addNeighborhoodEuclidean, 12
- addNeighborhoodWalking, 14
- addPlaguePit, 15
- addPump, 16
- addRoads, 16
- addSnow, 17
- addVoronoi, 17
- addWalkingPath, 18

- addWhitehead, 19
- anchor.case, 20, 80
- border, 21
- caseLocator, 20, 21, 25–27
- cholera-package, 4
- classifierAudit, 22
- distanceTime, 23
- euclideanPath, 23
- fatalities, 25
- fatalities.address, 26, 80
- fatalities.unstacked, 26, 80
- fixFatalities, 25, 27
- isoLines, 28
- isoVertices, 28
- landmark.squares, 29
- landmarkData, 29, 30
- landmarks, 30
- mapRange, 30
- nearestPump, 31
- neighborhoodData, 32
- neighborhoodEuclidean, 32
- neighborhoodVoronoi, 33
- neighborhoodWalking, 35, 67
- ortho.proj, 36, 80
- ortho.proj.pump, 36, 58
- ortho.proj.pump.vestry, 37, 58
- orthogonalProjection, 38
- oxford.weather, 38
- oxfordWeather, 39
- pearsonResiduals, 40
- plague.pit, 40

plot.classifier_audit, 41
plot.euclidean, 41
plot.euclidean_path, 42
plot.iso, 43
plot.neighborhood_data, 44
plot.oxfordWeather, 44
plot.povertyLondon, 45
plot.profile_perspective, 45
plot.time_series, 46, 78
plot.voronoi, 47
plot.walking, 48
plot.walking_path, 49
plot.winterTemperatures, 50
povertyLondon, 50
print.classifier_audit, 51
print.euclidean, 51
print.euclidean_path, 52
print.iso, 53
print.time_series, 53, 78
print.voronoi, 54
print.walking, 54
print.walking_path, 55
profile2D, 56
profile3D, 56
pumpCase, 57
pumpData, 37, 58, 59–61
pumpLocator, 58, 59, 60, 61
pumps, 58, 60
pumps.vestry, 58, 60

regular.cases, 61, 69
road.segments, 62, 63, 64
roads, 62, 63
roadSegments, 62, 63

segmentHighlight, 64
segmentLength, 65
segmentLocator, 62, 63, 65
sim.ortho.proj, 66, 69
sim.pump.case, 67
sim.walking.distance, 68, 69
simulateFatalities, 61, 67, 68
simulateWalkingDistance, 69
snow.neighborhood, 70
snowColors, 70
snowMap, 71
snowNeighborhood, 72
streetHighlight, 72
streetLength, 73
streetNameLocator, 25–27, 62, 63, 73
streetNames, 74
streetNumberLocator, 25–27, 62, 63, 75
subsetRoadsSamples, 76
summary.euclidean, 76
summary.voronoi, 77
summary.walking, 77

timeSeries, 46, 78

unitMeter, 79
unstackFatalities, 20, 26, 27, 36, 79

voronoiPolygons, 80

walkingPath, 81
winterTemperatures, 82
withinRadius, 83