

Package ‘equatiomatic’

January 31, 2022

Title Transform Models into 'LaTeX' Equations

Version 0.3.1

Description The goal of 'equatiomatic' is to reduce the pain associated with writing 'LaTeX' formulas from fitted models. The primary function of the package, `extract_eq()`, takes a fitted model object as its input and returns the corresponding 'LaTeX' code for the model.

License CC BY 4.0

Depends R (>= 3.3.0)

URL <https://github.com/datalorax/equatiomatic>,
<https://datalorax.github.io/equatiomatic/>

BugReports <https://github.com/datalorax/equatiomatic/issues>

Imports broom (>= 0.7.0), broom.mixed, shiny, knitr, stats, utils

Suggests covr, shinyWidgets, forecast (>= 8.13), ggplot2 (>= 3.3.3),
latex2exp (>= 0.4.0), lme4, MASS, ordinal, rmarkdown, testthat
(>= 3.0.0), texPreview, gtsummary

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

Config/testthat/edition 3

Config/testthat/parallel true

NeedsCompilation no

Author Daniel Anderson [aut, cre] (<<https://orcid.org/0000-0003-4699-4680>>),
Andrew Heiss [aut] (<<https://orcid.org/0000-0002-3948-3914>>),
Jay Sumners [aut],
Joshua Rosenberg [ctb] (<<https://orcid.org/0000-0003-2170-0447>>),
Jonathan Sidi [ctb] (<<https://orcid.org/0000-0002-4222-1819>>),
Ellis Hughes [ctb] (<<https://orcid.org/0000-0003-0637-4436>>),
Thomas Fung [ctb] (<<https://orcid.org/0000-0003-2601-0728>>),

Reza Norouzian [ctb] (<<https://orcid.org/0000-0002-0531-6886>>),
 Indrajeet Patil [ctb] (<<https://orcid.org/0000-0003-1995-6531>>,
 @patilindrajeets)

Maintainer Daniel Anderson <daniela@uoregon.edu>

Repository CRAN

Date/Publication 2022-01-30 23:20:02 UTC

R topics documented:

arrests	2
extract_eq	3
hsb	6
penguins	7
polls	8
print.equation	9
renderEq	9
simple_ts	10
sim_longitudinal	10
ts_reg_list	11

Index **12**

arrests	<i>Arrest data from Gelman & Hill</i>
---------	---

Description

Arrest data from Gelman & Hill's book, used in Chapter 6 (and others). The data have been aggregated by precinct and race/ethnicity, with the sum of prior arrests and stops calculated. You can download the original data here: <http://www.stat.columbia.edu/~gelman/arm/examples/police/>

Usage

arrests

Format

A tibble with 225 rows and 4 variables:

precinct An integer denoting the precinct identification number.

eth A factor with the coded race/ethnicity

stops The number of police stops

arrests The number of prior arrests (this is used as an offset variable in the book)

 extract_eq

'LaTeX' code for R models

Description

[Maturing] Extract the variable names from a model to produce a 'LaTeX' equation, which is output to the screen. Supports any model supported by [broom::tidy](#).

Usage

```
extract_eq(
  model,
  intercept = "alpha",
  greek = "beta",
  greek_colors = NULL,
  subscript_colors = NULL,
  var_colors = NULL,
  var_subscript_colors = NULL,
  raw_tex = FALSE,
  swap_var_names = NULL,
  swap_subscript_names = NULL,
  ital_vars = FALSE,
  label = NULL,
  index_factors = FALSE,
  show_distribution = FALSE,
  wrap = FALSE,
  terms_per_line = 4,
  operator_location = "end",
  align_env = "aligned",
  use_coefs = FALSE,
  coef_digits = 2,
  fix_signs = TRUE,
  font_size = NULL,
  mean_separate,
  return_variances = FALSE,
  ...
)
```

Arguments

model	A fitted model
intercept	How should the intercept be displayed? Default is "alpha", but can also accept "beta", in which case the it will be displayed as beta zero.
greek	What notation should be used for coefficients? Currently only accepts "beta" (with plans for future development). Can be used in combination with raw_tex to use any notation, e.g., "\hat{\beta}".

<code>greek_colors</code>	The colors of the greek notation in the equation. Must be a single color (named or HTML hex code) or a vector of colors (which will be recycled if smaller than the number of terms in the model). When rendering to PDF, I suggest using HTML hex codes, as not all named colors are recognized by LaTeX, but equationmatic will internally create the color definitions for you if HTML codes are supplied. Note that this is not yet implemented for mixed effects models (lme4).
<code>subscript_colors</code>	The colors of the subscripts for the greek notation. The argument structure is equivalent to <code>greek_colors</code> (i.e., see above for more detail).
<code>var_colors</code>	The color of the variable names. This takes a named vector of the form <code>c("variable" = "color")</code> . For example <code>c("bill_length_mm" = "#00d4fa", "island" = "#00fa85")</code> . Colors can be names (e.g., "red") or HTML hex codes, as shown in the example.
<code>var_subscript_colors</code>	The colors of the factor subscripts for categorical variables. The interface for this is equivalent to <code>var_colors</code> , and all subscripts for a given variable will be displayed in the provided color. For example, the code <code>c("island" = "green")</code> would result in the subscripts for "Dream" and "Torgersen" being green (assuming "Biscoe" was the reference group).
<code>raw_tex</code>	Logical. Is the greek code being passed to denote coefficients raw tex code?
<code>swap_var_names</code>	A vector of the form <code>c("old_var_name" = "new name")</code> . For example: <code>c("bill_length_mm" = "Bill Length (MM)")</code> .
<code>swap_subscript_names</code>	A vector of the form <code>c("old_subscript_name" = "new name")</code> . For example: <code>c("f" = "Female")</code> .
<code>ital_vars</code>	Logical, defaults to FALSE. Should the variable names not be wrapped in the <code>\operatorname{}</code> command?
<code>label</code>	A label for the equation, which can then be used for in-text references. See example here . Note that this only works for PDF output . The in-text references also must match the label exactly, and must be formatted as <code>\ref{eq: label}</code> , where <code>label</code> is a place holder for the specific label. Notice the space after the colon before the label. This also must be there, or the cross-reference will fail.
<code>index_factors</code>	Logical, defaults to FALSE. Should the factors be indexed, rather than using subscripts to display all levels?
<code>show_distribution</code>	Logical. When fitting a logistic or probit regression, should the binomial distribution be displayed? Defaults to FALSE.
<code>wrap</code>	Logical, defaults to FALSE. Should the terms on the right-hand side of the equation be split into multiple lines? This is helpful with models with many terms.
<code>terms_per_line</code>	Integer, defaults to 4. The number of right-hand side terms to include per line. Used only when <code>wrap</code> is TRUE.
<code>operator_location</code>	Character, one of "end" (the default) or "start". When terms are split across multiple lines, they are split at mathematical operators like +. If set to "end",

	each line will end with a trailing operator (+ or -). If set to “start”, each line will begin with an operator.
align_env	TeX environment to wrap around equation. Must be one of aligned, aligned*, align, or align*. Defaults to aligned.
use_coefs	Logical, defaults to FALSE. Should the actual model estimates be included in the equation instead of math symbols?
coef_digits	Integer, defaults to 2. The number of decimal places to round to when displaying model estimates.
fix_signs	Logical, defaults to FALSE. If disabled, coefficient estimates that are negative are preceded with a "+" (e.g. $5(x) + -3(z)$). If enabled, the "+ -" is replaced with "-" (e.g. $5(x) -3(z)$).
font_size	The font size of the equation. Defaults to default of the output format. Takes any of the standard LaTeX arguments (see here).
mean_separate	Currently only support for lmer models. Should the mean structure be inside or separated from the normal distribution? Defaults to NULL, in which case it will become TRUE if there are more than three fixed-effect parameters. If TRUE, the equation will be displayed as, for example, $\text{outcome} \sim N(\mu, \sigma)$; $\mu = \alpha + \beta_1(\text{wave})$. If FALSE, this same equation would be $\text{outcome} \sim N(\alpha + \beta, \sigma)$.
return_variances	Logical. When use_coefs = TRUE with a mixed effects model (e.g., <code>lme4::lmer()</code>), should the variances and co-variances be returned? If FALSE (the default) standard deviations and correlations are returned instead.
...	Additional arguments (for future development; not currently used).

Value

A character of class “equation”.

Examples

```
# Simple model
mod1 <- lm(mpg ~ cyl + disp, mtcars)
extract_eq(mod1)

# Include all variables
mod2 <- lm(mpg ~ ., mtcars)
extract_eq(mod2)

# Works for categorical variables too, putting levels as subscripts
mod3 <- lm(body_mass_g ~ bill_length_mm + species, penguins)
extract_eq(mod3)

set.seed(8675309)
d <- data.frame(
  cat1 = rep(letters[1:3], 100),
  cat2 = rep(LETTERS[1:3], each = 100),
  cont1 = rnorm(300, 100, 1),
```

```

    cont2 = rnorm(300, 50, 5),
    out = rnorm(300, 10, 0.5)
  )
mod4 <- lm(out ~ ., d)
extract_eq(mod4)

# Don't italicize terms
extract_eq(mod1, ital_vars = FALSE)

# Wrap equations in an "aligned" environment
extract_eq(mod2, wrap = TRUE)

# Wider equation wrapping
extract_eq(mod2, wrap = TRUE, terms_per_line = 4)

# Include model estimates instead of Greek letters
extract_eq(mod2, wrap = TRUE, terms_per_line = 2, use_coefs = TRUE)

# Don't fix doubled-up "+" "-" signs
extract_eq(mod2, wrap = TRUE, terms_per_line = 4, use_coefs = TRUE, fix_signs = FALSE)

# Use indices for factors instead of subscripts
extract_eq(mod2, wrap = TRUE, terms_per_line = 4, index_factors = TRUE)

# Use other model types, like glm
set.seed(8675309)
d <- data.frame(
  out = sample(0:1, 100, replace = TRUE),
  cat1 = rep(letters[1:3], 100),
  cat2 = rep(LETTERS[1:3], each = 100),
  cont1 = rnorm(300, 100, 1),
  cont2 = rnorm(300, 50, 5)
)
mod5 <- glm(out ~ ., data = d, family = binomial(link = "logit"))
extract_eq(mod5, wrap = TRUE)

```

hsb

A subset of the full 1982 High School and Beyond Survey

Description

This is the dataset used throughout Raudenbush & Bryk (2002).

Usage

hsb

Format

A tibble with 7185 rows and 8 variables:

sch.id An integer denoting the school identification number. There are 160 unique schools.

math Individual students' math score.

size The number of students in the school.

sector A dummy variable (integer) denoting whether the school is public (sector = 0) or catholic (sector = 1). There are 90 public schools and 70 catholic.

meanses A group-mean centered SES variable at the school level

minority A dummy variable indicating if the student was coded as white (minority = 0) or not (minority = 1).

female A dummy variable indicating if the student was coded as female (female = 1) or not (female = 0).

ses A student-level composite variable indicating the students' socio-economic status.

penguins	<i>Size measurements for adult foraging penguins near Palmer Station, Antarctica</i>
----------	--

Description

Data originally from [palmerpenguins](#). Includes measurements for penguin species, island in Palmer Archipelago, size (flipper length, body mass, bill dimensions), and sex.

Usage

penguins

Format

A tibble with 344 rows and 8 variables:

species a factor denoting penguin species (Adélie, Chinstrap and Gentoo)

island a factor denoting island in Palmer Archipelago, Antarctica (Biscoe, Dream or Torgersen)

bill_length_mm a number denoting bill length (millimeters)

bill_depth_mm a number denoting bill depth (millimeters)

flipper_length_mm an integer denoting flipper length (millimeters)

body_mass_g an integer denoting body mass (grams)

sex a factor denoting penguin sex (female, male)

year an integer denoting the study year (2007, 2008, or 2009)

Source

Adélie penguins: Palmer Station Antarctica LTER and K. Gorman. 2020. Structural size measurements and isotopic signatures of foraging among adult male and female Adélie penguins (*Pygoscelis adeliae*) nesting along the Palmer Archipelago near Palmer Station, 2007-2009 ver 5. Environmental Data Initiative doi: [10.6073/pasta/98b16d7d563f265cb52372c8ca99e60f](https://doi.org/10.6073/pasta/98b16d7d563f265cb52372c8ca99e60f)

Gentoo penguins: Palmer Station Antarctica LTER and K. Gorman. 2020. Structural size measurements and isotopic signatures of foraging among adult male and female Gentoo penguin (*Pygoscelis papua*) nesting along the Palmer Archipelago near Palmer Station, 2007-2009 ver 5. Environmental Data Initiative doi: [10.6073/pasta/7fca67fb28d56ee2ffa3d9370ebda689](https://doi.org/10.6073/pasta/7fca67fb28d56ee2ffa3d9370ebda689)

Chinstrap penguins: Palmer Station Antarctica LTER and K. Gorman. 2020. Structural size measurements and isotopic signatures of foraging among adult male and female Chinstrap penguin (*Pygoscelis antarcticus*) nesting along the Palmer Archipelago near Palmer Station, 2007-2009 ver 6. Environmental Data Initiative doi: [10.6073/pasta/c14dfcfada8ea13a17536e73eb6fbe9e](https://doi.org/10.6073/pasta/c14dfcfada8ea13a17536e73eb6fbe9e)

Originally published in: Gorman KB, Williams TD, Fraser WR (2014) Ecological Sexual Dimorphism and Environmental Variability within a Community of Antarctic Penguins (Genus *Pygoscelis*). PLoS ONE 9(3): e90081. doi: [10.1371/journal.pone.0090081](https://doi.org/10.1371/journal.pone.0090081)

polls

The polls data from Gelman and Hill ()

Description

This is the dataset used in Gelman & Hill's book, *Data Analysis Using Regression and Multi-level/Hierarchical Models*. They are polling data on the presidential election from 1988, collected one week before the election. You can download all the data from the book here: <http://www.stat.columbia.edu/~gelman/arm/> Note that this is only a few of the variables from the original data supplied with the book.

Usage

polls

Format

A tibble with 13,544 rows and 7 variables:

state An integer denoting the state identification number.

edu An ordered factor stating the education level of the respondent

age An unordered factor stating the age of range of the respondent

female A dummy variable (integer) denoting whether the respondent was coded as male (female = 0) or female (female = 1).

black A dummy variable (integer) denoting whether the respondent was coded as Black (black = 1) or not Black (black = 0).

weight A sampling weight

bush Whether the respondent stated they were in favor of voting for George Bush Sr.

print.equation	<i>Print 'LaTeX' equations</i>
----------------	--------------------------------

Description

```
lifecycle::badge("stable")
```

Usage

```
## S3 method for class 'equation'
print(x, ...)
```

Arguments

x	'LaTeX' equation built with extract_eq
...	not used

Details

Print 'LaTeX' equations built with [extract_eq](#).

renderEq	<i>Display equations in shiny apps</i>
----------	--

Description

[Experimental]

Usage

```
renderEq(expr, env = parent.frame(), quoted = FALSE, outputArgs = list())

eqOutput(outputId)
```

Arguments

expr	An R expression, specifically a call to extract_eq()
env	The environment
quoted	Is the expression quoted?
outputArgs	list of output arguments
outputId	The identifier of the output from the server. Should be passed as a string.

Details

These are a set of functions designed to help render equations in [shiny](#) applications. For a complete example see

Functions

- renderEq: Rendering function
- eqOutput: Output function

simple_ts	<i>Simple simulated time series data</i>
-----------	--

Description

Output from `set.seed(42); simple_ts <- ts(rnorm(1000), freq = 4)`. This is included primarily for unit testing.

Usage

```
simple_ts
```

Format

A tibble with 1000 rows and 8 variables:

- Qtr1** First quarter simulated values.
- Qtr2** Second quarter simulated values.
- Qtr3** Third quarter simulated values.
- Qtr4** Fourth quarter simulated values.

sim_longitudinal	<i>Simulated longitudinal data</i>
------------------	------------------------------------

Description

Data are simulated to be similar to longitudinal data collected within schools/districts.

Usage

```
sim_longitudinal
```

Format

A tibble with 1000 rows and 8 variables:

sid An integer denoting the individual student. There are 100 students.

school An integer denoting the school. There are 15 schools.

district An integer denoting the school district. There are 5 districts.

group A character variable denoting the instructional level of the student, low, medium, or high.

treatment A factor indicating whether the student received the intervention treatment (0 = no treatment received; 1 = treatment received).

prop_low The proportion of student in the school in the low instructional group.

wave The assessment wave. Each student has nine waves of data collection.

score The individual students' score at the given wave.

ts_reg_list

Simulated data for time-series regression

Description

Output from `set.seed(42); ts_reg_list <- list(x1 = rnorm(1000), x2 = rnorm(1000), ts_rnorm = rnorm(1000))`.

Usage

ts_reg_list

Format

A tibble with 1000 rows and 8 variables:

x1 Random normal simulated data.

x2 Random normal simulated data.

ts_rnorm Random normal simulated data.

Index

* datasets

- arrests, [2](#)
- hsb, [6](#)
- penguins, [7](#)
- polls, [8](#)
- sim_longitudinal, [10](#)
- simple_ts, [10](#)
- ts_reg_list, [11](#)

arrests, [2](#)

broom::tidy, [3](#)

eqOutput (renderEq), [9](#)

extract_eq, [3](#), [9](#)

extract_eq(), [9](#)

hsb, [6](#)

lmer, [5](#)

penguins, [7](#)

polls, [8](#)

print.equation, [9](#)

renderEq, [9](#)

shiny, [10](#)

sim_longitudinal, [10](#)

simple_ts, [10](#)

ts_reg_list, [11](#)