

Package ‘eurodata’

August 31, 2022

Type Package

Title Fast and Easy Eurostat Data Import and Search

Description Interface to Eurostat’s Bulk Download Facility with fast data.table-based import of data, labels, and metadata. On top of the core functionality, data search and data description/comparison functions are also provided.

Version 1.5.0

Date 2022-08-30

License GPL-2

URL <https://github.com/alekrutkowski/eurodata/>

Encoding UTF-8

Depends R (>= 3.5.0)

Imports utils, Rcpp, magrittr, data.table, R.utils, xtable, memoise, stringr, xml2

Collate RcppExports.R const.R helpers.R core_import.R core_search.R extras.R

LinkingTo Rcpp

RoxygenNote 7.2.0

NeedsCompilation yes

Author Aleksander Rutkowski [aut, cre]

Maintainer Aleksander Rutkowski <alek.rutkowski@gmail.com>

Repository CRAN

Date/Publication 2022-08-31 08:20:02 UTC

R topics documented:

as.EurostatDataList	2
browseDataList	2
compare	4
describe	4
find	5

importData	6
importDataList	7
importDimLabel	8
importLabels	8
importMetabase	9

Index**10**

as.EurostatDataList *Coerce a data.frame to a EurostatDataList*

Description

Some manipulations of the EurostatDataList data.frame (imported with `importDataList`) e.g. filtering with package `dplyr` may remove the S3 class tag EurostatDataList. This function coerces it back to EurostatDataList after checking that the critical columns (PCode, Dataset name,Link) are present. This is useful if a user wants to print and browse this filtered data.frame as a specially formatted HTML table.

Usage

```
as.EurostatDataList(x, SearchCriteria = "", ...)
```

Arguments

- `x` A (most likely filtered subset of) EurostatDataList data.frame returned by `importDataList`.
- `SearchCriteria` A string describing the search criteria used for filtering/subsetting.
- `...` Additional arguments to be passed to or from methods (currently not used).

Value

A data.frame of S3 class EurostatDataList.

browseDataList *Search Eurostat datasets and see the result as a table in a browser*

Description

Search Eurostat datasets and see the result as a table in a browser

Usage

```
browseDataList(subs)
```

Arguments

subs	An expression to be passed to <code>subset</code> . The column names of the table of datasets can be used – those with spaces should be backtick (`) quoted. See the examples below. The names of the available columns are:
	<ul style="list-style-type: none"> • `Data subgroup, level 0` • `Data subgroup, level 1` • `Data subgroup, level 2` • `Data subgroup, level 3` • `Data subgroup, level 4` • `Data subgroup, level 5` • `Data subgroup, level 6` • `Data subgroup, level 7` • `Dataset name` • `Code` • `Type` • `Last update of data` • `Last table structure change` • `Data start` • `Data end` • `Link`

Value

- Side effect (via `print`) – a table opened in a browser via `browseURL`.
- Value – a list with:
 - criteria – a string, search criteria,
 - time – the time of the query,
 - df – a data.frame, imported via `importDataList` and filtered based on the conditions specified in `subs`.
 - html – a string, with the HTML code that generated the table in a browser.

Examples

```
## Not run:
browseDataList(grepl('servic','Dataset name'))
browseDataList(grepl('bop',Code) & !grepl('its',Code))

## End(Not run)
## Not run:
browseDataList(grepl('GDP','Dataset name') &
  grepl('main','Dataset name') &
  grepl('international','Dataset name') &
  !grepl('quarterly','Dataset name'))
browseDataList(grepl('bop',Code) & grepl('its',Code))

## End(Not run)
```

compare	<i>Compare specific Eurostat datasets on the basis of information from Metabase</i>
---------	---

Description

Compare specific Eurostat datasets on the basis of information from Metabase

Usage

```
compare(..., import_labels = TRUE, import_dim_labels = TRUE)
```

Arguments

- ... Two or more Eurostat dataset code names, e.g. "nama_10_gdp" or "bop_its6_det", as strings.
- import_labels Boolean: should labels for the codes inside dimensions be imported. Default: TRUE.
- import_dim_labels Boolean: should the dimensions (e.g. geo, indic_is, or nace_r2) be labelled with a descriptive name (via [importDimLabel](#)). Default: TRUE.

Value

A [data.table](#) with columns Dim_name, Dim_name_label (if `import_dim_labels=TRUE`), Dim_val, Dim_val_label (if `import_labels=TRUE`), and logical columns corresponding to the dataset names in ... indicating in which dataset a given dimension and dimension value appears and in which it does not.

Examples

```
## Not run:
compare('nama_10_gdp', 'nama_10_pe')

## End(Not run)
```

describe	<i>Describe a given Eurostat dataset on the basis of information from Metabase</i>
----------	--

Description

Describe a given Eurostat dataset on the basis of information from Metabase

Usage

```
describe(
  EurostatDatasetCode,
  import_labels = !wide,
  wide = FALSE,
  import_dim_labels = TRUE
)
```

Arguments

EurostatDatasetCode
 A string with Eurostat dataset code name, e.g. "nama_10_gdp" or "bop_its6_det".
 See e.g.: https://ec.europa.eu/eurostat/estat-navtree-portlet-prod/BulkDownloadListing?sort=1&file=table_of_contents_en.pdf

import_labels Boolean: should labels for the codes inside dimensions be imported. Default: if wide is FALSE then import_labels is TRUE and vice versa.

wide Boolean: should each dimension be compressed to one row and all values within each dimension to a single, comma-separated string. Default: FALSE.

import_dim_labels Boolean: should the dimensions (e.g. geo, indic_is, or nace_r2) be labelled with a descriptive name (via `importDimLabel`). Default: TRUE.

Value

A `data.table` with columns Dim_name, Dim_name_label (if `import_dim_labels=TRUE`), either Dim_val (if `wide=FALSE`) or Dim_values (if `wide=TRUE`), Dim_val_label (if `import_labels=TRUE`), and a column with a name = `EurostatDatasetCode` with all its values = TRUE.

Examples

```
## Not run:
describe('nama_10_gdp')

## End(Not run)
```

find

*Search Eurostat datasets and see the result as text***Description**

A tool for a quick ad-hoc search.

Usage

```
find(...)
```

Arguments

...

A series of unquoted words to be searched either in Eurostat dataset codes or in dataset full names. All words not preceded by minus (-) will be linked with logical AND; all words preceded by a minus entail exclusion (logical NOT), a bit like in Google search. It is possible to search also with phrases that include spaces – in such a case the phrases should be quoted. Partial word/phrase match is applied. See the examples below.

Value

- Side effect (via `print`) – a text report file opened via `file.show`.
- Value – a list with:
 - criteria – a string, search criteria,
 - time – the time of the query,
 - df – a `data.frame`, imported via `importDataList` and filtered based on the conditions specified in ...,
 - report – a string, with the text report.

Examples

```
## Not run:
find(bop, its)
find(bop,-ybk,its)
find(nama_)
find(nama,10,64)
find('economic indic')

## End(Not run)
```

`importData`

Download and import a Eurostat dataset

Description

Download and import a Eurostat dataset

Usage

```
importData(EurostatDatasetCode)
```

Arguments

`EurostatDatasetCode`

A string (upper/lower-case difference is not relevant) with Eurostat dataset code name, e.g. `nama_10_gdp` or `bop_its6_det`. See https://ec.europa.eu/eurostat/databrowser/explore/all/all_themes to find a dataset code – the dataset codes are in tiny font in square brackets.

`importDataList`

7

Value

A Eurostat dataset as a ‘flat’ data.frame. A ‘flat’ dataset has all numeric values in one column, with each row representing one of the available combinations of all dimensions (e.g. if dimensions are: countries, years, sectors, and indicators, there can be a row for value added in retail in Germany in 2013).

Examples

```
## Not run:  
importData('nama_10_gdp')  
  
## End(Not run)
```

`importDataList`

Import and reshape Eurostat inventory of datasets

Description

Import and reshape Eurostat inventory of datasets

Usage

```
importDataList()
```

Value

The imported data.frame reflects the hierarchical structure of datasets (see the columns Data subgroup, level 0, Data subgroup, level 1, Data subgroup, level 2, etc.). It is tagged with S3 class `EurostatDataList`.

Examples

```
## Not run:  
importDataList()  
  
## End(Not run)
```

`importDimLabel`*Import Eurostat label (description) of a given dimension code*

Description

Import the appropriate description file for the selected Eurostat dimension, e.g. for "geo" it is "Geopolitical entity (reporting)", for "nace_r2" it is "Classification of economic activities - NACE Rev.2", for "indic_sb" it is "Economical indicator for structural business statistics" etc. See <https://ec.europa.eu/eurostat/estat-navtree-portlet-prod/BulkDownloadListing?sort=1&dir=desc%2Fen/> for the list of all codes (the .dic file extension to be ignored). Each description is web-scraped from a table (row "Label") at the specific url, e.g. for "geo" it is <https://dd.eionet.europa.eu/vocabulary/eurostat/geo/>.

Usage

```
importDimLabel(EurostatDimCode)
```

Arguments

`EurostatDimCode`

A string – the code name of the Eurostat dimension, e.g. "geo" or "nace_r2" or "indic_sb", etc.

Value

A character vector of length 1: the label/description of EurostatDimCode.

Examples

```
## Not run:
importDimLabel('nace_r2')

## End(Not run)
```

`importLabels`*Import Eurostat code list: labels (descriptions) for a given dimension code*

Description

Import the appropriate 'code list' from for the selected Eurostat dimension, e.g. geo (countries or other geographic entities), nace_r2 (sectors), indic_sb (indicators), etc.

Usage

```
importLabels(EurostatDimCode)
```

`importMetabase`

9

Arguments

`EurostatDimCode`

A string – the code name of the Eurostat dimension, e.g. `geo` or `nace_r2` or `indic_sb`.

Value

A `data.frame` with 2 columns: `codes` (with a name determined by `EurostatDimCode`) and corresponding labels (named with suffix `_labels`).

Examples

```
## Not run:  
importLabels('nace_r2')  
  
## End(Not run)
```

`importMetabase` *Import Eurostat “Metabase”*

Description

The Eurostat “Metabase” shows which datasets contain which dimensions (where a dimension is e.g. `geo` or `nace_r2` or `indic_sb`) and, within each dataset and dimension, which codes (e.g. which countries for the `geo` dimension).

Usage

```
importMetabase()
```

Value

The imported `data.frame` which reflects the hierarchical structure described above. It is a ‘flat’ `data.frame` with 3 columns, where each row corresponds to the combination of:

- `Code` – Eurostat dataset code names, e.g. `"nama_10_a64"`
- `Dim_name` – Eurostat dimension code names, e.g. `"nace_r2"`
- `Dim_val` – Eurostat dimension code values, e.g. `"EU28"` if `Dim_name` is `"geo"`; not to be confused with the actual numeric values in the actual datasets

Examples

```
## Not run:  
importMetabase()  
  
## End(Not run)
```

Index

as.EurostatDataList, 2
browseDataList, 2
browseURL, 3
compare, 4
data.table, 4, 5
describe, 4
file.show, 6
find, 5
importData, 6
importDataList, 2, 3, 6, 7
importDimLabel, 4, 5, 8
importLabels, 8
importMetabase, 9
subset, 3