

Package ‘geostats’

August 13, 2022

Title An Introduction to Statistics for Geoscientists

Version 1.5

Date 2022-08-13

Description A collection of datasets and simplified functions for an introductory (geo)statistics module at University College London. Provides functionality for compositional, directional and spatial data, including ternary diagrams, Wulff and Schmidt stereonet, and ordinary kriging interpolation. Implements logistic and (additive and centred) logratio transformations. Computes vector averages and concentration parameters for the von-Mises distribution. Includes a collection of natural and synthetic fractals, and a simulator for deterministic chaos using a magnetic pendulum example. The main purpose of these functions is pedagogical. Researchers can find more complete alternatives for these tools in other packages such as 'compositions', 'robCompositions', 'sp', 'gstat' and 'RFOC'. All the functions are written in plain R, with no compiled code and a minimal number of dependencies. Theoretical background and worked examples are available at <<https://tinyurl.com/UCLgeostats/>>.

Author Pieter Vermeesch [aut, cre]

Maintainer Pieter Vermeesch <p.vermeesch@ucl.ac.uk>

Depends R (>= 3.5.0)

Suggests MASS

License GPL-3

URL <https://github.com/pvermeesch/geostats/>

LazyData true

RoxygenNote 7.2.1

Encoding UTF-8

NeedsCompilation no

Repository CRAN

Date/Publication 2022-08-13 12:50:02 UTC

R topics documented:

ACNK 3

AFM	3
alr	4
boxcount	4
Britain	5
cantor	5
circle.plot	6
circle.points	7
clasts	7
clr	8
colourplot	8
Corsica	10
countQuakes	10
declustered	11
DZ	12
earthquakes	12
ellipse	12
exp	13
FAM	14
fault	14
Finland	14
forams	15
fractaldim	15
fractures	16
geostats	16
gutenberg	17
hills	17
koch	18
kriging	18
ksdist	19
logit	20
major	21
meanangle	21
meuse	22
Mode	22
palaeomag	23
PCA2D	23
pendulum	24
pH	24
pop	25
porosity	25
randy	25
Rbar	26
Rbar2kappa	27
rbsr	28
rwxyz	28
semivariogram	29
sierpinski	30
sizefrequency	31

ACNK	3
skew	32
stereonet	32
striations	34
ternary	34
test	35
training	35
vonMises	36
worldpop	36
xyz2xy	37
york	37
Index	39

ACNK	<i>A-CN-K compositions</i>
------	----------------------------

Description

Synthetic A (Al_2O_3) – CN ($\text{CaO}+\text{Na}_2\text{O}$) – K (K_2O) data table.

Examples

```
data(ACNK,package='geostats')
ternary(ACNK,type='p',labels=c(expression('Al'[2]*'O'[3]),
                                     expression('CaO+Na'[2]*'O'),
                                     expression('K'[2]*'O')))
```

AFM	<i>AFM data</i>
-----	-----------------

Description

1104 calc-alkaline and tholeiitic basalt compositions

Examples

```
data(AFM,package='geostats')
ternary(AFM[,-1],pch=21,bg=AFM[,1])
```

alr	<i>additive logratio transformation</i>
-----	---

Description

Maps compositional data from an n -dimensional simplex to an $(n - 1)$ -dimensional Euclidean space with Aitchison's additive logratio transformation.

Usage

```
alr(dat, inverse = FALSE)
```

Arguments

dat	an n column data frame or matrix
inverse	if TRUE, applies the inverse alr transformation

Value

If `inverse=FALSE`, returns an $(n - 1) \times m$ matrix of logratios; otherwise returns an $(n + 1) \times m$ matrix of compositional data whose columns add up to 1.

Examples

```
xyz <- rbind(c(0.03,99.88,0.09),
            c(70.54,25.95,3.51),
            c(72.14,26.54,1.32))
colnames(xyz) <- c('a','b','c')
rownames(xyz) <- 1:3
uv <- alr(xyz)
XYZ <- alr(uv,inverse=TRUE)
xyz/XYZ
```

boxcount	<i>box counting</i>
----------	---------------------

Description

Count the number of boxes needed to cover all the 1s in a matrix of 0s and 1s.

Count the number of boxes needed to cover all the 1s in a matrix of 0s and 1s.

Usage

```
boxcount(mat, size)
```

```
boxcount(mat, size)
```

Arguments

`mat` a square square matrix of 0s and 1s, whose size should be a power of 2.
`size` the size (pixels per side) of the boxes, whose size should be a power of 2.

Value

an integer
 an integer

Examples

```
g <- sierpinski(n=5)
boxcount(mat=g,size=16)
g <- sierpinski(n=5)
boxcount(mat=g,size=16)
```

 Britain

British coast

Description

A 512×512 pixel image of the British coastline.

Examples

```
data(Britain,package='geostats')
p <- par(mfrow=c(1,2))
image(Britain)
fractaldim(Britain)
par(p)
```

 cantor

Cantor set

Description

Calculates or plots a Cantor set of fractal lines, which is generated using a recursive algorithm that is built on a line segment whose middle third is removed. Each level of recursion replaces each black line by the same pattern.

Usage

```
cantor(n = 5, plot = FALSE, add = FALSE, Y = 0, lty = 1, col = "black", ...)
```

Arguments

n	an integer value controlling the number of recursive levels.
plot	logical. If TRUE, the Cantor set is plotted, otherwise a list of breaks and counts is returned.
add	logical (only used if plot=TRUE). If add=FALSE, then a brand new figure is created; otherwise the Cantor set is added to an existing plot.
Y	y-value for the plot (only used if plot=TRUE).
lty	line type (see pars() for details)
col	colour of the Cantor lines.
...	optional arguments to be passed on to matplot or matlines.

Value

a square matrix with 0s and 1s.

Examples

```
plot(c(0,1),y=c(0,1),type='n',bty='n',ann=FALSE,xaxt='n',yaxt='n',xpd=NA)
cantor(n=0,Y=1.00,plot=TRUE,add=TRUE)
cantor(n=1,Y=0.75,plot=TRUE,add=TRUE)
cantor(n=2,Y=0.50,plot=TRUE,add=TRUE)
cantor(n=3,Y=0.25,plot=TRUE,add=TRUE)
cantor(n=4,Y=0.00,plot=TRUE,add=TRUE)
```

circle.plot

plot circular data

Description

Plots directional data as ticks on a circle, with angles plotting in a clockwise direction from the top.

Usage

```
circle.plot(a, degrees = FALSE, tl = 0.1, ...)
```

Arguments

a	angle(s), scalar or vector
degrees	logical. TRUE for degrees, FALSE for radians
tl	tick length (value between 0 and 1)
...	optional arguments to be passed on to the generic matlines function

Value

no return value

Examples

```
data(striations,package='geostats')
circle.plot(striations,degrees=TRUE)
```

circle.points	<i>add points to a circular plot</i>
---------------	--------------------------------------

Description

Adds directional data as points on an existing circle plot, with angles plotting in a clockwise direction from the top.

Usage

```
circle.points(a, degrees = FALSE, ...)
```

Arguments

a	angle(s), scalar or vector
degrees	logical. TRUE for degrees, FALSE for radians
...	optional arguments to be passed on to the generic points function

Value

no return value

Examples

```
data(striations,package='geostats')
circle.plot(striations,degrees=TRUE)
md <- meanangle(striations,degrees=TRUE)
circle.points(md,pch=22,bg='black',degrees=TRUE)
```

clasts	<i>clast size data</i>
--------	------------------------

Description

20 clast size measurements, in cm.

Examples

```
data(clasts,package='geostats')
d <- density(log(clasts))
plot(d)
```

clr	<i>centred logratio transformation</i>
-----	--

Description

Maps compositional data from an n-dimensional simplex to an n-dimensional Euclidean space with Aitchison's centred logratio transformation.

Usage

```
clr(dat, inverse = FALSE)
```

Arguments

dat	an n x m matrix
inverse	logical. If TRUE, applies the inverse clr tranformation

Value

an n x m matrix

Examples

```
xyz <- rbind(c(0.03, 99.88, 0.09),  
            c(70.54, 25.95, 3.51),  
            c(72.14, 26.54, 1.32))  
colnames(xyz) <- c('a', 'b', 'c')  
rownames(xyz) <- 1:3  
pc <- prcomp(clr(xyz))  
biplot(pc)
```

colourplot	<i>colour plot</i>
------------	--------------------

Description

Adds a colour bar to a scatter plot and/or filled contour plot. This function, which is based on base R's `filled.contour` function, is useful for visualising kriging results.

Usage

```

colourplot(
  x,
  y,
  z,
  X,
  Y,
  Z,
  nlevels = 20,
  colspec = hcl.colors,
  pch = 21,
  cex = 1,
  plot.title,
  plot.axes,
  key.title,
  key.axes,
  asp = NA,
  xaxs = "i",
  yaxs = "i",
  las = 1,
  axes = TRUE,
  frame.plot = axes,
  extra,
  ...
)

```

Arguments

<code>x</code>	numerical vector of n equally spaced values to be used in the contour plot.
<code>y</code>	numerical vector of m equally spaced values to be used in the contour plot.
<code>z</code>	an $n \times m$ matrix of numerical values to be used in the contour plot.
<code>X</code>	numerical vector of N values to be used in the scatter plot.
<code>Y</code>	numerical vector of N values to be used in the scatter plot.
<code>Z</code>	numerical vector of N values to be used in the scatter plot.
<code>nlevels</code>	number of levels to be used in the contour plot.
<code>colspec</code>	colour specification (e.g., <code>rainbow</code> , <code>grey.colors</code> , <code>heat.colors</code> , <code>topo.colors</code>).
<code>pch</code>	plot character (21 – 25).
<code>cex</code>	plot character magnification.
<code>plot.title</code>	statements that add titles to the main plot.
<code>plot.axes</code>	statements that draw axes on the main plot. This overrides the default axes.
<code>key.title</code>	statements that add titles for the plot key.
<code>key.axes</code>	statements that draw axes on the plot key. This overrides the default axis.
<code>asp</code>	the y/x aspect ratio, see <code>plot.window</code> .
<code>xaxs</code>	the x axis style. The default is to use internal labelling.

yaxs	the y axis style. The default is to use internal labelling.
las	the style of labelling to be used. The default is to use horizontal labelling.
axes	logicals indicating if axes should be drawn.
frame.plot	logicals indicating if a box should be drawn, as in plot.default.
extra	(optional) extra intructions to be carried out in the main plot window, such as text annotations.
...	additional graphical parameters

Value

no return value

Examples

```
data('meuse',package='geostats')
colourplot(X=meuse$x,Y=meuse$y,Z=log(meuse$zinc),
           plot.title=title(main='Meuse',xlab='Easting',ylab='Northing'),
           key.title=title(main='log(Zn)'))
```

Corsica	<i>rivers on Corsica</i>
---------	--------------------------

Description

A 512 × 512 pixel image of the river network on Corsica.

Examples

```
data(Corsica,package='geostats')
p <- par(mfrow=c(1,2))
image(Corsica)
fractaldim(Corsica)
par(p)
```

countQuakes	<i>count the number of earthquakes per year</i>
-------------	---

Description

Counts the number of earthquakes per year that fall within a certain time interval.

Usage

```
countQuakes(qdat, minmag, from, to)
```

Arguments

qdat	a data frame containing columns named mag and year.
minmag	minimum magnitude
from	first year
to	last year

Value

a table with the number of earthquakes per year

Examples

```
data(declustered, package='geostats')
quakesperyear <- countQuakes(declustered, minmag=5.0, from=1917, to=2016)
table(quakesperyear)
```

declustered	<i>declustered earthquake data</i>
-------------	------------------------------------

Description

Dataset of 28267 earthquakes between 1769 and 2016, with aftershocks and precursor events removed.

References

Mueller, C.S., 2019. Earthquake catalogs for the USGS national seismic hazard maps. *Seismological Research Letters*, 90(1), pp.251-261.

Examples

```
data(declustered, package='geostats')
quakesperyear <- countQuakes(declustered, minmag=5.0, from=1917, to=2016)
table(quakesperyear)
```

DZ	<i>detrital zircon U-Pb data</i>
----	----------------------------------

Description

Detrital zircon U-Pb data of 13 sand samples from China.

References

Vermeesch, P. "Multi-sample comparison of detrital age distributions." *Chemical Geology* 341 (2013): 140-146.

Examples

```
data(DZ, package='geostats')
qqplot(DZ[['Y']], DZ[['5']])
```

earthquakes	<i>earthquake data</i>
-------------	------------------------

Description

Dataset of 20000 earthquakes between 2017 and 2000, downloaded from the USGS earthquake database (<https://earthquake.usgs.gov/earthquakes/search/>).

Examples

```
data(earthquakes, package='geostats')
gutenberg(earthquakes$mag)
```

ellipse	<i>ellipse</i>
---------	----------------

Description

Compute the x-y coordinates of an error ellipse.

Usage

```
ellipse(mean, cov, alpha = 0.05, n = 50)
```

Arguments

mean	two-element vector with the centre of the ellipse
cov	the 2 x 2 covariance matrix of x and y
alpha	confidence level of the ellipse
n	the number of points at which the ellipse is evaluated

Value

a two-column matrix of plot coordinates

Examples

```
X <- rnorm(100,mean=100,sd=1)
Y <- rnorm(100,mean=100,sd=1)
Z <- rnorm(100,mean=100,sd=5)
dat <- cbind(X/Z,Y/Z)
plot(dat)
ell <- ellipse(mean=colMeans(dat),cov=cov(dat))
polygon(ell)
```

 exp

exponential transformation

Description

Map a logged kernel density estimate from $[-\infty, +\infty]$ to $[0, \infty]$ by taking exponents.

Usage

```
## S3 method for class 'density'
exp(x)
```

Arguments

x an object of class density

Value

an object of class density

Examples

```
data(clasts,package='geostats')
lc <- log(clasts)
ld <- density(lc)
d <- exp(ld)
plot(d)
```

FAM	<i>A-F-M data</i>
-----	-------------------

Description

FeO - (Na₂O + K₂O) - MgO compositions of 630 calc-alkali basalts from the Cascade Mountains and 474 tholeiitic basalts from Iceland. Arranged in F-A-M order instead of A-F-M for consistency with the ternary function.

Examples

```
data(FAM,package='geostats')
ternary(FAM[, -1])
```

fault	<i>fault orientation data</i>
-------	-------------------------------

Description

Ten paired strike and dip measurements (in degrees), drawn from a von Mises - Fisher distribution with mean vector $\mu = \{-1, -1, 1\}/\sqrt{3}$ and concentration parameter $\kappa = 100$.

Examples

```
data(fault,package='geostats')
stereonet(trd=fault$strike,plg=fault$dip,option=2,degrees=TRUE,show.grid=FALSE)
```

Finland	<i>Finnish lake data</i>
---------	--------------------------

Description

Table of 2327 Finnish lakes, extracted from a hydroLAKES database.

References

Lehner, B., and Doll, P. (2004), Development and validation of a global database of lakes, reservoirs and wetlands, *Journal of Hydrology*, 296(1), 1-22, doi: 10.1016/j.jhydrol.2004.03.028.

Examples

```
data(Finland,package='geostats')
sf <- sizefrequency(Finland$area)
size <- sf[, 'size']
freq <- sf[, 'frequency']
plot(size,freq,log='xy')
fit <- lm(log(freq) ~ log(size))
lines(size,exp(predict(fit)))
```

forams	<i>foram count data</i>
--------	-------------------------

Description

Planktic foraminifera counts in surface sediments in the Atlantic ocean.

Examples

```
data(forams,package='geostats')
abundant <- forams[,c('quinteloba','pachyderma','incompta',
                    'glutinata','bulloides')]
other <- rowSums(forams[,c('uvula','scitula')])
dat <- cbind(abundant,other)
chisq.test(dat)
```

fractaldim	<i>calculate the fractal dimension</i>
------------	--

Description

Performs box counting on a matrix of 0s and 1s.

Usage

```
fractaldim(mat, plot = TRUE, ...)
```

Arguments

mat	a square matrix of 0s and 1s. Size must be a power of 2.
plot	logical. If TRUE, plots the results on a log-log scale.
...	optional arguments to the generic points function.

Value

an object of class `lm`

Examples

```
g <- sierpinski(n=5)
fractaldim(g)
```

fractures	<i>fractures</i>
-----------	------------------

Description

A 512×512 pixel image of a fracture network.

Examples

```
data(fractures, package='geostats')
p <- par(mfrow=c(1,2))
image(fractures)
fractalDIM(fractures)
par(p)
```

geostats	<i>library(geostats)</i>
----------	--------------------------

Description

A list of documented functions may be viewed by typing `help(package='geostats')`. Detailed instructions are provided at <https://github.com/pvermees/geostats/>.

Author(s)

Maintainer: Pieter Vermeesch <p.vermeesch@ucl.ac.uk>

See Also

Useful links:

- <https://github.com/pvermees/geostats/>

gutenberg	<i>create a Gutenberg-Richter plot</i>
-----------	--

Description

Calculate a semi-log plot with earthquake magnitude on the horizontal axis, and the cumulative number of earthquakes exceeding any given magnitude on the vertical axis.

Usage

```
gutenberg(m, n = 10, ...)
```

Arguments

m	a vector of earthquake magnitudes
n	the number of magnitudes to evaluate
...	optional arguments to the generic <code>points</code> function.

Value

the output of `lm` with earthquake magnitude as the independent variable (`mag`) and the logarithm (base 10) of the frequency as the dependent variable (`lfreq`).

Examples

```
data(declustered, package='geostats')
gutenberg(declustered$mag)
```

hills	<i>hills</i>
-------	--------------

Description

150 X-Y-Z values for a synthetic landscape that consists of three Gaussian mountains.

Examples

```
data(hills, package='geostats')
semivariogram(x=hills$X, y=hills$Y, z=hills$Z, model='gaussian')
```

koch	<i>Koch snowflake</i>
------	-----------------------

Description

Calculates or plots a Koch set of fractal lines, which is generated using a recursive algorithm that is built on a triangular hat shaped line segment. Each level of recursion replaces each linear segment by the same pattern.

Usage

```
koch(n = 4, plot = TRUE, res = 512)
```

Arguments

n	an integer value controlling the number of recursive levels.
plot	logical. If TRUE, the Koch flake is plotted.
res	the number of pixels in each side of the output matrix

Value

a res x res matrix with 0s and 1s

Examples

```
koch()
```

kriging	<i>kriging</i>
---------	----------------

Description

Ordinary kriging interpolation of spatial data. Implements a simple version of ordinary kriging that uses all the data in a training set to predict the z-value of some test data, using a semivariogram model generated by the [semivariogram](#) function.

Usage

```
kriging(x, y, z, xi, yi, svm, grid = FALSE, err = FALSE)
```

Arguments

x	numerical vector of training data
y	numerical vector of the same length as x
z	numerical vector of the same length as x
xi	scalar or vector with the x-coordinates of the points at which the z-values are to be evaluated.
yi	scalar or vector with the y-coordinates of the points at which the z-values are to be evaluated.
svm	output of the semivariogram function, a 3-element vector with the sill, nugget and range of the semivariogram fit.
grid	logical. If TRUE, evaluates the kriging interpolator along a regular grid of values defined by xi and yi.
err	logical. If TRUE, returns the variance of the kriging estimate.

Value

either a vector (if grid=FALSE) or a matrix (if grid=TRUE) of kriging interpolations. In the latter case, values that are more than 10% out of the data range are given NA values.

Examples

```
data(meuse, package='geostats')
x <- meuse$x
y <- meuse$y
z <- log(meuse$cadmium)
svm <- semivariogram(x=x, y=y, z=z)
kriging(x=x, y=y, z=z, xi=179850, yi=331650, svm=svm, grid=TRUE)
```

ksdist

Kolmogorov-Smirnov distance matrix

Description

Given a list of numerical vectors, fills a square matrix with Kolmogorov-Smirnov statistics.

Usage

```
ksdist(dat)
```

Arguments

dat	a list of numerical data vectors
-----	----------------------------------

Value

an object of class `dist`

Examples

```
data(DZ,package='geostats')
d <- ksdist(DZ)
mds <- cmdscale(d)
plot(mds,type='n')
text(mds,labels=names(DZ))
```

logit

logistic transformation

Description

Maps numbers from [0,1] to $[-\infty, +\infty]$ and back.

Usage

```
logit(x, ...)

## Default S3 method:
logit(x, inverse = FALSE, ...)

## S3 method for class 'density'
logit(x, inverse = TRUE, ...)
```

Arguments

x a vector of real numbers (strictly positive if `inverse=FALSE`) or an object of class `density`.

... optional arguments to the log function.

inverse logical. If `inverse=FALSE`, returns $\ln\left[\frac{x}{1-x}\right]$; otherwise returns $\frac{\exp[x]}{\exp[x]+1}$.

Value

a vector with the same length of `x`

Examples

```
data(porosity,package='geostats')
lp <- logit(porosity,inverse=FALSE)
ld <- density(lp)
d <- logit(ld,inverse=TRUE)
plot(d)
```

major	<i>composition of Namib dune sand</i>
-------	---------------------------------------

Description

Major element compositions of 16 Namib sand samples.

References

Vermeesch, P. & Garzanti, E. “Making geological sense of ‘Big Data’ in sedimentary provenance analysis.” *Chemical Geology* 409 (2015): 20-27.

Examples

```
data(major, package='geostats')
comp <- clr(major)
pc <- prcomp(comp)
biplot(pc)
```

meanangle	<i>mean angle</i>
-----------	-------------------

Description

Computes the vector mean of a collection of circular measurements.

Usage

```
meanangle(trd, plg = 0, option = 0, degrees = FALSE)
```

Arguments

trd	trend angle, in degrees, between 0 and 360 (if degrees=TRUE) or between 0 and 2π (if degrees=FALSE).
plg	(optional) plunge angle, in degrees, between 0 and 90 (if degrees=TRUE) or between 0 and 2π (if degrees=FALSE).
option	scalar. If option=0, then plg is ignored and the measurements are considered to be circular; if option=1, then trd is the azimuth and plg is the dip; if option=2, then trd is the strike and plg is the dip; if option=3 then trd is the longitude and plg is the latitude.
degrees	TRUE for degrees, FALSE for radians

Value

a scalar of 2-element vector with the mean orientation, either in radians (if degrees=FALSE), or in degrees.

Examples

```
data(striations,package='geostats')
meanangle(striations,degrees=TRUE)
```

 meuse

Meuse river data set

Description

This data set gives locations and topsoil heavy metal concentrations, collected in a flood plain of the river Meuse, near the village of Stein (NL). Heavy metal concentrations are from composite samples of an area of approximately 15 m x 15 m. This version of the meuse dataset is a trimmed down version of the eponymous dataset from the sp dataset.

Examples

```
data(meuse,package='geostats')
semivariogram(x=meuse$x,y=meuse$y,z=log(meuse$cadmium))
```

 Mode

get the mode of a dataset

Description

Computes the most frequently occurring value in a sampling distribution.

Usage

```
Mode(x, categorical = FALSE)
```

Arguments

x	a vector
categorical	logical. If TRUE, returns the most frequently occurring value for categorical variables. If FALSE, returns the value corresponding to the maximum kernel density for continuous variables

Value

a scalar

Examples

```

data(clasts,package='geostats')
m1 <- Mode(clasts,categorical=TRUE)

m2 <- 1:50
for (i in m2){
  m2[i] <- Mode(rnorm(100),categorical=FALSE)
}
hist(m2)

```

palaeomag

palaeomagnetic data

Description

Ten paired magnetic declination (azimuth) and inclination (dip) measurements, drawn from a von Mises - Fisher distribution with mean vector $\mu = \{2, 2, 1\}/3$ and concentration parameter $\kappa = 200$.

Examples

```

data(palaeomag,package='geostats')
stereonet(trd=palaeomag$decl,plg=palaeomag$incl,degrees=TRUE,show.grid=FALSE)

```

PCA2D

Principal Component Analysis of 2D data

Description

Produces a 4-panel summary plot for two dimensional PCA for didactical purposes.

Usage

```
PCA2D(X)
```

Arguments

X a matrix with two columns

Examples

```

X <- rbind(c(-1,7),c(3,2),c(4,3))
colnames(X) <- c('a','b')
PCA2D(X)

```

pendulum	<i>3-magnet pendulum experiment</i>
----------	-------------------------------------

Description

Simulates the 3-magnet pendulum experiment, starting at a specified position with a given start velocity.

Usage

```
pendulum(
  startpos = c(-2, 2),
  startvel = c(0, 0),
  src = rbind(c(0, 0), c(0.5, sqrt(0.75)), c(1, 0)),
  plot = TRUE
)
```

Arguments

startpos	2-element vector with the initial position
startvel	2-element vector with the initial velocity
src	$n \times 2$ matrix with the positions of the magnets
plot	logical. If TRUE, generates a plot with the trajectory of the pendulum.

Value

the end position of the pendulum

Examples

```
p <- par(mfrow=c(1,2))
pendulum(startpos=c(2.1,2))
pendulum(startpos=c(1.9,2))
par(p)
```

pH	<i>pH data</i>
----	----------------

Description

pH measurements in 20 samples of rain water.

Examples

```
data(pH, package='geostats')
hist(pH)
```

pop	<i>pop</i>
-----	------------

Description

The world population from 1750 until 2014

Examples

```
data(pop,package='geostats')
plot(population ~ year, data=pop, type='b')
```

porosity	<i>porosity data</i>
----------	----------------------

Description

20 porosity measurements, as fractions.

Examples

```
data(porosity,package='geostats')
plot(density(logit(porosity)))
```

randy	<i>generate bivariate random data</i>
-------	---------------------------------------

Description

Returns bivariate datasets from four synthetic distributions that have the shape of a circle, arrow, square and ellipse.

Usage

```
randy(pop = 1, n = 250)
```

Arguments

pop	an integer from 1 to 4 marking the population of choice: 1 = circle, 2 = arrow, 3 = solid square, 4 = ellipse.
n	the number of random draws to be drawn from population pop

Value

a [2xn] matrix of random numbers

Examples

```
p <- par(mfrow=c(1,4))
for (i in 1:4){
  plot(randy(pop=i))
}
par(p)
```

Rbar

calculate \bar{R}

Description

Given n circular or spherical measurements, the length of their normalised vector sum (\bar{R}) serves as a measure of directional concentration.

Usage

```
Rbar(trd, plg = 0, option = 0, degrees = FALSE)
```

Arguments

trd	trend angle, in degrees, between 0 and 360 (if degrees=TRUE) or between 0 and 2π (if degrees=FALSE).
plg	(optional) plunge angle, in degrees, between 0 and 90 (if degrees=TRUE) or between 0 and 2π (if degrees=FALSE).
option	scalar. If option=0, then plg is ignored and the measurements are considered to be circular; if option=1, then trd is the azimuth and plg is the dip; if option=2, then trd is the strike and plg is the dip; if option=3 then trd is the longitude and plg is the latitude.
degrees	TRUE for degrees, FALSE for radians

Value

a value between 0 and 1

Examples

```
data(striations,package='geostats')
Rbar(striations,degrees=TRUE)
```

Rbar2kappa	\bar{R} to κ conversion
------------	----------------------------------

Description

Converts the empirical concentration parameter \bar{R} to the von-Mises concentration parameter κ .

Usage

```
Rbar2kappa(R, p = 1)
```

Arguments

R	a scalar or vector of values between 0 and 1
p	the number of parameters

Details

\bar{R} and κ are two types of concentration parameter that are commonly used in directional data analysis. κ is one of the parameters of the parametric von Mises distribution, which is difficult to estimate from the data. \bar{R} is easier to calculate from data. Rbar2kappa converts \bar{R} to $\bar{\kappa}$ using the following approximate empirical formula:

$$\kappa = \frac{\bar{R}(p+1-\bar{R}^2)}{1-\bar{R}^2}$$

where p marks the number of parameters in the data space (1 for circle, 2 for a sphere).

Value

value(s) between 0 and $+\infty$

References

Banerjee, A., et al. "Clustering on the unit hypersphere using von Mises-Fisher distributions." Journal of Machine Learning Research 6.Sep (2005): 1345-1382.

Examples

```
data(striations, package='geostats')
Rbar2kappa(Rbar(striations, degrees=TRUE))
```

 rbsr

Rb-Sr data

Description

Synthetic dataset of 8 Rb-Sr analysis that form a 1Ga isochron.

Examples

```
data(rbsr,package='geostats')
plot(rbsr[, 'RbSr'], rbsr[, 'SrSr'])
fit <- lm(SrSr ~ RbSr, data=rbsr)
abline(fit)
```

 rwyxz

Spurious correlation

Description

Calculate the 'null correlation' of ratios, using the the spurious correlation formula of Pearson (1897).

Usage

```
rwyxz(
  mw,
  mx,
  my,
  mz,
  sw,
  sx,
  sy,
  sz,
  rwx = 0,
  rwy = 0,
  rwz = 0,
  rxy = 0,
  rxz = 0,
  ryz = 0
)
```

```
ryxy(mx, my, sx, sy, rxy = 0)
```

```
rxzyz(mx, my, mz, sx, sy, sz, rxy = 0, rxz = 0, ryz = 0)
```

Arguments

mw	the mean of variable w
mx	the mean of variable x
my	the mean of variable y
mz	the mean of variable z
sw	the standard deviation of variable w
sx	the standard deviation of variable x
sy	the standard deviation of variable y
sz	the standard deviation of variable z
rxw	the correlation coefficient between w and x
rwy	the correlation coefficient between w and y
rwz	the correlation coefficient between w and z
rxxy	the correlation coefficient between x and y
rxz	the correlation coefficient between x and z
ryz	the correlation coefficient between y and z

Value

the null correlation coefficient

References

Pearson, K. "Mathematical contributions to the theory of evolution. – on a form of spurious correlation which may arise when indices are used in the measurement of organs." Proceedings of the Royal Society of London 60.359-367 (1897): 489-498.

Examples

rxzyz(mx=100,my=100,mz=100,sx=1,sy=1,sz=10)

semivariogram

semivariogram

Description

Plots the semivariance of spatial data against inter-sample distance, and fits a spherical equation to it.

Usage

```
semivariogram(
  x,
  y,
  z,
  bw = NULL,
  nb = 13,
  plot = TRUE,
  fit = TRUE,
  model = c("spherical", "exponential", "gaussian"),
  ...
)
```

Arguments

<code>x</code>	numerical vector
<code>y</code>	numerical vector of the same length as <code>x</code>
<code>z</code>	numerical vector of the same length as <code>x</code>
<code>bw</code>	(optional) the bin width of the semivariance search algorithm
<code>nb</code>	(optional) the maximum number of bins to evaluate
<code>plot</code>	logical. If FALSE, suppresses the graphical output
<code>fit</code>	logical. If TRUE, returns the sill, nugget and range.
<code>model</code>	the parametric model to fit to the empirical semivariogram (only used if <code>fit=TRUE</code>).
<code>...</code>	optional arguments to be passed on to the generic <code>plot</code> function

Value

returns a list with the estimated semivariances at different distances for the data, and (if `fit=TRUE`), a vector with the sill, nugget and range.

Examples

```
data(meuse, package='geostats')
semivariogram(x=meuse$x, y=meuse$y, z=log(meuse$cadmium))
```

sierpinski

Sierpinski carpet

Description

Returns a matrix of 0s and 1s that form a Sierpinski carpet. This is a two dimensional fractal, which is generated using a recursive algorithm that is built on a grid of eight black squares surrounding a white square. Each level of recursion replaces each black square by the same pattern.

Usage

```
sierpinski(n = 5)
```

Arguments

`n` an integer value controlling the number of recursive levels.

Value

a square matrix with 0s and 1s.

Examples

```
g <- sierpinski(n=5)
image(g,col=c('white','black'),axes=FALSE,asp=1)
```

sizefrequency	<i>calculate the size-frequency distribution of things</i>
---------------	--

Description

Count the number of items exceeding a certain size.

Usage

```
sizefrequency(dat, n = 10, log = TRUE)
```

Arguments

`dat` a numerical vector

`n` the number of sizes to evaluate

`log` logical. If TRUE, uses a log spacing for the sizes at which the frequencies are evaluated

Value

a data frame with two columns `size` and `frequency`

Examples

```
data(Finland,package='geostats')
sf <- sizefrequency(Finland$area)
plot(frequency~size,data=sf,log='xy')
fit <- lm(log(frequency) ~ log(size),data=sf)
lines(x=sf$size,y=exp(predict(fit)))
```

skew	<i>calculate the skewness of a dataset</i>
------	--

Description

Compute the third moment of a sampling distribution.

Usage

```
skew(x)
```

Arguments

x a vector

Value

a scalar

Examples

```
data(porosity,package='geostats')
skew(porosity)
```

stereonet	<i>stereonet</i>
-----------	------------------

Description

Plots directional data on a Wulff or Schmidt stereonet. The Wulff equal angle polar Lambert projection preserves the shape of objects and is often used to visualise structural data. The Schmidt equal area polar Lambert projection preserves the size of objects and is more popular in mineralogy.

Usage

```
stereonet(
  trd,
  plg,
  coneAngle = rep(10, length(trd)),
  option = 1,
  wulff = TRUE,
  add = FALSE,
  degrees = FALSE,
  show.grid = TRUE,
  grid.col = "grey50",
  tl = 0.05,
```



```

    type = "p",
    labels = 1:length(trd),
    ...
)

```

Arguments

trd	trend angle, in degrees, between 0 and 360 (if degrees=TRUE) or between 0 and 2π (if degrees=FALSE).
plg	plunge angle, in degrees, between 0 and 90 (if degrees=TRUE) or between 0 and 2π (if degrees=FALSE).
coneAngle	if option=4, controls the radius of a small circle around the pole with azimuth trd and dip plg.
option	scalar. If option=1 or option=4, then trd is the azimuth and plg is the dip; if option=2, then trd is the strike and plg is the dip; if option=3, then trd is the longitude and plg is the latitude.
wulff	logical. If FALSE, produces a Schmidt net.
add	logical. If TRUE, adds to an existing stereonet.
degrees	logical. If FALSE, assumes that azimuth and dip are in radians.
show.grid	logical. If TRUE, decorates the plot with a grid of great and small circles.
grid.col	colour of the grid.
t1	tick length for the N, E, S, W markers (value between 0 and 1). Set to 0 to omit the markers.
type	if option=1 or 3, coordinates can be visualised as points (type='p'), lines (type='l') or decorated with text labels (type='t').
labels	if option=1 or 3 and type='t', specifies the text labels to be used to mark the measurements on the stereonet.
...	optional arguments to be passed on to the generic points function

Author(s)

based on a MATLAB script written by Nestor Cardozo.

References

Allmendinger, R.W., Cardozo, N., and Fisher, D.M. "Structural geology algorithms: Vectors and tensors". Cambridge University Press, 2011.

Examples

```

stereonet(trd=c(120,80),plg=c(10,30),degrees=TRUE,pch=16)
stereonet(trd=c(120,80),plg=c(10,30),degrees=TRUE,
          option=4,coneAngle=c(5,10),add=TRUE)

```

test	<i>composition of oceanic basalts</i>
------	---------------------------------------

Description

Major element compositions of 64 island arc basalts (IAB), 23 mid oceanic ridge basalts (MORB) and 60 ocean island basalts (OIB). This dataset can be used to test supervised learning algorithms.

References

Vermeesch, P. "Tectonic discrimination diagrams revisited." *Geochemistry, Geophysics, Geosystems* 7.6 (2006).

Examples

```
library(MASS)
data(training,package='geostats')
ld <- lda(x=alr(training[,-1]),grouping=training[,1])
data(test,package='geostats')
pr <- predict(ld,newdata=alr(test[,-1]))
table(test$affinity,pr$class)
```

training	<i>composition of oceanic basalts</i>
----------	---------------------------------------

Description

Major element compositions of 227 island arc basalts (IAB), 221 mid oceanic ridge basalts (MORB) and 198 ocean island basalts (OIB). This dataset can be used to train supervised learning algorithms.

References

Vermeesch, P. "Tectonic discrimination diagrams revisited." *Geochemistry, Geophysics, Geosystems* 7.6 (2006).

Examples

```
library(MASS)
data(training,package='geostats')
ld <- lda(x=alr(training[,-1]),grouping=training[,1])
pr <- predict(ld)
table(training$affinity,pr$class)
```

vonMises	<i>von Mises distribution</i>
----------	-------------------------------

Description

Returns the probability density of a von Mises distribution, which describes probability distributions on a circle using the following density function:

$$\frac{\exp(\kappa \cos(x-\mu))}{2\pi I_0(\kappa)}$$

where $I_0(\kappa)$ is a zero order Bessel function.

Usage

```
vonMises(a, mu = 0, kappa = 1, degrees = FALSE)
```

Arguments

a	angle(s), scalar or vector
mu	scalar containing the mean direction
kappa	scalar containing the concentration parameter
degrees	TRUE for degrees, FALSE for radians

Value

a scalar or vector of the same length as angles

Examples

```
plot(x=c(-1,1.2),y=c(-1,1.2),type='n',
      axes=FALSE,ann=FALSE,bty='n',asp=1)
a <- seq(from=-pi,to=pi,length.out=200)
d <- vonMises(a=a,mu=pi/4,kappa=5)
symbols(x=0,y=0,circles=1,add=TRUE,inches=FALSE,xpd=NA,fg='grey50')
lines(x=(1+d)*cos(a),y=(1+d)*sin(a),xpd=NA)
```

worldpop	<i>world population</i>
----------	-------------------------

Description

The world population from 1750 until 2014.

Examples

```
data(worldpop,package='geostats')
plot(worldpop)
```

xyz2xy	<i>get x,y plot coordinates of ternary data</i>
--------	---

Description

Helper function to generate bivariate plot coordinates for ternary data.

Usage

```
xyz2xy(xyz)
```

Arguments

xyz an n x 3 matrix or data frame

Value

an n x 2 numerical matrix

Examples

```
xyz <- rbind(c(1,0,0),c(0,1,0),c(0,0,1),c(1,0,0))
xy <- xyz2xy(xyz)
plot(xy,type='l',bty='n')
```

york	<i>Linear regression of X,Y-variables with correlated errors</i>
------	--

Description

Implements the unified regression algorithm of York et al. (2004) which, although based on least squares, yields results that are consistent with maximum likelihood estimates of Titterton and Halliday (1979).

Usage

```
york(dat, alpha = 0.05, plot = TRUE, fill = NA, ...)
```

Arguments

dat a 4 or 5-column matrix with the X-values, the analytical uncertainties of the X-values, the Y-values, the analytical uncertainties of the Y-values, and (optionally) the correlation coefficients of the X- and Y-values.

alpha cutoff value for confidence intervals.

plot logical. If true, creates a scatter plot of the data with the best fit line shown on it.

`fill` the fill colour of the error ellipses. For additional plot options, use the `IsoplotR` package.
... optional arguments for the scatter plot.

Details

Given n pairs of (approximately) collinear measurements X_i and Y_i (for $1 \leq i \leq n$), their uncertainties $s[X_i]$ and $s[Y_i]$, and their covariances $\text{cov}[X_i, Y_i]$, the `york` function finds the best fitting straight line using the least-squares algorithm of York et al. (2004). This algorithm is modified from an earlier method developed by York (1968) to be consistent with the maximum likelihood approach of Titterton and Halliday (1979).

Value

A two-element list of vectors containing:

coef the intercept and slope of the straight line fit

cov the covariance matrix of the coefficients

References

Titterton, D.M. and Halliday, A.N., 1979. On the fitting of parallel isochrons and the method of maximum likelihood. *Chemical Geology*, 26(3), pp.183-195.

York, Derek, et al., 2004. Unified equations for the slope, intercept, and standard errors of the best straight line. *American Journal of Physics* 72.3, pp.367-375.

Examples

```
data(rbsr, package='geostats')  
fit <- york(rbsr)
```

Index

* data

- ACNK, 3
- AFM, 3
- Britain, 5
- clasts, 7
- Corsica, 10
- declustered, 11
- DZ, 12
- earthquakes, 12
- FAM, 14
- fault, 14
- Finland, 14
- forams, 15
- fractures, 16
- hills, 17
- major, 21
- meuse, 22
- palaeomag, 23
- pH, 24
- pop, 25
- porosity, 25
- rbsr, 28
- striations, 34
- test, 35
- training, 35
- worldpop, 36
- _PACKAGE (geostats), 16

- ACNK, 3
- AFM, 3
- alr, 4

- boxcount, 4
- Britain, 5

- cantor, 5
- circle.plot, 6
- circle.points, 7
- clasts, 7
- clr, 8

- colourplot, 8
- Corsica, 10
- countQuakes, 10

- declustered, 11
- DZ, 12

- earthquakes, 12
- ellipse, 12
- exp, 13

- FAM, 14
- fault, 14
- Finland, 14
- forams, 15
- fractaldim, 15
- fractures, 16

- geostats, 16
- geostats-package (geostats), 16
- gutenberg, 17

- hills, 17

- koch, 18
- kriging, 18
- ksdist, 19

- logit, 20

- major, 21
- meanangle, 21
- meuse, 22
- Mode, 22

- palaeomag, 23
- PCA2D, 23
- pendulum, 24
- pH, 24
- pop, 25
- porosity, 25

randy, 25

Rbar, 26

Rbar2kappa, 27

rbsr, 28

rwyxz, 28

rxzyz (rwyxz), 28

ryxy (rwyxz), 28

semivariogram, 18, 19, 29

sierpinski, 30

sizefrequency, 31

skew, 32

stereonet, 32

striations, 34

ternary, 34

test, 35

training, 35

vonMises, 36

worldpop, 36

xyz2xy, 37

york, 37