

Package ‘lingtypology’

June 24, 2022

Type Package

Title Linguistic Typology and Mapping

Version 1.1.9

Depends R (>= 3.5.0)

Imports leaflet, leaflet.minicharts, stats, utils, stringdist,
grDevices, jsonlite

Description

Provides R with the Glottolog database <<https://glottolog.org/>> and some more abilities for purposes of linguistic mapping. The Glottolog database contains the catalogue of languages of the world. This package helps researchers to make a linguistic maps, using philosophy of the Cross-Linguistic Linked Data project <<https://clld.org/>>, which allows for while at the same time facilitating uniform access to the data across publications. A tutorial for this package is available on GitHub pages <<https://docs.ropensci.org/lingtypology/>> and package vignette. Maps created by this package can be used both for the investigation and linguistic teaching. In addition, package provides an ability to download data from typological databases such as WALS, AUTOTYP and some others and to create your own database website.

License GPL (>= 2)

URL <https://CRAN.R-project.org/package=lingtypology>,

<https://github.com/ropensci/lingtypology/>,

<https://ropensci.github.io/lingtypology/>

BugReports <https://github.com/ropensci/lingtypology/issues>

LazyData TRUE

RoxygenNote 7.1.2

Encoding UTF-8

Suggests knitr, rmarkdown, testthat, covr, MASS, sp, rgeos, rgdal,
ggplot2, ape

VignetteBuilder knitr

NeedsCompilation no

Author George Moroz [aut, cre] (<<https://orcid.org/0000-0003-1990-6083>>),
 Kirill Koncha [ctb] (<<https://orcid.org/0000-0003-0676-2658>>),
 Mikhail Leonov [ctb],
 Anna Smirnova [ctb],
 Sasha Shakhnova [ctb]

Maintainer George Moroz <agricolamz@gmail.com>

Repository CRAN

Date/Publication 2022-06-24 12:10:02 UTC

R topics documented:

abvd	3
abvd.feature	4
afbo.feature	4
aff.lang	5
amap	6
area.lang	6
atlas.database	7
autotyp	7
autotyp.feature	8
bantu	9
bantu.feature	9
bivaltyp.feature	10
circassian	10
countries	11
country.lang	11
eurasianphonology	12
eurasianphonology.feature	13
ggmap.feature	13
glottolog	15
gltc.iso	16
gltc.lang	16
imports	17
is.glottolog	17
iso.gltc	18
iso.lang	19
lang.aff	19
lang.country	20
lang.gltc	21
lang.iso	21
lat.lang	22
level.lang	23
long.lang	23
map.feature	24
oto_mangueanIC	30
oto_mangueanIC.feature	30
phoible	31

<i>abvd</i>	3
-------------	---

phoible.feature	31
phonological_profiles	32
polygon.points_fd	32
polygon.points_kde	33
providers	33
sails.feature	34
soundcomparisons	34
soundcomparisons.feature	35
subc.lang	36
uralex	36
uralex.feature	37
url.lang	37
valpal.feature	38
vanuatu.feature	39
wals	39
wals.feature	40

Index	41
--------------	-----------

abvd	<i>ABVD's Language identifiers</i>
-------------	------------------------------------

Description

Language identifiers from ABVD (<https://abvd.eva.mpg.de/austronesian/>). This dataset is created for **abvd.feature** function.

Usage

abvd

Format

A data frame with 1468 rows and 2 variables:

id language identifier

glottocode Glottocode

abvd.feature *Download ABVD data*

Description

This function downloads data from ABVD (<https://abvd.eva.mpg.de/austronesian/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
abvd.feature(feature)
```

Arguments

feature	A character vector that define a language id from ABVD (e. g. "1", "292").
---------	--

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[afbo.feature](#), [autotyp.feature](#), [bivaltyp.feature](#), [eurasianphonology.feature](#), [oto_mangueanIC.feature](#),
[phoible.feature](#), [sails.feature](#), [soundcomparisons.feature](#), [uralex.feature](#), [valpal.feature](#),
[vanuatu.feature](#), [wals.feature](#)

Examples

```
# abvd.feature(c(292, 7))
```

afbo.feature *Download AfBo data*

Description

This function downloads data from AfBo (<https://afbo.info/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
afbo.feature(features = "all", na.rm = TRUE)
```

Arguments

- features A character vector that define with an affix functions from AfBo (e. g. "all", "adjectivizer", "focus").
- na.rm Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

See Also

[abvd.feature](#), [autotyp.feature](#), [bivaltyp.feature](#), [eurasianphonology.feature](#), [oto_mangueanIC.feature](#),
[phoible.feature](#), [sails.feature](#), [soundcomparisons.feature](#), [uralex.feature](#), [valpal.feature](#),
[vanuatu.feature](#), [wals.feature](#)
[abvd.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#),
[uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# afbo.feature()
# afbo.feature(c("adjectivizer", "adverbializer"))
```

aff.lang	<i>Get affiliation by language</i>
----------	------------------------------------

Description

Takes any vector of languages and returns affiliation.

Usage

```
aff.lang(x)
```

Arguments

- x A character vector of the languages (can be written in lower case)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[area.lang](#), [country.lang](#), [gltc.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#), [subc.lang](#), [url.lang](#)

Examples

```
aff.lang('Korean')
aff.lang(c('Korean', 'Polish'))
```

amap*Atlantic center template for ggmap.feature() function***Description****Usage****amap****Format**

A list with 9 variables.

area.lang*Get macro area by language***Description**

Takes any vector of languages and returns macro area.

Usage**area.lang(x)****Arguments****x** character vector of the languages (can be written in lower case)**Author(s)**

George Moroz <agricolamz@gmail.com>

See Also[aff.lang](#), [country.lang](#), [gltc.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#), [subc.lang](#), [url.lang](#)**Examples**

```
area.lang('Adyghe')
area.lang(c('Adyghe', 'Aduge'))
```

atlas.database	<i>Create an atlas</i>
----------------	------------------------

Description

This function creates an rmarkdown based atlas from data provided by users. This function creates the template, after it should be rendered by rmarkdown package. The DT package is required during the rendering.

Usage

```
atlas.database(  
  languages,  
  latitude,  
  longitude,  
  features,  
  atlas.name = "",  
  author = ""  
)
```

Arguments

languages	character vector of languages (can be written in lower case)
latitude	numeric vector of latitudes (optional)
longitude	numeric vector of longitudes (optional)
features	dataframe where each column is a feature set
atlas.name	string with an atlas name
author	string with the authors list

autotyp	<i>AUTOTYP's Language identifiers</i>
---------	---------------------------------------

Description

Language identifiers from AUTOTYP v. 0.1.4 (<https://github.com/autotyp/autotyp-data/>). This dataset is created for `autotyp.feature` function.

Usage

```
autotyp
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 1336 rows and 3 columns.

Details

#' @format A data frame with 1336 rows and 3 variables:

path path to the dataset in autotyp repo
variable variable name
file topic name

autotyp.feature *Download AUTOTYP data*

Description

This function downloads data from AUTOTYP (<https://github.com/autotyp/autotyp-data#the-autotyp-database>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
autotyp.feature(features, na.rm = TRUE)
```

Arguments

features	A character vector that define with a feature names from AUTOTYP.
na.rm	Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

See Also

[abvd.feature](#), [afbo.feature](#), [bivaltyp.feature](#), [eurasianphonology.feature](#), [oto_mangueanIC.feature](#),
[phoible.feature](#), [sails.feature](#), [soundcomparisons.feature](#), [uralex.feature](#), [valpal.feature](#),
[vanuatu.feature](#), [wals.feature](#)

[abvd.feature](#), [afbo.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#),
[uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# autotyp.feature(c('Has Gender', 'Has Numeral Classifiers'))
```

bantu

BANTU's Language identifiers

Description

Language identifiers from BANTU (<https://abvd.eva.mpg.de/bantu/index.php>). This dataset is created for `bantu.feature` function.

Usage

```
bantu
```

Format

A data frame with 430 rows and 2 variables:

id BANTU word id
word word

bantu.feature

Download BANTU data

Description

This function downloads data from Bantu Basic Vocabulary Database (<https://abvd.eva.mpg.de/bantu/index.php>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
bantu.feature(features)
```

Arguments

features A character vector that define with a feature ids from BANTU ('house', 'cat').

Author(s)

Anna Smirnova <annedadada@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#)

Examples

```
# bantu.feature(c('house', 'cat'))
```

bivaltyp.feature	<i>Download BivalTyp data</i>
------------------	-------------------------------

Description

This function downloads data from BivalTyp (<https://www.bivaltyp.info/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
bivaltyp.feature()
```

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#),
[sails.feature](#), [valpal.feature](#), [wals.feature](#)
[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [eurasianphonology.feature](#), [oto_mangueanIC.feature](#),
[phoible.feature](#), [sails.feature](#), [soundcomparisons.feature](#), [uralex.feature](#), [valpal.feature](#),
[vanuatu.feature](#), [wals.feature](#) # bivaltyp.feature()

circassian	<i>Circassian villages in Russia</i>
------------	--------------------------------------

Description

A dataset contains the list of the Circassian villages in Russia with genealogical affiliation, coordinates and district names. Most data collected during the fieldworks (2011–2018).

Usage

```
circassian
```

Format

A data frame with 158 rows and 6 variables:

longitude longitude
latitude latitude
village name of the village

district names of the subjects of the Russian Federation: kbr — Kabardino–Balkar Republic, kch — Karachay–Cherkess Republic, kk — Krasnodar Krai, ra — Republic of Adygea, stv — Stavropol Krai

dialect names of the Circassian dialects

language according standard Circassian devision there are Adyghe and Kabardian languages

countries

Catalogue of countries

Description

Catalogue of countries, ISO-codes and official languages

Usage

```
countries
```

Format

A data frame with 189 rows and 5 variables:

alpha3 ISO 3166-3 code of the country

alpha2 ISO 3166-2 code of the country

country_name Country name

additional_names Additional names of the country

official_languages Official languages

country.lang

Get country by language

Description

Takes any vector of languages and returns countries where those languages are used as ISO 3166-1 alpha-2 codes.

Usage

```
country.lang(x, full_name = TRUE)
```

Arguments

- | | |
|-----------|--|
| x | A character vector of the languages (can be written in lower case) |
| full_name | A logical value, whether return ISO 3166-2 codes or full names. |

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [gltc.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#), [subc.lang](#), [url.lang](#)

Examples

```
country.lang('Korean')
country.lang(c('Korean', 'Polish'))
```

eurasianphonology *Eurasianphonology data*

Description

Data from The database of Eurasian phonological inventories (<https://eurphon.info>). This dataset is created for [eurasianphonology.feature](#) function.

Usage

`eurasianphonology`

Format

A data frame with 19825 rows and 19 variables:

- id** Language id
- iso** ISO code
- name** Another language name
- type** Language or dialect
- language** Language name
- latitude** latitude
- longitude** longitude
- gen1** Language Family
- gen2** Language Family
- tones** Inventory of tones
- syllab** Syllab structure
- cluster** Cluster
- finals** Finals
- source** Source
- comment** Comment

contr Contributor

segment_type Vowels or consonants

segments Segments

glottocode Glottocode

eurasianphonology.feature

Opens data from the database of Eurasian phonological inventories

Description

This function opens downloaded data from the database of Eurasian phonological inventories (<https://eurphon.info>).

Usage

```
eurasianphonology.feature()
```

Author(s)

Kirill Koncha <majortomblog@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [bivaltyp.feature](#), [oto_mangueanIC.feature](#),
[phoible.feature](#), [sails.feature](#), [soundcomparisons.feature](#), [uralex.feature](#), [valpal.feature](#),
[vanuatu.feature](#), [wals.feature](#)

Examples

```
eurasianphonology.feature()
```

ggmap.feature

Create a map with ggplot2

Description

Map a set of languages and color them by feature.

Usage

```
ggmap.feature(
  languages,
  features = "",
  latitude = NA,
  longitude = NA,
  color = NULL,
  title = NULL,
  legend = TRUE,
  width = 2,
  opacity = 1,
  map.orientation = "Atlantic"
)
```

Arguments

<code>languages</code>	character vector of languages (can be written in lower case).
<code>features</code>	character vector of features.
<code>latitude</code>	numeric vector of latitudes.
<code>longitude</code>	numeric vector of longitudes.
<code>color</code>	vector of colors or palette. The color argument can be (1) a character vector of RGM or named colors; (2) the name of an RColorBrewer palette; (3) the full name of a viridis palette; (4) a function that receives a single value between 0 and 1 and returns a color. For more examples see colorNumeric .
<code>title</code>	title of a legend.
<code>legend</code>	logical. If TRUE, function show legend. By default is TRUE.
<code>width</code>	a numeric vector of radius for circles or width for barcharts in minicharts.
<code>opacity</code>	a numeric vector of marker opacity.
<code>map.orientation</code>	a character verctor with values "Pacific" and "Atlantic". It distinguishes Pacific-centered and Atlantic-centered maps. By default is "Atlantic".

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
ggmap.feature(c("Adyghe", "Russian"))
```

glottolog

Catalogue of languages of the world

Description

A dataset contains the original catalogue of languages of the world involving genealogical affiliation, macro-area, country, iso code, and coordinates.

Usage

glottolog

Format

A data frame with 26285 rows and 10 variables:

glottocode languoid code from Glottolog 4.5

language name of the language

iso code based on ISO 639–3 <https://iso639-3.sil.org/>

level languoid type: dialect or language (possible values are dialect, language, family, bookkeeping, pseudo family, sign language, unclassifiable, pidgin, unattested, artificial language, speech register, mixed language)

area have six values Africa, Australia, Eurasia, North America, Papunesia, South America

latitude latitude

longitude longitude

countries list of countries, where the language is spoken

affiliation genealogical affiliation

subclassification subclassification in a Newick format

Details

Hammarström, Harald and Forkel, Robert and Haspelmath, Martin and Bank, Sebastian. 2022. Glottolog 4.6. Leipzig: Max Planck Institute for Evolutionary Anthropology. <https://doi.org/10.5281/zenodo.6578297> (Available online at <http://glottolog.org>, Accessed on 2022-05-29.)

Source

<https://glottolog.org/>

gltc.iso*Get Glottocode by ISO 639–3 code***Description**

Takes any vector of ISO 639–3 codes and returns Glottocodes.

Usage

```
gltc.iso(x)
```

Arguments

x	A character vector of the Glottocodes.
---	--

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
gltc.iso('ady')
gltc.iso(c('ady', 'rus'))
```

gltc.lang*Get Glottocode by language***Description**

Takes any vector of languages and returns Glottocode.

Usage

```
gltc.lang(x)
```

Arguments

x	A character vector of the languages (can be written in lower case)
---	--

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#), [subc.lang](#), [url.lang](#)

Examples

```
gltc.lang('Adyghe')
gltc.lang(c('Adyghe', 'Udi'))
```

imports

Objects imported from other packages

Description

These objects are imported from other packages. Follow the links to their documentation.

magrittr %>%

is.glottolog

Are these languages in glottolog?

Description

Takes any vector of languages or ISO codes and returns a logical vector.

Usage

```
is.glottolog(x, response = FALSE)
```

Arguments

- | | |
|----------|--|
| x | A character vector of languages (can be written in lower case)or ISO codes |
| response | logical. If TRUE, when language is absent, return warnings with a possible candidates. |

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
is.glotolog(c('Adyghe', 'Russian'))
is.glotolog('Buyaka')

# Add warning message with suggestions
is.glotolog(c('Adygey', 'Russian'), response = TRUE)
# > FALSE TRUE
# Warning message:
# In is.glotolog(c('Adyge', 'Russian'), response = TRUE) :
# Language Adyge is absent in our version of the Glottolog database. Did you mean Aduge, Adyghe?
```

iso.gltc

Get ISO 639–3 code by Glottocode

Description

Takes any vector of Glotocodes and returns ISO code.

Usage

```
iso.gltc(x)
```

Arguments

x	A character vector of Glottocodes.
---	------------------------------------

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
iso.gltc('adyg1241')
iso.gltc(c('adyg1241', 'udii1243'))
```

iso.lang *Get ISO 639–3 code by language*

Description

Takes any vector of languages and returns ISO code.

Usage

```
iso.lang(x)
```

Arguments

x A character vector of the languages (can be written in lower case)

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [gltc.lang](#), [lat.lang](#), [long.lang](#), [subc.lang](#), [url.lang](#)

Examples

```
iso.lang('Adyghe')
iso.lang(c('Adyghe', 'Udi'))
```

lang.aff *Get languages by affiliation*

Description

Takes any vector of affiliations and returns languages.

Usage

```
lang.aff(x, include.dialects = FALSE, list = FALSE)
```

Arguments

x A character vector of the affiliations (can be written in lower case)

include.dialects logical. If TRUE, it returns all languages and dialects, if FALSE it returns only languages.

list logical. If TRUE, it returns a list of languages, if FALSE it returns a named vector.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[lang.iso](#)

Examples

```
lang.aff('Slavic')
lang.aff(c('Slavic', 'Celtic'))
lang.aff(c('Slavic', 'Celtic'), list = TRUE)
```

lang.country

Get language by country

Description

Takes any vector of countries and returns languages.

Usage

```
lang.country(x, list = TRUE)
```

Arguments

- | | |
|------|---|
| x | character vector of the countries (in alpha-2 ISO codes) |
| list | logical. If TRUE, it returns a list of languages, if FALSE it returns a named vector. |

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [country.lang](#), [gltc.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#), [subc.lang](#), [url.lang](#)

Examples

```
lang.country('AD')
lang.country(c('AD', 'AE'))
```

lang.gltc	<i>Get language by Glottocode</i>
-----------	-----------------------------------

Description

Takes any vector of Glottocodes and returns languages.

Usage

```
lang.gltc(x)
```

Arguments

x A character vector of the Glottocodes.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[lang.aff](#)

Examples

```
lang.gltc('adyg1241')
lang.gltc(c('adyg1241', 'udii1243'))
```

lang.iso	<i>Get language by ISO 639–3 code</i>
----------	---------------------------------------

Description

Takes any vector of ISO codes and returns languages.

Usage

```
lang.iso(x)
```

Arguments

x A character vector of the ISO codes.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[lang.aff](#)

Examples

```
lang.iso('ady')
lang.iso(c('ady', 'rus'))
```

lat.lang

Get latitude by language

Description

Takes any vector of languages and returns latitude.

Usage

```
lat.lang(x)
```

Arguments

x	A character vector of the languages (can be written in lower case)
---	--

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [gltc.lang](#), [iso.lang](#), [long.lang](#), [subc.lang](#), [url.lang](#)

Examples

```
lat.lang('Adyghe')
long.lang('Adyghe')
lat.lang(c('Adyghe', 'Russian'))
long.lang(c('Adyghe', 'Russian'))
```

level.lang	<i>Get a level of language by language</i>
------------	--

Description

Takes any vector of languages and returns a level of language.

Usage

```
level.lang(x)
```

Arguments

x character vector of the languages (can be written in lower case)

Author(s)

Sasha Shakhnova

See Also

[aff.lang](#), [country.lang](#), [gltc.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#), [subc.lang](#), [url.lang](#)

Examples

```
level.lang('Russian Sign Language')
level.lang(c('Archi', 'Chechen'))
```

long.lang	<i>Get longitude by language</i>
-----------	----------------------------------

Description

Takes any vector of languages and returns longitude.

Usage

```
long.lang(x, map.orientation = "Pacific")
```

Arguments

x A character vector of the languages (can be written in lower case)

map.orientation A character vector with values "Pacific" and "Atlantic". It distinguishes Pacific-centered and Atlantic-centered maps. By default is "Pacific".

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [gltc.lang](#), [iso.lang](#), [lat.lang](#), [subc.lang](#), [url.lang](#)

Examples

```
lat.lang('Adyghe')
long.lang('Adyghe')
lat.lang(c('Adyghe', 'Russian'))
long.lang(c('Adyghe', 'Russian'))
long.lang(c('Adyghe', 'Aleut'), map.orientation = "Pacific")
```

map.feature

Create a map

Description

Map a set of languages and color them by feature or two sets of features.

Usage

```
map.feature(
  languages,
  features = "",
  label = "",
  popup = "",
  latitude = NA,
  longitude = NA,
  label.hide = TRUE,
  label.fsize = 15,
  label.font = "sans-serif",
  label.position = "right",
  label.emphasize = list(NULL, "black"),
  shape = NULL,
  shape.size = 20,
  pipe.data = NULL,
  shape.color = "black",
  stroke.features = NULL,
  point.cluster = FALSE,
  density.estimation = NULL,
  density.method = "fixed distance",
  density.estimation.color = NULL,
  density.estimation.opacity = 0.6,
  density.points = TRUE,
```

```
density.width = NULL,  
density.legend = TRUE,  
density.legend.opacity = 1,  
density.legend.position = "bottomleft",  
density.title = "",  
density.control = FALSE,  
isogloss = NULL,  
isogloss.color = "black",  
isogloss.opacity = 0.2,  
isogloss.line.width = 3,  
isogloss.width = NULL,  
color = NULL,  
stroke.color = NULL,  
image.url = NULL,  
image.width = 100,  
image.height = 100,  
image.X.shift = 0,  
image.Y.shift = 0,  
title = NULL,  
stroke.title = NULL,  
control = "",  
legend = TRUE,  
legend.opacity = 1,  
legend.position = "topright",  
stroke.legend = TRUE,  
stroke.legend.opacity = 1,  
stroke.legend.position = "bottomleft",  
width = 5,  
stroke.radius = 9.5,  
opacity = 1,  
stroke.opacity = 1,  
scale.bar = TRUE,  
scale.bar.position = "bottomleft",  
minimap = FALSE,  
minimap.position = "bottomright",  
minimap.width = 150,  
minimap.height = 150,  
facet = NULL,  
tile = "OpenStreetMap.Mapnik",  
tile.name = NULL,  
tile.opacity = 1,  
zoom.control = FALSE,  
zoom.level = NULL,  
rectangle.lng = NULL,  
rectangle.lat = NULL,  
rectangle.color = "black",  
line.lng = NULL,  
line.lat = NULL,
```

```

    line.type = "standard",
    line.color = "black",
    line.opacity = 0.8,
    line.label = NULL,
    line.width = 3,
    graticule = NULL,
    minichart = "bar",
    minichart.data = NULL,
    minichart.time = NULL,
    minichart.labels = FALSE,
    map.orientation = "Pacific",
    radius = NULL
)

```

Arguments

<code>languages</code>	character vector of languages (can be written in lower case)
<code>features</code>	character vector of features
<code>label</code>	character vector of strings that will appear near points
<code>popup</code>	character vector of strings that will appear in pop-up window
<code>latitude</code>	numeric vector of latitudes
<code>longitude</code>	numeric vector of longitudes
<code>label.hide</code>	logical. If FALSE, labels are displayed allways. If TRUE, labels are displayed on mouse over. By default is TRUE.
<code>label.fsize</code>	numeric value of the label font size. By default is 14.
<code>label.font</code>	string with values of generic family: "serif", "sans-serif", "monospace", or font name e. g. "Times New Roman"
<code>label.position</code>	the position of labels: "left", "right", "top", "bottom"
<code>label.emphasize</code>	is the list. First argument is a vector of points in datframe that should be emphasized. Second argument is a string with a color for emphasis.
<code>shape</code>	<ol style="list-style-type: none"> 1. if TRUE, creates icons (up to five categories) for values in the <code>features</code> variable; 2. it also could be a vector of any strings that represents the levels of the <code>features</code> variable; 3. it also could be a string vector that represents the number of observations in dataset.
<code>shape.size</code>	size of the shape icons
<code>pipe.data</code>	this variable is important, when you use <code>map.feature</code> with dplyr pipes. Expected usage: <code>pipe.data = .</code>
<code>shape.color</code>	color of the shape icons
<code>stroke.features</code>	additional independent stroke features
<code>point.cluster</code>	logical. If TRUE, points will be united into clusters.

density.estimation
 additional independent features, used for density estimation

density.method string with one of the two methods: "kernal density estimation" or "fixed distance" (default)

density.estimation.color
 vector of density polygons' colors

density.estimation.opacity
 a numeric vector of density polygons opacity.

density.points logical. If FALSE, it doesn't show points in polygons.

density.width for density.method = "fixed distance" it is a numeric measure (1 is 1km). For density.method = "kernal density estimation" it is a vector with two measures (first is latitude, secong is longitude). Defaults are normal reference bandwidth (see [bandwidth.nrd](#)).

density.legend logical. If TRUE, function show legend for density features. By default is FALSE.

density.legend.opacity
 a numeric vector of density-legend opacity.

density.legend.position
 the position of the legend: "topright", "bottomright", "bottomleft","topleft"

density.title title of a density-feature legend

density.control
 logical. If TRUE, function show layer control buttons for density plot. By default is FALSE

isogloss dataframe with corresponding features

isogloss.color vector of isoglosses' colors

isogloss.opacity
 a numeric vector of density polygons opacity.

isogloss.line.width
 a numeric value for line width

isogloss.width for density.method = "fixed distance" it is a numeric measure (1 is 1km). For density.method = "kernal density estimation" it is a vector with two measures (first is latitude, secong is longitude). Defaults are normal reference bandwidth (see [bandwidth.nrd](#)).

color vector of colors or palette. The color argument can be (1) a character vector of RGM or named colors; (2) the name of an RColorBrewer palette; (3) the full name of a viridis palette; (4) a function that receives a single value between 0 and 1 and returns a color. For more examples see [colorNumeric](#)

stroke.color vector of stroke colors

image.url character vector of URLs with an images

image.width numeric vector of image widths

image.height numeric vector of image heights

image.X.shift numeric vector of image's X axis shift relative to the latitude-longitude point

image.Y.shift numeric vector of image's Y axis shift relative to the latitude-longitude point

title title of a legend.

stroke.title title of a stroke-feature legend.

control vector of grouping values that make it possible to create control panel that can turn off/on some points on the map.

legend logical. If TRUE, function show legend. By default is TRUE.

legend.opacity a numeric vector of legend opacity.

legend.position the position of the legend: "topright", "bottomright", "bottomleft", "topleft"

stroke.legend logical. If TRUE, function show stroke.legend. By default is FALSE.

stroke.legend.opacity a numeric vector of stroke.legend opacity.

stroke.legend.position the position of the stroke.legend: "topright", "bottomright", "bottomleft", "topleft"

width a numeric vector of radius for circles or width for barcharts in minicharts.

stroke.radius a numeric vector of stroke radii for the circles.

opacity a numeric vector of marker opacity.

stroke.opacity a numeric vector of stroke opacity.

scale.bar logical. If TRUE, function shows scale-bar. By default is TRUE.

scale.bar.position the position of the scale-bar: "topright", "bottomright", "bottomleft", "topleft"

minimap logical. If TRUE, function shows mini map. By default is FALSE.

minimap.position the position of the minimap: "topright", "bottomright", "bottomleft", "topleft"

minimap.width The width of the minimap in pixels.

minimap.height The height of the minimap in pixels.

facet character vector that provide a grouping variable. If it is no NULL, then as a result a list of leaflets for sync or latticeView functions from *mapview* package is returned.

tile a character verctor with a map tiles, popularized by Google Maps. See [here](#) for the complete set.

tile.name a character verctor with a user's map tiles' names.

tile.opacity numeric value from 0 to 1 denoting opacity of the tile.

zoom.control logical. If TRUE, function shows zoom controls. By default is FALSE.

zoom.level a numeric value of the zoom level.

rectangle.lng vector of two longitude values for rectangle.

rectangle.lat vector of two latitude values for rectangle.

rectangle.color vector of rectangle border color.

line.lng vector of two (or more) longitude values for line.

line.lat vector of two (or more) latitude values for line.

line.type	a character string indicating which type of line is to be computed. One of "standard" (default), or "logit". The first one should be combined with the arguments line.lat and line.lng and provide simple lines. Other variant "logit" is the decision boundary of the logistic regression made using longitude and latitude coordinates (works only if feature argument have two levels).
line.color	vector of line color.
line.opacity	a numeric vector of line opacity.
line.label	character vector that will appear near the line.
line.width	a numeric vector of line width.
graticule	a numeric vector for graticule spacing in map units between horizontal and vertical lines.
minichart	citation from leaflet.minicharts package: "Possible values are "bar" for bar charts, "pie" for pie charts, "polar-area" and "polar-radius"."
minichart.data	citation from leaflet.minicharts package: "A numeric matrix with number of rows equal to the number of elements in lng or lat and number of column equal to the number of variables to represent. If parameter time is set, the number of rows must be equal to the length of lng times the number of unique time steps in the data."
minichart.time	citation from leaflet.minicharts package: "A vector with length equal to the number of rows in chartdata and containing either numbers representing time indices or dates or datetimes. Each unique value must appear as many times as the others. This parameter can be used when one wants to represent the evolution of some variables on a map."
minichart.labels	citation from leaflet.minicharts package: "Should values be displayed above chart elements."
map.orientation	a character vector with values "Pacific" and "Atlantic". It distinguishes Pacific-centered and Atlantic-centered maps. By default is "Pacific".
radius	deprecated argument

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
map.feature(c("Adyghe", "Russian"))
```

`oto_mangueanIC`

Oto-Manguean Inflectional Class Database Language identifiers

Description

Language identifiers from Oto-Manguean Inflectional Class Database (<https://oto-manguean.surrey.ac.uk/>). This dataset is created for `oto_mangueanIC.feature` function.

Usage

```
oto_mangueanIC
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 20 rows and 2 columns.

Details

#' @format A data frame with 20 rows and 2 variables:

Language.name Languaeg names from Oto-Manguean Inflectional Class Database

language Language names from Glottolog database

`oto_mangueanIC.feature`

Download Oto-Manguean Inflectional Class Database data

Description

This function downloads data from Oto-Manguean Inflectional Class Database (<https://oto-manguean.surrey.ac.uk/>) and creates a language column with the names from lingtypology database. You need the internet connection.

Usage

```
oto_mangueanIC.feature()
```

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

`abvd.feature`, `afbo.feature`, `autotyp.feature`, `phoible.feature`, `sails.feature`, `uralex.feature`,
`valpal.feature`, `wals.feature`
`abvd.feature`, `afbo.feature`, `autotyp.feature`, `bivaltyp.feature`, `eurasianphonology.feature`,
`phoible.feature`, `sails.feature`, `soundcomparisons.feature`, `uralex.feature`, `valpal.feature`,
`vanuatu.feature`, `wals.feature` # `oto_mangueanIC.feature()`

phoible*Phoible glottolog - language correspondencies*

Description

Language correspondencies for Phoible (<https://phoible.org/>). This dataset is created for `phoible.feature` function.

Usage

```
phoible
```

Format

A data frame with 2185 rows and 2 variables:

language language

Glottocode Glottocode

phoible.feature*Download PHOIBLE data*

Description

This function downloads data from PHOIBLE (<https://phoible.org/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
phoible.feature(source = "all", na.rm = TRUE)
```

Arguments

source A character vector that define with a source names from PHOIBLE (possible values: "all", "aa", "gm", "ph", "ra", "saphon", "spa", "upsid").

na.rm Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [bivaltyp.feature](#), [eurasianphonology.feature](#), [oto_mangueanIC.feature](#), [sails.feature](#), [soundcomparisons.feature](#), [uralex.feature](#), [valpal.feature](#), [vanuatu.feature](#), [wals.feature](#)

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Description

```
# phoible.feature()
# phoible.feature(c('consonants', 'vowels'), source = "UPSID")
```

phonological_profiles *Number of consonants and presence of ejectives*

Description

Number of consonants and presence of ejectives

Usage

```
phonological_profiles
```

Format

A data frame with 19 rows and 4 variables:

language language name

consonants number of consonants. Based on UPSID database.

vowels number of vowels. Based on UPSID database.

ejectives presence of ejective sounds.

tone presence of tone.

stress presence of stress.

long_vowels presence of long vowels.

polygon.points_fd *Get polygons from fixed distance circles around coordinates*

Description

This function is based on this answer: <https://www.r-bloggers.com/merging-spatial-buffers-in-r/>

Usage

```
polygon.points_fd(latitude, longitude, width)
```

Arguments

latitude	numeric vector of latitudes
longitude	numeric vector of longitudes
width	radius for creating polygons around points

polygon.points_kde *Get kernel density estimation poligon from coordinates*

Description

This function is based on this answer: <https://gis.stackexchange.com/a/203623/>

Usage

```
polygon.points_kde(latitude, longitude, latitude.width, longitude.width)
```

Arguments

latitude	numeric vector of latitudes
longitude	numeric vector of longitudes
latitude.width	bandwidths for latitude values. Defaults to normal reference bandwidth (see bandwidth.nrd).
longitude.width	bandwidths for longitude values. Defaults to normal reference bandwidth (see bandwidth.nrd).

providers *Providers*

Description

List of all providers with their variations taken from leaflet package

Usage

```
providers
```

Format

A list of characters

Source

<https://github.com/leaflet-extras/leaflet-providers/blob/master/leaflet-providers.js>

`sails.feature` *Download SAILS data*

Description

This function downloads data from SAILS (<https://sails.clld.org/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
sails.feature(features, na.rm = TRUE)
```

Arguments

- | | |
|-----------------------|---|
| <code>features</code> | A character vector that define with a feature ids from SAILS (e. g. "and1", "argex4-1-3"). |
| <code>na.rm</code> | Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE. |

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [bivaltyp.feature](#), [eurasianphonology.feature](#),
[oto_mangueanIC.feature](#), [phoible.feature](#), [soundcomparisons.feature](#), [uralex.feature](#),
[valpal.feature](#), [vanuatu.feature](#), [wals.feature](#)

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#),
[uralex.feature](#), [valpal.feature](#), [wals.feature](#)

Examples

```
# sails.feature(c("and1", "and11"))
```

soundcomparisons *SOUNDCOMPARISONS's Language identifiers*

Description

Language identifiers from SOUNDCOMPARISONS (<https://soundcomparisons.com/>). This dataset is created for `soundcomparisons.feature` function.

Usage

```
soundcomparisons
```

Format

An object of class `data.frame` with 556 rows and 3 columns.

Details

#' @format A data frame with 556 rows and 2 variables:

LanguageName SOUNDCOMPARISONS language identifier

LanguageId Language Id

soundcomparisons.feature

Download SOUNDCOMPARISONS data

Description

This function downloads data from SOUNDCOMPARISONS (<https://soundcomparisons.com/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
soundcomparisons.feature(word)
```

Arguments

word A character vector that define with a feature ids from SOUNDCOMPARISONS (e. g. "one", "sharp_fem", "near_neut", "on_the_left", "I_will_give", "write_ipv_sg", "your_pl_pl").

Author(s)

Anna Smirnova

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [vanuatu.feature](#), [eurasianphonology.feature](#), [eurasianphonology.feature](#)

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [bivaltyp.feature](#), [eurasianphonology.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [uralex.feature](#), [valpal.feature](#), [vanuatu.feature](#), [wals.feature](#)

Examples

```
# soundcomparisons.feature(c("sun", "house"))
```

subc.lang	<i>Get subclassification by language</i>
-----------	--

Description

Takes any vector of languoids and returns subclassification in the Newick tree format.

Usage

```
subc.lang(x)
```

Arguments

x	A character vector of the languoids (can be written in lower case)
---	--

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [gltc.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#)

Examples

```
subc.lang('Korean')
subc.lang(c('Korean', 'Lechitic'))
```

uralex	<i>UraLex's Language identifiers</i>
--------	--------------------------------------

Description

Language identifiers from UraLex (<https://github.com/lexibank/uralex/>). This dataset is created for [uralex.feature](#) function.

Usage

```
uralex
```

Format

A data frame with 27 rows and 3 variables:

language language name from database

Glottocode Glottocodes

language2 language from lingtypology

uralex.feature *Download UraLex data*

Description

This function downloads data from UraLex (<https://github.com/lexibank/uralex/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
uralex.feature(na.rm = TRUE)
```

Arguments

na.rm Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [bivaltyp.feature](#), [eurasianphonology.feature](#),
[oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [soundcomparisons.feature](#), [valpal.feature](#),
[vanuatu.feature](#), [wals.feature](#)

Examples

```
# uralex.feature()
```

url.lang *Make a url-link to glottolog page for a language*

Description

Takes any vector of languages and returns links to glottolog pages.

Usage

```
url.lang(x, popup = "")
```

Arguments

x A character vector of languages (can be written in lower case)
popup character vector of strings that will appear in pop-up window of the function
map.feature

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[aff.lang](#), [area.lang](#), [country.lang](#), [gltc.lang](#), [iso.lang](#), [lat.lang](#), [long.lang](#), [subc.lang](#)

Examples

```
url.lang('Korean')
url.lang(c('Gangou', 'Hachijo', 'Adyghe', 'Ganai'))
```

[valpal.feature](#)

Download ValPaL data

Description

This function downloads data from ValPal (<https://valpal.info>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
valpal.feature(na.rm = FALSE)
```

Arguments

na.rm	Logical. If TRUE function removes all languages not available in lingtypology database. By default is FALSE.
-------	--

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [bivaltyp.feature](#), [eurasianphonology.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [soundcomparisons.feature](#), [uralex.feature](#), [vanuatu.feature](#), [wals.feature](#)

Examples

```
# valpal.feature()
```

vanuatu.feature *Download Vanuatu Voices data*

Description

This function downloads data from Vanuatu Voices (<https://vanuatuvvoices.clld.org/>). You need the internet connection.

Usage

```
vanuatu.feature(features, na.rm = TRUE)
```

Arguments

features	A vector with parameters from Concepts (https://vanuatuvvoices.clld.org/parameters)
na.rm	Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

Author(s)

Mikhail Leonov

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [bivaltyp.feature](#), [eurasianphonology.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [soundcomparisons.feature](#), [uralex.feature](#), [valpal.feature](#), [wals.feature](#)

wals *WALS's Language identifiers*

Description

Language identifiers from WALS (<https://wals.info/>). This dataset is created for [wals.feature](#) function.

Usage

```
wals
```

Format

A data frame with 2950 rows and 2 variables:

wals.code WALS language identifier
glottocode Glottocode

wals.feature

Download WALS data

Description

This function downloads data from WALS (<https://wals.info/>) and changes language names to the names from lingtypology database. You need the internet connection.

Usage

```
wals.feature(features, na.rm = TRUE)
```

Arguments

- features A character vector that define with a feature ids from WALS (e. g. "1a", "21b").
na.rm Logical. If TRUE function removes all languages not available in lingtypology database. By default is TRUE.

Author(s)

George Moroz <agricolamz@gmail.com>

See Also

[abvd.feature](#), [afbo.feature](#), [autotyp.feature](#), [bivaltyp.feature](#), [eurasianphonology.feature](#), [oto_mangueanIC.feature](#), [phoible.feature](#), [sails.feature](#), [soundcomparisons.feature](#), [uralex.feature](#), [valpal.feature](#), [vanuatu.feature](#)

Examples

```
# wals.feature(c("1a", "20a"))
```

Index

- * datasets
 - abvd, 3
 - amap, 6
 - autotyp, 7
 - bantu, 9
 - circassian, 10
 - countries, 11
 - eurasianphonology, 12
 - glottolog, 15
 - oto_mangueanIC, 30
 - phoible, 31
 - phonological_profiles, 32
 - providers, 33
 - soundcomparisons, 34
 - uralex, 36
 - wals, 39
- %>% (imports), 17
- %>%, 17
- abvd, 3
- abvd.feature, 3, 4, 5, 8–10, 13, 30, 31, 34, 35, 37–40
- afbo.feature, 4, 4, 8–10, 13, 30, 31, 34, 35, 37–40
- aff.lang, 5, 6, 12, 16–20, 22–24, 36, 38
- amap, 6
- area.lang, 5, 6, 12, 16–19, 22, 24, 36, 38
- atlas.database, 7
- autotyp, 7
- autotyp.feature, 4, 5, 7, 8, 9, 10, 13, 30, 31, 34, 35, 37–40
- bandwidth.nrd, 27, 33
- bantu, 9
- bantu.feature, 9, 9
- bivaltyp.feature, 4, 5, 8, 10, 13, 30, 31, 34, 35, 37–40
- circassian, 10
- colorNumeric, 14, 27
- countries, 11
- country.lang, 5, 6, 11, 17, 19, 20, 22–24, 36, 38
- eurasianphonology, 12
- eurasianphonology.feature, 4, 5, 8, 10, 12, 13, 30, 31, 34, 35, 37–40
- ggmap.feature, 13
- glottolog, 15
- gltc.iso, 16
- gltc.lang, 5, 6, 12, 16, 19, 20, 22–24, 36, 38
- imports, 17
- is.glottolog, 17
- iso.gltc, 18
- iso.lang, 5, 6, 12, 17, 19, 20, 22–24, 36, 38
- lang.aff, 19, 21, 22
- lang.country, 20
- lang.gltc, 21
- lang.iso, 20, 21
- lat.lang, 5, 6, 12, 16–20, 22, 23, 24, 36, 38
- level.lang, 23
- long.lang, 5, 6, 12, 16–20, 22, 23, 23, 36, 38
- map.feature, 24
- oto_mangueanIC, 30
- oto_mangueanIC.feature, 4, 5, 8–10, 13, 30, 31, 34, 35, 37–40
- phoible, 31
- phoible.feature, 4, 5, 8–10, 13, 30, 31, 34, 35, 37–40
- phonological_profiles, 32
- polygon.points_fd, 32
- polygon.points_kde, 33
- providers, 33
- sails.feature, 4, 5, 8–10, 13, 30, 31, 34, 35, 37–40

soundcomparisons, 34
soundcomparisons.feature, 4, 5, 8, 10, 13,
 30, 31, 34, 35, 37–40
subc.lang, 5, 6, 12, 17, 19, 20, 22–24, 36, 38

uralex, 36
uralex.feature, 4, 5, 8–10, 13, 30, 31,
 34–36, 37, 38–40
url.lang, 5, 6, 12, 17, 19, 20, 22–24, 37

valpal.feature, 4, 5, 8–10, 13, 30, 31, 34,
 35, 37, 38, 39, 40
vanuatu.feature, 4, 5, 8, 10, 13, 30, 31, 34,
 35, 37, 38, 39, 40

wals, 39
wals.feature, 4, 5, 8, 10, 13, 30, 31, 34, 35,
 37–39, 40