

# Package ‘shinypivottabler’

February 22, 2021

**Title** Shiny Module to Create Pivot Tables

**Version** 1.0

**Description** Shiny Module to create, visualize, customize and export Excel-like pivot table.

**License** GPL-3

**Encoding** UTF-8

**Depends** R (>= 3.4)

**LazyData** true

**RoxygenNote** 7.1.1

**Imports** pivottabler (>= 1.5.0), shiny, openxlsx, colourpicker,  
htmltools

**NeedsCompilation** no

**Author** Benoit Thieurmél [aut, cre],  
Thibaut Dubois [aut]

**Maintainer** Benoit Thieurmél <benoit.thieurmél@datastorm.fr>

**Repository** CRAN

**Date/Publication** 2021-02-22 20:10:03 UTC

## R topics documented:

shinypivottabler . . . . .	1
<b>Index</b>	<b>6</b>

---

shinypivottabler	<i>Shiny module to render and export pivot tables.</i>
------------------	--

---

## Description

Shiny module to render and export pivot tables.

**Usage**

```
shinypivottabler(
  input,
  output,
  session,
  data,
  pivot_cols = NULL,
  indicator_cols = NULL,
  max_n_pivot_cols = 100,
  additional_expr_num = list(),
  additional_expr_char = list(),
  additional_combine = list(),
  theme = NULL,
  export_styles = TRUE,
  show_title = TRUE,
  initialization = NULL
)

shinypivottablerUI(id, app_colors = c("#59bb28", "#217346"), app_linewidth = 8)
```

**Arguments**

input	shiny input
output	shiny input
session	shiny input
data	data.frame / data.table. Initial data table.
pivot_cols	character (NULL). Columns to be used as pivot in rows and cols.
indicator_cols	character (NULL). Columns on which indicators will be calculated.
max_n_pivot_cols	numeric (100). Maximum unique values for a pivot_cols if pivot_cols = NULL
additional_expr_num	named list (list()). Additional computations to be allowed for quantitative vars.
additional_expr_char	named list (list()). Additional computations to be allowed for qualitative vars.
additional_combine	named list (list()). Additional combinations to be allowed.
theme	list (NULL). Theme to customize the output of the pivot table.
export_styles	boolean (TRUE). Whether or not to apply styles (like the theme) when exporting to Excel.
show_title	boolean (TRUE). Whether or not to display the app title. Some styles may not be supported by Excel.
initialization	named list (NULL). Initialization parameters to display a table when launching the module. Available fields are : <ul style="list-style-type: none"> <li>rows: Selected pivot rows.</li> </ul>

- cols: Selected pivot columns.
- target, combine\_target: Selected target and combine\_target columns..
- idc, combine\_idc: Selected idc and combine\_idc columns.
- combine: Selected combine operator.
- format\_digit, format\_prefix, format\_suffix, format\_sep\_thousands, format\_decimal: Selected formats for the table idc.
- idcs: idcs to be displayed (list of named list), see the example to get the fields.

id character. An ID string  
 app\_colors character. Vector of two colors c("#59bb28", "#217346") (borders)  
 app\_linewidth numeric. Borders width

### Value

Nothing. Just Start a Shiny module.

### Examples

```
if (interactive()) {
  require(shinypivotabler)
  require(shiny)

  # demo app
  runApp(system.file("demo_app", package = "shinypivotabler"))

  # create artificial dataset
  n <- 1000000
  data <- data.frame("gr1" = sample(c("A", "B", "C", "D"), size = n,
                                   prob = rep(1, 4), replace = T),
                    "gr2" = sample(c("E", "F", "G", "H"), size = n,
                                   prob = rep(1, 4), replace = T),
                    "gr3" = sample(c("I", "J", "K", "L"), size = n,
                                   prob = rep(1, 4), replace = T),
                    "gr4" = sample(c("M", "N", "O", "P"), size = n,
                                   prob = rep(1, 4), replace = T),
                    "value1" = 1:n,
                    "value2" = n:1)

  # Minimal example

  ui = shiny::fluidPage(
    shinypivotablerUI(id = "id")
  )

  server = function(input, output, session) {
    shiny::callModule(module = shinypivotabler,
                      id = "id",
                      data = data)
  }
}
```

```

}

shiny::shinyApp(ui = ui, server = server)

# Complete example

initialization <- list(
  "rows" = "gr1",
  "cols" = "gr2",
  "target" = "gr3",
  "combine_target" = "gr4",
  "idc" = "Count",
  "combine_idc" = "Count",
  "combine" = "/",
  "idcs" = c(
    list(
      c("label" = "Init_variable_1",
        "target" = "gr3", "idc" = "Count",
        "nb_decimals" = 0,
        "sep_thousands" = " ",
        "sep_decimal" = ".",
        "prefix" = "",
        "suffix" = "",
        "combine" = "/",
        "combine_target" = "gr4",
        "combine_idc" = "Count")
    ),
    list(
      c("label" = "Init_variable_2",
        "target" = "gr3", "idc" = "Count")
    )
  )
)

theme <- list(
  fontName="Courier New, Courier",
  fontSize="1em",
  headerBackgroundColor = "red",
  headerColor = "rgb(255, 255, 255)",
  cellBackgroundColor = "rgb(255, 255, 255)",
  cellColor = "rgb(0, 0, 0)",
  outlineCellBackgroundColor = "rgb(192, 192, 192)",
  outlineCellColor = "rgb(0, 0, 0)",
  totalBackgroundColor = "#59bb28",
  totalColor = "rgb(0, 0, 0)",
  borderColor = "rgb(64, 64, 64)"
)

ui = shiny::fluidPage(
  shinypivotablerUI(id = "id")
)

```

```
# we add two functions, one for quantitative variables (Q5) and
# one for qualitative variables (the mode, with a custom function), and
# one possible combination (the modulo).
my_mode <- function(x) names(which.max(table(x)))

server = function(input, output, session) {
  shiny::callModule(module = shinypivotabler,
    id = "id",
    data = data,
    pivot_cols = c("gr1", "gr2", "gr3", "gr4"),
    additional_expr_num = list(
      "Add_Q5" = "paste0('quantile(', target, ', probs = 0.05, na.rm = TRUE)')"
    ),
    additional_expr_char = list(
      "Add_mode" = "paste0('my_mode(', target, ')')"
    ),
    additional_combine = c("Add_modulo" = "%%"),
    theme = theme,
    initialization = initialization)
}

shiny::shinyApp(ui = ui, server = server)
}
```

# Index

`shinypivottabler`, [1](#)  
`shinypivottablerUI (shinypivottabler)`, [1](#)