

# Package ‘ROI.plugin.msbinlp’

August 29, 2020

**Version** 1.0-0

**Title** 'Multi-Solution' Binary Linear Problem Plug-in for the 'R'  
Optimization Interface

**Description** Enhances the 'R' Optimization Infrastructure ('ROI') package  
with the possibility to obtain multiple solutions for linear  
problems with binary variables. The main function is copied  
(with small modifications) from the relations package.

**Imports** stats, methods, utils, slam, ROI (>= 0.3-0)

**Suggests** ROI.plugin.glpk

**License** GPL-3

**URL** <http://roi.r-forge.r-project.org/>,  
<https://r-forge.r-project.org/projects/roi/>

**NeedsCompilation** no

**Author** Kurt Hornik [aut],  
David Meyer [aut],  
Florian Schwendinger [aut, cre]

**Maintainer** Florian Schwendinger <FlorianSchwendinger@gmx.at>

**Repository** CRAN

**Date/Publication** 2020-08-29 17:00:02 UTC

## R topics documented:

Example-1 . . . . .	2
Example-2 . . . . .	2
<b>Index</b>	<b>4</b>

---

 Example-1

*Multiple Solutions - Binary LP*


---

**Description**

$$\begin{aligned} & \text{maximize } x + y \\ & \text{subject to } x + y = 1 \\ & x, y \in \{0, 1\} \end{aligned}$$

**Examples**

```
## Not run:
library(ROI)
op <- OP(objective = c(1, 1),
         constraints = L_constraint(c(1, 1), "=", 1),
         types = c("B", "B"))

x <- ROI_solve(op, solver = "msbinlp", method = "glpk", nsol_max = 2L)
x
## 2 optimal solutions found.
## The objective value is: 1.000000e+00
solution(x)
## [[1]]
## [1] 1 0
##
## [[2]]
## [1] 0 1

## End(Not run)
```

---

 Example-2

*Multiple Solutions - Binary LP*


---

**Description**

$$\begin{aligned} & \text{maximize } -x_1 - x_2 - x_3 - x_4 - 99x_5 \\ & \text{subject to} \\ & x_1 + x_2 \leq 1 \\ & x_3 + x_4 \leq 1 \\ & x_4 + x_5 \leq 1 \\ & x_i \in \{0, 1\} \end{aligned}$$

**References**

Matteo Fischetti and Domenico Salvagnin (2010) *Pruning moves*. INFORMS Journal on Computing 22.1: 108-119.

**Examples**

```
## Not run:
library(ROI)
op <- OP()
objective(op) <- L_objective(c(-1, -1, -1, -1, -99))
mat <- simple_triplet_matrix(rep(1:3, 2),
                             c(c(1, 3, 4), c(2, 4, 5)),
                             rep(1, 6))
constraints(op) <- L_constraint(mat,
                                dir = leq(3),
                                rhs = rep.int(1, 3))
types(op) <- rep("B", length(op))

x <- ROI_solve(op, solver = "msbinlp", method = "glpk", nsol_max = 2L)
x
## 2 optimal solutions found.
## The objective value is: -1.010000e+02
solution(x)
## [[1]]
## [1] 0 1 1 0 1
##
## [[2]]
## [1] 1 0 1 0 1

## End(Not run)
```

# Index

Example-1, 2

Example-2, 2