

Package ‘covidcast’

May 4, 2021

Type Package

Title Client for Delphi's 'COVIDcast Epidata' API

Version 0.4.2

Date 2021-04-30

URL <https://cmu-delphi.github.io/covidcast/covidcastR/>,
<https://github.com/cmu-delphi/covidcast>

BugReports <https://github.com/cmu-delphi/covidcast/issues>

Description Tools for Delphi's 'COVIDcast Epidata' API: data access, maps and time series plotting, and basic signal processing. The API includes a collection of numerous indicators relevant to the COVID-19 pandemic in the United States, including official reports, de-identified aggregated medical claims data, large-scale surveys of symptoms and public behavior, and mobility data, typically updated daily and at the county level. All data sources are documented at <https://cmu-delphi.github.io/delphi-epidata/api/covidcast.html>.

Depends R (>= 3.5.0)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports dplyr, ggplot2, grDevices, httr, MMWRweek, purrr, rlang, sf, tidy

RoxygenNote 7.1.1

Suggests gridExtra, httpptest, knitr, mockery, rmarkdown, testthat, tibble, vdiff

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Author Taylor Arnold [aut],
Jacob Bien [aut],
Logan Brooks [aut],

Sarah Colquhoun [aut],
 David Farrow [aut],
 Jed Grabman [ctb],
 Pedrito Maynard-Zhang [ctb],
 Alex Reinhart [aut, cre] (<<https://orcid.org/0000-0002-6658-514X>>),
 Ryan Tibshirani [aut]

Maintainer Alex Reinhart <areinhar@stat.cmu.edu>

Repository CRAN

Date/Publication 2021-05-04 07:00:12 UTC

R topics documented:

abbr_to_fips	2
abbr_to_name	3
aggregate_signals	4
as.covidcast_signal	6
county_census	7
covidcast	8
covidcast_cor	9
covidcast_longer	10
covidcast_meta	10
covidcast_signal	11
covidcast_signals	15
fips_to_abbr	17
latest_issue	18
msa_census	18
name_to_abbr	19
name_to_fips	20
plot.covidcast_signal	21
print.covidcast_meta	24
print.covidcast_signal	24
state_census	25
state_fips_to_name	26
summary.covidcast_meta	27
summary.covidcast_signal	28
Index	29

abbr_to_fips	<i>Get FIPS codes from state abbreviations</i>
--------------	--

Description

Look up FIPS codes by state abbreviations (including District of Columbia and Puerto Rico); this function is based on `grep()`, and hence allows for regular expressions.

Usage

```
abbr_to_fips(
  abbr,
  ignore.case = TRUE,
  perl = FALSE,
  fixed = FALSE,
  ties_method = c("first", "all")
)
```

Arguments

abbr Vector of state abbreviations to look up.

ignore.case, perl, fixed Arguments to pass to `grep()`, with the same defaults as in the latter function, except for `ignore.case = TRUE`. Hence, by default, regular expressions are used; to match against a fixed string (no regular expressions), set `fixed = TRUE`.

ties_method If "first", then only the first match for each name is returned. If "all", then all matches for each name are returned.

Value

A vector of FIPS codes if `ties_method` equals "first", and a list of FIPS codes otherwise. These FIPS codes have five digits (ending in "000").

See Also

[abbr_to_name\(\)](#)

Examples

```
abbr_to_fips("PA")
abbr_to_fips(c("PA", "PR", "DC"))

# Note that name_to_fips() works for state names too:
name_to_fips("^Pennsylvania$")
```

abbr_to_name

Get state names from state abbreviations

Description

Look up state names by state abbreviations (including District of Columbia and Puerto Rico); this function is based on `grep()`, and hence allows for regular expressions.

Usage

```
abbr_to_name(
  abbr,
  ignore.case = FALSE,
  perl = FALSE,
  fixed = FALSE,
  ties_method = c("first", "all")
)
```

Arguments

abbr Vector of state abbreviations to look up.

ignore.case, perl, fixed Arguments to pass to `grep()`, with the same defaults as in the latter function. Hence, by default, regular expressions are used; to match against a fixed string (no regular expressions), set `fixed = TRUE`.

ties_method If "first", then only the first match for each name is returned. If "all", then all matches for each name are returned.

Value

A vector of state names if `ties_method` equals "first", and a list of state names otherwise.

See Also

[name_to_abbr\(\)](#)

Examples

```
abbr_to_name("PA")
abbr_to_name(c("PA", "PR", "DC"))
```

aggregate_signals *Aggregate covidcast_signal objects into one data frame*

Description

Aggregates `covidcast_signal` objects into one data frame, in either "wide" or "long" format. (In "wide" aggregation, only the latest issue from each data frame is retained, and several columns, including `data_source` and `signal` are dropped; see details below). See `vignette("multi-signals", package = "covidcast")` for examples.

Usage

```
aggregate_signals(x, dt = NULL, format = c("wide", "long"))
```

Arguments

x	Single covidcast_signal data frame, or a list of such data frames, such as is returned by covidcast_signals().
dt	Vector of shifts to apply to the values in the data frame x. Negative shifts translate into in a lag value and positive shifts into a lead value; for example, if dt = -1, then the value on June 2 that gets reported is the original value on June 1; if dt = 0, then the values are left as is. When x is a list of data frames, dt can either be a single vector of shifts or a list of vectors of shifts, this list having the same length as x (in order to apply, respectively, the same shifts or a different set of shifts to each data frame in x).
format	One of either "wide" or "long". The default is "wide".

Details

This function can be thought of having three use cases. In all three cases, the result will be a new data frame in either "wide" or "long" format, depending on format.

The first use case is to apply time-shifts to the values in a given covidcast_signal object. In this use case, x is a covidcast_signal data frame and dt is a vector of shifts.

The second use case is to bind together, into one data frame, signals that are returned by covidcast_signals(). In this use case, x is a list of covidcast_signal data frames, and dt is NULL.

The third use case is a combination of the first two: to bind together signals returned by covidcast_signals(), and simultaneously, apply time-shifts to their values. In this use case, x is a list of covidcast_signal data frames, and dt is either a vector of shifts—to apply the same shifts for each signal in x, or a list of vector of shifts—to apply different shifts for each signal in x.

Value

Data frame of aggregated signals in "wide" or "long" form, depending on format. In "long" form, an extra column dt is appended to indicate the value of the time-shift. In "wide" form, only the latest issue of data is retained; the returned data frame is formed via full joins of the input data frames (on geo_value and time_value as the join key), and the columns data_source, signal, issue, lag, stderr, sample_size are all dropped from the output. Each unique signal—defined by a combination of data source name, signal name, and time-shift—is given its own column, whose name indicates its defining quantities. For example, the column name "value+2:usa-facts_confirmed_incidence_num" corresponds to a signal defined by data_source = "usa-facts", signal = "confirmed_incidence_num", and dt = 2.

See Also

[covidcast_wider\(\)](#), [covidcast_longer\(\)](#)

as.covidcast_signal *Convert data from an external source into a form compatible with covidcast_signal.*

Description

Several methods are provided to convert common objects (such as data frames) into covidcast_signal objects, which can be used with the various covidcast_signal methods (such as plot.covidcast_signal() or covidcast_cor()). See vignette("external-data") for examples.

Usage

```
as.covidcast_signal(x, ...)

## S3 method for class 'covidcast_signal'
as.covidcast_signal(x, ...)

## S3 method for class 'data.frame'
as.covidcast_signal(
  x,
  signal = NULL,
  geo_type = c("county", "msa", "hrr", "dma", "state", "hhs", "nation"),
  time_type = c("day", "week"),
  data_source = "user",
  issue = NULL,
  metadata = list(),
  ...
)
```

Arguments

x	Object to be converted. See Methods section below for details on formatting of each input type.
...	Additional arguments passed to methods.
signal	The signal name to use for this data.
geo_type	The geography type stored in this object.
time_type	The time resolution stored in this object. If "day", the default, each observation covers one day. If "week", each time value is assumed to be the start date of the epiweek (MMWR week) that the data represents.
data_source	The name of the data source to use as a label for this data.
issue	Issue date to use for this data, if not present in x, as a Date object. If no issue date is present in x and issue is NULL, today's date will be used.
metadata	List of metadata to attach to the covidcast_signal object. See the "Metadata" section of covidcast_signal(). All objects will have geo_type, data_source, and signal columns included in their metadata; named entries in this list are added as additional columns.

Value

covidcast_signal object; see covidcast_signal() for documentation of fields and structure.

Methods (by class)

- covidcast_signal: Simply returns the covidcast_signal object unchanged.
- data.frame: The input data frame `x` must contain the columns `time_value`, `value`, and `geo_value`. If an `issue` column is present in `x`, it will be used as the issue date for each observation; if not, the `issue` argument will be used. Other columns will be preserved as-is.

See Also

[covidcast_signal\(\)](#)

county_census	<i>County census population data</i>
---------------	--------------------------------------

Description

Data set on county populations, from the 2019 US Census.

Usage

```
county_census
```

Format

A data frame with 3193 rows, one for each county (along with the 50 states and DC). Columns include:

SUMLEV Geographic summary level. Either 40 (state) or 50 (county).

REGION Census Region code

DIVISION Census Division code

STATE State FIPS code.

COUNTY County FIPS

STNAME Name of the state in which this county belongs.

CTYNAME County name, to help find counties by name.

POPESTIMATE2019 Estimate of the county's resident population as of July 1, 2019.

FIPS Five-digit county FIPS codes. These are unique identifiers used, for example, as the `geo_values` argument to `covidcast_signal()` to request data from a specific county.

Source

United States Census Bureau, at <https://www2.census.gov/programs-surveys/popest/datasets/2010-2019/counties/totals/co-est2019-alldata.csv>

References

Census Bureau documentation of all columns and their meaning: <https://www2.census.gov/programs-surveys/popest/datasets/2010-2019/counties/totals/co-est2019-alldata.pdf>, <https://www.census.gov/data/tables/time-series/demo/popest/2010s-total-puerto-rico-municipios.html>, and <https://www.census.gov/data/tables/2010/dec/2010-island-areas.html>

See Also

[county_fips_to_name\(\)](#), [name_to_fips\(\)](#)

covidcast

covidcast: Client for Delphi's COVIDcast API

Description

The covidcast package provides access to numerous COVID-19 data streams, updated daily, covering the United States of America. These include publicly reported cases and deaths data, along with data the Delphi research group collects or obtains from partners.

Finding data sources and documentation

The COVIDcast API includes:

- publicly reported COVID case and death data
- insurance claims data reporting on COVID-related doctor's visits and hospitalizations, obtained from health partners
- aggregate results from massive COVID symptom surveys conducted by Delphi
- mobility data aggregated from SafeGraph
- symptom search trends from Google

and numerous other important signals, most available daily at the county level.

Each data stream is identified by its data source and signal names. These are documented on the COVIDcast API website: https://cmu-delphi.github.io/delphi-epidata/api/covidcast_signals.html

Each data stream has a page giving detailed technical documentation on how the data is collected, how it is aggregated, and any limitations or known problems with the data.

Getting started

We recommend browsing the vignettes, which includes numerous examples: `browseVignettes(package = "covidcast")`.

See also `covidcast_signal()` for details on how to obtain COVIDcast data as a data frame.

covidcast_cor

*Compute correlations between two covidcast_signal data frames***Description**

Computes correlations between two covidcast_signal data frames, allowing for slicing by geo location, or by time. (Only the latest issue from each data frame is used for correlations.) See the correlations vignette for examples: vignette("correlation-utils", package = "covidcast")

Usage

```
covidcast_cor(
  x,
  y,
  dt_x = 0,
  dt_y = 0,
  by = c("geo_value", "time_value"),
  use = "na.or.complete",
  method = c("pearson", "kendall", "spearman")
)
```

Arguments

x, y	The covidcast_signal data frames to correlate.
dt_x, dt_y	Time shifts to consider for x and y, respectively, before computing correlations. Negative shifts translate into a lag value and positive shifts into a lead value; for example, if dt = -1, then the new value on June 2 is the original value on June 1; if dt = 1, then the new value on June 2 is the original value on June 3; if dt = 0, then the values are left as is. Default is 0 for both dt_x and dt_y.
by	If "geo_value", then correlations are computed for each geo location, over all time. Each correlation is measured between two time series at the same location. If "time_value", then correlations are computed for each time, over all geo locations. Each correlation is measured between all locations at one time. Default is "geo_value".
use, method	Arguments to pass to cor(), with "na.or.complete" the default for use (different than cor()) and "pearson" the default for method (same as cor()).

Value

A data frame with first column geo_value or time_value (depending on by), and second column value, which gives the correlation.

covidcast_longer	<i>Pivot aggregated signals between "wide" and "long" formats</i>
------------------	---

Description

These functions take signals returned from `aggregate_signals()` and convert between formats. `covidcast_longer()` takes the output of `aggregate_signals(..., format = "wide")` and converts it to "long" format, while `covidcast_wider()` takes the output of `aggregate_signals(..., format = "long")` and converts it to "wide" format.

Usage

```
covidcast_longer(x)
```

```
covidcast_wider(x)
```

Arguments

`x` A `covidcast_signal_wide` or `covidcast_signal_long` object, as returned from `aggregate_signals()` with the respective format argument.

Value

The object pivoted into the opposite form, i.e. as if `aggregate_signals()` had been called in the first place with that format argument.

See Also

[covidcast_signals\(\)](#)

covidcast_meta	<i>Obtain COVIDcast metadata</i>
----------------	----------------------------------

Description

Obtains a data frame of metadata describing all publicly available data streams from the COVIDcast API.

Usage

```
covidcast_meta()
```

Value

Data frame containing one row per signal, with the following columns:

data_source	Data source name.
signal	Signal name.
min_time	First day for which this signal is available.
max_time	Most recent day for which this signal is available.
geo_type	Geographic level for which this signal is available, such as county, state, msa, or hrr. Most signals are available at multiple geographic levels and will hence be listed in multiple rows with their own metadata.
time_type	Temporal resolution at which this signal is reported. "day", for example, means the signal is reported daily.
num_locations	Number of distinct geographic locations available for this signal. For example, if geo_type is county, the number of counties for which this signal has ever been reported.
min_value	Smallest value that has ever been reported.
max_value	Largest value that has ever been reported.
mean_value	Arithmetic mean of all reported values.
stdev_value	Sample standard deviation of all reported values.
max_issue	Most recent issue date for this signal.
min_lag	Smallest lag from observation to issue, in time_type units
max_lag	Largest lag from observation to issue, in time_type units

References

COVIDcast API sources and signals documentation: https://cmu-delphi.github.io/delphi-epidata/api/covidcast_signals.html

See Also

[summary.covidcast_meta\(\)](#)

covidcast_signal

Obtain a data frame for one COVIDcast signal

Description

Obtains data for selected date ranges for all geographic regions of the United States. Available data sources and signals are documented in the COVIDcast signal documentation. Most (but not all) data sources are available at the county level, but the API can also return data aggregated to metropolitan statistical areas, hospital referral regions, or states, as desired, by using the geo_type argument.

Usage

```

covidcast_signal(
  data_source,
  signal,
  start_day = NULL,
  end_day = NULL,
  geo_type = c("county", "hrr", "msa", "dma", "state", "hhs", "nation"),
  geo_values = "*",
  as_of = NULL,
  issues = NULL,
  lag = NULL,
  time_type = c("day", "week")
)

```

Arguments

<code>data_source</code>	String identifying the data source to query. See https://cmu-delphi.github.io/delphi-epidata/api/covidcast_signals.html for a list of available data sources.
<code>signal</code>	String identifying the signal from that source to query. Again, see https://cmu-delphi.github.io/delphi-epidata/api/covidcast_signals.html for a list of available signals.
<code>start_day</code>	Query data beginning on this date. Date object, or string in the form "YYYY-MM-DD". If <code>start_day</code> is NULL, defaults to first day data is available for this signal.
<code>end_day</code>	Query data up to this date, inclusive. Date object or string in the form "YYYY-MM-DD". If <code>end_day</code> is NULL, defaults to the most recent day data is available for this signal.
<code>geo_type</code>	The geography type for which to request this data, such as "county" or "state". Defaults to "county". See https://cmu-delphi.github.io/delphi-epidata/api/covidcast_geography.html for details on which types are available.
<code>geo_values</code>	Which geographies to return. The default, "*", fetches all geographies. To fetch specific geographies, specify their IDs as a vector or list of strings. See https://cmu-delphi.github.io/delphi-epidata/api/covidcast_geography.html for details on how to specify these IDs.
<code>as_of</code>	Fetch only data that was available on or before this date, provided as a Date object or string in the form "YYYY-MM-DD". If NULL, the default, return the most recent available data. Note that only one of <code>as_of</code> , <code>issues</code> , and <code>lag</code> should be provided; it does not make sense to specify more than one. For more on data revisions, see "Issue dates and revisions" below.
<code>issues</code>	Fetch only data that was published or updated ("issued") on these dates. Provided as either a single Date object (or string in the form "YYYY-MM-DD"), indicating a single date to fetch data issued on, or a vector specifying two dates, start and end. In this case, return all data issued in this range. There may be multiple rows for each observation, indicating several updates to its value. If NULL, the default, return the most recently issued data.

lag	Integer. If, for example, lag = 3, then we fetch only data that was published or updated exactly 3 days after the date. For example, a row with time_value of June 3 will only be included in the results if its data was issued or updated on June 6. If NULL, the default, return the most recently issued data regardless of its lag.
time_type	The temporal resolution to request this data. Most signals are available at the "day" resolution (the default); some are only available at the "week" resolution, representing an MMWR week ("epiweek").

Details

For data on counties, metropolitan statistical areas, and states, this package provides the [county_census](#), [msa_census](#), and [state_census](#) datasets. These include each area's unique identifier, used in the `geo_values` argument to select specific areas, and basic information on population and other Census data.

Downloading large amounts of data may be slow, so this function prints messages for each day of data it downloads. To suppress these, use `base::suppressMessages()`, as in `suppressMessages(covidcast_signal("fb-`

Value

`covidcast_signal` object with matching data. The object is a data frame with additional metadata attached. Each row is one observation of one signal on one day in one geographic location. Contains the following columns:

data_source	Data source from which this observation was obtained.
signal	Signal from which this observation was obtained.
geo_value	String identifying the location, such as a state name or county FIPS code.
time_value	Date object identifying the date of this observation. For data with <code>time_type = "week"</code> , this is the first day of the corresponding epiweek.
issue	Date object identifying the date this estimate was issued. For example, an estimate with a <code>time_value</code> of June 3 might have been issued on June 5, after the data for June 3rd was collected and ingested into the API.
lag	Integer giving the difference between <code>issue</code> and <code>time_value</code> , in days.
value	Signal value being requested. For example, in a query for the "confirmed_cumulative_num" signal from the "usa-facts" source, this would be the cumulative number of confirmed cases in the area, as of the given <code>time_value</code> .
stderr	Associated standard error of the signal value, if available.
sample_size	Integer indicating the sample size available in that geography on that day; sample size may not be available for all signals, due to privacy or other constraints, in which case it will be NA.

Consult the signal documentation for more details on how values and standard errors are calculated for specific signals.

The returned data frame has a `metadata` attribute containing metadata about the signal contained within; see "Metadata" below for details.

Metadata

The returned object has a `metadata` attribute attached containing basic information about the signal. Use `attributes(x)$metadata` to access this metadata. The metadata is stored as a data frame of one row, and contains the same information that `covidcast_meta()` would return for a given signal.

Note that not all `covidcast_signal` objects may have all fields of metadata attached; for example, an object created with `as.covidcast_signal()` using data from another source may only contain the `geo_type` variable, along with `data_source` and `signal`. Before using the metadata of a `covidcast_signal` object, always check for the presence of the attributes you need.

Issue dates and revisions

The COVIDcast API tracks updates and changes to its underlying data, and records the first date each observation became available. For example, a data source may report its estimate for a specific state on June 3rd on June 5th, once records become available. This data is considered "issued" on June 5th. Later, the data source may update its estimate for June 3rd based on revised data, creating a new issue on June 8th. By default, `covidcast_signal()` returns the most recent issue available for every observation. The `as_of`, `issues`, and `lag` parameters allow the user to select specific issues instead, or to see all updates to observations. These options are mutually exclusive, and you should only specify one; if you specify more than one, you may get an error or confusing results.

Note that the API only tracks the initial value of an estimate and *changes* to that value. If a value was first issued on June 5th and never updated, asking for data issued on June 6th (using `issues` or `lag`) would *not* return that value, though asking for data `as_of` June 6th would. See `vignette("covidcast")` for examples.

Note also that the API enforces a maximum result row limit; results beyond the maximum limit are truncated. This limit is sufficient to fetch observations in all counties in the United States on one day. This client automatically splits queries for multiple days across multiple API calls. However, if data for one day has been issued many times, using the `issues` argument may return more results than the query limit. A warning will be issued in this case. To see all results, split your query across multiple calls with different `issues` arguments.

References

COVIDcast API documentation: <https://cmu-delphi.github.io/delphi-epidata/api/covidcast.html>

Documentation of all COVIDcast sources and signals: https://cmu-delphi.github.io/delphi-epidata/api/covidcast_signals.html

COVIDcast public dashboard: <https://delphi.cmu.edu/covidcast/>

See Also

`plot.covidcast_signal()`, `covidcast_signals()`, `as.covidcast_signal()`, `county_census`, `msa_census`, `state_census`

Examples

```
## Not run:  
## Fetch all counties from 2020-05-10 to the most recent available data
```

```

covidcast_signal("fb-survey", "smoothed_cli", start_day = "2020-05-10")
## Fetch all counties on just 2020-05-10 and no other days
covidcast_signal("fb-survey", "smoothed_cli", start_day = "2020-05-10",
  end_day = "2020-05-10")
## Fetch all states on 2020-05-10, 2020-05-11, 2020-05-12
covidcast_signal("fb-survey", "smoothed_cli", start_day = "2020-05-10",
  end_day = "2020-05-12", geo_type = "state")
## Fetch all available data for just Pennsylvania and New Jersey
covidcast_signal("fb-survey", "smoothed_cli", geo_type = "state",
  geo_values = c("pa", "nj"))
## Fetch all available data in the Pittsburgh metropolitan area
covidcast_signal("fb-survey", "smoothed_cli", geo_type = "msa",
  geo_values = name_to_cbsa("Pittsburgh"))

## End(Not run)

```

covidcast_signals *Obtain multiple COVIDcast signals at once*

Description

This convenience function uses `covidcast_signal()` to obtain multiple signals, potentially from multiple data sources.

Usage

```

covidcast_signals(
  data_source,
  signal,
  start_day = NULL,
  end_day = NULL,
  geo_type = c("county", "hrr", "msa", "dma", "state", "hhs", "nation"),
  geo_values = "*",
  as_of = NULL,
  issues = NULL,
  lag = NULL
)

```

Arguments

<code>data_source</code>	String identifying the data source to query. See https://cmu-delphi.github.io/delphi-epidata/api/covidcast_signals.html for a list of available data sources.
<code>signal</code>	String identifying the signal from that source to query. Again, see https://cmu-delphi.github.io/delphi-epidata/api/covidcast_signals.html for a list of available signals.

start_day	Query data beginning on this date. Date object, or string in the form "YYYY-MM-DD". If start_day is NULL, defaults to first day data is available for this signal.
end_day	Query data up to this date, inclusive. Date object or string in the form "YYYY-MM-DD". If end_day is NULL, defaults to the most recent day data is available for this signal.
geo_type	The geography type for which to request this data, such as "county" or "state". Defaults to "county". See https://cmu-delphi.github.io/delphi-epidata/api/covidcast_geography.html for details on which types are available.
geo_values	Which geographies to return. The default, "*", fetches all geographies. To fetch specific geographies, specify their IDs as a vector or list of strings. See https://cmu-delphi.github.io/delphi-epidata/api/covidcast_geography.html for details on how to specify these IDs.
as_of	Fetch only data that was available on or before this date, provided as a Date object or string in the form "YYYY-MM-DD". If NULL, the default, return the most recent available data. Note that only one of as_of, issues, and lag should be provided; it does not make sense to specify more than one. For more on data revisions, see "Issue dates and revisions" below.
issues	Fetch only data that was published or updated ("issued") on these dates. Provided as either a single Date object (or string in the form "YYYY-MM-DD"), indicating a single date to fetch data issued on, or a vector specifying two dates, start and end. In this case, return all data issued in this range. There may be multiple rows for each observation, indicating several updates to its value. If NULL, the default, return the most recently issued data.
lag	Integer. If, for example, lag = 3, then we fetch only data that was published or updated exactly 3 days after the date. For example, a row with time_value of June 3 will only be included in the results if its data was issued or updated on June 6. If NULL, the default, return the most recently issued data regardless of its lag.

Details

The argument structure is just as in `covidcast_signal()`, except the first four arguments `data_source`, `signal`, `start_day`, `end_day` are permitted to be vectors. The first two arguments `data_source`, `signal` are recycled appropriately, in the calls to `covidcast_signal()`; see example below. The next two arguments `start_day`, `end_day`, unless NULL, must be either length 1 or N.

Value

A list of `covidcast_signal` data frames, of length $N = \max(\text{length}(\text{data_source}), \text{length}(\text{signal}))$. This list can be aggregated into a single data frame of either "wide" or "long" format using `aggregate_signals()`.

See Also

[covidcast_signal\(\)](#), [aggregate_signals\(\)](#)

Examples

```
## Not run:
## Fetch USAFacts confirmed cases and deaths over the same time period
covidcast_signals("usa-facts", signal = c("confirmed_incidence_num",
                                           "deaths_incidence_num"),
                  start_day = "2020-08-15", end_day = "2020-10-01")

## End(Not run)
```

fips_to_abbr

Get state abbreviations from FIPS codes

Description

Look up state abbreviations by FIPS codes (including District of Columbia and Puerto Rico). Will match the first two digits of the input codes, so should work for 5-digit county codes, or even longer tract and census block FIPS codes.

Usage

```
fips_to_abbr(code)
```

Arguments

`code` Vector of FIPS codes to look up; will match the first two digits of the code. Note that these are treated as strings; the number 1 will not match "01".

Value

A vector of state abbreviations.

See Also

[abbr_to_fips\(\)](#)

Examples

```
fips_to_abbr("42000")
fips_to_abbr(c("42", "72", "11"))
```

latest_issue	<i>Fetch the latest or earliest issue for each observation</i>
--------------	--

Description

The data returned from `covidcast_signal()` or `covidcast_signals()` can, if called with the `issues` argument, contain multiple issues for a single observation in a single location. These functions filter the data frame to contain only the earliest issue or only the latest issue.

Usage

```
latest_issue(df)
```

```
earliest_issue(df)
```

Arguments

`df` A `covidcast_signal` or `covidcast_signal_long` data frame, such as returned from `covidcast_signal()` or the "long" format of `aggregate_signals()`.

Value

A data frame in the same form, but with only the earliest or latest issue of every observation. Note that these functions sort the data frame as part of their filtering, so the output data frame rows may be in a different order.

msa_census	<i>Metro area population data</i>
------------	-----------------------------------

Description

Data set on metropolitan area populations, from the 2019 US Census. This includes metropolitan and micropolitan statistical areas, although the COVIDcast API only supports fetching data from metropolitan statistical areas.

Usage

```
msa_census
```

Format

A data frame with 2797 rows, each representing one core-based statistical area (including metropolitan and micropolitan statistical areas, county or county equivalents, and metropolitan divisions). There are many columns. The most crucial are:

CBSA Core Based Statistical Area code. These are unique identifiers used, for example, as the `geo_values` argument to `covidcast_signal()` when requesting data from specific metro areas (with `geo_type = 'msa'`).

MDIV Metropolitan Division code

STCOU State and county code

NAME Name or title of the area.

LSAD Legal/Statistical Area Description, identifying if this is a metropolitan or micropolitan area, a metropolitan division, or a county.

STATE State FIPS code.

POPESTIMATE2019 Estimate of the area's resident population as of July 1, 2019.

Source

United States Census Bureau, at <https://www2.census.gov/programs-surveys/popest/datasets/2010-2019/metro/totals/cbsa-est2019-alldata.csv>

References

Census Bureau documentation of all columns and their meaning: <https://www2.census.gov/programs-surveys/popest/datasets/2010-2019/metro/totals/cbsa-est2019-alldata.pdf>

See Also

[cbsa_to_name\(\)](#), [name_to_cbsa\(\)](#)

name_to_abbr

Get state abbreviations from state names

Description

Look up state abbreviations by state names (including District of Columbia and Puerto Rico); this function is based on `grep()`, and hence allows for regular expressions.

Usage

```
name_to_abbr(
  name,
  ignore.case = FALSE,
  perl = FALSE,
  fixed = FALSE,
  ties_method = c("first", "all")
)
```

Arguments

name Vector of state names to look up.
ignore.case, **perl**, **fixed** Arguments to pass to `grep()`, with the same defaults as in the latter function. Hence, by default, regular expressions are used; to match against a fixed string (no regular expressions), set `fixed = TRUE`.
ties_method If "first", then only the first match for each name is returned. If "all", then all matches for each name are returned.

Value

A vector of state abbreviations if `ties_method` equals "first", and a list of state abbreviations otherwise.

See Also

[abbr_to_name\(\)](#)

Examples

```
name_to_abbr("Penn")
name_to_abbr(c("Penn", "New"), ties_method = "all")
```

name_to_fips

Get FIPS or CBSA codes from county or metropolitan area names

Description

Look up FIPS or CBSA codes by county or metropolitan area names, respectively; these functions are based on `grep()`, and hence allow for regular expressions.

Usage

```
name_to_fips(
  name,
  ignore.case = FALSE,
  perl = FALSE,
  fixed = FALSE,
  ties_method = c("first", "all"),
  state = NULL
)

name_to_cbsa(
  name,
  ignore.case = FALSE,
  perl = FALSE,
```

```

    fixed = FALSE,
    ties_method = c("first", "all"),
    state = NULL
  )

```

Arguments

name Vector of county or metropolitan area names to look up.

ignore.case, perl, fixed Arguments to pass to `grep()`, with the same defaults as in the latter function. Hence, by default, regular expressions are used; to match against a fixed string (no regular expressions), set `fixed = TRUE`.

ties_method If "first", then only the first match for each name is returned. If "all", then all matches for each name are returned.

state Two letter state abbreviation (case insensitive) indicating a parent state used to restrict the search. For example, when `state = "NY"`, then `name_to_fips()` searches only over only counties lying in New York state, whereas `name_to_cbsa()` searches over the metropolitan areas lying, either fully or partially (as a metropolitan area can span several states), in New York state. If `NULL`, the default, then the search is performed US-wide (not restricted to any state in particular).

Value

A vector of FIPS or CBSA codes if `ties_method` equals "first", and a list of FIPS or CBSA codes otherwise.

See Also

[state_fips_to_name\(\)](#), [cbsa_to_name\(\)](#)

Examples

```

name_to_fips("Allegheny")
name_to_cbsa("Pittsburgh")
name_to_fips("Miami")
name_to_fips("Miami", ties_method = "all")
name_to_fips(c("Allegheny", "Miami", "New "), ties_method = "all")

```

`plot.covidcast_signal` *Plot covidcast_signal object as choropleths, bubbles, or time series*

Description

Several plot types are provided, including choropleth plots (maps), bubble plots, and time series plots showing the change of signals over time, for a data frame returned by `covidcast_signal()`. (Only the latest issue from the data frame is used for plotting.) See `vignette("plotting-signals", package = "covidcast")` for examples.

Usage

```
## S3 method for class 'covidcast_signal'
plot(
  x,
  plot_type = c("choro", "bubble", "line"),
  time_value = NULL,
  include = c(),
  range = NULL,
  choro_col = c("#FFFFCC", "#FD893C", "#800026"),
  alpha = 0.5,
  bubble_col = "purple",
  num_bins = 8,
  title = NULL,
  choro_params = list(),
  bubble_params = list(),
  line_params = list(),
  ...
)
```

Arguments

x	The covidcast_signal object to map or plot. If the object contains multiple issues of the same observation, only the most recent issue is mapped or plotted.
plot_type	One of "choro", "bubble", "line" indicating whether to plot a choropleth map, bubble map, or line (time series) graph, respectively. The default is "choro".
time_value	Date object (or string in the form "YYYY-MM-DD") specifying the day to map, for choropleth and bubble maps. If NULL, the default, then the last date in x is used for the maps. Time series plots always include all available time values in x.
include	Vector of state abbreviations (case insensitive, so "pa" and "PA" both denote Pennsylvania) indicating which states to include in the choropleth and bubble maps. Default is c(), which is interpreted to mean all states.
range	Vector of two values: min and max, in this order, to use when defining the color scale for choropleth maps and the size scale for bubble maps, or the range of the y-axis for the time series plot. If NULL, the default, then for the maps, the min and max are set to be the mean +/- 3 standard deviations, where this mean and standard deviation are as provided in the metadata for the given data source and signal; and for the time series plot, they are set to be the observed min and max of the values over the given time period.
choro_col	Vector of colors, as specified in hex code, to use for the choropleth color scale. Can be arbitrary in length. Default is similar to that from https://delphi.cmu.edu/covidcast/ .
alpha	Number between 0 and 1, indicating the transparency level to be used in the maps. For choropleth maps, this determines the transparency level for the mega counties. For bubble maps, this determines the transparency level for the bubbles. Default is 0.5.

bubble_col	Bubble color for the bubble map. Default is "purple".
num_bins	Number of bins for determining the bubble sizes for the bubble map (here and throughout, to be precise, by bubble size we mean bubble area). Default is 8. These bins are evenly-spaced in between the min and max as specified through the range parameter. Each bin is assigned the same bubble size. Also, values of zero special: it has its own separate (small) bin, and values mapped to the zero bin are not drawn.
title	Title for the plot. If NULL, the default, then a simple title is used based on the given data source, signal, and time values.
choro_params, bubble_params, line_params	Additional parameter lists for the different plot types, for further customization. See details below.
...	Additional arguments, for compatibility with plot(). Currently unused.

Details

The following named arguments are supported through the lists `choro_params`, `bubble_params`, and `line_params`.

For both choropleth and bubble maps:

`subtitle` Subtitle for the map.

`missing_col` Color assigned to missing or NA geo locations.

`border_col` Border color for geo locations.

`border_size` Border size for geo locations.

`legend_position` Position for legend; use "none" to hide legend.

`legend_height`, `legend_width` Height and width of the legend.

`breaks` Breaks for a custom (discrete) color or size scale. Note that we must set `breaks` to be a vector of the same length as `choro_col` for choropleth maps. This works as follows: we assign the i th color for choropleth maps, or the i th size for bubble maps, if and only if the given value satisfies $\text{breaks}[i] \leq \text{value} < \text{breaks}[i+1]$, where we take by convention $\text{breaks}[0] = -\text{Inf}$ and $\text{breaks}[N+1] = \text{Inf}$ for $N = \text{length}(\text{breaks})$.

`legend_digits` Number of decimal places to show for the legend labels.

For choropleth maps only:

`legend_n` Number of values to label on the legend color bar. Ignored for discrete color scales (when `breaks` is set manually).

For bubble maps only:

`remove_zero` Should zeros be excluded from the size scale (hence effectively drawn as bubbles of zero size)?

`min_size`, `max_size` Min size for the size scale.

For line graphs:

`xlab`, `ylab` Labels for the x-axis and y-axis.

`stderr_bands` Should standard error bands be drawn?

`stderr_alpha` Transparency level for the standard error bands.

Value

A ggplot object that can be customized and styled using standard ggplot2 functions.

```
print.covidcast_meta
```

Print covidcast_meta object

Description

Prints a brief summary of the metadata, and then prints the underlying data frame, for an object returned by `covidcast_meta()`.

Usage

```
## S3 method for class 'covidcast_meta'  
print(x, ...)
```

Arguments

<code>x</code>	The <code>covidcast_meta</code> object.
<code>...</code>	Additional arguments passed to <code>print.data.frame()</code> to print the data.

Value

The `covidcast_meta` object, unchanged.

```
print.covidcast_signal
```

Print covidcast_signal object

Description

Prints a brief summary of the data source, signal, and geographic level, and then prints the underlying data frame, for an object returned by `covidcast_signal()`.

Usage

```
## S3 method for class 'covidcast_signal'  
print(x, ...)
```

Arguments

<code>x</code>	The <code>covidcast_signal</code> object.
<code>...</code>	Additional arguments passed to <code>print.data.frame()</code> to print the data.

Value

The `covidcast_signal` object, unchanged.

state_census	<i>State population data</i>
--------------	------------------------------

Description

Data set on state populations, from the 2019 US Census.

Usage

```
state_census
```

Format

Data frame with 53 rows (including one for the United States as a whole, plus the District of Columbia and the Puerto Rico Commonwealth). Important columns:

SUMLEV Geographic summary level.

REGION Census Region code

DIVISION Census Division code

STATE State FIPS code

NAME Name of the state

POPESTIMATE2019 Estimate of the state's resident population in 2019.

POPEST18PLUS2019 Estimate of the state's resident population in 2019 that is over 18 years old.

PCNT_POPEST18PLUS Estimate of the percent of a state's resident population in 2019 that is over 18.

ABBR Postal abbreviation of the state

Source

United States Census Bureau, at <https://www2.census.gov/programs-surveys/popest/datasets/2010-2019/counties/totals/co-est2019-alldata.pdf>, <https://www.census.gov/data/tables/time-series/demo/popest/2010s-total-puerto-rico-municipios.html>, and <https://www.census.gov/data/tables/2010/dec/2010-island-areas.html>

See Also

[abbr_to_name\(\)](#), [name_to_abbr\(\)](#), [abbr_to_fips\(\)](#), [fips_to_abbr\(\)](#)

state_fips_to_name	<i>Get state, county or metropolitan area names from FIPS or CBSA codes</i>
--------------------	---

Description

Look up county or metropolitan area names by FIPS or CBSA codes. Looking up FIPS code is done with the first 2 numbers (state) or 5 numbers (county) and therefore can be called with longer FIPS codes.

Usage

```
state_fips_to_name(code)
county_fips_to_name(code)
cbsa_to_name(code)
```

Arguments

code Vector of FIPS or CBSA codes to look up.

Value

A vector of state, county or metro names.

See Also

[name_to_fips\(\)](#), [name_to_cbsa\(\)](#)

Examples

```
state_fips_to_name("42")
state_fips_to_name("42003") # same as previous
county_fips_to_name("42003")
county_fips_to_name("42000") # the county "000" returns the state name
cbsa_to_name("38300")
```

```
summary.covidcast_meta
```

Summarize covidcast_meta object

Description

Prints a tabular summary of the object returned by `covidcast_meta()`, containing each source and signal and a summary of the geographic levels it is available at.

Usage

```
## S3 method for class 'covidcast_meta'
summary(object, ...)
```

Arguments

<code>object</code>	The <code>covidcast_meta</code> object.
<code>...</code>	Additional arguments, for compatibility with <code>summary()</code> . Currently unused.

Value

A data frame with one row per unique signal in the metadata, with the following columns:

<code>data_source</code>	Data source name
<code>signal</code>	Signal name
<code>county</code>	"*" if this signal is available at the county level, "" otherwise
<code>msa</code>	"*" if this signal is available at the Metropolitan Statistical Area level, "" otherwise
<code>dma</code>	"*" if this signal is available at the Designated Marketing Area level, "" otherwise
<code>hrr</code>	"*" if this signal is available at the Hospital Referral Region level, "" otherwise
<code>state</code>	"*" if this signal is available at the state level, "" otherwise
<code>hhs</code>	"*" if this signal is available at the Health and Human Services region level, "" otherwise
<code>nation</code>	"*" if this signal is available at the national level, "" otherwise

```
summary.covidcast_signal
```

```
    Summarize covidcast_signal object
```

Description

Prints a variety of summary statistics about the underlying data, such as median values, the date range included, sample sizes, and so on, for an object returned by `covidcast_signal()`.

Usage

```
## S3 method for class 'covidcast_signal'  
summary(object, ...)
```

Arguments

<code>object</code>	The <code>covidcast_signal</code> object.
<code>...</code>	Additional arguments, for compatibility with <code>summary()</code> . Currently unused.

Value

No return value; called only to print summary statistics.

Index

* datasets

- county_census, 7
- msa_census, 18
- state_census, 25

abbr_to_fips, 2

abbr_to_fips(), 17, 25

abbr_to_name, 3

abbr_to_name(), 3, 20, 25

aggregate_signals, 4

aggregate_signals(), 16

as.covidcast_signal, 6

as.covidcast_signal(), 14

base::suppressMessages(), 13

cbsa_to_name (state_fips_to_name), 26

cbsa_to_name(), 19, 21

county_census, 7, 13, 14

county_fips_to_name
(state_fips_to_name), 26

county_fips_to_name(), 8

covidcast, 8

covidcast_cor, 9

covidcast_longer, 10

covidcast_longer(), 5

covidcast_meta, 10

covidcast_signal, 11

covidcast_signal(), 7, 16

covidcast_signals, 15

covidcast_signals(), 10, 14

covidcast_wider (covidcast_longer), 10

covidcast_wider(), 5

earliest_issue (latest_issue), 18

fips_to_abbr, 17

fips_to_abbr(), 25

latest_issue, 18

msa_census, 13, 14, 18

name_to_abbr, 19

name_to_abbr(), 4, 25

name_to_cbsa (name_to_fips), 20

name_to_cbsa(), 19, 26

name_to_fips, 20

name_to_fips(), 8, 26

plot.covidcast_signal, 21

plot.covidcast_signal(), 14

print.covidcast_meta, 24

print.covidcast_signal, 24

state_census, 13, 14, 25

state_fips_to_name, 26

state_fips_to_name(), 21

summary.covidcast_meta, 27

summary.covidcast_meta(), 11

summary.covidcast_signal, 28