

Package ‘KappaGUI’

March 22, 2018

Type Package

Title An R-Shiny Application for Calculating Cohen's and Fleiss' Kappa

Version 2.0.2

Date 2018-03-22

Author Frédéric Santos

Maintainer Frédéric Santos <frederic.santos@u-bordeaux.fr>

Depends R (>= 3.4.0), shiny, irr

Description Offers a graphical user interface for the evaluation of inter-rater agreement with Cohen's and Fleiss' Kappa. The calculation of kappa statistics is done using the R package 'irr', so that 'KappaGUI' is essentially a Shiny front-end for 'irr'.

License GPL (>= 2)

Encoding UTF-8

NeedsCompilation no

Repository CRAN

Date/Publication 2018-03-22 15:52:45 UTC

R topics documented:

KappaGUI-package	2
kappaCohen	3
kappaFleiss	4
StartKappa	5
Index	7

KappaGUI-package

An R-Shiny application for calculating Cohen's and Fleiss' Kappa

Description

Offers a graphical user interface for the evaluation of inter-rater agreement with Cohen's and Fleiss' Kappa. The calculation of kappa statistics is done using the R package 'irr', so that 'KappaGUI' is essentially a Shiny front-end for 'irr'.

Details

Package: KappaGUI
Type: Package
Version: 2.0.2
Date: 2018-03-22
License: GPL >=2

Author(s)

Frédéric Santos, <frederic.santos@u-bordeaux.fr>

References

Cohen, J. (1960) A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, **20**, 37–46.

Cohen, J. (1968) Weighted kappa: Nominal scale agreement with provision for scaled disagreement or partial credit. *Psychological Bulletin*, **70**, 213–220.

See Also

irr::kappa2

Examples

```
## Not run: StartKappa()
```

kappaCohen	<i>Calculates Cohen's kappa for all pairs of columns in a given dataframe</i>
------------	---

Description

This function is based on the function 'kappa2' from the package 'irr', and simply adds the possibility of calculating several kappas at once.

Usage

```
kappaCohen(data, weight="unweighted")
```

Arguments

data	dataframe with $2 \times p$ columns, p being the number of traits coded by the two raters. The first two columns represent the scores attributed by the two raters for the first trait; the next two columns represent the scores attributed by the two raters for the second trait; etc. The dataframe must contain a header, and each column must be labeled as follows: 'VariableName_X', where X is a unique character (letter or number) associated with each rater (cf. below for an example).
weight	character string specifying the weighting scheme ("unweighted", "equal" or "squared"). See the function 'kappa2' from the package 'irr'.

Details

For each trait, only complete cases are used for the calculation.

Value

A dataframe with p rows (one per trait) and three columns, giving respectively the kappa value for each trait, the number of individuals used to calculate this value, and the associated p -value.

Author(s)

Frédéric Santos, <frederic.santos@u-bordeaux.fr>

References

Cohen, J. (1960) A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, **20**, 37–46.

Cohen, J. (1968) Weighted kappa: Nominal scale agreement with provision for scaled disagreement or partial credit. *Psychological Bulletin*, **70**, 213–220.

See Also

irr::kappa2

Examples

```
# Here we create and display an artificial dataset,
# describing two traits coded by two raters:
scores <- data.frame(
  Trait1_A = c(1,0,2,1,1,1,0,2,1,1),
  Trait1_B = c(1,2,0,1,2,1,0,1,2,1),
  Trait2_A = c(1,4,5,2,3,5,1,2,3,4),
  Trait2_B = c(2,5,2,2,4,5,1,3,1,4)
)
scores

# Retrieve Cohen's kappa for Trait1 and Trait2,
# to evaluate inter-rater agreement between raters A and B:
kappaCohen(scores, weight="unweighted")
kappaCohen(scores, weight="squared")
```

kappaFleiss	<i>Calculates Fleiss' kappa between k raters for all k-uplets of columns in a given dataframe</i>
-------------	---

Description

This function is based on the function 'kappam.fleiss' from the package 'irr', and simply adds the possibility of calculating several kappas at once.

Usage

```
kappaFleiss(data, nb_raters=3)
```

Arguments

data	dataframe with $k \times p$ columns, k being the number of raters, and p the number of traits. The first k columns represent the scores attributed by the k raters for the first trait; the next k columns represent the scores attributed by the k raters for the second trait; etc. The dataframe must contain a header, and each column must be labeled as follows: 'VariableName_X', where X is a unique character (letter or number) associated with each rater (cf. below for an example).
nb_raters	integer for the number of raters.

Details

For each trait, only complete cases are used for the calculation.

Value

A dataframe with p rows (one per trait) and two columns, giving respectively the kappa value for each trait, and the number of individuals used to calculate this value.

Author(s)

Frédéric Santos, <frederic.santos@u-bordeaux.fr>

References

Cohen, J. (1960) A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, **20**, 37–46.

Cohen, J. (1968) Weighted kappa: Nominal scale agreement with provision for scaled disagreement or partial credit. *Psychological Bulletin*, **70**, 213–220.

See Also

irr::kappam.fleiss

Examples

```
# Here we create and display an artificial dataset,  
# describing two traits coded by three raters:  
scores <- data.frame(  
  Trait1_A = c(1,0,2,1,1,1,0,2,1,1),  
  Trait1_B = c(1,2,0,1,2,1,0,1,2,1),  
  Trait1_C = c(2,2,2,1,1,1,0,1,2,1),  
  Trait2_A = c(1,4,5,2,3,5,1,2,3,4),  
  Trait2_B = c(2,5,2,2,4,5,1,3,1,4),  
  Trait2_C = c(2,4,3,2,4,5,2,2,3,4)  
)  
scores  
  
# Retrieve Fleiss' kappa for Trait1 and Trait2,  
# to evaluate inter-rater agreement between raters A, B and C:  
kappaFleiss(scores, nb_raters=3)
```

StartKappa

A graphical user interface for calculating Cohen's and Fleiss' Kappa

Description

Launches the R-Shiny application. The user can retrieve inter-rater agreement scores from a file (.CSV or .TXT) loaded directly through the graphical interface.

Usage

StartKappa()

Details

Data importation is done directly through the graphical user interface. Only CSV and TXT files are accepted.

If there are p variables observed by k raters on n individuals, the input file should be a data frame with n rows and $(k \times p)$ columns. The first k columns represent the scores attributed by the k raters for the first variable; the next k columns represent the scores attributed by the k raters for the second variable; etc. Cohen's or Fleiss' kappas are returned for each variable.

The data file must contain a header, and the columns must be labeled as follows: 'Variable-Name_X', where X is a unique character (letter or number) associated with each rater. An example of correct data file with two raters is given here: http://www.pacea.u-bordeaux.fr/IMG/csv/data_Kappa_Cohen.csv.

Kappa values are calculated using the functions `kappa2` and `kappam.fleiss` from the package 'irr'. Please check their help pages for more technical details, in particular about the weighting options for Cohen's kappa. For ordered factors, linear or quadratic weighting could be a good choice, as they give more importance to strong disagreements. If linear or quadratic weighting are chosen, the levels of the factors will be supposed to be ordered alphabetically (as a consequence, a factor with three levels "Low", "Medium" and "High" would be ordered in an inconvenient way: in this case, please recode the levels with names matching the natural order of the levels).

Value

The function returns no value, but the table of results can be downloaded as a CSV file through the user interface.

Author(s)

Frédéric Santos, <frederic.santos@u-bordeaux.fr>

References

Cohen, J. (1960) A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, **20**, 37–46.

Cohen, J. (1968) Weighted kappa: Nominal scale agreement with provision for scaled disagreement or partial credit. *Psychological Bulletin*, **70**, 213–220.

See Also

`irr::kappa2`, `irr::kappam.fleiss`

Index

*Topic **Cohen**

kappaCohen, [3](#)

StartKappa, [5](#)

*Topic **Fleiss**

kappaFleiss, [4](#)

StartKappa, [5](#)

*Topic **Kappa**

kappaCohen, [3](#)

kappaFleiss, [4](#)

KappaGUI-package, [2](#)

StartKappa, [5](#)

kappaCohen, [3](#)

kappaFleiss, [4](#)

KappaGUI (KappaGUI-package), [2](#)

KappaGUI-package, [2](#)

StartKappa, [5](#)