

Package ‘ModelMatrixModel’

August 17, 2021

Type Package

Title Create Model Matrix and Save the Transforming Parameters

Version 0.1.0

Author Xinyong Tian

Maintainer Xinyong Tian <xinyongtian@gmail.com>

Description

The model.matrix() function in R is convenient for transforming training dataset for modeling. But it does not save any parameter used in transformation, so it is hard to apply the same transformation to test dataset or new dataset. This package is created to solve the problem.

License GPL-3

Encoding UTF-8

LazyData false

RoxygenNote 7.1.1

Imports Matrix

Suggests rmarkdown, knitr

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2021-08-17 08:00:10 UTC

R topics documented:

| | |
|------------------------------------|---|
| ModelMatrixModel | 2 |
| predict.ModelMatrixModel | 3 |

| | |
|--------------|----------|
| Index | 4 |
|--------------|----------|

ModelMatrixModel *ModelMatrixModel()* function

Description

This function transforms a data.frame to matrix (or sparse matrix) based on a r formula. The mean different from model.matrix() function is that it outputs a class stored with the transformed matrix, as well as the transforming parameters which can be applied to new data.

Usage

```
ModelMatrixModel(
  rformula,
  data,
  sparse = TRUE,
  center = FALSE,
  scale = FALSE,
  remove_1st_dummy = FALSE,
  verbose = FALSE
)
```

Arguments

| | |
|------------------|--|
| rformula | a formula, e.g. formula("~ 1+x1+x2"), "~ 1+x1+x2", or ~ 1+x1+x2 . Note the interpreting of the formula might be different slightly from model.matrix function. In model.matrix(), intercept column will be included in output matrix with or without "1" in the formula. But in ModelMatrixModel(), intercept column will be included in output matrix only when "1" is present. Moreover "0" or "." in the formula will be ignored. |
| data | a data.frame. |
| sparse | boolean, if TRUE return a sparse matrix, i.e. a "dgCMatrix" class. |
| center | boolean, if center the output. |
| scale | boolean, if scale the output. |
| remove_1st_dummy | boolean, if remove the first dummy variable in one hot key transformation. |
| verbose | boolean, if print out progress. |

Details

see vignettes.

Value

A ModelMatrixModel class, which includes the transformed matrix and the transforming parameters.

Examples

```
library(ModelMatrixModel)
traindf= data.frame(x1 = sample(LETTERS[1:5], replace = TRUE, 20),
                    x2 = rnorm(20, 100, 5),
                    y = rnorm(20, 10, 2))
mm=ModelMatrixModel(~x1+x2,traindf,remove_1st_dummy = FALSE)
data.frame(as.matrix(head(mm$x,2)))
```

```
predict.ModelMatrixModel
  predict() function
```

Description

This function transforms new data based on transforming parameters from a ModelMatrixModel object

Usage

```
## S3 method for class 'ModelMatrixModel'
predict(object, data, handleInvalid = "keep", verbose = FALSE, ...)
```

Arguments

| | |
|---------------|---|
| object | a ModelMatrixModel object. |
| data | a data.frame. |
| handleInvalid | a string,'keep' or 'error'. In dummy variable transformation, if categorical variable has a factor level that is unseen before, 'keep' will keep the record, output dummy variables will be all zero. |
| verbose | boolean, if print out progress. |
| ... | other parameters. |

Value

A ModelMatrixModel class,which includes the transformed matrix and the necessary transforming parameters copied from input object.

Examples

```
library(ModelMatrixModel)
traindf= data.frame(x1 = sample(LETTERS[1:5], replace = TRUE, 20),
                    x2 = rnorm(20, 100, 5),
                    y = rnorm(20, 10, 2))
newdf=data.frame(x1 = sample(LETTERS[1:5], replace = TRUE, 3),
                 x2 = rnorm(3, 100, 5))
mm=ModelMatrixModel(~x1+x2,traindf,remove_1st_dummy = FALSE)
mm_pred=predict(mm,newdf)
data.frame(as.matrix(head(mm_pred$x,2)))
```

Index

`ModelMatrixModel`, [2](#)

`predict.ModelMatrixModel`, [3](#)