

Package ‘ROI.models.netlib’

August 29, 2020

Type Package

Title 'ROI' Optimization Problems Based on 'NETLIB-LP'

Version 1.1-1

Author Florian Schwendinger [aut, cre]

Maintainer Florian Schwendinger <FlorianSchwendinger@gmx.at>

Description A collection of 'ROI' optimization problems based on the 'NETLIB-LP' collection. 'Netlib' is a software repository, which amongst many other software for scientific computing contains a collection of linear programming problems. The purpose of this package is to make this problems easily accessible from 'R' as 'ROI' optimization problems.

Imports ROI (>= 0.3-0)

Suggests Rglpk (>= 0.6-2)

License GPL-3

NeedsCompilation no

Repository CRAN

Date/Publication 2020-08-29 19:20:02 UTC

R topics documented:

netlib	1
Index	4

netlib	<i>Obtain Netlib Linear Problems</i>
--------	--------------------------------------

Description

If x is missing a character vector giving the names of all available problems is returned. If x is "all" a list containing all the optimization problems is returned. If x is the name of an optimization problem, the given optimization problem is returned. If x is "metainfo" a data.frame containing all the meta info is returned.

Usage

```
netlib(x=c("all", "metainfo", "adlittle", "afiro", "agg", "agg2",
          "agg3", "bandm", "beaconfd", "blend", "bn1", "bn12",
          "boeing1", "boeing2", "bore3d", "brandy", "capri", "cycle",
          "czprob", "d2q06c", "d6cube", "degen2", "degen3", "df1001",
          "e226", "etamacro", "fffff800", "finnis", "fit1d", "fit1p",
          "fit2d", "fit2p", "forplan", "ganges", "gfrd.pnc", "greenbea",
          "greenbeb", "grow15", "grow22", "grow7", "israel", "kb2",
          "lotfi", "maros.r7", "maros", "modszk1", "nesm", "perold",
          "pilot.ja", "pilot", "pilot.we", "pilot4", "pilot87",
          "pilotnov", "recipe", "sc105", "sc205", "sc50a", "sc50b",
          "scagr25", "scagr7", "scfxm1", "scfxm2", "scfxm3", "scorpion",
          "scrs8", "scsd1", "scsd6", "scsd8", "sctap1", "sctap2", "sctap3",
          "seba", "share1b", "share2b", "shell", "ship041", "ship04s", "ship081",
          "ship08s", "ship121", "ship12s", "sierra", "stair",
          "standata", "standmps", "stocfor1", "stocfor2", "stocfor3",
          "truss", "tuff", "vtp.base", "wood1p", "woodw", "x25fv47", "x80bau3b"))
```

Arguments

x a character giving the name of the optimization problem to be returned.

Details

Netlib is a software repository, which amongst many other software for scientific computing contains a collection of linear programming problems. The column `optimal_value` contains the results published in Koch (2004).

References

[NETLIB-LP] Koch, Thorsten (2004) The final NETLIB-LP results. Operations Research Letters <https://opus4.kobv.de/opus4-zib/files/727/ZR-03-05.pdf>

Examples

```
## Not run:
library(ROI)
library(ROI.models.netlib)
## list all available problems
netlib()
## get all problems as a list
ntlb <- netlib("all")
## get a certain problem by name
netlib("afiro")
ntlb[["afiro"]]
## get the meta info to the problems
netlib("metainfo")
## solve a problem
sol <- ROI_solve(netlib("afiro"))
sol
```

```
sol$objval - as.numeric(netlib("metainfo")["afiro", "final_results"])  
## End(Not run)
```

Index

netlib, 1