

Package ‘bestNormalize’

June 13, 2022

Type Package

Title Normalizing Transformation Functions

Version 1.8.3

Date 2022-06-13

Description Estimate a suite of normalizing transformations, including a new adaptation of a technique based on ranks which can guarantee normally distributed transformed data if there are no ties: ordered quantile normalization (ORQ). ORQ normalization combines a rank-mapping approach with a shifted logit approximation that allows the transformation to work on data outside the original domain. It is also able to handle new data within the original domain via linear interpolation. The package is built to estimate the best normalizing transformation for a vector consistently and accurately. It implements the Box-Cox transformation, the Yeo-Johnson transformation, three types of Lambert WxF transformations, and the ordered quantile normalization transformation. It estimates the normalization efficacy of other commonly used transformations, and it allows users to specify custom transformations or normalization statistics. Finally, functionality can be integrated into a machine learning workflow via recipes.

URL <https://petersonr.github.io/bestNormalize/>,
<https://github.com/petersonR/bestNormalize>

License GPL-3

Depends R (>= 3.1.0)

Imports LambertW (>= 0.6.5), nortest, dplyr, doParallel, foreach,
doRNG, recipes, tibble, methods, butcher, purrr

Suggests knitr, rmarkdown, MASS, testthat, mgcv, parallel, ggplot2,
scales, rlang, covr

VignetteBuilder knitr

LazyData true

RoxygenNote 7.2.0

Encoding UTF-8

NeedsCompilation no

Author Ryan Andrew Peterson [aut, cre]
(<https://orcid.org/0000-0002-4650-5798>)

Maintainer Ryan Andrew Peterson <ryan.a.peterson@cuanschutz.edu>

Repository CRAN

Date/Publication 2022-06-13 20:50:02 UTC

R topics documented:

bestNormalize-package	2
arcsinh_x	3
autotrader	4
bestNormalize	5
binarize	8
boxcox	10
exp_x	11
lambert	13
log_x	15
no_transform	16
orderNorm	18
plot.bestNormalize	20
sqrt_x	21
step_best_normalize	22
step_orderNorm	24
yeojohnson	26
Index	28

bestNormalize-package *bestNormalize: Flexibly calculate the best normalizing transformation for a vector*

Description

The bestNormalize package provides several normalizing transformations, and introduces a new transformation based off of the order statistics, orderNorm. Perhaps the most useful function is bestNormalize, which attempts all of these transformations and picks the best one based off of a goodness of fit statistic.

Author(s)

Maintainer: Ryan Andrew Peterson <ryan.a.peterson@cuanschutz.edu> ([ORCID](https://orcid.org/0000-0002-4650-5798))

See Also

Useful links:

- <https://petersonr.github.io/bestNormalize/>
- <https://github.com/petersonR/bestNormalize>

arcsinh_x

arcsinh(x) Transformation

Description

Perform a arcsinh(x) transformation

Usage

```
arcsinh_x(x, standardize = TRUE, ...)

## S3 method for class 'arcsinh_x'
predict(object, newdata = NULL, inverse = FALSE, ...)

## S3 method for class 'arcsinh_x'
print(x, ...)
```

Arguments

x	A vector to normalize with with x
standardize	If TRUE, the transformed values are also centered and scaled, such that the transformation attempts a standard normal
...	additional arguments
object	an object of class 'arcsinh_x'
newdata	a vector of data to be (potentially reverse) transformed
inverse	if TRUE, performs reverse transformation

Details

arcsinh_x performs an arcsinh transformation in the context of bestNormalize, such that it creates a transformation that can be estimated and applied to new data via the predict function.

The function is explicitly: $\log(x + \sqrt{x^2 + 1})$

Value

A list of class `arcsinh_x` with elements

<code>x.t</code>	transformed original data
<code>x</code>	original data
<code>mean</code>	mean after transformation but prior to standardization
<code>sd</code>	sd after transformation but prior to standardization
<code>n</code>	number of nonmissing observations
<code>norm_stat</code>	Pearson's P / degrees of freedom
<code>standardize</code>	was the transformation standardized

The `predict` function returns the numeric value of the transformation performed on new data, and allows for the inverse transformation as well.

Examples

```
x <- rgamma(100, 1, 1)

arcsinh_x_obj <- arcsinh_x(x)
arcsinh_x_obj
p <- predict(arcsinh_x_obj)
x2 <- predict(arcsinh_x_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)
```

autotrader

Prices of 6,283 cars listed on Autotrader

Description

A dataset containing the prices and other attributes of over 6000 cars in the Minneapolis area.

Usage

```
autotrader
```

Format

A data frame with 6283 rows and 10 variables:

price price, in US dollars

Car_Info Raw description from website

Link hyperlink to listing (must be appended to <https://www.autotrader.com/>)

Make Car manufacturer

Year Year car manufactured

Location Location of listing
Radius Radius chosen for search
mileage mileage on vehicle
status used/new/certified
model make and model, separated by space

Source

<https://www.autotrader.com/>

bestNormalize	<i>Calculate and perform best normalizing transformation</i>
---------------	--------------------------------------------------------------

Description

Performs a suite of normalizing transformations, and selects the best one on the basis of the Pearson P test statistic for normality. The transformation that has the lowest P (calculated on the transformed data) is selected. See details for more information.

Usage

```
bestNormalize(
  x,
  standardize = TRUE,
  allow_orderNorm = TRUE,
  allow_lambert_s = FALSE,
  allow_lambert_h = FALSE,
  allow_exp = TRUE,
  out_of_sample = TRUE,
  cluster = NULL,
  k = 10,
  r = 5,
  loo = FALSE,
  warn = FALSE,
  quiet = FALSE,
  tr_opts = list(),
  new_transforms = list(),
  norm_stat_fn = NULL,
  ...
)

## S3 method for class 'bestNormalize'
predict(object, newdata = NULL, inverse = FALSE, ...)

## S3 method for class 'bestNormalize'
print(x, ...)
```

```
## S3 method for class 'bestNormalize'
tidy(x)
```

Arguments

<code>x</code>	A 'bestNormalize' object.
<code>standardize</code>	If TRUE, the transformed values are also centered and scaled, such that the transformation attempts a standard normal. This will not change the normality statistic.
<code>allow_orderNorm</code>	set to FALSE if orderNorm should not be applied
<code>allow_lambert_s</code>	Set to FALSE if the lambertW of type "s" should not be applied (see details). Expect about 2-3x elapsed computing time if TRUE.
<code>allow_lambert_h</code>	Set to TRUE if the lambertW of type "h" should be applied (see details). Expect about 2-3x elapsed computing time.
<code>allow_exp</code>	Set to TRUE if the exponential transformation should be applied (sometimes this will cause errors with heavy right skew)
<code>out_of_sample</code>	if FALSE, estimates quickly in-sample performance
<code>cluster</code>	name of cluster set using makeCluster
<code>k</code>	number of folds
<code>r</code>	number of repeats
<code>loo</code>	should leave-one-out CV be used instead of repeated CV? (see details)
<code>warn</code>	Should bestNormalize warn when a method doesn't work?
<code>quiet</code>	Should a progress-bar not be displayed for cross-validation progress?
<code>tr_opts</code>	a list (of lists), specifying options to be passed to each transformation (see details)
<code>new_transforms</code>	a named list of new transformation functions and their predict methods (see details)
<code>norm_stat_fn</code>	if specified, a function to calculate to assess normality (default is the Pearson chi-squared statistic divided by its d.f.)
<code>...</code>	additional arguments.
<code>object</code>	an object of class 'bestNormalize'
<code>newdata</code>	a vector of data to be (reverse) transformed
<code>inverse</code>	if TRUE, performs reverse transformation

Details

bestNormalize estimates the optimal normalizing transformation. This transformation can be performed on new data, and inverted, via the predict function.

This function currently estimates the Yeo-Johnson transformation, the Box-Cox transformation (if the data is positive), the $\log_{10}(x+a)$ transformation, the square-root $(x+a)$ transformation, and the

arcsinh transformation. `a` is set to $\max(0, -\min(x) + \text{eps})$ by default. If `allow_orderNorm == TRUE` and if `out_of_sample == FALSE` then the ordered quantile normalization technique will likely be chosen since it essentially forces the data to follow a normal distribution. More information on the `orderNorm` technique can be found in the package vignette, or using `?orderNorm`.

Repeated cross-validation is used by default to estimate the out-of-sample performance of each transformation if `out_of_sample = TRUE`. While this can take some time, users can speed it up by creating a cluster via the `parallel` package's `makeCluster` function, and passing the name of this cluster to `bestNormalize` via the `cl` argument. For best performance, we recommend the number of clusters to be set to the number of repeats `r`. Care should be taken to account for the number of observations per fold; too small a number and the estimated normality statistic could be inaccurate, or at least suffer from high variability.

As of version 1.3, users can use leave-one-out cross-validation as well for each method by setting `loo` to `TRUE`. This will take a lot of time for bigger vectors, but it will have the most accurate estimate of normalization efficacy. Note that if this method is selected, arguments `k`, `r` are ignored. This method will still work in parallel with the `cl` argument.

Note that the Lambert transformation of type "h" can be done by setting `allow_lambert_h = TRUE`, however this can take significantly longer to run.

Use `tr_opts` in order to set options for each transformation. For instance, if you want to override the default a selection for `log_x`, set `tr_opts$log_x = list(a = 1)`.

See the package's vignette on how to use custom functions with `bestNormalize`. All it takes is to create an S3 class and predict method for the new transformation and load it into the environment, then the new custom function (and its predict method) can be passed to `bestNormalize` with `new_transform`.

Value

A list of class `bestNormalize` with elements

<code>x.t</code>	transformed original data
<code>x</code>	original data
<code>norm_stats</code>	Pearson's P / degrees of freedom
<code>method</code>	out-of-sample or in-sample, number of folds + repeats
<code>chosen_transform</code>	the chosen transformation (of appropriate class)
<code>other_transforms</code>	the other transformations (of appropriate class)
<code>oos_preds</code>	Out-of-sample predictions (if <code>loo == TRUE</code>) or normalization stats

The `predict` function returns the numeric value of the transformation performed on new data, and allows for the inverse transformation as well.

See Also

[boxcox](#), [orderNorm](#), [yeojohnson](#)

Examples

```

x <- rgamma(100, 1, 1)

## Not run:
# With Repeated CV
BN_obj <- bestNormalize(x)
BN_obj
p <- predict(BN_obj)
x2 <- predict(BN_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)

## End(Not run)

## Not run:
# With leave-one-out CV
BN_obj <- bestNormalize(x, loo = TRUE)
BN_obj
p <- predict(BN_obj)
x2 <- predict(BN_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)

## End(Not run)

# Without CV
BN_obj <- bestNormalize(x, allow_orderNorm = FALSE, out_of_sample = FALSE)
BN_obj
p <- predict(BN_obj)
x2 <- predict(BN_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)

```

binarize

Binarize

Description

This function will perform a binarizing transformation, which could be used as a last resort if the data cannot be adequately normalized. This may be useful when accidentally attempting normalization of a binary vector (which could occur if implementing `bestNormalize` in an automated fashion).

Note that the transformation is not one-to-one, in contrast to the other functions in this package.

Usage

```
binarize(x, location_measure = "median")
```



```
## S3 method for class 'binarize'
predict(object, newdata = NULL, inverse = FALSE, ...)

## S3 method for class 'binarize'
print(x, ...)
```

Arguments

x	A vector to binarize
location_measure	which location measure should be used? can either be "median", "mean", "mode", a number, or a function.
object	an object of class 'binarize'
newdata	a vector of data to be (reverse) transformed
inverse	if TRUE, performs reverse transformation
...	additional arguments

Value

A list of class binarize with elements

x.t	transformed original data
x	original data
method	location_measure used for original fitting
location	estimated location_measure
n	number of nonmissing observations
norm_stat	Pearson's P / degrees of freedom

The predict function with inverse = FALSE returns the numeric value (0 or 1) of the transformation on newdata (which defaults to the original data).

If inverse = TRUE, since the transform is not 1-1, it will create and return a factor that indicates where the original data was cut.

Examples

```
x <- rgamma(100, 1, 1)
binarize_obj <- binarize(x)
(p <- predict(binarize_obj))

predict(binarize_obj, newdata = p, inverse = TRUE)
```

 boxcox

Box-Cox Normalization

Description

Perform a Box-Cox transformation and center/scale a vector to attempt normalization

Usage

```
boxcox(x, standardize = TRUE, ...)

## S3 method for class 'boxcox'
predict(object, newdata = NULL, inverse = FALSE, ...)

## S3 method for class 'boxcox'
print(x, ...)
```

Arguments

x	A vector to normalize with Box-Cox
standardize	If TRUE, the transformed values are also centered and scaled, such that the transformation attempts a standard normal
...	Additional arguments that can be passed to the estimation of the lambda parameter (lower, upper, epsilon)
object	an object of class 'boxcox'
newdata	a vector of data to be (reverse) transformed
inverse	if TRUE, performs reverse transformation

Details

boxcox estimates the optimal value of lambda for the Box-Cox transformation. This transformation can be performed on new data, and inverted, via the predict function.

The function will return an error if a user attempt to transform nonpositive data.

Value

A list of class boxcox with elements

x.t	transformed original data
x	original data
mean	mean after transformation but prior to standardization
sd	sd after transformation but prior to standardization
lambda	estimated lambda value for skew transformation
n	number of nonmissing observations

norm_stat	Pearson's P / degrees of freedom
standardize	was the transformation standardized

The predict function returns the numeric value of the transformation performed on new data, and allows for the inverse transformation as well.

References

Box, G. E. P. and Cox, D. R. (1964) An analysis of transformations. Journal of the Royal Statistical Society B, 26, 211-252.

See Also

[boxcox](#)

Examples

```
x <- rgamma(100, 1, 1)

bc_obj <- boxcox(x)
bc_obj
p <- predict(bc_obj)
x2 <- predict(bc_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)
```

exp_x

exp(x) Transformation

Description

Perform a $\exp(x)$ transformation

Usage

```
exp_x(x, standardize = TRUE, warn = TRUE, ...)

## S3 method for class 'exp_x'
predict(object, newdata = NULL, inverse = FALSE, ...)

## S3 method for class 'exp_x'
print(x, ...)
```

Arguments

x	A vector to normalize with with x
standardize	If TRUE, the transformed values are also centered and scaled, such that the transformation attempts a standard normal
warn	Should a warning result from infinite values?
...	additional arguments
object	an object of class 'exp_x'
newdata	a vector of data to be (potentially reverse) transformed
inverse	if TRUE, performs reverse transformation

Details

exp_x performs a simple exponential transformation in the context of bestNormalize, such that it creates a transformation that can be estimated and applied to new data via the predict function.

Value

A list of class exp_x with elements

x.t	transformed original data
x	original data
mean	mean after transformation but prior to standardization
sd	sd after transformation but prior to standardization
n	number of nonmissing observations
norm_stat	Pearson's P / degrees of freedom
standardize	was the transformation standardized

The predict function returns the numeric value of the transformation performed on new data, and allows for the inverse transformation as well.

Examples

```
x <- rgamma(100, 1, 1)

exp_x_obj <- exp_x(x)
exp_x_obj
p <- predict(exp_x_obj)
x2 <- predict(exp_x_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)
```

lambert

Lambert W x F Normalization

Description

Perform Lambert's $W \times F$ transformation and center/scale a vector to attempt normalization via the LambertW package.

Usage

```
lambert(x, type = "s", standardize = TRUE, warn = FALSE, ...)

## S3 method for class 'lambert'
predict(object, newdata = NULL, inverse = FALSE, ...)

## S3 method for class 'lambert'
print(x, ...)
```

Arguments

x	A vector to normalize with Box-Cox
type	a character indicating which transformation to perform (options are "s", "h", and "hh", see details)
standardize	If TRUE, the transformed values are also centered and scaled, such that the transformation attempts a standard normal
warn	should the function show warnings
...	Additional arguments that can be passed to the LambertW::Gaussianize function
object	an object of class 'lambert'
newdata	a vector of data to be (reverse) transformed
inverse	if TRUE, performs reverse transformation

Details

lambert uses the LambertW package to estimate a normalizing (or "Gaussianizing") transformation. This transformation can be performed on new data, and inverted, via the predict function.

NOTE: The type = "s" argument is the only one that does the 1-1 transform consistently, and so it is the only method currently used in bestNormalize(). Use type = "h" or type = 'hh' at risk of not having this estimate 1-1 transform. These alternative types are effective when the data has exceptionally heavy tails, e.g. the Cauchy distribution.

Additionally, sometimes (depending on the distribution) this method will be unable to extrapolate beyond the observed bounds. In these cases, NaN is returned.

Value

A list of class `lambert` with elements

<code>x.t</code>	transformed original data
<code>x</code>	original data
<code>mean</code>	mean after transformation but prior to standardization
<code>sd</code>	sd after transformation but prior to standardization
<code>tau.mat</code>	estimated parameters of <code>LambertW::Gaussianize</code>
<code>n</code>	number of nonmissing observations
<code>norm_stat</code>	Pearson's P / degrees of freedom
<code>standardize</code>	was the transformation standardized

The `predict` function returns the numeric value of the transformation performed on new data, and allows for the inverse transformation as well.

References

Georg M. Goerg (2016). `LambertW`: An R package for Lambert $W \times F$ Random Variables. R package version 0.6.4.

Georg M. Goerg (2011): Lambert W random variables - a new family of generalized skewed distributions with applications to risk estimation. *Annals of Applied Statistics* 3(5). 2197-2230.

Georg M. Goerg (2014): The Lambert Way to Gaussianize heavy-tailed data with the inverse of Tukey's h transformation as a special case. *The Scientific World Journal*.

See Also

[Gaussianize](#)

Examples

```
## Not run:
x <- rgamma(100, 1, 1)

lambert_obj <- lambert(x)
lambert_obj
p <- predict(lambert_obj)
x2 <- predict(lambert_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)

## End(Not run)
```

log_x	<i>Log(x + a) Transformation</i>
-------	----------------------------------

Description

Perform a $\log_b(x+a)$ normalization transformation

Usage

```
log_x(x, a = NULL, b = 10, standardize = TRUE, eps = 0.001, warn = TRUE, ...)
```

```
## S3 method for class 'log_x'
predict(object, newdata = NULL, inverse = FALSE, ...)
```

```
## S3 method for class 'log_x'
print(x, ...)
```

Arguments

x	A vector to normalize with with x
a	The constant to add to x (defaults to $\max(0, -\min(x) + \text{eps})$)
b	The base of the log (defaults to 10)
standardize	If TRUE, the transformed values are also centered and scaled, such that the transformation attempts a standard normal
eps	The allowed error in the expression for the selected a
warn	Should a warning result from infinite values?
...	additional arguments
object	an object of class 'log_x'
newdata	a vector of data to be (potentially reverse) transformed
inverse	if TRUE, performs reverse transformation

Details

log_x performs a simple log transformation in the context of bestNormalize, such that it creates a transformation that can be estimated and applied to new data via the predict function. The parameter a is essentially estimated by the training set by default (estimated as the minimum possible to some extent epsilon), while the base must be specified beforehand.

Value

A list of class log_x with elements

x.t	transformed original data
x	original data

mean	mean after transformation but prior to standardization
sd	sd after transformation but prior to standardization
a	estimated a value
b	estimated base b value
n	number of nonmissing observations
norm_stat	Pearson's P / degrees of freedom
standardize	was the transformation standardized

The predict function returns the numeric value of the transformation performed on new data, and allows for the inverse transformation as well.

Examples

```
x <- rgamma(100, 1, 1)

log_x_obj <- log_x(x)
log_x_obj
p <- predict(log_x_obj)
x2 <- predict(log_x_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)
```

no_transform	<i>Identity transformation and center/scale transform</i>
--------------	-----------------------------------------------------------

Description

Perform an identity transformation. Admittedly it seems odd to have a dedicated function to essentially do $I(x)$, but it makes sense to keep the same syntax as the other transformations so it plays nicely with them. As a benefit, the bestNormalize function will also show a comparable normalization statistic for the untransformed data. If standardize == TRUE, center_scale passes to bestNormalize instead.

Usage

```
no_transform(x, warn = TRUE, ...)

## S3 method for class 'no_transform'
predict(object, newdata = NULL, inverse = FALSE, ...)

## S3 method for class 'no_transform'
print(x, ...)

center_scale(x, warn = TRUE, ...)
```



```
## S3 method for class 'center_scale'
predict(object, newdata = NULL, inverse = FALSE, ...)

## S3 method for class 'center_scale'
print(x, ...)

## S3 method for class 'no_transform'
tidy(x)
```

Arguments

x	A 'no_transform' object.
warn	Should a warning result from infinite values?
...	additional arguments
object	an object of class 'no_transform'
newdata	a vector of data to be (potentially reverse) transformed
inverse	if TRUE, performs reverse transformation

Details

no_transform creates a identity transformation object that can be applied to new data via the predict function.

Value

A list of class no_transform with elements

x.t	transformed original data
x	original data
n	number of nonmissing observations
norm_stat	Pearson's P / degrees of freedom

The predict function returns the numeric value of the transformation performed on new data, and allows for the inverse transformation as well.

Examples

```
x <- rgamma(100, 1, 1)

no_transform_obj <- no_transform(x)
no_transform_obj
p <- predict(no_transform_obj)
x2 <- predict(no_transform_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)
```

orderNorm

Calculate and perform Ordered Quantile normalizing transformation

Description

The Ordered Quantile (ORQ) normalization transformation, `orderNorm()`, is a rank-based procedure by which the values of a vector are mapped to their percentile, which is then mapped to the same percentile of the normal distribution. Without the presence of ties, this essentially guarantees that the transformation leads to a uniform distribution.

The transformation is:

$$g(x) = \Phi^{-1}((\text{rank}(x) - .5)/(\text{length}(x)))$$

Where Φ refers to the standard normal cdf, `rank(x)` refers to each observation's rank, and `length(x)` refers to the number of observations.

By itself, this method is certainly not new; the earliest mention of it that I could find is in a 1947 paper by Bartlett (see references). This formula was outlined explicitly in Van der Waerden, and expounded upon in Beasley (2009). However there is a key difference to this version of it, as explained below.

Using linear interpolation between these percentiles, the ORQ normalization becomes a 1-1 transformation that can be applied to new data. However, outside of the observed domain of x , it is unclear how to extrapolate the transformation. In the ORQ normalization procedure, a binomial glm with a logit link is used on the ranks in order to extrapolate beyond the bounds of the original domain of x . The inverse normal CDF is then applied to these extrapolated predictions in order to extrapolate the transformation. This mitigates the influence of heavy-tailed distributions while preserving the 1-1 nature of the transformation. The extrapolation will provide a warning unless `warn = FALSE`.) However, we found that the extrapolation was able to perform very well even on data as heavy-tailed as a Cauchy distribution (paper to be published).

The fit used to perform the extrapolation uses a default of 10000 observations (or `length(x)` if that is less). This added approximation improves the scalability, both computationally and in terms of memory used. Do not set this value to be too low (e.g. `<100`), as there is no benefit to doing so. Increase if your test data set is large relative to 10000 and/or if you are worried about losing signal in the extremes of the range.

This transformation can be performed on new data and inverted via the `predict` function.

Usage

```
orderNorm(x, n_logit_fit = min(length(x), 10000), ..., warn = TRUE)
```

```
## S3 method for class 'orderNorm'
predict(object, newdata = NULL, inverse = FALSE, warn = TRUE, ...)
```

```
## S3 method for class 'orderNorm'
print(x, ...)
```

Arguments

<code>x</code>	A vector to normalize
<code>n_logit_fit</code>	Number of points used to fit logit approximation
<code>...</code>	additional arguments
<code>warn</code>	transforms outside observed range or ties will yield warning
<code>object</code>	an object of class 'orderNorm'
<code>newdata</code>	a vector of data to be (reverse) transformed
<code>inverse</code>	if TRUE, performs reverse transformation

Value

A list of class `orderNorm` with elements

<code>x.t</code>	transformed original data
<code>x</code>	original data
<code>n</code>	number of nonmissing observations
<code>ties_status</code>	indicator if ties are present
<code>fit</code>	fit to be used for extrapolation, if needed
<code>norm_stat</code>	Pearson's P / degrees of freedom

The `predict` function returns the numeric value of the transformation performed on new data, and allows for the inverse transformation as well.

References

Bartlett, M. S. "The Use of Transformations." *Biometrics*, vol. 3, no. 1, 1947, pp. 39-52. JSTOR www.jstor.org/stable/3001536.

Van der Waerden BL. Order tests for the two-sample problem and their power. 1952;55:453-458. Ser A.

Beasley TM, Erickson S, Allison DB. Rank-based inverse normal transformations are increasingly used, but are they merited? *Behav. Genet.* 2009;39(5): 580-595. pmid:19526352

See Also

[boxcox](#), [lambert](#), [bestNormalize](#), [yeojohnson](#)

Examples

```
x <- rgamma(100, 1, 1)

orderNorm_obj <- orderNorm(x)
orderNorm_obj
p <- predict(orderNorm_obj)
x2 <- predict(orderNorm_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)
```

plot.bestNormalize *Transformation plotting*

Description

Plots transformation functions for objects produced by the bestNormalize package

Usage

```
## S3 method for class 'bestNormalize'
plot(
  x,
  inverse = FALSE,
  bounds = NULL,
  cols = NULL,
  methods = NULL,
  leg_loc = "top",
  ...
)

## S3 method for class 'orderNorm'
plot(x, inverse = FALSE, bounds = NULL, ...)

## S3 method for class 'boxcox'
plot(x, inverse = FALSE, bounds = NULL, ...)

## S3 method for class 'yeojohnson'
plot(x, inverse = FALSE, bounds = NULL, ...)

## S3 method for class 'lambert'
plot(x, inverse = FALSE, bounds = NULL, ...)
```

Arguments

x	a fitted transformation
inverse	if TRUE, plots the inverse transformation
bounds	a vector of bounds to plot for the transformation
cols	a vector of colors to use for the transforms (see details)
methods	a vector of transformations to plot
leg_loc	the location of the legend on the plot
...	further parameters to be passed to plot and lines

Details

The plots produced by the individual transformations are simply plots of the original values by the newly transformed values, with a line denoting where transformations would take place for new data.

For the bestNormalize object, this plots each of the possible transformations run by the original call to bestNormalize. The first argument in the "cols" parameter refers to the color of the chosen transformation.

sqrt_x	<i>sqrt(x + a) Normalization</i>
--------	----------------------------------

Description

Perform a sqrt (x+a) normalization transformation

Usage

```
sqrt_x(x, a = NULL, standardize = TRUE, ...)

## S3 method for class 'sqrt_x'
predict(object, newdata = NULL, inverse = FALSE, ...)

## S3 method for class 'sqrt_x'
print(x, ...)
```

Arguments

x	A vector to normalize with with x
a	The constant to add to x (defaults to max(0, -min(x)))
standardize	If TRUE, the transformed values are also centered and scaled, such that the transformation attempts a standard normal
...	additional arguments
object	an object of class 'sqrt_x'
newdata	a vector of data to be (potentially reverse) transformed
inverse	if TRUE, performs reverse transformation

Details

sqrt_x performs a simple square-root transformation in the context of bestNormalize, such that it creates a transformation that can be estimated and applied to new data via the predict function. The parameter a is essentially estimated by the training set by default (estimated as the minimum possible), while the base must be specified beforehand.

Value

A list of class `sqrt_x` with elements

<code>x.t</code>	transformed original data
<code>x</code>	original data
<code>mean</code>	mean after transformation but prior to standardization
<code>sd</code>	sd after transformation but prior to standardization
<code>n</code>	number of nonmissing observations
<code>norm_stat</code>	Pearson's P / degrees of freedom
<code>standardize</code>	was the transformation standardized

The `predict` function returns the numeric value of the transformation performed on new data, and allows for the inverse transformation as well.

Examples

```
x <- rgamma(100, 1, 1)

sqrt_x_obj <- sqrt_x(x)
sqrt_x_obj
p <- predict(sqrt_x_obj)
x2 <- predict(sqrt_x_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)
```

`step_best_normalize` *Run bestNormalize transformation for recipes implementation*

Description

‘`step_best_normalize`’ creates a specification of a recipe step (see ‘`recipes`’ package) that will transform data using the best of a suite of normalization transformations estimated (by default) using cross-validation.

Usage

```
step_best_normalize(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  transform_info = NULL,
  transform_options = list(),
  num_unique = 5,
  skip = FALSE,
```

```

  id = rand_id("best_normalize")
)

## S3 method for class 'step_best_normalize'
tidy(x, ...)

## S3 method for class 'step_best_normalize'
axe_env(x, ...)

```

Arguments

recipe	A formula or recipe
...	One or more selector functions to choose which variables are affected by the step. See [selections()] for more details. For the 'tidy' method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	For recipes functionality
transform_info	A numeric vector of transformation values. This (was transform_info) is 'NULL' until computed by [prep.recipe()].
transform_options	options to be passed to bestNormalize
num_unique	An integer where data that have less possible values will not be evaluate for a transformation.
skip	For recipes functionality
id	For recipes functionality
x	A 'step_best_normalize' object.

Details

The bestnormalize transformation can be used to rescale a variable to be more similar to a normal distribution. See '?bestNormalize' for more information; 'step_best_normalize' is the implementation of 'bestNormalize' in the 'recipes' context.

As of version 1.7, the 'butcher' package can be used to (hopefully) improve scalability of this function on bigger data sets.

Value

An updated version of 'recipe' with the new step added to the sequence of existing steps (if any). For the 'tidy' method, a tibble with columns 'terms' (the selectors or variables selected) and 'value' (the lambda estimate).

See Also

[bestNormalize](#) [orderNorm](#), [recipe()] [prep.recipe()] [bake.recipe()]

Examples

```

library(recipes)
rec <- recipe(~ ., data = as.data.frame(iris))

bn_trans <- step_best_normalize(rec, all_numeric())

bn_estimates <- prep(bn_trans, training = as.data.frame(iris))

bn_data <- bake(bn_estimates, as.data.frame(iris))

plot(density(iris[, "Petal.Length"]), main = "before")
plot(density(bn_data$Petal.Length), main = "after")

tidy(bn_trans, number = 1)
tidy(bn_estimates, number = 1)

```

step_orderNorm

ORQ normalization (orderNorm) for recipes implementation

Description

‘step_orderNorm’ creates a specification of a recipe step (see ‘recipes’ package) that will transform data using the ORQ (orderNorm) transformation, which approximates the "true" normalizing transformation if one exists. This is considerably faster than ‘step_bestNormalize’.

Usage

```

step_orderNorm(
  recipe,
  ...,
  role = NA,
  trained = FALSE,
  transform_info = NULL,
  transform_options = list(),
  num_unique = 5,
  skip = FALSE,
  id = rand_id("orderNorm")
)

## S3 method for class 'step_orderNorm'
tidy(x, ...)

## S3 method for class 'step_orderNorm'
axe_env(x, ...)

```


Arguments

recipe	A formula or recipe
...	One or more selector functions to choose which variables are affected by the step. See [selections()] for more details. For the ‘tidy’ method, these are not currently used.
role	Not used by this step since no new variables are created.
trained	For recipes functionality
transform_info	A numeric vector of transformation values. This (was transform_info) is ‘NULL’ until computed by [prep.recipe()].
transform_options	options to be passed to orderNorm
num_unique	An integer where data that have less possible values will not be evaluate for a transformation.
skip	For recipes functionality
id	For recipes functionality
x	A ‘step_orderNorm’ object.

Details

The orderNorm transformation can be used to rescale a variable to be more similar to a normal distribution. See ‘?orderNorm’ for more information; ‘step_orderNorm’ is the implementation of ‘orderNorm’ in the ‘recipes’ context.

As of version 1.7, the ‘butcher’ package can be used to (hopefully) improve scalability of this function on bigger data sets.

Value

An updated version of ‘recipe’ with the new step added to the sequence of existing steps (if any). For the ‘tidy’ method, a tibble with columns ‘terms’ (the selectors or variables selected) and ‘value’ (the lambda estimate).

References

Ryan A. Peterson (2019). Ordered quantile normalization: a semiparametric transformation built for the cross-validation era. *Journal of Applied Statistics*, 1-16.

See Also

[orderNorm](#) [bestNormalize](#), [recipe()] [prep.recipe()] [bake.recipe()]

Examples

```
library(recipes)
rec <- recipe(~ ., data = as.data.frame(iris))

orq_trans <- step_orderNorm(rec, all_numeric())
```

```

orq_estimates <- prep(orq_trans, training = as.data.frame(iris))

orq_data <- bake(orq_estimates, as.data.frame(iris))

plot(density(iris[, "Petal.Length"]), main = "before")
plot(density(orq_data$Petal.Length), main = "after")

tidy(orq_trans, number = 1)
tidy(orq_estimates, number = 1)

```

yeojohnson

Yeo-Johnson Normalization

Description

Perform a Yeo-Johnson Transformation and center/scale a vector to attempt normalization

Usage

```

yeojohnson(x, eps = 0.001, standardize = TRUE, ...)

## S3 method for class 'yeojohnson'
predict(object, newdata = NULL, inverse = FALSE, ...)

## S3 method for class 'yeojohnson'
print(x, ...)

```

Arguments

x	A vector to normalize with Yeo-Johnson
eps	A value to compare lambda against to see if it is equal to zero
standardize	If TRUE, the transformed values are also centered and scaled, such that the transformation attempts a standard normal
...	Additional arguments that can be passed to the estimation of the lambda parameter (lower, upper)
object	an object of class 'yeojohnson'
newdata	a vector of data to be (reverse) transformed
inverse	if TRUE, performs reverse transformation

Details

yeojohnson estimates the optimal value of lambda for the Yeo-Johnson transformation. This transformation can be performed on new data, and inverted, via the predict function.

The Yeo-Johnson is similar to the Box-Cox method, however it allows for the transformation of nonpositive data as well. The step_YeoJohnson function in the recipes package is another useful resource (see references).

Value

A list of class yeojohnson with elements

x.t	transformed original data
x	original data
mean	mean after transformation but prior to standardization
sd	sd after transformation but prior to standardization
lambda	estimated lambda value for skew transformation
n	number of nonmissing observations
norm_stat	Pearson's P / degrees of freedom
standardize	Was the transformation standardized

The predict function returns the numeric value of the transformation performed on new data, and allows for the inverse transformation as well.

References

Yeo, I. K., & Johnson, R. A. (2000). A new family of power transformations to improve normality or symmetry. *Biometrika*.

Max Kuhn and Hadley Wickham (2017). *recipes: Preprocessing Tools to Create Design Matrices*. R package version 0.1.0.9000. <https://github.com/topepo/recipes>

Examples

```
x <- rgamma(100, 1, 1)

yeojohnson_obj <- yeojohnson(x)
yeojohnson_obj
p <- predict(yejohnson_obj)
x2 <- predict(yejohnson_obj, newdata = p, inverse = TRUE)

all.equal(x2, x)
```

Index

- * **datasets**
 - autotrader, 4
- * **preprocessing**
 - step_best_normalize, 22
 - step_orderNorm, 24
- * **transformation_methods**
 - step_best_normalize, 22
 - step_orderNorm, 24
- _PACKAGE (bestNormalize-package), 2
- arcsinh_x, 3
- autotrader, 4
- axe_env.step_best_normalize (step_best_normalize), 22
- axe_env.step_orderNorm (step_orderNorm), 24
- bestNormalize, 5, 19, 23, 25
- bestNormalize-package, 2
- binarize, 8
- boxcox, 7, 10, 11, 19
- center_scale (no_transform), 16
- exp_x, 11
- Gaussianize, 14
- lambert, 13, 19
- log_x, 15
- no_transform, 16
- orderNorm, 7, 18, 23, 25
- plot.bestNormalize, 20
- plot.boxcox (plot.bestNormalize), 20
- plot.lambert (plot.bestNormalize), 20
- plot.orderNorm (plot.bestNormalize), 20
- plot.yeojohnson (plot.bestNormalize), 20
- predict.arcsinh_x (arcsinh_x), 3
- predict.bestNormalize (bestNormalize), 5
- predict.binarize (binarize), 8
- predict.boxcox (boxcox), 10
- predict.center_scale (no_transform), 16
- predict.exp_x (exp_x), 11
- predict.lambert (lambert), 13
- predict.log_x (log_x), 15
- predict.no_transform (no_transform), 16
- predict.orderNorm (orderNorm), 18
- predict.sqrt_x (sqrt_x), 21
- predict.yeojohnson (yeojohnson), 26
- print.arcsinh_x (arcsinh_x), 3
- print.bestNormalize (bestNormalize), 5
- print.binarize (binarize), 8
- print.boxcox (boxcox), 10
- print.center_scale (no_transform), 16
- print.exp_x (exp_x), 11
- print.lambert (lambert), 13
- print.log_x (log_x), 15
- print.no_transform (no_transform), 16
- print.orderNorm (orderNorm), 18
- print.sqrt_x (sqrt_x), 21
- print.yeojohnson (yeojohnson), 26
- sqrt_x, 21
- step_best_normalize, 22
- step_bestNormalize (step_best_normalize), 22
- step_bestNormalize_new (step_best_normalize), 22
- step_orderNorm, 24
- tidy.bestNormalize (bestNormalize), 5
- tidy.no_transform (no_transform), 16
- tidy.step_best_normalize (step_best_normalize), 22
- tidy.step_orderNorm (step_orderNorm), 24
- yeojohnson, 7, 19, 26