

Package ‘lgtdl’

September 19, 2017

Version 1.1.5

Author R. Gentleman

Title A Set of Methods for Longitudinal Data Objects

Description A very simple implementation of a class for longitudinal data.

Depends R(>= 1.2)

Imports graphics, stats

License GPL (>= 2)

Maintainer Arthur Allignol <arthur.allignol@gmail.com>

NeedsCompilation no

Repository CRAN

Date/Publication 2017-09-19 16:18:13 UTC

R topics documented:

as.lgtdl	2
getcov	3
interplinar	4
interpprev	5
lgtdl	6
plot.lgtdl	6
toString.lgtdl	7
Index	9

`as.lgtdl`*Longitudinal Class*

Description

`as.lgtdl` coerces its argument to class `lgtdl` if possible. `is.lgtdl` returns TRUE if its argument is of class `lgtdl` and FALSE otherwise.

Usage

```
as.lgtdl(x, row.names=NULL)
is.lgtdl(x)
```

Arguments

<code>x</code>	An object which is coerced to a <code>lgtdl</code> object for <code>as.lgtdl</code> or tested with <code>is.lgtdl</code> .
<code>row.names</code>	An optional set of row names to be used for the names of the covariates in the resulting <code>lgtdl</code> object.

Value

<code>is.lgtdl</code>	Returns TRUE if its argument is of class <code>lgtdl</code> .
<code>as.lgtdl</code>	Returns an object of class <code>lgtdl</code> .

Author(s)

Robert Gentleman

See Also

[plot.lgtdl](#), [lgtdl](#)

Examples

```
x1<-data.frame(time=c(1,3,5), cov=c(4,6,8))
x2<-data.frame(time=c(11,13,15), interest=c(66,45,88))

x1<-as.lgtdl(x1)
x2<-as.lgtdl(x2)

is.lgtdl(TRUE)
```

`getcov`*A function to extract the covariate from an object of class `lgtdl`.*

Description

The covariate component of the `lgtdl` object is returned.

Usage

```
getcov(x, ...)  
## S3 method for class 'lgtdl'  
getcov(x, cov, ...)
```

Arguments

<code>x</code>	The <code>lgtdl</code> object.
<code>cov</code>	The name of the covariate to be extracted.
<code>...</code>	Ignored, there for potential future use.

Value

The covariate, as either a matrix or vector, is returned.

Author(s)

Robert Gentleman

See Also

[lgtdl](#), [as.lgtdl](#)

Examples

```
x1<-data.frame(time=c(1,3,5), cov=c(4,6,8))  
x2<-data.frame(time=c(11,13,15), interest=c(66,45,88))  
  
x1<-as.lgtdl(x1)  
x2<-as.lgtdl(x2)  
getcov(x1)  
getcov(x2)
```

interplinear	<i>A function to provide estimates of the response for a longitudinal data object. The estimate is obtained by linear interpolation from the preceding and following observations.</i>
--------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Description

A linear interpolation, using [approx](#), is used to obtain estimates of the covariate at times other than those observed.

Usage

```
interplinear(x, ...)  
## S3 method for class 'lgtddl'  
interplinear(x, time, cov = NULL, ...)  
## S3 method for class 'AsIs'  
interplinear(x, ...)
```

Arguments

x	The lgtddl object that is to be interpolated.
time	The time(s) at which interpolation is desired.
cov	The name of the covariate in the lgtddl object on which the interpolation should be based. It is not required if there is only one covariate.
...	Ignored.

Value

A vector containing the interpolated estimates of the covariate values at the requested times.

Author(s)

Robert Gentleman

See Also

[interpprev](#)

Examples

```
x1<-data.frame(time=c(1,3,5), cov=c(4,6,8))  
x2<-data.frame(time=c(11,13,15), interest=c(66,45,88))  
x1<-as.lgtddl(x1)  
x2<-as.lgtddl(x2)  
interpprev(x1, 4)  
interpprev(x2, c(12, 14))
```

`interpprev`*Interpolation Using the Previous Value*

Description

These functions provide an interpolation mechanism for objects of class `lgtdl`. The `AsIs` method is the vectorized version.

Usage

```
interpprev(x, ...)  
## S3 method for class 'lgtdl'  
interpprev(x, time, cov, ...)  
## S3 method for class 'AsIs'  
interpprev(x, ...)
```

Arguments

<code>x</code>	<code>x</code> is either an object of class <code>lgtdl</code> or of class <code>AsIs</code> . It is the object on which interpolation is to be performed.
<code>time</code>	A vector of times at which interpolation is requested.
<code>cov</code>	The name of the covariate on which interpolation is requested. It is only required if <code>x</code> has more than one covariate.
<code>...</code>	Ignored.

Details

If objects of class `lgtdl` are inserted into a data frame they become a vector with class `AsIs`. In order to operate on these we provide a method for that class. The method is simply a vectorized version.

Value

`interpprev.lgtdl` returns a numeric vector of the interpolated values of the covariate at the time(s) specified by `time`. `interpprev.AsIs` returns a vector of interpolated values of the covariate. In this case the vector contains one value for each element `x`. `time` must be either the same length as `x` or of length one. In the latter case all interpolations are done at that time.

Author(s)

Robert Gentleman

See Also

[interplinear](#)

Examples

```
x1<-data.frame(time=c(1,3,5), cov=c(4,6,8))
x2<-data.frame(time=c(11,13,15), interest=c(66,45,88))
x1<-as.lgtdl(x1)
x2<-as.lgtdl(x2)
interpprev(x1, c(2,4))
interpprev(x2, c(12, 14))
```

lgtdl	<i>Longitudinal Class</i>
-------	---------------------------

Description

The lgtdl class is a simple class of R/S objects that make it simpler to manipulate longitudinal data.

Author(s)

Robert Gentleman

References

Gentleman Robert (2001). Modeling with Objects. *Proceedings of the 2nd International Workshop on Distributed Statistical Computing*. <http://r-project.org/nosvn/conferences/DSC-2001/Proceedings/Gentleman.pdf>

plot.lgtdl	<i>A function for plotting lgtdl objects.</i>
------------	-----------------------------------------------

Description

A lgtdly object consists of a time component and one or more covariates measured or observed at the times specified in the time component. This function plots the covariate trajectories as lines on the y axis.

Usage

```
## S3 method for class 'lgtdl'
plot(x, ...)
```

Arguments

x	An object of class <code>lgtdl</code> .
...	Optional arguments to control the plotting.

Details

One should be able to specify values for any of the graphics parameters to change the appearance of the plot.

Value

No value is returned. A line plot of the longitudinal object is rendered on the active graphics device.

Author(s)

Robert Gentleman

See Also

[lgtdl](#)

Examples

```
x1<-data.frame(time=c(1,3,5), cov=c(4,6,8))
x2<-data.frame(time=c(11,13,15), interest=c(66,45,88))

x1<-as.lgtdl(x1)
x2<-as.lgtdl(x2)
plot(x1)
plot(x2)
```

toString.lgtdl

Produce a character string suitable for printing.

Description

Data frames can contain lgtdl objects as elements. When the data frame is printed this function provides a suitable string for printing.

Usage

```
## S3 method for class 'lgtdl'
toString(x, width, ...)
```

Arguments

x	The object to be formatted.
width	To control the width of the returned string-ignored.
...	Ignored.

Value

A character string. Currently it is "lgtdl, length = " with the length of the time component added.

Author(s)

Robert Gentleman

See Also

`toString`

Index

- *Topic **hplot**
 - plot.lgtdl, 6
- *Topic **manip**
 - as.lgtdl, 2
- *Topic **methods**
 - lgtdl, 6
- *Topic **smooth**
 - interplinear, 4
 - interpPrev, 5
- *Topic **utilities**
 - getcov, 3
 - toString.lgtdl, 7

approx, 4

as.lgtdl, 2, 3

getcov, 3

interplinear, 4, 5

interpPrev, 4, 5

is.lgtdl (as.lgtdl), 2

lgtdl, 2, 3, 6, 6, 7

plot.lgtdl, 2, 6

toString.lgtdl, 7