

Package ‘metabolighteR’

February 9, 2022

Type Package

Title Interface to the 'Metabolights' REST API

Version 0.1.3

Date 2022-02-09

Description Access to the 'Metabolights' REST API <<https://www.ebi.ac.uk/metabolights/index>>. Retrieve elements of publicly available 'Metabolights' studies.

Depends magrittr

Imports httr, dplyr, purrr, crayon

License GPL (>= 3)

URL <https://github.com/aberHRML/metabolighteR>

BugReports <https://github.com/aberHRML/metabolighteR/issues>

RoxygenNote 7.1.1

Encoding UTF-8

Suggests covr, testthat, tibble, knitr, rmarkdown, tidy

VignetteBuilder knitr

NeedsCompilation no

Author Tom Wilson [aut, cre] (<<https://orcid.org/0000-0003-3112-4682>>)

Maintainer Tom Wilson <tpw2@aber.ac.uk>

Repository CRAN

Date/Publication 2022-02-09 22:30:10 UTC

R topics documented:

download_study_file	2
get_isa_investigation	2
get_private_studies	3
get_studies	4
get_study_contacts	4
get_study_desc	5

get_study_descriptors	5
get_study_factors	6
get_study_files	6
get_study_meta	7
get_study_org	7
get_study_protocols	8
get_study_pubs	8
get_study_samples	9
get_study_tech	9
get_study_title	10
get_webservice	10
mtbls_key	11

Index 12

download_study_file *Download Study File Contents*

Description

Download the contents of a specified file from a public study

Usage

```
download_study_file(study_id, filename)
```

Arguments

study_id	a character string of a valid MTBLS study id
filename	a character of the full filename and extension to download

Value

a tibble of file contents

get_isa_investigation *Get ISA Investigation File*

Description

Retrieve the ISA Investigation for a specified Metabolights Study

Usage

```
get_isa_investigation(study_id)
```

Arguments

`study_id` A character string of a valid MTBLS study id

Value

the ISA-tab Investigation output

Examples

```
## Not run:  
ISA <- get_isa_investigation('MTBLS375')  
writeLines(isa_investigation_parse, con = paste0('outpath/ISA.txt'))  
  
## End(Not run)
```

`get_private_studies` *Get Private Studies*

Description

Retrieve all private studies which belong to your user account

Usage

```
get_private_studies()
```

Value

a tibble of your private Study IDs

Examples

```
## Not run:  
get_private_studies()  
  
## End(Not run)
```

`get_studies`*Get Studies*

Description

Retrieve a list of all publically available Metabolights studies

Usage

```
get_studies()
```

Value

a tibble of Study IDs

Examples

```
get_studies()
```

`get_study_contacts`*Get Study Contacts*

Description

Retrieve the contact details for a specified public study '

Usage

```
get_study_contacts(study_id)
```

Arguments

`study_id` a character string of a valid MTBLS study id

Value

a tibble of study contacts

Examples

```
get_study_contacts('MTBLS375')
```

`get_study_desc` *Get Study Description*

Description

Retrieve the abstract based description of a public study

Usage

```
get_study_desc(study_id)
```

Arguments

`study_id` A character string of a valid MTBLS study id

Value

a character string of the study description

Examples

```
get_study_desc('MTBLS375')
```

`get_study_descriptors` *Get Study Descriptors*

Description

Retrieve the study descriptors and annotation values for a publically available study

Usage

```
get_study_descriptors(study_id)
```

Arguments

`study_id` A character string of a valid MTBLS study id

Value

a tibble of study descriptors

Examples

```
get_study_descriptors('MTBLS375')
```

get_study_factors *Get Study Factors*

Description

Retrieve the study factors and annotation values for a publically available study

Usage

```
get_study_factors(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a tibble of study factors

Examples

```
get_study_factors('MTBLS375')
```

get_study_files *Get Study Files*

Description

Retrieve the names and type of all files that have been deposited with the public study. If raw_data is TRUE then details of raw data files(ie, .mzML) are also returned.

Usage

```
get_study_files(study_id, raw_data = FALSE)
```

Arguments

study_id A character string of a valid MTBLS study id
raw_data logical; if TRUE then raw data file info is also returned. (Default is FALSE)

Value

a tibble of file info

Examples

```
get_study_files('MTBLS375', raw_data = FALSE)
```

get_study_meta	<i>Get Study Meta</i>
----------------	-----------------------

Description

Retrieve the meta data for a publically available study

Usage

```
get_study_meta(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a tibble of study meta data

Examples

```
get_study_meta('MTBLS375')
```

get_study_org	<i>Get Study Organisms</i>
---------------	----------------------------

Description

Retrieve the organisms used within a study

Usage

```
get_study_org(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a tibble of study organism data

Examples

```
## Not run:  
get_study_org('MTBLS375')  
  
## End(Not run)
```

`get_study_protocols` *Get Study Protocols*

Description

Retrieve the protocol information that has been deposited for a public study

Usage

```
get_study_protocols(study_id)
```

Arguments

`study_id` A character string of a valid MTBLS study id

Value

a tibble of study protocols

Examples

```
get_study_protocols('MTBLS375')
```

`get_study_pubs` *Get Study Publications*

Description

Retrieve details on any publications that have been associated with the study

Usage

```
get_study_pubs(study_id)
```

Arguments

`study_id` A character string of a valid MTBLS study id

Value

a tibble of study publications

Examples

```
get_study_pubs('MTBLS375')
```

get_study_samples	<i>Get Study Samples</i>
-------------------	--------------------------

Description

Get a list of all sample names mapped to files within the study

Usage

```
get_study_samples(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a tibble of filename sample name and reliability score. 1.0 indicates a perfect match

Examples

```
## Not run:  
get_study_samples('MTBLS375')  
  
## End(Not run)
```

get_study_tech	<i>Get Study Technology</i>
----------------	-----------------------------

Description

Retrieve a tibble of all Study IDs and the analytical technology used in the study

Usage

```
get_study_tech()
```

Value

a tibble of study id and technology

Examples

```
get_study_tech()
```

get_study_title *Get Study Title*

Description

Retrieve the full title of the study

Usage

```
get_study_title(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a character string of the study title

Examples

```
get_study_title('MTBLS375')
```

get_webservice *Get Web-service details*

Description

Retrieve details about the Metabolights RESTful Webservice

Usage

```
get_webservice()
```

Value

a list of the MTBLS webservice information

Examples

```
get_webservice()
```

`mtbls_key`*Set API Token*

Description

Set your Metabolights API Token as global option. If MTBLS_API_KEY is set in `.Renvirom` then this variable will be passed directly to the MTBLS_API_KEY option. If no MTBLS_API_KEY is set in `.Renvirom`, then the API Token must be passed as an input in the `set_api_token` function

Usage

```
mtbls_key(API_KEY = NULL)
```

Arguments

API_KEY a character string of your Metabolights API Token (Default is NULL)

Examples

```
## Not run:  
  
# If API Token is set in `.Renvirom`  
  
mtbls_key()  
  
# If API Token is not set in `.Renvirom`  
  
mtbls_key('XXXX-0000-XXXX-0000')  
  
## End(Not run)
```

Index

download_study_file, 2

get_isa_investigation, 2
get_private_studies, 3
get_studies, 4
get_study_contacts, 4
get_study_desc, 5
get_study_descriptors, 5
get_study_factors, 6
get_study_files, 6
get_study_meta, 7
get_study_org, 7
get_study_protocols, 8
get_study_pubs, 8
get_study_samples, 9
get_study_tech, 9
get_study_title, 10
get_webservice, 10

mtbls_key, 11