

# Package ‘odds.n.ends’

September 17, 2021

**Title** Odds Ratios, Contingency Table, and Model Significance from a Generalized Linear Model Object

**Version** 0.1.4

**Imports** MASS

**Description** Computes odds ratios and 95% confidence intervals from a generalized linear model object. It also computes model significance with the chi-squared statistic and p-value and it computes model fit using a contingency table to determine the percent of observations for which the model correctly predicts the value of the outcome. Calculates model sensitivity and specificity.

**License** CC0

**Encoding** UTF-8

**RoxygenNote** 7.1.1

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Jenine Harris [aut, cre]

**Maintainer** Jenine Harris <harrisj@wustl.edu>

**Repository** CRAN

**Date/Publication** 2021-09-17 20:20:02 UTC

## R topics documented:

odds.n.ends . . . . . 2

**Index** . . . . . 3

---

`odds.n.ends`*A binary logistic regression function*

---

### Description

This function allows you to compute model significance (model chi-squared), model fit (percent correctly predicted, sensitivity, specificity), ROC plot, predicted probability plot, and odds ratios with 95 percent confidence intervals for a glm object from a binary logistic regression analysis.

### Usage

```
odds.n.ends(  
  mod,  
  thresh = 0.5,  
  rocPlot = FALSE,  
  predProbPlot = FALSE,  
  color1 = "#7463AC",  
  color2 = "deeppink"  
)
```

### Arguments

<code>mod</code>	is a glm object
<code>thresh</code>	is the threshold between 0-1 for predicted prob to be considered a case
<code>rocPlot</code>	is TRUE or FALSE to display an ROC plot
<code>predProbPlot</code>	is TRUE or FALSE to display predicted prob histogram by outcome value
<code>color1</code>	choose color for plot
<code>color2</code>	choose 2nd color for plot

### Examples

```
sick <- c(0, 0, 0, 0, 1, 1, 1, 1, 1, 0, 0, 0, 0, 1, 1, 1, 1, 1, 1, 1)  
age <- c(23, 25, 26, 34, 54, 46, 48, 95, 81, 42, 62, 25, 31, 49, 57, 52, 54, 63, 61, 50)  
logisticModel <- glm(sick ~ age, na.action = na.exclude, family = binomial(logit))  
odds.n.ends(mod = logisticModel)
```

# Index

- \* **fit**  
odds . n . ends, 2
  - \* **glm**  
odds . n . ends, 2
  - \* **logistic**  
odds . n . ends, 2
  - \* **odds**  
odds . n . ends, 2
- odds . n . ends, 2