

Package ‘pdynmc’

August 30, 2022

Type Package

Title Moment Condition Based Estimation of Linear Dynamic Panel Data Models

Version 0.9.8

Date 2022-08-30

Author Markus Fritsch [aut, cre],
Joachim Schnurbus [aut],
Andrew Adrian Yu Pua [aut]

Maintainer Markus Fritsch <Markus.Fritsch@uni-Passau.de>

Depends R (>= 3.6.0)

Imports data.table (>= 1.12.2), MASS (>= 7.3-51.4), Matrix (>= 1.2-17), optimx (>= 2018-07.10), qlcMatrix (>= 0.9.7), stats (>= 3.6.0), Rdpack (>= 0.11-0)

Suggests pder (>= 1.0-1), testthat (>= 2.3.2), R.rsp (>= 0.43.2)

RdMacros Rdpack

Description Linear dynamic panel data modeling based on linear and nonlinear moment conditions as proposed by Holtz-Eakin, Newey, and Rosen (1988) <[doi:10.2307/1913103](https://doi.org/10.2307/1913103)>, Ahn and Schmidt (1995) <[doi:10.1016/0304-4076\(94\)01641-C](https://doi.org/10.1016/0304-4076(94)01641-C)>, and Arellano and Bover (1995) <[doi:10.1016/0304-4076\(94\)01642-D](https://doi.org/10.1016/0304-4076(94)01642-D)>. Estimation of the model parameters relies on the Generalized Method of Moments (GMM), numerical optimization (when nonlinear moment conditions are employed) and the computation of closed form solutions (when estimation is based on linear moment conditions). One-step, two-step and iterated estimation is available. For inference and specification testing, Windmeijer (2005) <[doi:10.1016/j.jeconom.2004.02.005](https://doi.org/10.1016/j.jeconom.2004.02.005)> and doubly corrected standard errors (Hwang, Kang, Lee, 2021 <[doi:10.1016/j.jeconom.2020.09.010](https://doi.org/10.1016/j.jeconom.2020.09.010)>) are available. Additionally, serial correlation tests, tests for overidentification, and Wald tests are provided. Functions for visualizing panel data structures and modeling results obtained from GMM estimation are also available. The plot methods include

functions to plot unbalanced panel structure, coefficient ranges and coefficient paths across GMM iterations (the latter is implemented according to the plot shown in Hansen and Lee, 2021 <[doi:10.3982/ECTA16274](https://doi.org/10.3982/ECTA16274)>). For a more detailed description of the functionality, please see Fritsch, Pua, Schnurbus (2021) <[doi:10.32614/RJ-2021-035](https://doi.org/10.32614/RJ-2021-035)>.

License GPL (>= 2)

URL <https://github.com/markusfritsch/pdynmc>

BugReports <https://github.com/markusfritsch/pdynmc/issues>

VignetteBuilder R.rsp

Encoding UTF-8

Classification/JEL C23, C26, C87

RoxygenNote 7.2.1

NeedsCompilation no

Repository CRAN

Date/Publication 2022-08-30 16:40:02 UTC

R topics documented:

ABdata	3
case.names.pdynmc	4
cigDemand	5
coef.pdynmc	6
data.info	7
dummy.coef.pdynmc	8
fitted.pdynmc	10
jtest.fct	11
model.matrix.pdynmc	13
mttest.fct	14
ninst	16
ninst.pdynmc	17
nobs.pdynmc	18
optimIn	20
optimIn.pdynmc	21
pdynmc	22
plot.pdynmc	31
print.pdynmc	34
print.summary.pdynmc	35
residuals.pdynmc	37
strucUPD.plot	38
summary.pdynmc	39
variable.names.pdynmc	41
vcov.pdynmc	42
wald.fct	43

<i>ABdata</i>	3
wmat	45
wmat.pdynmc	46
Index	48

ABdata	<i>Employment, wages, capital, and output for companies based in the UK</i>
--------	-----------------------------------------------------------------------------

Description

Unbalanced panel dataset of 140 firms from different sectors located in the UK which were observed over the years 1976 until 1984. The dataset contains the variables firm, year, sector, employment, wages, capital, and output and was used in Arellano and Bond (1991) which also provides more details on the different variables.

Usage

```
data(ABdata)
```

Format

A dataset with 1031 rows and 7 variables containing:

- firm** firm identifier
- year** year
- sector** sector
- emp** number of firm employees in the UK
- wage** real wage
- capital** gross capital stock
- output** industry output

References

Arellano M, Bond S (1991). “Some Tests of Specification for Panel Data: Monte Carlo Evidence and an Application to Employment Equations.” *The Review of Economic Studies*, **58**(2), 277–297. [doi:10.2307/2297968](https://doi.org/10.2307/2297968).

Examples

```
## Not run:
data(ABdata, package = "pdynmc")
n <- ABdata$emp
w <- ABdata$wage
\donttest{plot(y = n, x = w)}

## End(Not run)
```

case.names.pdynmc *Case and Variable Names of Fitted Model.*

Description

case.names extracts variable names of cross-sectional and longitudinal identifiers of an object of class 'pdynmc'.

Usage

```
## S3 method for class 'pdynmc'
case.names(object, ...)
```

Arguments

object	An object of class 'pdynmc'.
...	further arguments.

Value

A list containing two character vectors with the variable names of the cross-sectional and the longitudinal identifiers from object of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
case.names(m1)
```

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
case.names(m1)
```

cigDemand

Cigarette consumption in the US

Description

Balanced panel dataset on annual cigarette consumption in the US for the 48 continental states in the years 1985 until 1995. The dataset is available from Stock and Watson (2003) and used in Stock and Watson (2019) and Fritsch et al. (2022). Gratitude is owed to Jonathan Gruber of MIT for providing the data.

Usage

```
data(cigDemand)
```

Format

A dataset with 528 rows and 9 variables containing:

state state

year year

cpi consumer price index (US)

pop state population

packpc number of cigarette packs sold per capita and year

income state personal income (total, nominal)

tax average federal, state, and local excise taxes on cigarettes for fiscal year in cents per pack

avgprs average price during fiscal year in cents per pack (including sales taxes)

taxs average excise tax for fiscal year in cents per pack (including sales taxes)

References

Fritsch M, Pua AAY, Schnurbus J (2022). “Teaching Advanced Topics in Econometrics using an Introductory Textbook: The Case of Dynamic Panel Data Methods.” Working Paper.

Stock JH, Watson MM (2019). *Introduction to Econometrics*, Fourth edition. Pearson.

Stock JH, Watson MW (2003). “cig_ ch10, cig85_95, Instructional Stata datasets for econometrics cig8595.” <https://ideas.repec.org/p/boc/bocins/cig8595.html>.

Examples

```
## Not run:
data(cigDemand, package = "pdynmc")
packs <- cigDemand$packpc
tax <- cigDemand$tax
\donttest{plot(y = packs, x = tax)}

## End(Not run)
```

coef.pdynmc

Extract Coefficient Estimates of Fitted Model.

Description

coef.pdynmc extracts coefficient estimates of an object of class ‘pdynmc’.

Usage

```
## S3 method for class 'pdynmc'
coef(object, ...)
```

Arguments

object An object of class ‘pdynmc’.
 ... further arguments.

Value

Extract coefficient estimates from object of class ‘pdynmc’.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
coef(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
coef(m1)

```

data.info

Show Basic Structure of Panel Dataset.

Description

data.info shows basic structure of a balanced/unbalanced panel dataset contained in a 'data.frame'.

Usage

```
data.info(object, i.name = NULL, t.name = NULL, ...)
```

Arguments

object	An object of class 'data.frame'.
i.name	Column name of cross-section identifier.
t.name	Column name of time-series identifier.
...	further arguments.

Value

Returns information if panel dataset contained in an object of class 'data.frame' is a balanced or unbalanced panel dataset.

Author(s)

Markus Fritsch, Joachim Schnurbus

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
data.info(dat, i.name = "firm", t.name = "year")

data.info(dat[dat$year %in% 1979:1981, ], i.name = "firm", t.name = "year")
```

dummy.coef.pdynmc *Extract Coefficient Estimates of Time Dummies of Fitted Model.*

Description

dummy.coef.pdynmc extracts coefficient estimates of time dummies of an object of class 'pdynmc'.

Usage

```
## S3 method for class 'pdynmc'
dummy.coef(object, ...)
```


Arguments

object An object of class 'pdynmc'.
 ... further arguments.

Value

Extract coefficient estimates of time dummies from object of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
dummy.coef(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
dummy.coef(m1)
```

fitted.pdynmc

Extract Fitted Values of Fitted Model.

Description

fitted.pdynmc extracts fitted values of an object of class 'pdynmc'.

Usage

```
## S3 method for class 'pdynmc'
fitted(object, step = object$iter, na.rm = FALSE, ...)
```

Arguments

object	An object of class 'pdynmc'.
step	An integer denoting the iteration step for which fitted values are extracted (defaults to last iteration step used for obtaining parameter estimates).
na.rm	A logical variable indicating whether missing values should be removed from the vector of fitted values (defaults to 'FALSE').
...	further arguments.

Value

Extract fitted values from object of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
             use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
```

```

include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
opt.meth = "none")
fitted(m1, na.rm = TRUE)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
opt.meth = "none")
fitted(m1, na.rm = TRUE)

```

jtest.fct

Hansen J-Test.

Description

jtest.fct tests the validity of the overidentifying restrictions.

Usage

```
jtest.fct(object)
```

Arguments

object An object of class 'pdynmc'.

Details

The null hypothesis is that the overidentifying restrictions are valid. The test statistic is computed as proposed by Hansen (1982). As noted by Bowsher (2002) and Windmeijer (2005) the test statistic is weakened by many instruments.

Value

An object of class ‘htest’ which contains the Hansen J-test statistic and corresponding p-value for the null hypothesis that the overidentifying restrictions are valid.

References

Bowsher CG (2002). “On testing overidentifying restrictions in dynamic panel data models.” *Economics Letters*, **77**(2), 211–220. doi:10.1016/S01651765(02)001301.

Hansen LP (1982). “Large Sample Properties of Generalized Method of Moments Estimators.” *Econometrica*, **50**(4), 1029–1054. doi:10.2307/1912775.

Windmeijer F (2005). “A finite sample correction for the variance of linear efficient two-step GMM estimators.” *Journal of Econometrics*, **126**(1), 25–51. doi:10.1016/j.jeconom.2004.02.005.

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(140:0), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
jtest.fct(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
```

```
w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
jtest.fct(m1)
```

model.matrix.pdynmc *Extract Instrument Matrix of Fitted Model.*

Description

model.matrix.pdynmc extracts instrument matrix of an object of class 'pdynmc'.

Usage

```
## S3 method for class 'pdynmc'
model.matrix(object, sparse = TRUE, ...)
```

Arguments

object	An object of class 'pdynmc'.
sparse	Whether to return a sparse matrix (if set to 'TRUE') or a regular matrix (if set to 'FALSE').
...	further arguments.

Value

Extracts instrument matrix from an object of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
```

```

include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
opt.meth = "none")
model.matrix(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
opt.meth = "none")
model.matrix(m1)

```

mtest.fct

Arellano and Bond Serial Correlation Test.

Description

mtest.pdynmc Methods to test for serial correlation in the error terms for objects of class ‘pdynmc’.

Usage

```
mtest.fct(object, order = 2, ...)
```

Arguments

object	An object of class ‘pdynmc’.
order	A number denoting the order of serial correlation to test for (defaults to ‘2’).
...	further arguments.

Details

The null hypothesis is that there is no serial correlation of a particular order. The test statistic is computed as proposed by Arellano and Bond (1991) and Arellano (2003).

Value

An object of class 'htest' which contains the Arellano and Bond m test statistic and corresponding p-value for the null hypothesis that there is no serial correlation of the given order.

References

Arellano M (2003). *Panel Data Econometrics*. Oxford University Press. doi:10.1093/0199245282.001.0001.

Arellano M, Bond S (1991). "Some Tests of Specification for Panel Data: Monte Carlo Evidence and an Application to Employment Equations." *The Review of Economic Studies*, 58(2), 277–297. doi:10.2307/2297968.

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(140:0), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
mtest.fct(m1, order = 2)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
mtest.fct(m1, order = 2)
```

ninst

Extract Instrument Count of Fitted Model.

Description

ninst is a generic function for extracting the instrument count of an object.

Usage

```
ninst(object, ...)
```

Arguments

object	An object for which the instrument count is desired.
...	further arguments.

Value

Extracts instrument count from an object.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
```



```

ninst(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
ninst(m1)

```

ninst.pdynmc

Extract Instrument Count of Fitted Model.

Description

ninst.pdynmc extracts instrument count of an object of class 'pdynmc'.

Usage

```
## S3 method for class 'pdynmc'
ninst(object, ...)
```

Arguments

object	An object of class 'pdynmc'.
...	further arguments.

Value

Extracts instrument count from an object of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
ninst(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
ninst(m1)

```

nobs.pdynmc

Extract Number of Observations of Fitted Model.

Description

nobs.pdynmc extracts number of observations in cross-section dimension and longitudinal dimension of an object of class 'pdynmc'.

Usage

```

## S3 method for class 'pdynmc'
nobs(object, ...)

```

Arguments

object An object of class 'pdynmc'.
 ... further arguments.

Value

Extracts number of observations in cross-section dimension and longitudinal dimension of an object of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]
```

```
## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
nobs(m1)
```

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
```

```
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
nobs(m1)
```

optimIn*Extract Input Parameters of Numeric Optimization of Fitted Model.*

Description

optimIn is a generic function for extracting input parameters of numeric optimization for an object.

Usage

```
optimIn(object, ...)
```

Arguments

object	An object for which input parameters of numeric optimization are desired.
...	further arguments.

Value

optimIn extracts input parameters used in numeric optimization from object.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
```

```

optimIn(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "BFGS")
optimIn(m1)

```

optimIn.pdynmc

Extract Input Parameters of Numeric Optimization of Fitted Model.

Description

optimIn.pdynmc extracts input parameters of numeric optimization for an object of class ‘pdynmc’.

Usage

```

## S3 method for class 'pdynmc'
optimIn(object, step = object$iter, ...)

```

Arguments

object	An object of class ‘pdynmc’.
step	An integer denoting the iteration step for which input parameters are extracted (defaults to last iteration step used for obtaining parameter estimates).
...	further arguments.

Value

Extracts input parameters of numeric optimization from object of class ‘pdynmc’.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
optimIn(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "BFGS")
optimIn(m1)
```

pdynmc

pdynmc: A package for moment conditions based estimation of linear dynamic panel data models

Description

The `pdynmc` package provides four categories of functions that are available to the user: A function for model fitting, functions for visualizing estimation results and panel data structures, functions

for specification testing, and functions that extract and summarize particular information from fitted model objects.

pdynmc fits a linear dynamic panel data model based on moment conditions with the Generalized Method of Moments (GMM).

Usage

```
pdynmc(  
  dat,  
  varname.i,  
  varname.t,  
  use.mc.diff,  
  use.mc.lev,  
  use.mc.nonlin,  
  use.mc.nonlinAS = NULL,  
  inst.stata = FALSE,  
  include.y,  
  varname.y = NULL,  
  lagTerms.y = NULL,  
  maxLags.y = NULL,  
  include.x = FALSE,  
  varname.reg.end = NULL,  
  lagTerms.reg.end = NULL,  
  maxLags.reg.end = NULL,  
  varname.reg.pre = NULL,  
  lagTerms.reg.pre = NULL,  
  maxLags.reg.pre = NULL,  
  varname.reg.ex = NULL,  
  lagTerms.reg.ex = NULL,  
  maxLags.reg.ex = NULL,  
  inst.reg.ex.expand = TRUE,  
  include.x.instr = FALSE,  
  varname.reg.instr = NULL,  
  include.x.toInstr = FALSE,  
  varname.reg.toInstr = NULL,  
  fur.con = FALSE,  
  fur.con.diff = NULL,  
  fur.con.lev = NULL,  
  varname.reg.fur = NULL,  
  lagTerms.reg.fur = NULL,  
  include.dum = FALSE,  
  dum.diff = NULL,  
  dum.lev = NULL,  
  varname.dum = NULL,  
  col_tol = 0.65,  
  w.mat = "iid.err",  
  w.mat.stata = FALSE,  
  std.err = "corrected",
```

```

estimation = "iterative",
max.iter = 100,
iter.tol = 0.01,
inst.thresh = NULL,
opt.meth = "BFGS",
hessian = FALSE,
optCtrl = list(kkt = FALSE, kkttol = .Machine$double.eps^(1/3), kkt2tol =
  .Machine$double.eps^(1/3), starttests = TRUE, dowarn = TRUE, badval = (0.25) *
  .Machine$double.xmax, usenumDeriv = FALSE, reltol = 1e-12, maxit = 200, trace = TRUE,
  follow.on = FALSE, save.failures = TRUE, maximize = FALSE, factr = 1e+07, pgtol = 0,
  all.methods = FALSE),
custom.start.val = FALSE,
start.val = NULL,
start.val.lo = -1,
start.val.up = 1,
seed.input = 42
)

```

Arguments

<code>dat</code>	A dataset.
<code>varname.i</code>	The name of the cross-section identifier.
<code>varname.t</code>	The name of the time-series identifier.
<code>use.mc.diff</code>	A logical variable indicating whether moment conditions from equations in differences (i.e. instruments in levels) should be used.
<code>use.mc.lev</code>	A logical variable indicating whether moment conditions from equations in levels (i.e. instruments in differences) should be used.
<code>use.mc.nonlin</code>	A logical variable indicating whether nonlinear (quadratic) moment conditions should be used.
<code>use.mc.nonlinAS</code>	A logical variable indicating whether only the nonlinear (quadratic) moment conditions in the form proposed by Ahn and Schmidt (1995) should be used (is set to 'TRUE' when nonlinear moment conditions are employed).
<code>inst.stata</code>	A logical variable indicating whether to use the moment conditions from equations in levels as in Stata implementations <code>xtabond2</code> Roodman (2018) and <code>xtdpdgm</code> Kripfganz (2019).
<code>include.y</code>	A logical variable indicating whether instruments should be derived from the lags of the dependent variable.
<code>varname.y</code>	A character string denoting the name of the dependent variable in the dataset.
<code>lagTerms.y</code>	An integer indicating the number of lags of the dependent variable. Note that setting 'lagTerms.y' to zero excludes the dependent variable from the right-hand-side of the model specification.
<code>maxLags.y</code>	An integer indicating the maximum number of lags of the dependent variable from which instruments should be derived.

<code>include.x</code>	A logical variable indicating whether instruments should be derived from the covariates. Setting the argument to 'TRUE' requires specifying whether the covariates are endogenous, predetermined, or (strictly) exogenous (defaults to 'FALSE').
<code>varname.reg.end</code>	One or more character strings denoting the covariate(s) in the dataset to be treated as endogenous (defaults to 'NULL').
<code>lagTerms.reg.end</code>	One or more integers indicating the number of lags of the endogenous covariate(s). One integer per covariate needs to be given in the same order as the covariate names (defaults to 'NULL').
<code>maxLags.reg.end</code>	One or more integers indicating the maximum number of lags of the endogenous covariate(s) used for deriving instruments. One integer per covariate needs to be given in the same order as the covariate names (defaults to 'NULL').
<code>varname.reg.pre</code>	One or more character strings denoting the covariate(s) in the dataset to be treated as predetermined (defaults to 'NULL').
<code>lagTerms.reg.pre</code>	One or more integers indicating the number of lags of the predetermined covariate(s). One integer per covariate needs to be given in the same order as the covariate name (defaults to 'NULL').
<code>maxLags.reg.pre</code>	One or more integers indicating the maximum number of lags of the predetermined covariate(s) used for deriving instruments. One integer per covariate needs to be given in the same order as the covariate names (defaults to 'NULL').
<code>varname.reg.ex</code>	One or more character strings denoting the covariate(s) in the dataset to be treated as (strictly) exogenous (defaults to 'NULL').
<code>lagTerms.reg.ex</code>	One or more integers indicating the number of lags of the (strictly) exogenous covariate(s). One integer per covariate needs to be given in the same order as the covariate name (defaults to 'NULL').
<code>maxLags.reg.ex</code>	One or more integers indicating the maximum number of lags of the (strictly) exogenous covariate(s) used for deriving instruments. One integer per covariate needs to be given in the same order as the covariate names (defaults to 'NULL').
<code>inst.reg.ex.expand</code>	A logical variable that allows for using all past, present, and future observations of 'varname.reg.ex' to derive instruments (defaults to 'TRUE'). If set to 'FALSE', only past and present time periods are used to derive instruments.
<code>include.x.instr</code>	A logical variable that allows to include additional IV-type instruments (i.e., include covariates which are used as instruments but for which no parameters are estimated; defaults to 'FALSE').
<code>varname.reg.instr</code>	One or more character strings denoting the covariate(s) in the dataset treated as instruments in estimation (defaults to 'NULL'). Note that the instrument type

needs to be specified by including the names of the covariate(s) in any of the arguments 'varname.reg.end', 'varname.reg.pre', or 'varname.reg.ex'.

include.x.toInstr	A logical variable that allows to instrument covariate(s) (i.e., covariates which are not used as instruments but for which parameters are estimated; defaults to 'FALSE').
varname.reg.toInstr	One or more character strings denoting the covariate(s) in the dataset to be instrumented (defaults to 'NULL'). Note that the names of the covariate(s) should not be included in any other function argument.
fur.con	A logical variable indicating whether further control variables (covariates) are included (defaults to 'FALSE').
fur.con.diff	A logical variable indicating whether to include further control variables in equations from differences (defaults to 'NULL').
fur.con.lev	A logical variable indicating whether to include further control variables in equations from level (defaults to 'NULL').
varname.reg.fur	One or more character strings denoting covariate(s) in the dataset to treat as further controls (defaults to 'NULL').
lagTerms.reg.fur	One or more integers indicating the number of lags of the further controls. One integer per further control needs to be given in the same order as the corresponding variable names (defaults to 'NULL').
include.dum	A logical variable indicating whether dummy variables for the time periods are included (defaults to 'FALSE').
dum.diff	A logical variable indicating whether dummy variables are included in the equations in first differences (defaults to 'NULL').
dum.lev	A logical variable indicating whether dummy variables are included in the equations in levels (defaults to 'NULL').
varname.dum	One or more character strings from which time dummies should be derived (can be different from varname.t; defaults to 'NULL').
col_tol	A numeric variable in [0,1] indicating the absolute correlation threshold for collinearity checks (columns are omitted when pairwise correlations are above the threshold; defaults to 0.65).
w.mat	One of the character strings c("iid.err", "identity", "zero.cov") indicating the type of weighting matrix to use (defaults to "iid.err").
w.mat.stata	A logical variable that slightly adjusts the weighting matrix according to the Stata function xtddpmm (defaults to 'FALSE').
std.err	One of the character strings c("corrected", "unadjusted", "dbl.corrected"). The second and third options compute corrected standard error according to Windmeijer (2005) and Hwang et al. (2021), respectively (defaults to "corrected").
estimation	One of the character strings c("onestep", "twostep", "iterative"). Denotes the number of iterations of the parameter procedure (defaults to "twostep").

<code>max.iter</code>	An integer indicating the maximum number of iterations (defaults to 'NULL'; if estimation is set to "iterative", 'max.iter' defaults to 100).
<code>iter.tol</code>	A numeric variable in [0,1] indicating the tolerance for determining convergence of the iterative approach (defaults to 'NULL'; if estimation is set to "iterative", iter.tol defaults to 0.01).
<code>inst.thresh</code>	An integer denoting above which instrument count a generalized inverse is used to invert the weighting matrix (defaults to 'NULL').
<code>opt.meth</code>	A character string denoting the numerical optimization procedure. When no nonlinear moment conditions are employed in estimation, closed form estimates can be computed by setting the argument to "none" (defaults to "BFGS"; for details on the further available optimizers see the documentation of package optimx).
<code>hessian</code>	A logical variable indicating if the hessian matrix should be approximated in optimization (defaults to 'FALSE').
<code>optCtrl</code>	A list of arguments that are passed to optimx . For details on the arguments and the available options see the package documentation.
<code>custom.start.val</code>	A logical variable indicating whether prespecified starting values for the parameters are provided by the user (defaults to 'FALSE'; if set to 'TRUE', starting values need to be provided via argument 'start.val').
<code>start.val</code>	A vector of numeric variables denoting the starting values for the parameter vector for numeric optimization (defaults to 'NULL').
<code>start.val.lo</code>	A numeric variable denoting the lower limit for drawing starting values with uniform density (defaults to -1; ignored if 'custom.start.val' is set to 'TRUE').
<code>start.val.up</code>	A numeric variable denoting the upper limit for drawing starting values with uniform density (defaults to 1; ignored if 'custom.start.val' is set to 'TRUE').
<code>seed.input</code>	An integer used as seed for drawing starting values (defaults to 42; required if custom.start.val is set to 'FALSE').

Details

The function estimates a linear dynamic panel data model of the form

$$y_{i,t} = y_{i,t-1}\rho_1 + \mathbf{x}'_{i,t}\boldsymbol{\beta} + a_i + \varepsilon_{i,t}$$

where $y_{i,t-1}$ is the lagged dependent variable, ρ_1 is the lag parameter, $\mathbf{x}_{i,t}$ are further covariates, $\boldsymbol{\beta}$ are the corresponding parameters, a_i is an unobserved individual specific effect, and $\varepsilon_{i,t}$ is an idiosyncratic remainder component. The model structure accounts for unobserved individual specific heterogeneity and dynamics. Note that the specification given above is simplified for illustrative purposes and more general lag structures are allowed in `pdynmc`.

Estimation of the model parameters in `pdynmc` is based on moment conditions with the generalized method of moments (GMM). Linear dynamic panel data models The moment conditions employed in estimation can be linear and nonlinear in parameters and estimation is carried out iteratively. In case only linear moment conditions are used in estimation, closed form solutions can be for computing parameter estimates – while when nonlinear moment conditions are employed, parameter estimation relies on numerical optimization of the objective function.

'pdynmc' provides an implementation of some of the functionality available in the Stata library `xtpdgmm` Kripfganz (2019) and allows for "onestep", "twostep", and "iterative" GMM estimation based on the moment conditions of Holtz-Eakin et al. (1988), Arellano and Bover (1995), and Ahn and Schmidt (1995). Standard error corrections according to Windmeijer (2005) and Hwang et al. (2021) are available. For further details, please see Fritsch et al. (2021).

Value

An object of class 'pdynmc' with the following elements:

<code>coefficients</code>	a vector containing the coefficient estimates
<code>data</code>	a list of elements on which computation of the model fit is based
<code>dep.clf</code>	a list of vectors containing the dependent variable for the cross-sectional observations
<code>dat.clf</code>	a list of matrices containing the covariates for the cross-sectional observations
<code>w.mat</code>	a list of weighting matrices for the different estimation steps
<code>H_i</code>	a matrix used to create the weighting matrix for the first estimation step
<code>par.optim</code>	a list of vectors containing the parameter estimates obtained from numerical optimization for the estimation steps
<code>ctrl.optim</code>	a list of control parameters used in numerical optimization for the estimation steps
<code>par.clfForm</code>	a list of vectors containing the parameter estimates obtained from the closed form for the estimation steps
<code>iter</code>	a scalar denoting the number of iteration steps carried out to obtain parameter estimates
<code>fitted.values</code>	a list for each estimation step that contains a list of vectors of fitted values for each cross-sectional observation
<code>residuals</code>	a list for each estimation step that contains a list of vectors of residuals for each cross-sectional observation
<code>vcov</code>	a list of matrices containing the variance covariance matrix of the parameter estimates for each estimation step
<code>stderr</code>	a list of vectors containing the standard errors of the parameter estimates for each estimation step
<code>zvalue</code>	a list of vectors containing the z scores for the parameter estimates for each estimation step
<code>pvalue</code>	a list of vectors containing the p-values for the parameter estimates for each estimation step

It has 'case.names', 'coef', 'dum.coef', 'fitted', 'model.matrix', 'ninst', 'nobs', 'optimIn', 'plot', 'print', 'residuals', 'summary', 'variable.names', 'vcov', and 'wmat' methods.

Author(s)

Markus Fritsch

References

- Ahn SC, Schmidt P (1995). “Efficient estimation of models for dynamic panel data.” *Journal of Econometrics*, **68**(1), 5–27. doi:10.1016/03044076(94)01641C.
- Arellano M, Bover O (1995). “Another look at the instrumental variable estimation of error-components models.” *Journal of Econometrics*, **68**(1), 29–51. doi:10.1016/03044076(94)01642D.
- Fritsch M, Pua AAY, Schnurbus J (2021). “pdynmc: A Package for Estimating Linear Dynamic Panel Data Models Based on Nonlinear Moment Conditions.” *The R Journal*, **13**(1), 218–231. doi:10.32614/RJ2021035.
- Holtz-Eakin D, Newey WK, Rosen HS (1988). “Estimating Vector Autoregressions with Panel Data.” *Econometrica*, **56**(6), 1371–1395. doi:10.2307/1913103.
- Hwang J, Kang B, Lee S (2021). “A doubly corrected robust variance estimator for linear GMM.” *Journal of Econometrics*, **forthcoming**. doi:10.1016/j.jeconom.2020.09.010.
- Kripfganz S (2019). “XTDPDGMM: Stata module to perform generalized method of moments estimation of linear dynamic panel data models.” <https://econpapers.repec.org/RePEc:boc:bocode:s458395>.
- Roodman D (2018). “xtabond2: Stata module to extend xtabond dynamic panel data estimator.” <https://econpapers.repec.org/software/bocbocode/s435901.htm>.
- Windmeijer F (2005). “A finite sample correction for the variance of linear efficient two-step GMM estimators.” *Journal of Econometrics*, **126**(1), 25–51. doi:10.1016/j.jeconom.2004.02.005.

See Also

[wald.fct](#) for Wald tests, [jtest.fct](#) for the Hansen J test, and [mtest.fct](#) for serial correlation tests. [optimx](#) for details on alternative routines and options for numerical optimization

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
summary(m1)
```

```

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Arellano and Bond (1991) estimation in Table 4, column (a1)
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
summary(m1)

## Arellano and Bond (1991) estimation in Table 4, column (a2)
m2 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "twostep",
  opt.meth = "none")
summary(m2)

## Arellano and Bond (1991) twostep estimation extended by nonlinear moment
## conditions
m3 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = TRUE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "twostep",
  opt.meth = "BFGS")
summary(m3)

## Arellano and Bond (1991) iterative estimation extended by nonlinear moment
## conditions
m4 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = TRUE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "iterative",
  max.iter = 4, opt.meth = "BFGS")
summary(m4)

```

```
## Arellano and Bond (1991) twostep estimation extended by linear moment
## conditions from equations in levels
m5 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
             use.mc.diff = TRUE, use.mc.lev = TRUE, use.mc.nonlin = FALSE,
             include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
             fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
             varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
             include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
             w.mat = "iid.err", std.err = "corrected", estimation = "twostep",
             opt.meth = "none")
summary(m5)
```

plot.pdynmc

Plot Coefficient Estimates and Corresponding Ranges of Fitted Model.

Description

plot.pdynmc Plot methods for objects of class 'pdynmc'. The available plot options visualize: Fitted values versus residuals, coefficient ranges across GMM iterations, coefficient paths and objective function values across GMM iterations as proposed by Hansen and Lee (2021).

Usage

```
## S3 method for class 'pdynmc'
plot(
  x,
  type = "fire",
  include.dum = FALSE,
  include.fur.con = FALSE,
  col.coefRange = 1,
  col.coefInitial = "darkgrey",
  col.coefEst = "royalblue",
  omit1step = FALSE,
  boxplot.coef = FALSE,
  co = NULL,
  add.se.approx = NULL,
  conf.lev = 0.95,
  ...
)
```

Arguments

x An object of class 'pdynmc'. The function requires twostep or iterative GMM estimates.

<code>type</code>	Whether to plot fitted values against residuals (argument <code>'fire'</code> ; default), coefficient ranges (argument <code>'coef.range'</code> ; this requires twostep or iterative GMM estimates), path of coefficient estimates across GMM iterations (argument <code>'coef.path'</code> ; this requires twostep or iterative GMM estimates).
<code>include.dum</code>	Include estimates of parameters corresponding to time dummies (defaults to <code>'black'</code> ; requires <code>'type = coef.range'</code>).
<code>include.fur.con</code>	Include estimates of parameters corresponding to further controls (defaults to <code>'FALSE'</code> ; requires <code>'type = coef.range'</code>).
<code>col.coefRange</code>	Specify color for plotting range of coefficient estimates (defaults to <code>'NULL'</code> ; requires <code>'type = coef.range'</code>).
<code>col.coefInitial</code>	Specify color for plotting initial coefficient estimates (defaults to <code>'darkgrey'</code> ; requires <code>'type = coef.range'</code>).
<code>col.coefEst</code>	Specify color for plotting coefficient estimate (defaults to <code>'royalblue'</code> ; requires <code>'type = coef.range'</code>).
<code>omit1step</code>	Omit coefficient estimates from one-step GMM estimation in coefficient range plot. The argument can after obtaining coefficient estimates from numerical optimization methods to exclude the randomly drawn starting values from the plotted coefficient range (defaults to <code>'FALSE'</code>). Set to <code>'TRUE'</code> to exert the option; this argument requires iterative GMM estimates and argument <code>'type = coef.range'</code> .
<code>boxplot.coef</code>	Whether to draw boxplots for coefficient estimates (defaults to <code>'FALSE'</code>); requires iterative GMM with at least 10 iterations and argument <code>'type = coef.range'</code> . Proceed with caution as this argument is experimental.
<code>co</code>	Character string denoting the variable name(s) for which to plot the path of coefficient estimate(s) across GMM iterations (defaults to <code>'NULL'</code>) as proposed in Hansen and Lee (2021); if no coefficient name is given, all coefficient paths are plotted; requires at least two iterations and argument <code>'type = coef.path'</code> .
<code>add.se.approx</code>	A logical variable indicating if standard errors should be added to the plot of the path of coefficient estimate(s) across GMM iterations (defaults to <code>'NULL'</code>); requires at least two iterations and argument <code>'type = coef.path'</code> . This option is only available when plotting a single coefficient path (i.e., when <code>'co'</code> contains only a single variable name).
<code>conf.lev</code>	A numeric variable indicating the confidence level for approximating standard errors in the plot of the path of coefficient estimate(s) across GMM iterations (defaults to 0.95; sensible values lie in the interval]0,1[); requires argument <code>'type = coef.path'</code> and argument <code>'add.se.approx = TRUE'</code> .
<code>...</code>	further arguments.

Value

Plot fitted values against residuals (`'type = fire'`) or coefficient estimates and coefficient estimate ranges (`'type = coef.range'`) for object of class `'pdynmc'`. The latter plot requires twostep or iterative GMM estimates.

Author(s)

Markus Fritsch and Joachim Schnurbus

References

Hansen BE, Lee S (2021). “Inference for Iterated GMM Under Misspecification.” *Econometrica*, **89**(3), 1419–1447. doi:10.3982/ECTA16274.

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "twostep",
  opt.meth = "none")
plot(m1)
plot(m1, type = "coef.range")
plot(m1, type = "coef.path")

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "iterative",
  opt.meth = "none")
plot(m1)
plot(m1, type = "coef.range")
plot(m1, type = "coef.path")
```

print.pdynmc	<i>Print Fitted Model Object.</i>
--------------	-----------------------------------

Description

print.pdynmc prints objects of class 'pdynmc'.

Usage

```
## S3 method for class 'pdynmc'
print(x, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

x	An object of class 'pdynmc'.
digits	An integer indicating the maximum number of digits to display in the object.
...	further arguments.

Value

Print objects of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
```

```

      opt.meth = "none")
m1

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
m1

```

print.summary.pdynmc *Print Summary of Fitted Model Object.*

Description

print.summary.pdynmc prints the summary for objects of class 'pdynmc'.

Usage

```

## S3 method for class 'summary.pdynmc'
print(
  x,
  digits = max(3, getOption("digits") - 3),
  signif.stars = getOption("show.signif.stars"),
  ...
)

```

Arguments

x	An object of class 'summary.pdynmc'.
digits	An integer indicating the maximum number of digits to display in the object.
signif.stars	Argument is defined as in options .
...	further arguments.

Value

Print information on objects of class ‘summary.pdynmc’.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
summary(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
summary(m1)
```

residuals.pdynmc	<i>Extract Residuals of Fitted Model.</i>
------------------	-------------------------------------------

Description

residuals.pdynmc extracts residuals from an object of class 'pdynmc'.

Usage

```
## S3 method for class 'pdynmc'  
residuals(object, step = object$iter, na.rm = FALSE, ...)
```

Arguments

object	An object of class 'pdynmc'.
step	An integer denoting the iteration step for which fitted values are extracted (defaults to last iteration step used for obtaining parameter estimates).
na.rm	A logical variable indicating whether missing values should be removed from the vector of fitted values (defaults to 'FALSE').
...	further arguments.

Value

Extract residuals from object of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data  
data(ABdata, package = "pdynmc")  
dat <- ABdata  
dat[,c(4:7)] <- log(dat[,c(4:7)])  
dat <- dat[c(1:140), ]  
  
## Code example  
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",  
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,  
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,  
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,  
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),  
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
```

```

    w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
    opt.meth = "none")
residuals(m1, na.rm = TRUE)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
residuals(m1, na.rm = TRUE)

```

strucUPD.plot

Plot on Structure of Unbalanced Panel Dataset.

Description

strucUPD.plot Plot on cross-section and longitudinal structure of an object of class ‘data.frame’ containing an unbalanced panel dataset.

Usage

```

strucUPD.plot(
  object,
  i.name = NULL,
  t.name = NULL,
  col.range = c("gold", "darkblue"),
  plot.name = "Unbalanced panel structure",
  ...
)

```

Arguments

object	An object of class ‘data.frame’.
i.name	Column name of cross-section identifier.
t.name	Column name of time-series identifier.

col.range	A vector of at least two colors used to visualize the structure of the unbalanced panel data set (defaults to 'gold' and 'darkblue'); must be a valid argument to col2rgb .
plot.name	A vector indicating the title of the plot (defaults to 'Unbalanced panel structure').
...	further arguments.

Value

Returns a plot for an unbalanced panel dataset contained in an object of class 'data.frame' that visualizes the structure of the data. Cross-section dimension is plotted on the ordinate, longitudinal dimension on the abscissa. Each cross-sectional observation is represented by a bar. Breaks in the bars represent missing longitudinal observations.

Author(s)

Markus Fritsch, Joachim Schnurbus

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Code example
strucUPD.plot(dat, i.name = "firm", t.name = "year")
```

summary.pdynmc

Summary for Fitted Model Object.

Description

summary.pdynmc generates the summary for objects of class 'pdynmc'.

Usage

```
## S3 method for class 'pdynmc'
summary(object, ...)
```

Arguments

object An object of class 'pdynmc'.
 ... further arguments.

Value

Object of class 'summary.pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
summary(m1, na.rm = TRUE)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
summary(m1)
```

variable.names.pdynmc *Extract Names of Explanatory Variables of Fitted Model.*

Description

variable.names.pdynmc extracts explanatory variables from an object of class 'pdynmc'.

Usage

```
## S3 method for class 'pdynmc'  
variable.names(object, ...)
```

Arguments

object	An object of class 'pdynmc'.
...	further arguments.

Value

Extract explanatory variables from an object of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data  
data(ABdata, package = "pdynmc")  
dat <- ABdata  
dat[,c(4:7)] <- log(dat[,c(4:7)])  
dat <- dat[c(1:140), ]  
  
## Code example  
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",  
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,  
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,  
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,  
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),  
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",  
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",  
  opt.meth = "none")
```

```

variable.names(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
variable.names(m1)

```

vcov.pdynmc

Extract Variance Covariance Matrix of Fitted Model.

Description

vcov.pdynmc extracts variance covariance matrix of the parameter estimates from an object of class 'pdynmc'.

Usage

```

## S3 method for class 'pdynmc'
vcov(object, step = object$iter, ...)

```

Arguments

object	An object of class 'pdynmc'.
step	An integer denoting the iteration step for which fitted values are extracted (defaults to last iteration step used for obtaining parameter estimates).
...	further arguments.

Value

Extract variance covariance matrix of the parameter estimates from an object of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
vcov(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
vcov(m1)
```

wald.fct

Wald Test.

Description

wald.fct computes F test statistics and corresponding p-values for ‘pdynmc’ objects.

Usage

```
wald.fct(object, param)
```

Arguments

object	An object of class 'pdynmc'.
param	A character string that denotes the null hypothesis. Choices are time.dum (i.e., all time dummies are jointly zero), slope (i.e., all slope coefficients are jointly zero), and all (i.e., all dummies and slope coefficients are jointly zero).

Details

The three available null hypothesis are: All time dummies are jointly zero, all slope coefficients are jointly zero, all times dummies and slope coefficients are jointly zero.

Value

An object of class 'hstest' which contains the F test statistic and corresponding p-value for the tested null hypothesis.

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(140:0), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
wald.fct(param = "all", m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

## Further code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
```

```

include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
opt.meth = "none")
wald.fct(m1, param = "all")

```

wmat

Extract Weighting Matrix of Fitted Model.

Description

wmat is a generic function for extracting the weighting matrix of an object.

Usage

```
wmat(object, ...)
```

Arguments

object An object for which the weighting matrix is desired.
... further arguments.

Value

Extract weighting matrix from an object.

Author(s)

Markus Fritsch

See Also

[pdynmc](#) for fitting a linear dynamic panel data model.

Examples

```

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,

```

```

varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
opt.meth = "none")
wmat(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
opt.meth = "none")
wmat(m1)

```

wmat.pdynmc

Extract Weighting Matrix of Fitted Model.

Description

wmat.pdynmc extracts weighting matrix from an object of class 'pdynmc'.

Usage

```

## S3 method for class 'pdynmc'
wmat(object, step = object$iter, ...)

```

Arguments

object	An object of class 'pdynmc'.
step	An integer denoting the iteration step for which fitted values are extracted (defaults to last iteration step used for obtaining parameter estimates).
...	further arguments.

Value

Extract weighting matrix from an object of class 'pdynmc'.

Author(s)

Markus Fritsch

See Also[pdynmc](#) for fitting a linear dynamic panel data model.**Examples**

```
## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])
dat <- dat[c(1:140), ]

## Code example
m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
wmat(m1)

## Load data
data(ABdata, package = "pdynmc")
dat <- ABdata
dat[,c(4:7)] <- log(dat[,c(4:7)])

m1 <- pdynmc(dat = dat, varname.i = "firm", varname.t = "year",
  use.mc.diff = TRUE, use.mc.lev = FALSE, use.mc.nonlin = FALSE,
  include.y = TRUE, varname.y = "emp", lagTerms.y = 2,
  fur.con = TRUE, fur.con.diff = TRUE, fur.con.lev = FALSE,
  varname.reg.fur = c("wage", "capital", "output"), lagTerms.reg.fur = c(1,2,2),
  include.dum = TRUE, dum.diff = TRUE, dum.lev = FALSE, varname.dum = "year",
  w.mat = "iid.err", std.err = "corrected", estimation = "onestep",
  opt.meth = "none")
wmat(m1)
```

Index

* **datasets**
 ABdata, 3
 cigDemand, 5

ABdata, 3

case.names.pdynmc, 4
cigDemand, 5
coef.pdynmc, 6
col2rgb, 39

data.info, 7
dummy.coef.pdynmc, 8

fitted.pdynmc, 10

jtest.fct, 11, 29

model.matrix.pdynmc, 13
mtest.fct, 14, 29

ninst, 16
ninst.pdynmc, 17
nobs.pdynmc, 18

optimIn, 20
optimIn.pdynmc, 21
optimx, 29
options, 35

pdynmc, 4, 6, 8–10, 12, 13, 15–17, 19, 20, 22,
 22, 33, 34, 36, 37, 39–41, 43–45, 47

plot.pdynmc, 31
print.pdynmc, 34
print.summary.pdynmc, 35

residuals.pdynmc, 37

strucUPD.plot, 38
summary.pdynmc, 39

variable.names.pdynmc, 41

vcov.pdynmc, 42

wald.fct, 29, 43
wmat, 45
wmat.pdynmc, 46